

# Mu Runtime Reference

mu namespace, version 0.2.8

## type keywords and aliases

<i>supertype</i>	<i>T</i>	
<i>bool</i>	() , :nil are false, otherwise true	
<i>condition</i>	keyword, see <b>Exception</b>	
<i>list</i>	:cons or () , :nil	
:null	() , :nil	
:char	char	
:cons	cons	
:fixnum	fixnum, fix	56 bit signed integer
:float	float, fl	32 bit IEEE float
:func	function, fn	function
:keyword	keyword, key	symbol
:ns	namespace, ns	namespace
:stream	stream	file or string type
:struct	struct	typed vector
:symbol	symbol, sym	LISP-1 symbol
:vector	vector, string, str	
	:bit :char :t	
	:byte :fixnum :float	

## Features

[dependencies]  
default = [ "env", "procinfo", "std", "nix", "sysinfo" ]

env	<b>heap-room</b>	vector	allocations
	#(:t :type size total free ...)		
	<b>heap-info</b>	list	heap info
	(type page-size npages)		
	<b>heap-size</b>	keyword	fixnum type size
	<b>heap-free</b>	fixnum	bytes free
	<b>env</b>	list	env state
	<b>core</b>	list	core state
	<b>uname</b>		
	<b>command, exit</b>		
nix	<b>sysinfo</b> (disabled on macOS)		
	<b>process-mem-virt</b>	fixnum	virtual memory in bytes
	<b>process-mem-res</b>	fixnum	reserve in bytes
	<b>process-time</b>	fixnum	microseconds
std	<b>time-units-per-sec</b>	fixnum	
	<b>prof-control</b>		enable semispace heap
sysinfo			
procinfo			
prof			
semispace			

## configuration API

config string format:

"npages:N, gc-mode:GCMODE, page-size:N, heap-type:HEAPTYPE"

N: unsigned integer  
GCMODE: none | auto | demand  
HEAPTYPE: semispace | bump // needs semispace feature

## Special Forms

<b>:lambda</b> list . list'	function	anonymous function
<b>:quote</b> form	list	quoted form
<b>:if</b> form T T'	T	conditional

## Reader/Printer

<b>read</b> stream bool T	T	read stream object
<b>write</b> T bool stream	T	write escaped object

## Core

<b>*null/*</b>	ns	null namespace
<b>apply</b> fn list	T	apply fn to list
<b>eval</b> form	T	evaluate form
<b>eq</b> T T'	bool	T and T' identical?
<b>type-of</b> T	key	type keyword
<b>compile</b> form	T	mu form compiler
<b>view</b> form	vector	vector of object

<b>%if</b> fn fn' fn"	bool	:if implementation
-----------------------	------	--------------------

<b>repr</b> T	vector	tag representation
<b>unrepr</b> vector	T	tag representation

vector is an 8 element :byte vector of little-endian argument tag bits.

<b>fix</b> fn T	T	fixpoint of fn
<b>gc</b>	bool	garbage collection

## Frames

<b>%frame-stack</b>	list	active frames
<b>%frame-pop</b> fn	fn	pop function's top frame binding
frame binding: (fn . #(:t ...))		
<b>%frame-push</b> frame	cons	push frame
<b>%frame-ref</b> fn fix	T	function, offset

## Symbols

<b>boundp</b> symbol	bool	is symbol bound?
<b>make-symbol</b> string	symbol	uninterned symbol
<b>symbol-namespace</b> symbol	ns	namespace
<b>symbol-name</b> symbol	string	name binding
<b>symbol-value</b> symbol	T	value binding

## Fixnums

<b>mul</b> fix fix'	fixnum	product
<b>add</b> fix fix'	fixnum	sum
<b>sub</b> fix fix'	fixnum	difference
<b>less-than</b> fix fix'	bool	fix < fix'?
<b>div</b> fix fix'	fixnum	quotient
<b>ash</b> fix fix'	fixnum	arithmetic shift
<b>logand</b> fix fix'	fixnum	bitwise and
<b>logor</b> fix fix'	fixnum	bitwise or
<b>lognot</b> fix	fixnum	bitwise complement

## Floats

<b>fmul</b> fl fl'	float	product
<b>fadd</b> fl fl'	float	sum
<b>fsub</b> fl fl'	float	difference
<b>fless-than</b> fl fl'	bool	fl < fl'?
<b>fdiv</b> fl fl'	float	quotient

## Conses/Lists

<b>append</b> list	list	append lists
<b>car</b> list	T	head of list
<b>cdr</b> list	T	tail of list
<b>cons</b> T T'	cons	(T . T')
<b>length</b> list	fixnum	length of list
<b>nth</b> fix list	T	nth car of list
<b>nthcdr</b> fix list	T	nth cdr of list

## Vectors

<b>make-vector</b> key list	vector	specialized vector from list
<b>vector-length</b> vector	fixnum	length of vector
<b>vector-type</b> vector	key	type of vector
<b>svref</b> vector fix	T	nth element

## Streams n

**\*standard-input\*** *stream* std input *stream*  
**\*standard-output\*** *stream* std output *stream*  
**\*error-output\*** *stream* std error *stream*

**open** *type dir string bool*  
*stream* open *stream*  
raise error if *bool*

*type* :file :string  
*dir* :input :output :bidir

**close** *stream bool* close *stream*  
**openp** *stream bool* is *stream* open?

**flush** *stream bool* flush output *stream*  
**get-string** *stream string* from *string stream*

**read-byte** *stream bool T*  
*byte* read *byte* from  
*stream*, error on  
eof, *T*: eof value

**read-char** *stream bool T*  
*char* read *char* from  
*stream*, error on  
eof, *T*: eof value

**unread-char** *char stream*  
*char* push *char* onto  
*stream*

**write-byte** *byte stream byte* write *byte* to *stream*  
**write-char** *char stream char* write *byte* to *stream*

## Namespaces .

**make-namespace** *str ns* make *namespace*  
**namespace-map** *list* list of mapped  
*namespaces*  
**namespace-name** *ns string* *namespace* name  
**intern** *ns str value symbol* intern bound symbol  
**find-namespace** *str ns* map *string* to  
*namespace*  
**find** *ns string symbol* map *string* to  
*symbol*  
**namespace-symbols** *ns list* *namespace* symbols

## Exceptions n

**with-exception** *fn fn' T* catch exception

*fn* - (:lambda (*obj cond src*) . *body*)  
*fn'* - (:lambda () . *body*)

**raise** *T keyword* raise exception  
on *T* with  
condition:

:arity :div0 :eof :error :except  
:future :ns :open :over :quasi  
:range :read :exit :signal :stream  
:syntax :syscall :type :unbound :under  
:write :storage

## Structs t

**make-struct** *key list* *struct* of *type key* from *list*  
**struct-type** *struct key* *struct* type *keyword*  
**struct-vec** *struct vector* of *struct* members

## mu library API I

[dependencies]  
mu = {  
git = "https://github.com/Software-Knife-and-Tool/mu.git",  
branch = "main"  
}

use mu:: { Condition, Config, Env, Exception, Core, Mu, Result,  
Tag };

```
impl Mu {
  const VERSION: &str

  fn config(_: Option<String>) -> Option<Config>
  fn make_env(_: &Config) -> Env
  fn apply(_: &Env, _: Tag, _: Tag) -> Result<Tag>
  fn compile(_: &Env, _: Tag) -> Result<Tag>
  fn eq(_: Tag, _: Tag) -> bool;
  fn exception_string(_: &Env, _: Exception) -> String
  fn eval(_: &Env, _: Tag) -> Result<Tag>
  fn eval_str(_: &Env, _: &str) -> Result<Tag>
  fn load(_: &Env, _: &str) -> Result<bool>
  fn read(_: &Env, _: Tag, _: bool, _: Tag) -> Result<Tag>
  fn read_str(_: &Env, _: &str) -> Result<Tag>
  fn core() -> &Core
  fn err_out() -> Tag
  fn std_in() -> Tag
  fn std_out() -> Tag
  fn write(_: &Env, _: Tag, _: bool, _: Tag) -> Result<()>
  fn write_str(_: &Env, _: &str, _: Tag) -> Result<()>
  fn write_to_string(_: &Env, _: Tag, _: bool) -> String
}
```

## Reader Syntax x

; comment to end of line  
#|...|# block comment  
'form quoted form  
`form backquoted form  
`(...) backquoted list (proper lists)  
,form eval backquoted form  
,@form eval-splice backquoted form  
(...) constant *list*  
() empty *list*, prints as :nil  
(...) dotted *list*  
"..." *string*, *char vector*  
| single escape in strings

#\*... bit vector  
#X... hexadecimal *fixnum*  
# read-time eval  
#\ *char*  
#(:type ...) *vector*  
#s(:type ...) *struct*  
#:symbol uninterned *symbol*

"` , ; terminating macro *char*  
# non-terminating macro *char*

!\$%&\*+- . symbol constituents  
<=>?@[| |  
: ^ \_ { } ~ /  
A..Za..z  
0..9

0x09 #\tab whitespace  
0x0a #\linefeed  
0x0c #\page  
0x0d #\return  
0x20 #\space

## mu-sys .

**mu-sys: 0.0.2: [celq] [file...]**

c: name:value,... runtime configuration  
e: form eval and print result  
l: path load from path  
q: form eval quietly