

Mu Runtime Reference

version 0.2.11

type keywords and aliases

<i>supertype</i>	<i>T</i>	
<i>bool</i>	<code>()</code> , <code>:nil</code> are false, otherwise true	
<i>condition</i>	keyword, see exceptions	
<i>list</i>	<code>:cons</code> or <code>()</code> , <code>:nil</code>	
<i>ns</i>	<code>#s(:ns #(:t fixnum symbol))</code>	
<i>:null</i>	<code>()</code> , <code>:nil</code>	
<i>:char</i>	<i>char</i>	8 bit ASCII
<i>:cons</i>	<i>cons</i> , <i>list</i>	list, cons, dotted pair
<i>:fixnum</i>	<i>fixnum</i> , <i>fix</i>	56 bit signed integer
<i>:float</i>	<i>float</i> , <i>fl</i>	32 bit IEEE float
<i>:func</i>	<i>function</i> , <i>fn</i>	function
<i>:keyword</i>	<i>keyword</i> , <i>key</i>	symbol
<i>:stream</i>	<i>stream</i>	file or string type
<i>:struct</i>	<i>struct</i>	see structs
<i>:symbol</i>	<i>symbol</i> , <i>sym</i>	LISP-1 symbol
<i>:vector</i>	<i>vector</i> , <i>string</i> , <i>str</i>	typed vector
	<i>:bit</i> <i>:char</i> <i>:t</i>	
	<i>:byte</i> <i>:fixnum</i> <i>:float</i>	

core

apply <i>fn list</i>	<i>T</i>	apply <i>fn</i> to <i>list</i>
compile <i>form</i>	<i>T</i>	mu form compiler
eq <i>T T'</i>	<i>bool</i>	<i>T</i> and <i>T'</i> identical?
eval <i>form</i>	<i>T</i>	evaluate <i>form</i>
type-of <i>T</i>	<i>key</i>	type keyword
view <i>for</i>	<i>vector</i>	vector of object
fix <i>fn T</i>	<i>T</i>	fixpoint of <i>fn</i>
gc	<i>bool</i>	garbage collection
repr <i>T</i>	<i>vector</i>	tag representation
unrepr <i>vector</i>	<i>T</i>	tag representation

special forms

<code>:lambda list . list'</code>	<i>function</i>	anonymous <i>fn</i>
<code>:alambda list . list'</code>	<i>function</i>	anonymous <i>fn</i>
<code>:quote T</code>	<i>list</i>	quoted form
<code>:if T T' T''</code>	<i>T</i>	conditional
vector is an 8 element :byte vector of little-endian argument tag bits.		

frames

frame binding: `(fn . #(:t ...))`

%frame-stack	<i>list</i>	active frames
%frame-pop <i>fn</i>	<i>frame</i>	pop <i>function</i> 's top frame binding
%frame-push <i>frame</i>	<i>cons</i>	push frame
%frame-ref <i>fn fix</i>	<i>T</i>	<i>function</i> , offset

symbols

boundp <i>sym</i>	<i>bool</i>	is <i>symbol</i> bound?
make-symbol <i>string</i>	<i>sym</i>	uninterned <i>symbol</i>
symbol-namespace <i>sym</i>	<i>ns</i>	namespace
symbol-name <i>symbol</i>	<i>string</i>	name binding
symbol-value <i>symbol</i>	<i>T</i>	value binding

fixnums

add <i>fix fix'</i>	<i>fixnum</i>	sum
ash <i>fix fix'</i>	<i>fixnum</i>	arithmetic shift
div <i>fix fix'</i>	<i>fixnum</i>	quotient
less-than <i>fix fix'</i>	<i>bool</i>	<i>fix</i> < <i>fix'</i> ?
logand <i>fix fix'</i>	<i>fixnum</i>	bitwise and
lognot <i>fix</i>	<i>fixnum</i>	bitwise complement
logor <i>fix fix'</i>	<i>fixnum</i>	bitwise or
mul <i>fix fix'</i>	<i>fixnum</i>	product
sub <i>fix fix'</i>	<i>fixnum</i>	difference

floats

fadd <i>fl fl'</i>	<i>float</i>	sum
fdiv <i>fl fl'</i>	<i>float</i>	quotient
fless-than <i>fl fl'</i>	<i>bool</i>	<i>fl</i> < <i>fl'</i> ?
fmul <i>fl fl'</i>	<i>float</i>	product
fsub <i>fl fl'</i>	<i>float</i>	difference

conses/lists

append <i>list</i>	<i>list</i>	append lists
car <i>list</i>	<i>T</i>	head of <i>list</i>
cdr <i>list</i>	<i>T</i>	tail of <i>list</i>
cons <i>T T'</i>	<i>cons</i>	(<i>T</i> . <i>T'</i>)
length <i>list</i>	<i>fixnum</i>	length of <i>list</i>
nth <i>fix list</i>	<i>T</i>	<i>nth</i> car of <i>list</i>
nthcdr <i>fix list</i>	<i>T</i>	<i>nth</i> cdr of <i>list</i>

vectors

make-vector <i>key list</i>	<i>vector</i>	specialized <i>vector</i> from <i>list</i>
vector-length <i>vector</i>	<i>fixnum</i>	length of <i>vector</i>
vector-type <i>vector</i>	<i>key</i>	type of <i>vector</i>
suref <i>vector fix</i>	<i>T</i>	<i>nth</i> element

namespaces

defined namespaces: *mu*, *keyword*

make-namespace <i>str ns</i>	<i>ns</i>	make namespace
namespace-name <i>ns</i>	<i>string</i>	namespace name
intern <i>ns str value</i>	<i>symbol</i>	intern <i>symbol</i> in namespace
find-namespace <i>str ns</i>	<i>ns</i>	map <i>string</i> to namespace
find <i>ns string</i>	<i>symbol</i>	map <i>string</i> to <i>symbol</i>

structs

make-struct <i>key list</i>	<i>struct</i>	type <i>key</i> from <i>list</i>
struct-type <i>struct</i>	<i>key</i>	<i>struct</i> type <i>key</i>
struct-vec <i>struct</i>	<i>vector</i>	of <i>struct</i> members

streams

standard-input	<i>stream</i>	std input <i>stream</i>
standard-output	<i>stream</i>	std out <i>stream</i>
error-output	<i>stream</i>	std error <i>stream</i>
open <i>type dir str bool</i>	<i>stream</i>	open <i>stream</i> , raise error if <i>bool</i>
	<i>type</i> <i>dir</i>	<i>:file</i> <i>:string</i> <i>:input</i> <i>:output</i> <i>:bidir</i>
close <i>stream</i>	<i>bool</i>	close <i>stream</i>
openp <i>stream</i>	<i>bool</i>	is <i>stream</i> open?
flush <i>stream</i>	<i>bool</i>	flush <i>stream</i>
get-string <i>stream</i>	<i>string</i>	from <i>string stream</i>
read-byte <i>stream bool T</i>	<i>byte</i>	read <i>byte</i> from <i>stream</i> , error on eof, <i>T</i> : eof-value
read-char <i>stream bool T</i>	<i>char</i>	read <i>char</i> from <i>stream</i> , error on eof, <i>T</i> : eof-value
unread-char <i>char stream char</i>		push <i>char</i> onto <i>stream</i>
write-byte <i>byte stream</i>	<i>byte</i>	write <i>byte</i>
write-char <i>char stream</i>	<i>char</i>	write <i>char</i>
read <i>stream bool T</i>	<i>T</i>	read <i>stream</i>
write <i>T bool stream</i>	<i>T</i>	write with escape

exceptions	environment	Reader																																																						
<p>with-exception <i>fn fn' T</i> catch exception</p> <p><i>fn</i> - (:lambda (<i>obj cond src</i>) . <i>body</i>)</p> <p><i>fn'</i> - (:lambda () . <i>body</i>)</p> <p>raise <i>T keyword</i> raise exception on <i>T</i> with condition:</p> <p>:arity :div0 :eof :error :except :future :ns :open :over :quasi :range :read :exit :signal :stream :syntax :syscall :type :unbound :under :write :storage</p>	<p>JSON config format:</p> <pre>{ "pages": N, "gc-mode": "none" "auto", }</pre> <p>Mu library API</p> <pre>[dependencies] mu = { git = "https://github.com/Software-Knife-and-Tool/mu.git", branch = "main" }</pre> <p>use mu::({ Condition, Core, Env, Exception, Mu, Result, Tag });</p> <pre>impl Mu { fn apply(_: &Env, _: Tag, _: Tag) → Result<Tag> fn compile(_: &Env, _: Tag) → Result<Tag> fn config(_: Option<String>) → Option<Config> fn core() → &Core fn eq(_: Tag, _: Tag) → bool; fn err_out() → Tag fn eval_str(_: &Env, _: &str) → Result<Tag> fn eval(_: &Env, _: Tag) → Result<Tag> fn exception_string(_: &Env, _: Exception) → String fn load(_: &Env, _: &str) → Result<bool> fn make_env(_: &Config) → Env fn read_str(_: &Env, _: &str) → Result<Tag> fn read(_: &Env, _: Tag, _: bool, _: Tag) → Result<Tag> fn std_in() → Tag fn std_out() → Tag fn version() → &str fn write_str(_: &Env, _: &str, _: Tag) → Result<()> fn write_to_string(_: &Env, _: Tag, _: bool) → String fn write(_: &Env, _: Tag, _: bool, _: Tag) → Result<()> }</pre>	<p>;</p> <p># ... #</p> <p><i>'form</i> <i>`form</i> <i>`(...)</i> <i>.form</i> <i>,@form</i></p> <p>(...) () (... . .) "..." </p> <p>#*</p> <p>#X</p> <p>#.</p> <p>#\ #(:type ...) #s(:type ...) #:</p> <p>"` , ; #</p> <p>!\$%&*+- . <=>=?@[: ^ _ { } ~ / A..Za..z 0..9</p> <p>0x09 #\tab 0x0a #\linefeed 0x0c #\page 0x0d #\return 0x20 #\space</p>																																																						
Features	mu-sys																																																							
<pre>[dependencies] default = ["core", "env", "system"]</pre> <p>mu/core</p> <table> <tr> <td>core</td><td><i>list</i></td><td>core state</td></tr> <tr> <td>delay</td><td><i>fixnum</i></td><td>microseonds</td></tr> <tr> <td>process-mem-virt</td><td><i>fixnum</i></td><td>vmem</td></tr> <tr> <td>process-mem-res</td><td><i>fixnum</i></td><td>reserve</td></tr> <tr> <td>process-time</td><td><i>fixnum</i></td><td>microseconds</td></tr> <tr> <td>time-units-per-sec</td><td><i>fixnum</i></td><td></td></tr> <tr> <td>ns-symbols ns :nil</td><td><i>list</i></td><td><i>symbol</i> list</td></tr> </table> <p>mu/env</p> <table> <tr> <td>env</td><td><i>list</i></td><td>env state</td></tr> <tr> <td>heap-info</td><td>()</td><td>heap info to stdout</td></tr> <tr> <td>heap-room</td><td><i>vector</i></td><td>allocations</td></tr> <tr> <td>heap-size keyword</td><td><i>fixnum</i></td><td>type size</td></tr> <tr> <td>cache-room</td><td><i>vector</i></td><td>allocations</td></tr> <tr> <td>cache-size keyword</td><td><i>fixnum</i></td><td>type size</td></tr> </table> <p>mu/system</p> <table> <tr> <td>uname</td><td></td><td>system info</td></tr> <tr> <td>shell string list</td><td><i>fixnum</i></td><td>shell command</td></tr> <tr> <td>exit fixnum</td><td></td><td></td></tr> <tr> <td>sysinfo</td><td></td><td>not on macOS</td></tr> </table> <p>mu/prof</p> <table> <tr> <td>prof-control key</td><td>key vec</td><td>:on :off :get</td></tr> </table>	core	<i>list</i>	core state	delay	<i>fixnum</i>	microseonds	process-mem-virt	<i>fixnum</i>	vmem	process-mem-res	<i>fixnum</i>	reserve	process-time	<i>fixnum</i>	microseconds	time-units-per-sec	<i>fixnum</i>		ns-symbols ns :nil	<i>list</i>	<i>symbol</i> list	env	<i>list</i>	env state	heap-info	()	heap info to stdout	heap-room	<i>vector</i>	allocations	heap-size keyword	<i>fixnum</i>	type size	cache-room	<i>vector</i>	allocations	cache-size keyword	<i>fixnum</i>	type size	uname		system info	shell string list	<i>fixnum</i>	shell command	exit fixnum			sysinfo		not on macOS	prof-control key	key vec	:on :off :get	<p>comment to end of line block comment</p> <p>quoted form backquoted form backquoted list (proper lists) eval backquoted form eval-splice backquoted form</p> <p>constant <i>list</i> empty <i>list</i>, prints as :nil dotted <i>list</i> <i>string</i>, <i>char</i> vector single escape in strings</p> <p>bit vector hexadecimal <i>fixnum</i> read-time eval <i>char</i> <i>vector</i> <i>struct</i> uninterned <i>symbol</i></p> <p>terminating macro char non-terminating macro char</p> <p>symbol constituent</p> <p>character designators</p>	
core	<i>list</i>	core state																																																						
delay	<i>fixnum</i>	microseonds																																																						
process-mem-virt	<i>fixnum</i>	vmem																																																						
process-mem-res	<i>fixnum</i>	reserve																																																						
process-time	<i>fixnum</i>	microseconds																																																						
time-units-per-sec	<i>fixnum</i>																																																							
ns-symbols ns :nil	<i>list</i>	<i>symbol</i> list																																																						
env	<i>list</i>	env state																																																						
heap-info	()	heap info to stdout																																																						
heap-room	<i>vector</i>	allocations																																																						
heap-size keyword	<i>fixnum</i>	type size																																																						
cache-room	<i>vector</i>	allocations																																																						
cache-size keyword	<i>fixnum</i>	type size																																																						
uname		system info																																																						
shell string list	<i>fixnum</i>	shell command																																																						
exit fixnum																																																								
sysinfo		not on macOS																																																						
prof-control key	key vec	:on :off :get																																																						