libenv Reference

lib namespace, version 0.1.48

Type Keywords and aliases

supertype bool condition list frame ns	T (),:nil are false keyword, see Ex cons or (),:nil cons, see Frame keyword or (), see	ception
<pre>:null :char :cons :fixnum :float :func :keyword :stream :struct :symbol :vector</pre>	(),:nil char cons fixnum, fix float, fl function, fn keyword, key stream, strm struct symbol, sym vector, string, st :char:t:byte	56 bit signed integer 32 bit IEEE float function symbol file or string type typed vector LISP-1 symbol r :fixnum :float

Неар

hp-info	<pre>vector heap static information #(:t type pages pagesize)</pre>
hp-stat	<pre>vector heap allocations #(:t : type size total free</pre>

hp-size *T fixnum* heap occupancy in bytes

Frame

frames

frame binding: (fn . #(:t ...))
list active frame binding list

 $\begin{array}{lll} \textbf{fr-pop} \ \textit{fn} & \textit{fn}, & \textit{pop} \ \textit{function's} \ \textit{top} \\ \textbf{frame} \ \textit{binding} \\ \textbf{fr-push} \ \textit{frame} \ \textit{cons} \\ \textbf{fr-ref} \ \textit{fix} \ \textit{fx} & T & \textit{frame} \ \textit{id}, \ \textit{offset} \\ \end{array}$

Symbol

boundp sym	bool	is <i>symbol</i> bound?
keyword str	key	keyword from string
symbol str	symbol	uninterned symbol
sy-ns sym	key	symbol namespace
sy-name sym	string	symbol name binding
sy-val sym	T	symbol value binding

Special Forms

:lambda list .	list'	
	functi	on anonymous function
:quote form	list	quoted form
: if form TT'	T	conditional

Core

apply fn list	T	apply function to list
eval form	T	evaluate <i>form</i>
eq T T'	bool	are T and T'identical?
type-of T	keywo	rd

compile formTmu form compiview formvectorvector of objectutimefixnumelapsed time us	
---	--

repr type T T tag representation

type - :t :vector

if type is :vector, return 8 byte byte vector of argument tag bits, otherwise convert argument byte vector to tag.

 $\begin{array}{lll} \textbf{fix} \, fn \, form & T & \text{fixpoint of} \, function \, \text{on} \, form \\ \textbf{gc} \, bool & bool & \text{garbage collection, verbose} \end{array}$

version *string* type *symbol*, version string

Future

fapply fn list	struct	future application
fwait struct	T	wait for completion
fpoll struct	bool	poll completion

Fixnum

fx-mul <i>fix fix</i> '	fixnum	product
fx-add fix fix'	fixnum	sum
fx-sub <i>fix fix'</i>	fixnum	difference
fx-lt fix fix'	bool	fix < fix?
fx-div fix fix'	fixnum	quotient
ash fix fix'	fixnum	arithmetic shift
logand fix fix'	fixnum	bitwise and
logor fix fix'	fixnum	bitwise or
lognot fix	fixnum	bitwise complement

Float

fl-mul <i>fl fl'</i>	float	product
fl-add <i>fl fl</i> '	float	sum
fl-sub <i>fl fl'</i>	float	difference
fl-lt fl fl'	bool	<i>fl</i> < <i>fl</i> '?
fl-div fl fl'	float	quotient

Conses/Lists

append list T	list	append
car list	list	head of <i>list</i>
cdr list	T	tail of <i>list</i>
$\mathbf{cons}\ T\ T'$	cons	(form.form')
length list	fixnum	length of <i>list</i>
nth fix list	T	nth car of list
nthcdr fix list	T	nth cdr of list

Vector

specialized vector from list
length of vector
<i>n</i> th element
type of <i>vector</i>

Reader/Printer

read $strm\ bool\ T \rightarrow T$	read stream object
write T bool $strm \rightarrow T$	write escaped object

Struct

struct key list	struct	of type key from list
st-type struct	key	struct type keyword
st-vec struct	vector	of struct members

Exception with-ex fn fn' Tcatch exception fn - (:lambda (obj cond src) . body) fn'-(:lambda () , body) raise T keuword raise exception with condition :open :read :syscall :arity :eof :write :error :syntax:type :sigint :stream:range :except :future :div0 :ns :over :under :unbound Stream std-in symbol standard input stream std-out symbol standard output stream

flush stream bool flush output steam **get-str** stream string from string stream

rd-byte stream bool T

byte read byte from stream, error on eof, T: eof value

rd-char stream bool T char

read *char* from *stream*, error on eof, *T*: eof value

un-char char stream char

push *char* onto *stream*

 $\mathbf{wr\text{-}byte}\ byte\ stream$

byte

write bute to stream

wr-char char stream char

write char to stream

Namespace

```
make-ns ns
               keu
                       make namespace
ns-map
               list
                       list of mapped namespaces
unbound ns string
               symbol intern unbound symbol
intern ns string value
               sumbol intern bound symbol
ns-find ns string
               symbol map string to symbol
ns-syms type ns
                       namespace's symbols
                       - :list :vector
               type
```

Features

```
[dependencies]
default = [ "nix", "std", "sysinfo" ]
```

[dependencies]

libenv API

```
git = "https://github.com/Software-Knife-and-Tool/mu.git"
  branch=main
use libenv::{Condition, Config, Env, Exception, Result, Tag}
config string format: "npages:N,gcmode:GCMODE"
       GCMODE - { none, auto, demand }
If the signal_exception() interface is called, ^C will
generate a :sigint exception.
impl Env {
 const VERSION: &str
  fn signal exception()
  fn config(config: Option < String >) \rightarrow Option < Config >
  fn new(config: &Config) → Mu
  fn apply(&self, func: Tag, args: Tag) → Result<Tag>
  fn compile(&self, form: Tag) → Result<Tag>
  fn eq(&self, func: Tag, args: Tag) → bool;
  fn exception_string(&self, ex: Exception) → String
  fn eval(&self, exp: Tag) → Result<Tag>
  fn eval_str(&self, exp: &str) → Result<Tag>
  fn load(&self, file_path: &str) → Result<bool>
  fn load image(&self, path: &str) → Result<bool>;
  fn read(&self, st: Tag, eofp: bool, eof: Tag) → Result<Tag>
  fn read_str(&self, str: &str) → Result<Tag>
  fn save_and_exit(&self, path: &str) → Result<bool>
  fn err_out(&self) → Tag
  fn std_in(&self) → Tag
  fn std out(&self) → Tag
  fn write(&self, exp: Tag, esc: bool, st: Tag) → Result<()>
  fn write_str(&self, str: &str, st: Tag) → Result<()>
  fn write_to_string(&self, exp: Tag, esc: bool) → String
```

Reader Syntax

```
comment to end of line
#|...|#
                 block comment
'form
                 quoted form
                 backquoted form
`form
 (...)
                 backguoted list (proper lists only)
, form
                 eval backquoted form
                 eval-splice backquoted form
, @form
(...)
                 constant list
()
                 empty list, prints as : nil
(... . .)
                 dotted list
                 string, char vector
                 single escape in strings
                 hexadecimal fixnum
#x
#\c
                 char
#(:type ...)
                 vector
#s(:type ...)
                 struct
                 uninterned symbol
#:symbol
                 terminating macro char
                 non-terminating macro char
!$%&*+-.
                 symbol constituents
<>=?@[]|
:^ {}~/
A..Za..z
0..9
0x09 #\tab
                 whitespace
0x0a #\linefeed
0x0c #\page
0x0d #\return
0x20 #\space
```

Runtime

```
mu-sys: x.y.z: [-h?pvcelq0] [file...]
?: usage message
h: usage message
c: [name:value,...]
e: eval [form] and print result
l: load [path]
p: pipe mode (no repl)
q: eval [form] quietly
v: print version and exit
0: null terminate
```