

Mu Runtime Reference

version 0.2.19

type keywords and aliases

<i>supertype</i>	<i>T</i>	
<i>bool</i>	<code>()</code> , <code>:nil</code>	are false, otherwise true
<i>condition</i>	<i>keyword</i> , see exceptions	
<i>list</i>	<code>:cons</code> or <code>()</code> , <code>:nil</code>	
<i>ns</i>	<code>#s(:ns #(:t fixnum symbol))</code>	
<i>ns-designator</i>	<i>ns</i>	
<code>:null</code>	<code>()</code> , <code>:nil</code>	
<code>:char</code>	<i>char</i>	8 bit ASCII
<code>:cons</code>	<i>cons</i> , <i>list</i>	list, cons, dotted pair
<code>:fixnum</code>	<i>fixnum</i> , <i>fix</i>	56 bit signed integer
<code>:float</code>	<i>float</i> , <i>fl</i>	32 bit IEEE float
<code>:func</code>	<i>function</i> , <i>fn</i>	function
<code>:keyword</code>	<i>keyword</i> , <i>key</i>	symbol
<code>:stream</code>	<i>stream</i>	file or string type
<code>:struct</code>	<i>struct</i>	see structs
<code>:symbol</code>	<i>symbol</i> , <i>sym</i>	LISP-1 symbol
<code>:vector</code>	<i>vector</i> , <i>string</i> , <i>str</i>	typed vector
	<code>:bit</code> <code>:char</code> <code>:t</code>	
	<code>:byte</code> <code>:fixnum</code> <code>:float</code>	

core

apply <i>fn list</i>	<i>T</i>	apply <i>fn</i> to <i>list</i>
compile <i>form</i>	<i>T</i>	<i>mu</i> form compiler
eq <i>T T'</i>	<i>bool</i>	<i>T</i> and <i>T'</i> identical?
eval <i>form</i>	<i>T</i>	evaluate <i>form</i>
type-of <i>T</i>	<i>key</i>	type keyword
view <i>for</i>	<i>vector</i>	vector of object
fix <i>fn T</i>	<i>T</i>	fixpoint of <i>fn</i>
gc	<i>bool</i>	garbage collection
repr <i>T</i>	<i>vector</i>	tag representation
unrepr <i>vector</i>	<i>T</i>	tag representation

tag *vector* is an 8 element `:byte` vector of little-endian argument tag bits.

special forms

<code>:lambda</code> <i>list . list'</i>	<i>function</i>	anonymous <i>fn</i>
<code>:lambda</code> <i>list . list'</i>	<i>function</i>	anonymous <i>fn</i>
<code>:quote</code> <i>T</i>	<i>list</i>	quoted form
<code>:if</code> <i>T T' T''</i>	<i>T</i>	conditional

frames

frame binding: `(fn . #(:t ...))`

%frame-stack	<i>list</i>	active frames
%frame-pop <i>fn</i>	<i>frame</i>	pop <i>function</i> 's top frame binding
%frame-push <i>frame</i>	<i>cons</i>	push frame
%frame-ref <i>fn fix</i>	<i>T</i>	<i>function</i> , offset

symbols

boundp <i>sym</i>	<i>bool</i>	is <i>symbol</i> bound?
make-symbol <i>string</i>	<i>sym</i>	uninterned <i>symbol</i>
symbol-namespace <i>sym</i>	<i>ns-designator</i>	namespace designator
symbol-name <i>symbol</i>	<i>string</i>	name binding
symbol-value <i>symbol</i>	<i>T</i>	value binding

fixnums

add <i>fix fix'</i>	<i>fixnum</i>	sum
ash <i>fix fix'</i>	<i>fixnum</i>	arithmetic shift
div <i>fix fix'</i>	<i>fixnum</i>	quotient
less-than <i>fix fix'</i>	<i>bool</i>	<i>fix</i> < <i>fix'</i> ?
logand <i>fix fix'</i>	<i>fixnum</i>	bitwise and
lognot <i>fix</i>	<i>fixnum</i>	bitwise complement
logor <i>fix fix'</i>	<i>fixnum</i>	bitwise or
mul <i>fix fix'</i>	<i>fixnum</i>	product
sub <i>fix fix'</i>	<i>fixnum</i>	difference

floats

fadd <i>fl fl'</i>	<i>float</i>	sum
fdiv <i>fl fl'</i>	<i>float</i>	quotient
fless-than <i>fl fl'</i>	<i>bool</i>	<i>fl</i> < <i>fl'</i> ?
fmul <i>fl fl'</i>	<i>float</i>	product
fsub <i>fl fl'</i>	<i>float</i>	difference

conses/lists

append <i>list</i>	<i>list</i>	append lists
car <i>list</i>	<i>T</i>	head of <i>list</i>
cdr <i>list</i>	<i>T</i>	tail of <i>list</i>
cons <i>T T'</i>	<i>cons</i>	(<i>T . T'</i>)
length <i>list</i>	<i>fixnum</i>	length of <i>list</i>
nth <i>fix list</i>	<i>T</i>	<i>nth</i> car of <i>list</i>
nthcdr <i>fix list</i>	<i>T</i>	<i>nth</i> cdr of <i>list</i>

vectors

make-vector <i>key list</i>	<i>vector</i>	specialized <i>vector</i> from <i>list</i>
vector-length <i>vector</i>	<i>fixnum</i>	length of <i>vector</i>
vector-type <i>vector</i>	<i>key</i>	type of <i>vector</i>
svref <i>vector fix</i>	<i>T</i>	<i>nth</i> element

namespaces

mu (static), **keyword**, **ns**: `#s(:ns #(:t str))`

make-namespace <i>str ns</i>	<i>ns</i>	make namespace
namespace-name <i>ns</i>	<i>string</i>	namespace name
intern <i>ns str value</i>	<i>symbol</i>	intern <i>symbol</i> in non-static namespace
find-namespace <i>str ns</i>	<i>ns</i>	map <i>string</i> to namespace
find <i>ns string</i>	<i>symbol</i>	map <i>string</i> to <i>symbol</i>

structs

make-struct <i>key list</i>	<i>struct</i>	type <i>key</i> from <i>list</i>
struct-type <i>struct</i>	<i>key</i>	<i>struct</i> type <i>key</i>
struct-vec <i>struct</i>	<i>vector</i>	of <i>struct</i> members

streams

standard-input	<i>stream</i>	std input <i>stream</i>
standard-output	<i>stream</i>	std out <i>stream</i>
error-output	<i>stream</i>	std error <i>stream</i>
open <i>type dir str bool</i>	<i>stream</i>	open <i>stream</i> , raise error if <i>bool</i>
	<i>type</i> <i>dir</i>	<code>:file</code> <code>:string</code> <code>:input</code> <code>:output</code> <code>:bidir</code>
close <i>stream</i>	<i>bool</i>	close <i>stream</i>
openp <i>stream</i>	<i>bool</i>	is <i>stream</i> open?
flush <i>stream</i>	<i>bool</i>	flush <i>stream</i>
get-string <i>stream</i>	<i>string</i>	from <i>string</i> <i>stream</i>
read-byte <i>stream bool T</i>	<i>byte</i>	read <i>byte</i> from <i>stream</i> , error on eof, <i>T</i> : eof-value
read-char <i>stream bool T</i>	<i>char</i>	read <i>char</i> from <i>stream</i> , error on eof, <i>T</i> : eof-value
unread-char <i>char stream char</i>		push <i>char</i> onto <i>stream</i>
write-byte <i>byte stream</i>	<i>byte</i>	write <i>byte</i>
write-char <i>char stream</i>	<i>char</i>	write <i>char</i>
read <i>stream bool T</i>	<i>T</i>	read <i>stream</i>
write <i>T bool stream</i>	<i>T</i>	write with escape

exceptions

with-exception *fn fn'* *T* catch exception

fn - (:lambda (*obj cond src*) . *body*)
fn' - (:lambda () . *body*)

raise *T T'* keyword

raise exception on *T* from
source designator *T'* with
keyword condition

:arity	:div0	:eof	:error	:except
:future	:ns	:open	:over	:quasi
:range	:read	:exit	:signal	:stream
:syntax	:syscall	:type	:unbound	:under
:write	:storage	:user		

Features

```
[features]
default = [ "core", "env", "system" ]
```

feature/core	core-info	<i>list</i>	core state
	process-fds	<i>list</i>	file descriptors
	process-mem-virt	<i>fixnum</i>	vmem
	process-mem-res	<i>fixnum</i>	reserve
	process-time	<i>fixnum</i>	microseconds
feature/env	time-units-per-sec	<i>fixnum</i>	
	sleep	<i>fixnum</i>	
		<i>()</i>	sleep for uses
	env-info	<i>list</i>	env info
	heap-info	<i>list</i>	list of heap info
	heap-room	<i>key vector</i>	allocations
		<i>#(:t size total free ...)</i>	
	heap-size	<i>key fixnum</i>	type size
	cache-room	<i>vector</i>	allocations
		<i>#(:t size total ...)</i>	
feature/system	load	<i>string bool</i>	load mu source
	symbols	<i>ns list</i>	ns symbol list
	uname	<i>:t</i>	system info
	shell	<i>string list fixnum</i>	shell command
feature/socket	exit	<i>fixnum</i>	doesn't return
	sysinfo	<i>:t</i>	not on macOS
	accept		
	bind		
	connect		
	getpeername		
	getsockname		
	getsockopt		
	listen		
	read		
	recv		
	select		
	send		
	shutdown		
	socket		
	socketpair		
	write		

environment config

JSON config format:

```
{
  "pages": N,
  "gc-mode": "none" | "auto",
}
```

Mu library API

```
[dependencies]
mu = {
  git =
    "https://github.com/Software-Knife-and-Tool/mu.git",
  branch = "main"
}

use mu::[ Mu, Env, Config ];
use mu::[ Result, Tag, Exception, Condition ];

impl Mu {
  fn compile(_: &Env, _: Tag) → Result<Tag>
  fn config(_: Option<String>) → Config
  fn env(_: &Config) → Env
  fn eq(_: Tag, _: Tag) → bool;
  fn err_out() → Tag
  fn eval_str(_: &Env, _: &str) → Result<Tag>
  fn eval(_: &Env, _: Tag) → Result<Tag>
  fn exception_string(_: &Env, _: Exception) → String
  fn load(_: &Env, _: &str) → Result<bool>
  fn env(_: &Config) → Env
  fn nil() → Tag
  fn read_str(_: &Env, _: &str) → Result<Tag>
  fn read(_: &Env, _: Tag, _: bool, _: Tag) → Result<Tag>
  fn std_in() → Tag
  fn std_out() → Tag
  fn version() → &str
  fn write_str(_: &Env, _: &str, _: Tag) → Result<()>
  fn write_to_string(_: &Env, _: Tag, _: bool) → String
  fn write(_: &Env, _: Tag, _: bool, _: Tag) → Result<()>
}
```

API reference:

```
compile &Env T → Result<Tag>
config Option<String> → Config
env &Config → Env
eq T T' → bool
err_out → Tag
eval_str &Env &str → Result<Tag>
eval &Env T → Result<Tag>
exception_string &Env Exception → String
load &Env &str → Result<bool>
env &Config → Env
nil → Tag
read_str &Env &str → Result<Tag>
read &Env stream bool eof-value → Result<Tag>
// bool - raise exception on end of stream
std_in → Tag
std_out → Tag
version → &str
write_str &Env &str stream → Result<()>
write_to_string &Env T bool → String
// bool - print escaped
write &Env T bool stream → Result<()>
// bool - print escape
```

Reader Syntax

;	comment to end of line
# ... #	block comment
'form	quoted form
`form	backquoted form
`(...)	backquoted list (proper lists)
.form	eval backquoted form
,@form	eval-splice backquoted form
(...)	constant <i>list</i>
()	empty <i>list</i> , prints as :nil
(... . .)	dotted <i>list</i>
"..."	<i>string</i> , <i>char</i> vector
	single escape in strings
ns:name	qualified <i>symbol</i> , where <i>ns</i> and <i>name</i> are <i>symbol constituents</i>
name	lexical <i>symbol</i>
##	bit vector
#X	hexadecimal <i>fixnum</i>
#.	read-time eval
#\	<i>char</i>
#(:type ...)	<i>vector</i>
#s(:type ...)	<i>struct</i>
#:...	uninterned <i>symbol</i>
"` , ;	terminating macro char
#	non-terminating macro char
!\$%&*+-.	<i>symbol constituent</i>
<=>?@[]	
:^_{ } ~ /	
A..Za..z	
0..9	
0x09 #\tab	character designators
0x0a #\linefeed	
0x0c #\page	
0x0d #\return	
0x20 #\space	