

# Mu Namespace

mu version 0.0.20

## Type keywords and aliases

<i>supertype</i>	<i>T</i> , object
<i>bool</i>	() , :nil is false, otherwise true
<i>condition</i>	keyword, see <b>Exceptions</b>
<i>type</i>	type-of returns keyword
<i>list</i>	cons or () , :nil
<i>frame</i>	see <b>Frames</b>
<i>string</i>	char vector

:null	() , :nil
:asyncid	async future id
:char	char
:cons	cons
:fixnum	fix, fixnum, 61 bit signed integer
:float	float, fl, 32 bit IEEE float
:func	fn, a function
:keyword	keyword symbol
:stream	stream, file or string type
:struct	struct
:symbol	sym, symbol
:vector	simple vector, string (:char) :t :byte :fixnum :float

## Heap

<b>hp-info</b>	vector, heap allocations #(:t type total alloc in-use)
----------------	---

<b>size-of</b> <i>T</i>	fixnum, size in bytes of object
-------------------------	---------------------------------

## Frames

frame binding: (fn . #(:t ...))

<b>frames</b>	list, active frame binding list
<b>fr-pop</b> <i>fn</i>	fn, pop function's top frame binding
<b>fr-push</b> <i>frame</i>	cons, push frame binding
<b>fr-ref</b> <i>fix fix</i>	<i>T</i> , frame id, offset

## Structs

<b>make-st</b>	keyword list struct, of type keyword from list
<b>st-type</b> <i>struct</i>	keyword, struct type keyword
<b>st-vec</b> <i>struct</i>	vector, of struct members

## Symbols

<b>boundp</b> <i>sym</i>	bool, is symbol bound?
<b>keyword</b> <i>string</i>	keyword from string
<b>make-sy</b> <i>string sym</i>	uninterned symbol
<b>sy-ns</b> <i>sym</i>	ns, symbol namespace
<b>sy-name</b> <i>sym</i>	string, symbol name binding
<b>sy-val</b> <i>sym</i>	<i>T</i> , value binding

## Special Forms

<b>:async</b> <i>fn . list</i>	:asyncid, create future context
<b>:lambda</b> <i>list . list'</i>	function, anonymous
<b>:quote</b> <i>form</i>	list, quoted form
<b>:if</b> <i>form fn' fn''</i>	<i>T</i> , conditional

## Core

<b>apply</b> <i>fn list</i>	<i>T</i> , apply function to list
<b>eval</b> <i>form</i>	<i>T</i> , evaluate form
<b>eq</b> <i>T T'</i>	bool, are <i>T</i> and <i>T'</i> identical?
<b>type-of</b> <i>T</i>	keyword

<b>*await</b> : async	<i>T</i> , return value of async future
<b>*abort</b> : async	<i>T</i> , abort future

<b>compile</b> <i>form</i>	<i>T</i> , library form compiler
<b>view</b> <i>form</i>	vector, vector of object
<b>repr</b> <i>bool T</i>	<i>T</i> , tag representation conversion: if <i>bool</i> is (), return 8 byte vector of argument tag bits, otherwise convert argument byte vector to tag

<b>fix</b> <i>fn form</i>	<i>T</i> , fixpoint of function on form
<b>*gc</b>	bool, garbage collection
<b>exit</b> <i>fix</i>	exit process with return code

## System

<b>real-tm</b> <i>T</i>	fixnum, system clock secs
<b>run-us</b> <i>T</i>	fixnum, process time $\mu$ s

## Fixnums

<b>fx-mul</b> <i>fix fix'</i>	fixnum, product
<b>fx-add</b> <i>fix fix'</i>	fixnum, sum
<b>fx-sub</b> <i>fix fix'</i>	fixnum, difference
<b>fx-lt</b> <i>fix fix'</i>	bool, <i>fix</i> < <i>fix'</i>
<b>fx-div</b> <i>fix fix'</i>	fixnum, quotient
<b>logand</b> <i>fix fix'</i>	fixnum, bitwise and
<b>logor</b> <i>fix fix'</i>	fixnum, bitwise or

## Floats

<b>fl-mul</b> <i>fl fl'</i>	float, product
<b>fl-add</b> <i>fl fl'</i>	float, sum
<b>fl-sub</b> <i>fl fl'</i>	float, difference
<b>fl-lt</b> <i>fl fl'</i>	bool, <i>fl</i> < <i>fl'</i>
<b>fl-div</b> <i>fl fl'</i>	float, quotient

## Conses and Lists

<b>%append</b> <i>list T</i>	list, append
<b>car</b> <i>list</i>	list, head of list
<b>cdr</b> <i>list</i>	<i>T</i> , tail of list
<b>cons</b> <i>form form'</i>	cons, (form . form')
<b>length</b> <i>list</i>	fixnum, length of list
<b>nth</b> <i>fix list</i>	<i>T</i> , nth car of list
<b>nthcdr</b> <i>fix list</i>	<i>T</i> , nth cdr of list

## Vectors

<b>make-sv</b>	keyword list vector, typed vector of list
<b>sv-len</b> <i>vector</i>	fixnum, length of vector
<b>sv-ref</b> <i>vector fix T</i>	<i>T</i> , nth element
<b>sv-type</b> <i>vector</i>	keyword, type of vector

## Exceptions

<b>with-ex</b> <i>fn fn' T</i>	catch exception <i>fn</i> - (:lambda (obj cond src) . body) <i>fn'</i> - (:lambda () . body)
--------------------------------	--

<b>raise</b> <i>T keyword</i>	raise exception with condition:
-------------------------------	---------------------------------

:arity	:eof	:open	:read
:write	:error	:syntax	:type
:div0	:stream	:range	:except
:ns	:unbound		

## Reader/Printer

**read** *stream* *bool T*  
*T*, read stream object  
**write** *T* *bool stream*  
*T*, write escaped object

## Streams

**std-in** *symbol*, standard input *stream*  
**std-out** *symbol*, standard output *stream*  
**err-out** *symbol*, standard error *stream*

**open** *type* *direction* *string*  
*stream*, open *stream*  
*type* - :file :string  
*direction* - :input :output

**close** *stream* *bool*, close *stream*  
**openp** *stream* *bool*, is *stream* open?  
**eof** *stream* *bool*, is *stream* at end of file?  
**flush** *stream* *bool*, flush output steam  
**get-str** *stream* *string*, from *string* *stream*

**rd-byte** *stream* *bool T*  
*byte*, read *byte* from *stream*,  
*bool*: error on eof, *T*: eof value

**rd-char** *stream* *bool T*  
*char*, read *char* from *stream*,  
*bool*: error on eof, *T*: eof value

**un-char** *char* *stream*  
*char*, push *char* onto *stream*

**wr-byte** *byte* *stream*  
*byte*, write *byte* to *stream*

**wr-char** *char* *stream*  
*char*, write *char* to *stream*

## Namespaces

**make-ns** *keyword*  
*keyword*, make namespace

**untern** *keyword* *string*  
*symbol*, intern unbound symbol

**intern** *keyword* *string* *value*  
*symbol*, intern bound symbol

**ns-find** *keyword* *string*  
*symbol*, map *string* to *symbol*

**ns-syms** *keyword*  
*list*, namespace's symbols

## library API

```
[dependencies]
mu = { git =
  "https://github.com/Software-Knife-and-Tool/thorn.git",
  branch=main }
```

```
use mu::{Condition, Exception, Mu, Result, System, Tag}
```

```
const Mu::VERSION: &str
```

```
Mu::new(config: String)-> Mu
Mu::apply(&self, func: Tag, args: Tag)-> Result
Mu::eq(&self, func: Tag, args: Tag) -> Result
Mu::eval(&self, expr: Tag) -> Result
Mu::compile(&self, form: Tag) -> Result
Mu::read(&self, stream: Tag, eofp: bool, value: Tag) -> Result
Mu::write(&self, form: Tag, esc: bool, stream: Tag) -> Result
Mu::get_string(&self, stream: Tag) -> Result
Mu::write_string(&self, str: String, stream: Tag) -> Result
Mu::from_u64(&self, tag: u64) -> Tag
Mu::as_u64(&self, tag: Tag) -> u64
Mu::std_in(&self) -> Tag
Mu::std_out(&self) -> Tag
Mu::err_out(&self) -> Tag
```

```
System::new(config: String)-> System
System::mu(&self)-> &Mu
System::version(&self) -> String
System::eval(&self, expr: &String) -> Result
System::error(&self, ex: Exception) -> String
System::read(&self, string: String) -> Result
System::write(&self, expr: Tag, escape: bool) -> String
System::load(&self, file_path: &String) -> Result
```

## Reader Syntax

;  
#|...|# comment to end of line  
block comment  
  
'form quoted form  
  
`form backquoted form  
`(...) backquoted list (proper lists only)  
,form eval backquoted form  
,@form eval-splice backquoted form  
  
(...) constant list  
( ) empty list, prints as :nil  
(... . .) dotted list

"..." string, char vector  
\ single escape in strings

#x hexadecimal fixnum  
#\c char  
#(:type ...) vector  
#s(:type ...) struct  
#:symbol uninterned symbol

"` , ; terminating macro char  
# non-terminating macro char

!\$%&\*+- . symbol constituents  
<=>?@[| |  
: ^ \_ { } ~ /  
A . . Z a . . z  
0 . . 9

0x09 #\tab whitespace  
0x0a #\linefeed  
0x0c #\page  
0x0d #\return  
0x20 #\space

## Runtime

```
runtime: x.y.z: [-h?pvcdlq] [file...]
```

```
? : usage message
h : usage message
c : [name:value,...]
d : enable debugging
e : eval [form] and print result
l : load [path]
p : pipe mode (no repl)
q : eval [form] quietly
v : print version and exit
```