

# Mu Namespace

mu version 0.0.21

## Type keywords and aliases

<i>supertype</i>	<i>T</i> , object
<i>bool</i>	() , :nil is false, otherwise true
<i>condition</i>	keyword, see <b>Exceptions</b>
<i>type</i>	type-of returns keyword
<i>list</i>	cons or () , :nil
<i>frame</i>	see <b>Frames</b>
<i>string</i>	char vector
:null	() , :nil
:asyncid	async future id
:char	char
:cons	cons
:fixnum	fix, fixnum, 56 bit signed integer
:float	float, fl, 32 bit IEEE float
:func	fn, a function
:keyword	keyword symbol
:map	map object
:stream	stream, file or string type
:struct	struct
:symbol	sym, symbol
:vector	simple vector, string (:char) :t :byte :fixnum :float

## Heap

<b>hp-info</b>	vector, heap allocations #(:t type total alloc in-use)
<b>size-of</b> <i>T</i>	fixnum, size in bytes of object

## Frame

frame binding: (fn . #(:t ...))

<b>frames</b>	list, active frame binding list
<b>fr-pop</b> <i>fn</i>	fn, pop function's top frame binding
<b>fr-push</b> <i>frame</i>	cons, push frame binding
<b>fr-ref</b> <i>fix fix</i>	<i>T</i> , frame id, offset

## Struct

<b>make-st</b>	keyword list struct, of type keyword from list
<b>st-type</b> <i>struct</i>	keyword, struct type keyword
<b>st-vec</b> <i>struct</i>	vector, of struct members

## Symbol

<b>boundp</b> <i>sym</i>	bool, is symbol bound?
<b>keyword</b> <i>string</i>	keyword from string
<b>make-sy</b> <i>string</i>	sym, uninterned symbol
<b>sy-ns</b> <i>sym</i>	ns, symbol namespace
<b>sy-name</b> <i>sym</i>	string, symbol name binding
<b>sy-val</b> <i>sym</i>	<i>T</i> , value binding

## Special Forms

<b>:async</b> <i>fn . list</i>	:asyncid, create future context
<b>:lambda</b> <i>list . list'</i>	function, anonymous
<b>:quote</b> <i>form</i>	list, quoted form
<b>:if</b> <i>form fn' fn''</i>	<i>T</i> , conditional

## Core

<b>apply</b> <i>fn list</i>	<i>T</i> , apply function to list
<b>eval</b> <i>form</i>	<i>T</i> , evaluate form
<b>eq</b> <i>T T'</i>	bool, are <i>T</i> and <i>T'</i> identical?
<b>type-of</b> <i>T</i>	keyword

<b>*await</b> : async	<i>T</i> , return value of async future
<b>*abort</b> : async	<i>T</i> , abort future

<b>compile</b> <i>form</i>	<i>T</i> , library form compiler
<b>view</b> <i>form</i>	vector, vector of object

<b>repr</b> <i>bool T</i>	<i>T</i> , tag representation conversion: if <i>bool</i> is (), return 8 byte vector of argument tag bits, otherwise convert argument byte vector to tag
---------------------------	---

<b>fix</b> <i>fn form</i>	<i>T</i> , fixpoint of function on form
<b>*gc</b>	bool, garbage collection
<b>exit</b> <i>fix</i>	exit process with return code

## Fixnum

<b>fx-mul</b> <i>fix fix'</i>	fixnum, product
<b>fx-add</b> <i>fix fix'</i>	fixnum, sum
<b>fx-sub</b> <i>fix fix'</i>	fixnum, difference
<b>fx-lt</b> <i>fix fix'</i>	bool, fix < fix'
<b>fx-div</b> <i>fix fix'</i>	fixnum, quotient
<b>logand</b> <i>fix fix'</i>	fixnum, bitwise and
<b>logor</b> <i>fix fix'</i>	fixnum, bitwise or

## Float

<b>fl-mul</b> <i>fl fl'</i>	float, product
<b>fl-add</b> <i>fl fl'</i>	float, sum
<b>fl-sub</b> <i>fl fl'</i>	float, difference
<b>fl-lt</b> <i>fl fl'</i>	bool, fl < fl'
<b>fl-div</b> <i>fl fl'</i>	float, quotient

## Conses and Lists

<b>%append</b> <i>list T</i>	list, append
<b>car</b> <i>list</i>	list, head of list
<b>cdr</b> <i>list</i>	list, tail of list
<b>cons</b> <i>form form'</i>	cons, (form . form')
<b>length</b> <i>list</i>	fixnum, length of list
<b>nth</b> <i>fix list</i>	<i>T</i> , nth car of list
<b>nthcdr</b> <i>fix list</i>	<i>T</i> , nth cdr of list

## Vector

<b>make-sv</b>	keyword list vector, typed vector of list
<b>sv-len</b> <i>vector</i>	fixnum, length of vector
<b>sv-ref</b> <i>vector fix T</i>	<i>T</i> , nth element
<b>sv-type</b> <i>vector</i>	keyword, type of vector

## Map

<b>make-mp</b>	map, make a new map
<b>map</b> <i>map T T'</i>	map, add to map
<b>mp-ref</b> <i>map T</i>	<i>T</i> , reference map
<b>mp-len</b> <i>map</i>	fixnum, size of map

## System

<b>real-tm</b> <i>T</i>	fixnum, system clock secs
<b>run-us</b> <i>T</i>	fixnum, process time $\mu$ s

## Exception

**with-ex** *fn fn' T*, catch exception  
*fn* - (:lambda (*obj cond src*) . *body*)  
*fn'* - (:lambda () . *body*)

**raise** *T keyword*  
 raise exception with *condition*:

```
:arity :eof :open :read
:write :error :syntax :type
:div0 :stream :range :except
:ns :unbound
```

## Stream

**std-in** *symbol*, standard input *stream*  
**std-out** *symbol*, standard output *stream*  
**err-out** *symbol*, standard error *stream*

**open** *type direction string*  
*stream*, open *stream*  
*type* - :file :string  
*direction* - :input :output

**close** *stream bool*, close *stream*  
**openp** *stream bool*, is *stream* open?  
**eof** *stream bool*, is *stream* at end of file?  
**flush** *stream bool*, flush output *stream*

**get-str** *stream string*, from *string stream*

**rd-byte** *stream bool T*  
*byte*, read *byte* from *stream*,  
*bool*: error on eof, *T*: eof value

**rd-char** *stream bool T*  
*char*, read *char* from *stream*,  
*bool*: error on eof, *T*: eof value

**un-char** *char stream*  
*char*, push *char* onto *stream*

**wr-byte** *byte stream*  
*byte*, write *byte* to *stream*

**wr-char** *char stream*  
*char*, write *char* to *stream*

## Namespace

**make-ns** *keyword*  
*keyword*, make namespace

**untern** *keyword string*  
*symbol*, intern unbound *symbol*

**intern** *keyword string value*  
*symbol*, intern bound *symbol*

**ns-find** *keyword string*  
*symbol*, map *string* to *symbol*

**ns-syms** *keyword*  
*list*, namespace's *symbols*

## Reader/Printer

**read** *stream bool T*  
*T*, read *stream* object  
**write** *T bool stream*  
*T*, write escaped object

## library API

```
[dependencies]
mu = { git =
  "https://github.com/Software-Knife-and-Tool/thorn.git",
  branch=main }
```

```
use mu::{Condition, Exception, Mu, Result, System, Tag}
```

```
const Mu::VERSION: &str
```

```
Mu::new(config: String)-> Mu
Mu::apply(&self, func: Tag, args: Tag)-> Result
Mu::eq(&self, func: Tag, args: Tag) -> Result
Mu::eval(&self, expr: Tag) -> Result
Mu::compile(&self, form: Tag) -> Result
Mu::read(&self, stream: Tag, eofp: bool, value: Tag) -> Result
Mu::write(&self, form: Tag, esc: bool, stream: Tag) -> Result
Mu::get_string(&self, stream: Tag) -> Result
Mu::write_string(&self, str: String, stream: Tag) -> Result
Mu::from_u64(&self, tag: u64) -> Tag
Mu::as_u64(&self, tag: Tag) -> u64
Mu::std_in(&self) -> Tag
Mu::std_out(&self) -> Tag
Mu::err_out(&self) -> Tag
```

```
System::new(config: String)-> System
System::mu(&self)-> &Mu
System::version(&self) -> String
System::eval(&self, expr: &String) -> Result
System::error(&self, ex: Exception) -> String
System::read(&self, string: String) -> Result
System::write(&self, expr: Tag, escape: bool) -> String
System::load(&self, file_path: &String) -> Result
```

## Reader Syntax

```
; comment to end of line
#|...|# block comment

'form quoted form

`form backquoted form
`(...) backquoted list (proper lists only)
,form eval backquoted form
,@form eval-splice backquoted form

(...) constant list
() empty list, prints as :nil
(...) dotted list
```

```
"..." string, char vector
\ single escape in strings
```

```
#x hexadecimal fixnum
#\c char
#(:type ...) vector
#s(:type ...) struct
#:symbol uninterned symbol
```

```
"` , ; terminating macro char
# non-terminating macro char
```

```
!$%&*+-. symbol constituents
<=>?@[|
: ^_{ } ~ /
A..Za..z
0..9
```

```
0x09 #\tab whitespace
0x0a #\linefeed
0x0c #\page
0x0d #\return
0x20 #\space
```

## Runtime

```
runtime: x.y.z: [-h?pvcdlq] [file...]
```

```
? : usage message
h : usage message
c : [name:value,...]
d : enable debugging
e : eval [form] and print result
l : load [path]
p : pipe mode (no repl)
q : eval [form] quietly
v : print version and exit
```