

jStar Eclipse tutorial

September 24, 2010

1 Installation

Prerequisites:

- JDK 6 (not JRE since it does not have a compiler needed for annotation processing). You can specify it in eclipse.ini:

Windows Example

```
-vm  
C:\Java\JDK\1.6\bin\javaw.exe
```

Linux Example

```
-vm  
/opt/sun-jdk-1.6.0.02/bin/java
```

Mac Example

```
-vm  
/System/Library/Frameworks/JavaVM.framework/Versions/1.6.0/Home/bin/java
```

For more information go to <http://wiki.eclipse.org/Eclipse.ini>


Two ways:

1. Add the jar file **plugin.jar/com.jstar.eclipse_1.0.0.x.jar** to **eclipse/dropins/** folder and restart Eclipse.
2. **Need to create an update site.**

2 Configuration

2.1 Windows with cygwin

Go to Windows → Preferences → jStar and set the required directories.



rt.jar could be found in jdk1.6.0/jre/lib/. It is required library for soot. The plugin will try to find it automatically.

2.2 Linux

rt.jar could be found in jdk1.6.0/jre/lib/. It is required library for soot. The plugin will try to find it automatically.


2.3 Mac

classes.jar and ui.jar could be found in /System/Library/Frameworks/JavaVM.framework/Versions/1.6.0/Classes/. They are required libraries for soot. The plugin will try to find them automatically.

3 Verification

You can verify source file by selecting **Verify with jStar** from the context menu or the main toolbar.

By selecting **Verify with jStar Configurations...**, you can indicate the location of specification, logic and abstraction rules.



Specification in source file

If you want to write specification in the source file, you need to add annotations.jar (can be found in com.jstar.eclipse/jar files/annotations) to your project Java Build Path. More information about annotations could be found in 4 .

Verification errors

In case there are some verification errors, you can see error messages in console. The lines in source code where the problem appeared are annotated as squiggly marks.



4 Annotation Processing

Annotations

- `@Import` has one element `String[] value`. This annotation can be used to annotate only type declarations.
- `@Predicate` is used for `define` and `export` statements. It has three elements: `String predicate`, `String formula`, `DefinitionType type`. `DefinitionType` is enum with two values `Define` and `Export`. The default value of type is `DefinitionType.Define`. This annotation can be used to annotate only type declarations.
- `@Predicates` is used if you want to have more than one `define` and/or `export` statements. It has one element `Predicate[] value`. This annotation can be used to annotate only type declarations.
- `@InitSpec` is a (dynamic / both static and dynamic) specification for constructor which is not explicitly defined in the source code. It has two elements: `String pre`, `String post`. This annotation can be used to annotate only type declarations.
- `@InitSpecs` is (dynamic / both static and dynamic) specifications which are conjuncted with `also` for constructor which is not explicitly defined in the source code. It has one element `InitSpec[] value`. This annotation can be used to annotate only type declarations.
- `@InitSpecStatic` is a static specification for constructor which is not explicitly defined in the source code. It has two elements: `String pre`, `String post`. This annotation can be used to annotate only type declarations.
- `@InitSpecsStatic` is static specifications which are conjuncted with `also` for constructor which is not explicitly defined in the source code. It has one element `InitSpecStatic[] value`. This annotation can be used to annotate only type declarations.
- `@Spec` is a (dynamic / both static and dynamic) specification for a method or a constructor. It has two elements: `String pre`, `String post`. This annotation can be used to annotate only method and constructor declarations.
- `@Specs` is (dynamic / both static and dynamic) specifications which are conjuncted with `also` for a method or a constructor. It has one element: `Spec[] value`. This annotation can be used to annotate only method and constructor declarations.
- `@SpecStatic` is a static specification for a method or a constructor. It has two elements: `String pre`, `String post`. This annotation can be used to annotate only method and constructor declarations.

- `@SpecsStatic` is static specifications which are conjuncted with `also` for a method or a constructor. It has one element: `SpecStatic[]` value. This annotation can be used to annotate only method and constructor declarations.

Examples of annotations in the source code:

Annotation in source file	Generated specification file
<code>@Import("Spec.spec")</code>	<code>import("Spec.spec");</code>
<code>@Import({"Spec1.spec", "Spec2.spec"})</code>	<code>import("Spec1.spec"); import("Spec2.spec");</code>
<code>@Predicate(predicate = "P(x)", formula = "F(x)")</code>	<code>define P(x) as F(x);</code>
<code>@Predicate(predicate = "P(x)", formula = "F(x)", type = DefinitionType.Export)</code>	<code>export P(x) as F(x);</code>
<code>@Predicates(@Predicate(predicate = "P1(x)", formula = "F1(x)", type = DefinitionType.Export), @Predicate(predicate = "P2(x)", formula = "F2(x)"))</code>	<code>export P1(x) as F1(x); define P2(x) as F2(x);</code>

```
@InitSpec(
    pre = "precondition",
    post = "postcondition"
)
```

```
@InitSpecs({
    @InitSpec(
        pre = "precondition 1",
        post = "postcondition 1"
    ),
    @InitSpec(
        pre = "precondition 2",
        post = "postcondition 2"
    )
})
```

```
@InitSpecStatic(
    pre = "precondition",
    post = "postcondition"
)
```

```
@InitSpecsStatic({
    @InitSpecStatic(
        pre = "precondition 1",
        post = "postcondition 1"
    ),
    @InitSpecStatic(
        pre = "precondition 2",
        post = "postcondition 2"
    )
})
```

```
@Spec(
    pre = "precondition",
    post = "postcondition"
)
```

method declaration

```
void <init>() :
    { precondition }
    { postcondition }
```

```
void <init>() :
    { precondition 1 }
    { postcondition 1 }
    andalso
    { precondition 2 }
    { postcondition 2 }
```

```
void <init>() static :
    { precondition }
    { postcondition }
```

```
void <init>() static :
    { precondition 1 }
    { postcondition 1 }
    andalso
    { precondition 2 }
    { postcondition 2 }
```

method declaration :

```
{ precondition }
{ postcondition }
```

```

@Specs({
    @Spec(
        pre = "precondition 1",
        post = "postcondition 1"
    ),
    @Spec(
        pre = "precondition 2",
        post = "postcondition 2"
    )
})

```

method declaration

```

@SpecStatic(
    pre = "precondition",
    post = "postcondition"
)

```

method declaration

```

@SpecsStatic({
    @SpecStatic(
        pre = "precondition 1",
        post = "postcondition 1"
    ),
    @SpecStatic(
        pre = "precondition 2",
        post = "postcondition 2"
    )
})

```

method declaration

method declaration :

```

{ precondition 1 }
{ postcondition 1 }
andalso
{ precondition 2 }
{ postcondition 2 }

```

method declaration static :

```

{ precondition }
{ postcondition }

```

method declaration static :

```

{ precondition 1 }
{ postcondition 1 }
andalso
{ precondition 2 }
{ postcondition 2 }

```

Eclipse plugin

You can write specifications in your java source file. By selecting an option "Specification is included in the source file" in verification configuration, the specification file will be generated from your annotations. This specification file will be used to verify your program.

Command line

You can generate a specification file from your java source file with annotations using command line:

javac

-proc:only

-cp “.;jstar_processing.jar;commons-io-1.4.jar;annotations.jar”

-d .

-processor com.jstar.eclipse.processing.SpecAnnotationProcessor

MyClass.java

-proc:only

Only annotation processing is done, without any subsequent compilation.

-cp

Specifies the classpath. As well as specifying the classpath to the classes MyClass is referencing to, you need to add the following jar files:

- jstar_processing.jar
where the processor **com.jstar.eclipse.processing.SpecAnnotationProcessor** lives in.
- commons-io-1.4.jar
required library for annotation processing.
- annotations.jar
where the specification annotations live in.

-d

The destination directory for the specification file.

-processor

The name of annotation processor.

MyClass.java

One or more source files with annotations.