Hazard Analysis
FPVR

Team 9, Software Mandems
John Cho
Ibrahim Tariq
Vikram Chandar
Sankalpa Chhetri Dhakal
Arjun Sasidaran

Table 1: Revision History

Date	**Developer(s)**	**Change**
Sept 30	Sankalpa Chhetri Dhakal	Completed Introduction
Oct 6	Sankalpa Chhetri Dhakal	Completed Scope and Purpose and System Boundaries
...	...	...

Contents

1 Introduction **1**

2 Scope and Purpose of Hazard Analysis **1**

3 System Boundaries and Components **1**

3.1 VR Headset 2

3.2 Controller Thumbsticks, Triggers, Buttons, and Input Connection 2

3.3 Host Computer 2

3.4 Unity Application 2

3.5 Drone Physics Simulation 3

3.6 VR Rendering and XR Subsystem 3

3.7 Training and Scoring System 3

3.8 User Interface 3

3.9 Data Storage 4

4 System Boundaries and Components **4**

5 Critical Assumptions **4**

6 Failure Mode and Effect Analysis **5**

7 Safety and Security Requirements **6**

7.1 Functional Requirements 6

8 Non-Functional Requirements **9**

9 Roadmap **10**

10 Appendix — Generative AI Use Disclosure **11**

10.1 AI Tools Used 11

10.2 How and Where Used 11

10.3 Verification of AI-Generated Content 12

11 Appendix — Reflection **14**

[You are free to modify this template. —SS]

1 Introduction

This document presents the Hazard Analysis for the VR-Based FPV Drone Operator Training Game. The purpose of the project is to provide users with a virtual environment where they can learn and practice FPV drone operation before flying a real drone. The system is intended to support both new users who are learning basic FPV controls and more experienced drone operators who want to practice manoeuvres, test their skills, or become familiar with different training scenarios in a low-risk environment.

For this project, a hazard is defined as a system condition, failure, or interaction that could result in harm or loss. This may include physical injury to the user, damage to equipment, loss of data, system failure, or incorrect training caused by unrealistic simulator behaviour. Although the system is primarily a software simulation, hazards may still arise from the use of VR hardware, software failures, inaccurate drone physics, or incorrect user interaction with the system.

2 Scope and Purpose of Hazard Analysis

3 System Boundaries and Components

The system boundary includes the software and hardware directly involved in running and interacting with the FPV drone training simulator. This includes the VR headset, input devices, host computer, Unity application, drone simulation, training functionality, user interface, and locally stored data. The user and their physical surroundings interact with the system and are considered when identifying hazards, but they are not components of the software system itself. Real FPV drones and real-world drone operation are outside the system boundary.

The system consists of several major software and hardware components. These components are considered independently during hazard identification because a failure in one component may affect the safety or correctness of the overall system.

3.1 VR Headset

The VR headset, expected to be a **Meta Quest 3S**, provides the user's visual representation of the simulated environment and tracks the position and orientation of the user's head.

Potential hazards associated with this component include loss of tracking, visual latency, incorrect orientation, poor headset fit, and the user becoming unaware of their physical surroundings.

3.2 Controller Thumbsticks, Triggers, Buttons, and Input Connection

Controller thumbsticks and triggers provide axis values that are mapped to drone throttle, pitch, roll, and yaw. Buttons provide discrete commands such as pause, restart, and respawn. Depending on the final implementation, these controls may be provided by VR controllers, a game controller, or an external FPV-style radio controller. The controller connection carries these values and button events to the application.

Failures may include thumbstick drift, where a centred stick reports an input and causes unintended drone movement; a stuck thumbstick or trigger, which maintains a control value after release; or a stuck or unresponsive button, which repeats or prevents a command. Incorrect axis mappings, inverted axis directions, or incorrect centre, range, or dead-zone calibration may produce unintended throttle or steering responses. A disconnected controller, dropped input updates, or delayed input delivery may cause loss of control, continued use of a stale control value, or a delayed response to a pilot command.

3.3 Host Computer

A computer executes the Unity application and associated simulation software.

Failures may include insufficient hardware performance, overheating, loss of power, driver issues, or resource exhaustion.

3.4 Unity Application

Unity provides the primary execution environment for the game.

This component is responsible for scene management, game logic, user interaction, rendering, and communication between major software modules.

3.5 Drone Physics Simulation

The drone physics subsystem models properties such as:

- thrust;
- gravity;
- acceleration;
- angular velocity;
- momentum;
- collisions; and
- drone response to pilot input.

Incorrect behaviour in this component represents an important hazard because users are expected to learn flying behaviour from the simulator.

3.6 VR Rendering and XR Subsystem

This subsystem renders the virtual environment and communicates with the VR headset.

Failures may result in visual artifacts, low frame rate, latency, incorrect camera movement, or loss of tracking.

3.7 Training and Scoring System

The training subsystem may contain tutorials, objectives, checkpoints, scoring metrics, crash detection, and user performance feedback.

Incorrect scoring or feedback could indicate that unsafe or incorrect flying behaviour is acceptable.

3.8 User Interface

The interface includes menus, settings, warnings, calibration options, pause controls, and training instructions.

Poor interface design could prevent the user from understanding warnings or exiting the simulation quickly.

3.9 Data Storage

The system may locally store information such as:

- user settings;
- controller configuration;
- training progress;
- scores; and
- application configuration.

Data corruption or unauthorized modification could affect system operation or training results.

4 System Boundaries and Components

[Dividing the system into components will help you brainstorm the hazards. You shouldn't do a full design of the components, just get a feel for the major ones. For projects that involve hardware, the components will typically include each individual piece of hardware. If your software will have a database, or an important library, these are also potential components. —SS]

5 Critical Assumptions

1. **Stable Internet Connection:** Users have access to a sufficiently stable internet connection for online features, including forms, multiplayer elements, and reviews.
   Rationale: Online features require reliable network connectivity to transmit user input, synchronize multiplayer gameplay, and submit or retrieve reviews. This assumption allows the system to be designed around the availability of network connectivity.

2. **Honest User Feedback:** Users provide honest gameplay reviews and feedback, and accurately report their experiences with the game.
   Rationale: Honest feedback helps ensure that reviews and user evaluations accurately represent gameplay experiences, allowing developers to identify issues and measure goals accurately without accounting for fake comments.

3. **Available Storage Capacity:** Users have sufficient available storage space on their systems to install the game and store any locally saved gameplay data.
   Rationale: The game requires storage for its installation files, course assets, and locally saved data. Insufficient storage may prevent installation, updates, or the saving of gameplay progress. It may require additional storage after progressing through levels such as save states and leaderboards, this storage should be available for the simulation to use.

4. **Basic Gaming Familiarity:** Users have basic familiarity with video games and standard user interface elements, including start screens, settings menus, and navigation controls.
   Rationale: This familiarity allows users to navigate the application and access gameplay features without requiring extensive introductory instruction, reducing the complexity of the user interface design.

5. **Suitable Hardware Performance:** Users have VR equipment that meets the minimum hardware requirements for running the game.
   Rationale: Meeting the minimum hardware requirements helps ensure that the system can maintain acceptable performance, provide a responsive VR experience, and execute the simulation as intended.

6. **Accurate Self-Reported Drone Experience:** Users who identify themselves as competent or experienced drone operators accurately represent their level of drone operating experience.
   Rationale: The system may rely on users' self-reported experience to understand their familiarity with drone operation and interpret their training results. Assuming these claims are accurate helps ensure that user classifications and performance evaluations are based on their stated level of experience.

6 Failure Mode and Effect Analysis

[Include your FMEA table here. This is the most important part of this document. —SS] [The safety requirements in the table do not have to have the prefix SR. The most important thing is to show traceability to your SRS. You might trace to requirements you have already written, or you might need to add new requirements. —SS] [If no safety requirement can be devised, other mitigation strategies can be entered in the table, including strategies involving providing additional documentation, and/or test cases. —SS]

7 Safety and Security Requirements

[Newly discovered requirements. These should also be added to the SRS. (A rationale design process how and why to fake it.) —SS]

`‘latex

7.1 Functional Requirements

SR1: The system shall provide users with a safety notice before their first VR session, reminding them to clear their physical play area of obstacles and remain aware of their surroundings.
Rationale: Users may collide with nearby objects while immersed in the virtual environment, potentially causing injury or damaging equipment.
Risk: Medium

SR2: The system shall allow users to pause or exit gameplay at any time during a VR session.
Rationale: Users may experience motion sickness, dizziness, or discomfort that requires them to stop playing immediately.
Risk: High

SR3: The system shall suspend active gameplay when the VR platform reports a headset disconnection or loss of tracking that prevents reliable interaction.
Rationale: Continuing gameplay when tracking is unreliable may cause unexpected interactions and increase user disorientation.
Risk: High

SR4: The system shall verify that required VR hardware is detected and initialized before allowing users to begin a flight session.
Rationale: Missing or improperly initialized hardware may prevent reliable controller input and compromise gameplay.
Risk: Medium

SR5: The system shall validate controller input values before applying them to the drone simulation and reject values outside supported input ranges.
Rationale: Invalid controller inputs may produce unintended drone movements or unpredictable simulation behaviour.

Risk: Medium

SR6: The system shall verify connectivity to required external services before enabling features that depend on them.
Rationale: Service connectivity failures may prevent multiplayer sessions or cause dependent features to behave incorrectly.
Risk: Medium

SR9: The system shall validate data received from multiplayer clients before accepting it for gameplay state updates or performance record storage.
Rationale: Malformed or manipulated network messages may cause inconsistent multiplayer behaviour or compromise recorded statistics.
Risk: High

SR11: The system shall notify users when a network interruption prevents access to multiplayer functionality.
Rationale: Users may otherwise be unaware that multiplayer functionality is unavailable or their session has been interrupted.
Risk: Low

SR12: The system shall disclose what gameplay data is collected, how it is used, and whether it is transmitted to external services before collecting user-associated data.
Rationale: Users need to understand how their gameplay information is handled to make informed decisions about their privacy.
Risk: Medium

SR13: The system shall require users to authenticate before accessing personal accounts or user-specific gameplay records, if account functionality is implemented.
Rationale: Authentication helps prevent unauthorized users from accessing personal information and saved progress.
Risk: High

SR14: The system shall enforce authorization checks before allowing users to view, modify, or delete stored gameplay records.
Rationale: Authorization prevents users from accessing or modifying records

belonging to other users.
Risk: High

SR16: The system shall validate and sanitize user-provided data before processing or storing it.
Rationale: Improperly handled input may enable injection attacks, corrupt stored records, or cause unexpected system behaviour.
Risk: High

SR18: The system shall terminate or invalidate multiplayer session credentials when a user leaves a session or the session expires.
Rationale: Invalidating expired session credentials reduces the risk of unauthorized reuse or continued access to multiplayer sessions.
Risk: Medium

SR7: The system shall use encrypted communication when transmitting user data or multiplayer session information over a network.
Rationale: Unencrypted network traffic may expose user information or session data to unauthorized parties.
Risk: High

SR8: The system shall restrict access to stored user-specific gameplay records to the relevant user and authorized system components.
Rationale: Unauthorized access may expose private information or allow gameplay records to be modified.
Risk: Medium

SR10: The system shall preserve previously saved gameplay records when unexpected software errors or network interruptions occur.
Rationale: Unexpected failures may otherwise result in corrupted records or the loss of user progress.
Risk: Medium

SR15: The system shall securely store authentication credentials and shall not store passwords in plaintext. Passwords shall be protected using an appropriate salted password-hashing algorithm.
Rationale: Plaintext passwords may be exposed if stored data is accessed by an unauthorized party.
Risk: High

SR17: The system shall prevent unauthorized modification of stored gameplay records and verify data integrity when records are retrieved or updated.
Rationale: Tampered performance records may produce inaccurate results and undermine the reliability of user progress tracking.
Risk: Medium

SR19: The system shall limit repeated authentication attempts within a defined period.
Rationale: Limiting repeated attempts helps reduce automated password-guessing and brute-force attacks.
Risk: Medium

SR20: The system shall record security-relevant events, including failed authentication attempts and unauthorized access attempts, without unnecessarily logging sensitive user information.
Rationale: Security logs support the investigation of suspicious activity while minimizing the exposure of sensitive data.
Risk: Medium

8 Non-Functional Requirements

NFR1: The system shall maintain a frame rate of at least 30 frames per second during standard single-player gameplay on the minimum supported VR hardware.
Rationale: Maintaining a consistent frame rate helps reduce visual discomfort and supports an immersive VR experience.
Risk: High

NFR2: The system shall respond to valid controller inputs within 50 milliseconds under normal operating conditions.
Rationale: Low input latency supports precise drone control and provides a more realistic flight simulation experience.
Risk: High

NFR3: The system shall operate correctly on all VR headsets, controllers, and operating system configurations explicitly listed as supported in the system doc-

umentation.
Rationale: Defining supported configurations ensures consistent operation and reduces hardware compatibility issues.
Risk: Medium

NFR4: The system shall restore access to the main menu within 10 seconds of recovering from a recoverable VR tracking or network interruption, provided that the required hardware and services are available.
Rationale: Prompt recovery minimizes disruption and reduces the need to restart the application.
Risk: Medium

9 Roadmap

[Which safety requirements will be implemented as part of the capstone timeline? Which requirements will be implemented in the future? —SS]

10 Appendix — Generative AI Use Disclosure

10.1 AI Tools Used

Claude Opus 5.5 and GPT Astra 6.1.

10.2 How and Where Used

1. **How were the AI tools used?**

   ChatGPT was used to brainstorm potential hazards for the FPVR drone flight simulation system, suggest safety and security requirements, and improve the clarity and organization of technical writing. It was also used to help identify potential risks that could be overlooked during manual analysis, including VR tracking loss, invalid controller inputs, network interruptions, unauthorized access, and corruption or loss of gameplay records. Additionally, ChatGPT assisted in developing rationales for proposed requirements and explaining why particular hazards could affect users or system functionality.

2. **Which parts of the document were affected by AI assistance?**

   AI assistance contributed to several sections of the Hazard Analysis document:

   - **Scope and Purpose of Hazard Analysis:** Assistance with organizing explanations of the purpose of identifying and mitigating hazards in the FPVR system.
   - **System Boundaries and Components:** Assistance with considering potential sources of hazards associated with VR hardware, controller inputs, networking, and gameplay data.
   - **Critical Assumptions:** Assistance with clarifying assumptions concerning internet connectivity, available storage, minimum hardware capabilities, gaming familiarity, and users' self-reported drone experience.
   - **Failure Mode and Effect Analysis:** Assistance with brainstorming potential failure scenarios, their effects, and possible mitigation strategies.
   - **Safety and Security Requirements:** Assistance with drafting and refining proposed requirements concerning VR safety, controller input validation, hardware initialization, network reliability, authentication, data privacy, and gameplay record integrity.
   - **Non-Functional Requirements:** Assistance with expressing proposed performance, responsiveness, compatibility, and recovery targets in measurable terms.

AI-generated suggestions were used as drafting and brainstorming aids rather than accepted automatically. The team remained responsible for reviewing the content and ensuring that the final document accurately reflected the FPVR project's scope, requirements, and design decisions.

10.3 Verification of AI-Generated Content

1. **How did the team check AI-generated or AI-assisted material before including it in the document?**

   The team treated AI-generated content as a starting point for brainstorming and drafting rather than accepting it without review. Suggestions were evaluated against the FPVR project's objectives, intended functionality, and existing requirements. For example, AI assistance was used to identify potential hazards associated with VR headset tracking loss, invalid controller inputs, and network interruptions. The team considered whether these scenarios were relevant to the system and whether the proposed mitigations addressed the associated risks. AI-assisted wording was also reviewed for clarity, consistency, and relevance before being included in the document.

2. **How did the team verify factual claims, technical assertions, requirements, calculations, and references?**

   Technical claims and proposed requirements were reviewed in the context of the FPVR system and the team's understanding of VR development and software engineering. For example, the proposed requirement to maintain at least 30 frames per second (NFR1) and the target of responding to controller inputs within 50 milliseconds (NFR2) were treated as design targets rather than confirmed system capabilities. These targets would need to be validated through performance testing on supported VR hardware. Similarly, proposed security requirements concerning encrypted communication, authentication, and gameplay record integrity were considered in relation to the system's planned networking and data-storage functionality.

   The team also reviewed requirement identifiers, rationales, and risk ratings for consistency and considered whether each proposed mitigation addressed its associated hazard. AI-generated suggestions were not treated as proof that a feature had been implemented or tested. Any factual claims, technical details, calculations, or external references used in the final document must be checked against reliable documentation or independent calculations where applicable. Where implementation details or test results were unavailable, the document distinguished proposed requirements from verified outcomes.

3. **Who is responsible for the accuracy, completeness, consistency, and appropriateness of the submitted document?**

The team is ultimately responsible for the accuracy, completeness, consistency, and appropriateness of the submitted Hazard Analysis, regardless of whether material was written by team members or generated with AI assistance. AI tools can support brainstorming, drafting, and identifying potential omissions, but their suggestions may be inaccurate, incomplete, or unsuitable for the project's scope. Therefore, the team must critically evaluate AI-assisted content and ensure that the final document accurately represents the FPVR system, its hazards, and its proposed mitigations.

11 Appendix — Reflection

The purpose of reflection questions is to give you a chance to assess your own learning and that of your group as a whole, and to find ways to improve in the future. Reflection is an important part of the learning process. Reflection is also an essential component of a successful software development process.

Reflections are most interesting and useful when they're honest, even if the stories they tell are imperfect. You will be marked based on your depth of thought and analysis, and not based on the content of the reflections themselves. Thus, for full marks we encourage you to answer openly and honestly and to avoid simply writing "what you think the evaluator wants to hear."

Please answer the following questions. Some questions can be answered on the team level, but where appropriate, each team member should write their own response:

Vikram – Reflection

1. What went well while writing this deliverable?
2. What pain points did you experience during this deliverable, and how did you resolve them?
3. Which of your listed risks had your team thought of before this deliverable, and which did you think of while doing this deliverable? For the latter ones (ones you thought of while doing the Hazard Analysis), how did they come about?
4. Other than the risk of physical harm (some projects may not have any appreciable risks of this form), list at least 2 other types of risk in software products. Why are they important to consider?

1. **What went well while writing this deliverable?**

   The team was able to identify potential hazards associated with FPVR, our VR drone flight simulation game, and consider how they could affect users, gameplay, and system reliability. Examining the system component by component helped us identify potential failures involving VR hardware, controller inputs, the flight simulation, multiplayer functionality, and stored gameplay records. Translating these hazards into safety and security requirements also helped us define specific system behaviours that could be verified through testing.

2. **What pain points did you experience during this deliverable, and how did you resolve them?**

One challenge was distinguishing general software defects from hazards that could affect user safety, data integrity, or system reliability. For example, a VR tracking failure could affect both gameplay and user comfort, while a network interruption could cause multiplayer issues or lost progress. We addressed these challenges by examining the possible causes and consequences of each failure and identifying appropriate mitigation strategies. Another challenge was determining suitable risk classifications and writing requirements that were specific enough to test. We addressed this by providing rationales for each requirement and identifying system behaviours that could be verified during testing.

3. **How many of your requirements were inspired by speaking to your clients or their proxies, such as peers, stakeholders, and potential users?**

   Several requirements were informed by discussions with stakeholders and potential users, including drone enthusiasts and members of the McMaster MARS Rover team. For example, the requirement for responsive and realistic drone controls was motivated by the need to provide an authentic FPV flying experience that would be useful for both beginners and experienced drone operators. Another example is the requirement to provide multiple flight courses with varying levels of difficulty, which reflects the need to accommodate users with different levels of flying experience and allow them to progressively improve their skills. These discussions helped ensure that the system's requirements reflected the needs and expectations of its intended users.

4. **Which courses have you taken, or are currently taking, that will help your team succeed with the capstone project?**

   Several courses provide relevant knowledge for developing FPVR. Course 4HC3, Human Interface Design, will help the team design intuitive VR interactions, controller mappings, menus, and accessible interfaces. Its concepts will also support usability evaluation and improving user comfort.

   Course 4AA4, Control Systems, will help the team understand the relationship between controller inputs and simulated drone movement. Control systems concepts will support the development of responsive flight behaviour and the evaluation of the simulation's control model.

   Course 2AA4, Software Design, will help the team structure the application into modular components with clearly defined responsibilities and interfaces. This will be important when integrating VR interactions, flight physics, course management, multiplayer functionality, and performance evaluation.

   Additionally, programming and software engineering courses provide a foundation in object-oriented programming, requirements analysis, testing, debugging, and collaborative development. These skills will help the

team implement the simulation, verify its requirements, and integrate its components reliably.

5. **What knowledge and skills will the team collectively need to acquire to successfully complete this capstone project?**

   The team will need to acquire knowledge and skills in several areas to complete FPVR successfully:

   - **VR development and hardware integration:** The team will need to learn Unity, C#, OpenXR, and the XR Interaction Toolkit to implement VR interactions, integrate supported headsets and controllers, and handle tracking information.
   - **Drone simulation and control systems:** The team will need to understand drone movement, flight dynamics, controller mappings, and how user inputs affect simulated flight behaviour.
   - **Performance optimization:** The team will need to learn how to profile Unity applications, identify rendering and processing bottlenecks, and optimize frame rate and input latency for a responsive VR experience.
   - **Software testing and user evaluation:** The team will need to develop test cases for gameplay, controller responsiveness, hardware compatibility, and recovery from interruptions. It will also need to evaluate usability, immersion, and user comfort through structured testing.
   - **Data analysis and training evaluation:** The team will need to learn how to record and interpret flight performance data, including completion times, crashes, control consistency, and unnecessary corrections. This knowledge will support performance summaries and the potential AI-based feedback feature.
   - **Version control and collaboration:** The team will need to use Git, feature branches, pull requests, and code reviews effectively. Consistent coding conventions and clearly defined component interfaces will help reduce integration problems.
   - **Technical documentation and communication:** The team will need to document implementation decisions, testing procedures, and design changes. Clear communication will also be necessary for coordinating work, resolving disagreements, and presenting the completed project.

   These areas can be distributed among team members according to their existing experience and responsibilities. Testing, documentation, and collaboration will remain shared responsibilities across the team.

6. **For each knowledge area and skill identified above, what are at least two approaches to acquiring the knowledge or mastering**

the skill? Which approaches will each team member pursue, and why?

The team will combine structured learning with practical implementation. Tutorials and documentation will provide foundational knowledge, while prototypes and testing will allow team members to apply that knowledge to FPVR.

- **VR development and hardware integration:** One approach is to complete official Unity, OpenXR, and XR Interaction Toolkit tutorials. A second approach is to develop a prototype that supports headset tracking, controller input, and basic VR interactions. The team member responsible for VR integration will pursue both approaches because tutorials provide a structured introduction, while prototyping reveals practical hardware and integration issues.
- **Drone simulation and control systems:** One approach is to review control systems course material and introductory resources on drone flight dynamics. A second approach is to implement a basic flight model and iteratively test how controller inputs affect movement. The team member responsible for flight simulation will combine theoretical study with experimentation to understand the underlying principles and tune the simulation's response.
- **Performance optimization:** One approach is to study Unity profiling tools and official VR optimization documentation. A second approach is to profile the application during gameplay, identify bottlenecks, and measure performance before and after changes. The team member responsible for performance will use both approaches to ensure that optimization decisions are based on measured results.
- **Software testing and user evaluation:** One approach is to study software testing techniques and usability evaluation methods. A second approach is to create test cases and conduct structured trials with representative users. The team member responsible for testing will combine these methods to identify both functional defects and usability issues.
- **Data analysis and training evaluation:** One approach is to study performance metrics and methods for evaluating control efficiency and consistency. A second approach is to build a prototype that records flight behaviour and generates feedback using measurable performance indicators. The team member responsible for performance evaluation will start with interpretable metrics before exploring more advanced AI-based approaches, allowing the evaluation feature to be validated incrementally.
- **Version control and collaboration:** One approach is to review Git documentation and collaborative development practices. A second approach is to apply feature branches, pull requests, and code

reviews in the project repository. All team members will practise these workflows because consistent collaboration is necessary to integrate independently developed components.

- **Technical documentation and communication:** One approach is to study examples of technical documentation and practise writing concise design descriptions and test reports. A second approach is to maintain project documentation and present progress during team meetings and project reviews. All team members will participate so that implementation decisions remain documented and project knowledge is shared.

The responsibilities described above are organized by technical area rather than by individual name. The team will assign specific owners based on members' experience, interests, and workload. This approach allows each member to develop a particular area of expertise while contributing to the team's overall progress.

7. **Which of your listed risks had your team thought of before this deliverable, and which did you think of while doing the Hazard Analysis? For the latter risks, how did they come about?**

   Before completing the Hazard Analysis, the team had already considered risks related to VR performance, controller responsiveness, hardware compatibility, and user discomfort. These risks were closely related to the project's objective of providing an immersive, responsive, and usable drone flight simulation experience.

   The Hazard Analysis encouraged us to examine additional scenarios, including loss of VR tracking, invalid controller inputs, unexpected hardware disconnections, network interruptions, unauthorized access to gameplay records, and corruption or loss of saved progress. Some of these risks may have been recognized informally earlier, but the analysis helped us identify their causes and consequences more explicitly.

   These risks emerged by examining each system component and considering what could happen if it failed, received invalid data, or interacted incorrectly with another component. For example, examining controller inputs highlighted the possibility of unexpected drone movements. Examining multiplayer communication raised concerns about manipulated messages and inconsistent gameplay states. Finally, examining data storage highlighted the possibility of unauthorized access and the loss of saved records. This process demonstrated that risks extend beyond the simulation itself to include network communication, user information, and the reliability of stored data.

8. **Other than physical harm, list at least two other types of risk in software products. Why are they important to consider?**

   Several non-physical risks are relevant to FPVR.

Security and privacy risks: Unauthorized access to accounts or gameplay records could expose user information or allow stored results to be modified. These risks are important because users need to trust that their information is protected and that access to personal records is appropriately restricted.

Data integrity and reliability risks: Software errors, unexpected shutdowns, or network interruptions could corrupt gameplay records or cause users to lose progress. These risks are important because training evaluation and performance tracking depend on accurate and consistent data.

Performance and usability risks: Low frame rates, delayed controller responses, or confusing interactions could reduce immersion and make the simulation difficult to use effectively. These risks are especially important in VR because responsiveness and consistent visual feedback contribute to a comfortable and usable experience.

Compatibility risks: Differences between supported headsets, controllers, and operating system configurations could cause features to fail or behave inconsistently. Considering these risks helps the team define supported configurations and plan appropriate compatibility tests.

Project and integration risks: Poor coordination, incompatible components, or delays in integrating individual contributions could prevent the team from completing planned features within the capstone timeline. These risks are important because components that work independently may still fail when combined into the complete application.

Identifying these risks early allows the team to prioritize mitigations, make informed design decisions, and establish appropriate tests. Addressing them throughout development will help ensure that FPVR is reliable, secure, usable, and feasible to deliver within the available time.