

```

upstream backend {
    ip_hash;
    least_conn;
    server node01.omarwsaleh.com weight=3;
    server node02.omarwsaleh.com weight=1;
}

server {
    listen 80;
    listen [::]:80;

    # SSL configuration
    #
    # listen 443 ssl default_server;
    # listen [::]:443 ssl default_server;
    #
    # Note: You should disable ssl for production sites.

```

```

# include snippets/snakeoil.conf;

#       root /var/www/kareem;

# Add index.php to the list if you are using PHP
index index.html index.htm index.nginx-debian.html;

server_name www.backend.com;

location / {
    # First attempt to serve request as file, then
    # as directory, then fall back to displaying a 404.
    #try_files $uri $uri/ =404;
    proxy_pass http://backend;
}

```

```
nginx: configuration file /etc/nginx/nginx.conf test failed
root@ubuntu:/etc/nginx/sites-enabled# vim load_b.conf
root@ubuntu:/etc/nginx/sites-enabled# nginx -t
nginx: the configuration file /etc/nginx/nginx.conf syntax is ok
nginx: configuration file /etc/nginx/nginx.conf test is successful
root@ubuntu:/etc/nginx/sites-enabled# systemctl reload nginx
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node01
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node01
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node01
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node01
root@ubuntu:/etc/nginx/sites-enabled# vim load_b.conf
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node02
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node01
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node01
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node01
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node02
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node01
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node01
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node01
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node02
root@ubuntu:/etc/nginx/sites-enabled# curl -H "Host: www.backend.com" localhost
Hello from node01
```