

### Task 1:

```
soha@ubuntu:~/depi_r3/lec15$ kubectl create namespace database-server --dry-run=client -o yaml > database-server.yaml
```

```
soha@ubuntu:~/depi_r3/lec15$ kubectl create deployment mariadb --image=mariadb:latest -n database-server --dry-run=client -o yaml > mariadb-deployment.yaml
```

```
soha@ubuntu:~/depi_r3/lec15$ vim mariadb-deployment.yaml
```

```
soha@ubuntu:~/depi_r3/lec15$ kubectl create service clusterip mariadb-service1 --tcp=3306:3306 -n database-server --dry-run=client -o yaml > mariadb-service1.yaml
```

```
soha@ubuntu:~/depi_r3/lec15$ kubectl apply -f database-server.yaml
namespace/database-server configured
```

```
soha@ubuntu:~/depi_r3/lec15$ kubectl apply -f mariadb-deployment.yaml
deployment.apps/mariadb created
```

```
soha@ubuntu:~/depi_r3/lec15$ kubectl apply -f mariadb-service1.yaml
service/mariadb-service configured
```

```
soha@ubuntu:~/depi_r3/lec15$ kubectl delete svc mariadb-service1 -n database-server
```

```
kubectl expose deployment mariadb --port=3306 --target-port=3306 --name=mariadb-service1 -n database-server --dry-run=client -o yaml > mariadb-service1.yaml
```

```
service "mariadb-service1" deleted
```

```
soha@ubuntu:~/depi_r3/lec15$ kubectl get endpoints mariadb-service1 -n database-server
```

```
Warning: v1 Endpoints is deprecated in v1.33+; use discovery.k8s.io/v1 EndpointSlice
```

NAME	ENDPOINTS	AGE
mariadb-service1	10.244.0.49:3306	4m44s

```
soha@ubuntu:~/depi_r3/lec15$ kubectl run -it mysql-client --rm --image=alpine/mysql -n database-server -- -h mariadb-service1 -u root -prootpassword
```

```
If you don't see a command prompt, try pressing enter.
```

```
MariaDB [(none)]>
```

```
soha@ubuntu:~/depi_r3/lec15$ kubectl run -it mysql-client --rm --image=alpine/mysql -n database-server -- -h mariadb-service1 -u root -prootpassword
```

```
If you don't see a command prompt, try pressing enter.
```

```
MariaDB [(none)]>
```

Task 2:

```
soha@ubuntu:~$ kubectl create namespace apps
namespace/apps created
```

```
soha@ubuntu:~$ kubectl create deployment flask-app --image=sohaash/simple_flask_app:v0.3 -n apps
deployment.apps/flask-app created
```

```
soha@ubuntu:~$ kubectl expose deployment flask-app --name=flask-service --type=NodePort --port=5000 --target-port=5000
n apps
service/flask-service exposed
```

```
soha@ubuntu:~$ kubectl get nodes -o wide
```

NAME	STATUS	ROLES	AGE	VERSION	INTERNAL-IP	EXTERNAL-IP	OS-IMAGE	KERNEL-VERSION
CONTAINER-RUNTIME								
ip1ubuntu1	Ready	control-plane	7120h	v1.23.4	192.168.10.2	192.168.10.2	Ubuntu 22.04.5 LTS	6.4.0-30-generic

```
soha@ubuntu:~$ curl http://192.168.49.2:30452
Hello, Docker!soha@ubuntu:~$
```