The following opcodes are used for **addition**:

- ADDI Add Signed Integer
- ADDU Add Unsigned Integer
- ADDF Add Floating Point

ADDI — Add Signed Integer {#ADDI}

???+ note "Properties"

=== "ADDI Algorithm"

```
L2 = L2 + <signed_imm>
L2 = L2 + <reg_val>
L2 = L2 + <const>
```

=== "ADDI Example"

```
```linenums="1" hl_lines="1 3 5 7"
; imm +ve
 ADDI 1
; imm -ve
 ADDI -123
; reg val
 ADDI val(QT)
; const
 ADDI SOME_CONST_VAL
```

## ADDU — Add Unsigned Integer {#ADDU}

Use ADDU to add an unsigned value to whatever value is stored within the L3 register. If the register L3

is not set, then initial value of L3 is assumed to be 0, and not a garbage value.

### === "ADDU Algorithm"

```
L3 = L3 + <unsigned_imm>
L3 = L3 + <reg_val>
L3 = L3 + <const>
```

#### === "ADDU Example"

```
``linenums="1" hl_lines="1 3 5"
; imm +ve
 ADDU 1
; reg val
 ADDU val(QT)
; const
 ADDU SOME_CONST_VAL
```

# ADDF — Add Float value {#ADDF}

Use ADDF to add a floating point value to whatever value is stored within the L1 register. If the register L1 is not set, then initial value of L1 is assumed to be 0, and not a garbage value.

# === "ADDF Algorithm"

```
L1 = L1 + <float>
L1 = L1 + <reg_val>
L1 = L1 + <const>
```

# === "ADDF Example"

```
```linenums="1" hl_lines="1 3 5"
; imm float
   ADDF   3.14
; reg val
   ADDF   val(QT)
; const
   ADDF   SOME_CONST_VAL
```