

Bill of Materials - ACT-BP-4500 Drillable Bridge Plug, 4-1/2 in.

Engineering Bill of Materials | Document BOM-BP-4500 Rev D

Product / Assembly	ACT-BP-4500
Document No. / Rev	BOM-BP-4500 Rev D
Effective Date	2025-10-07
Prepared By	A. Gutierrez
Checked By	T. Okafor
Approved By	J. Martinez, P.E.
ERP Reference	ITEM-BP-4500

Revision History

Rev	Date	Description of Change	By
A	2022-03-15	Initial release	J. Martinez, P.E.
B	2023-01-19	Back-up ring material change to AISI 1008	A. Gutierrez
C	2024-04-30	Tension nut shear value standardized at 32,000 lbf	R. Callahan
D	2025-10-07	Slip inserts upgraded to 55 HRC heat-treated per ECO-2025-091	R. Callahan

Bill of Materials

Hierarchy: Level 0 = top assembly; Level 1 = component or sub-assembly; Level 2 = sub-assembly component. Indented descriptions belong to the sub-assembly immediately above. Quantities are per one (1) next-higher assembly.

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
1	0	ACT-BP-4500	BRIDGE PLUG ASSY, 4-1/2 IN. DRILLABLE, 10K	1	EA	-	Wireline set w/ ACT-ST-10 + AK-45 adapter kit
2	1	ACT-BP-4500-01	■ MANDREL, PLUG	1	EA	CAST IRON CL 40 (ASTM A48)	Drillable
3	1	ACT-BP-4500-02	■ ELEMENT, PACKING, 3-PIECE	1	EA	HNBR 80/90/80A	Rated 300 degF
4	1	ACT-BP-4500-03	■ SLIP, UPPER, SEGMENTED	4	EA	CAST IRON CL 40, HT INSERTS 55 HRC	Mat'l per ECO-2025-091 (Rev D)
5	1	ACT-BP-4500-04	■ SLIP, LOWER, SEGMENTED	4	EA	CAST IRON CL 40, HT INSERTS 55 HRC	Mat'l per ECO-2025-091 (Rev D)
6	1	ACT-BP-4500-05	■ CONE, UPPER	1	EA	CAST IRON CL 40	
7	1	ACT-BP-4500-06	■ CONE, LOWER	1	EA	CAST IRON CL 40	
8	1	ACT-BP-4500-07	■ RING, BACK-UP, EXPANDABLE	2	EA	SOFT STEEL AISI 1008	
9	1	ACT-BP-4500-08	■ NUT, TENSION, RELEASING STUD	1	EA	AISI 12L14	Shears at 32,000 lbf +/- 10%
10	1	ACT-BP-4500-09	■ GUIDE, BULLNOSE, BOTTOM	1	EA	CAST IRON CL 40	

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
11	1	ACT-BP-4500-10	■ PIN, SHEAR, 3/16 DIA	2	EA	BRASS C36000	
12	1	ACT-BP-AK-45	■ ADAPTER KIT, SETTING, SIZE #10 TOOL	1	KT	-	
13	2	ACT-BP-AK-45-01	■ SLEEVE, SETTING	1	EA	AISI 4140	Alpha #10 compatible
14	2	ACT-BP-AK-45-02	■ ROD, ADAPTER, TENSION	1	EA	AISI 4140 HT 28-32 HRC	
15	2	ACT-BP-AK-45-03	■ CROSSOVER, QUICK-CHANGE	1	EA	AISI 4140	

General Notes

- All elastomer components are single-use: replace at every redress from the applicable redress kit.
- Load-path metallic components require heat traceability to a mill certificate (EN 10204 Type 3.1) retained in the device history record.
- Shear devices (rings, screws, pins) are calibrated items - substitute parts are prohibited.
- Torque all threaded connections per ACT specification TS-100 (packers/plugs) or TS-200 (accessories).
- Sour service (NACE MR0175/ISO 15156) configurations use the materials noted; verify trim level on the sales order before assembly.
- Referenced documents: datasheet DS-BP-4500, applicable manual/procedure, and quality plan ACT-QP-08.

Approvals

Role	Name	Signature	Date
Design Engineering	A. Gutierrez	/signed electronically/	2025-10-07
Manufacturing Engineering	T. Okafor	/signed electronically/	2025-10-07
Quality Assurance	S. Nguyen	/signed electronically/	2025-10-07
Engineering Manager	J. Martinez, P.E.	/signed electronically/	2025-10-07