

Bill of Materials - ACT-CR-5500 Drillable Cement Retainer, 5-1/2 in.

Engineering Bill of Materials | Document BOM-CR-5500 Rev B

Product / Assembly	ACT-CR-5500
Document No. / Rev	BOM-CR-5500 Rev B
Effective Date	2024-08-14
Prepared By	A. Gutierrez
Checked By	T. Okafor
Approved By	J. Martinez, P.E.
ERP Reference	ITEM-CR-5500

Revision History

Rev	Date	Description of Change	By
A	2023-02-27	Initial release	R. Callahan
B	2024-08-14	Poppet spring changed to 302 SS; stinger kit added	A. Gutierrez

Bill of Materials

Hierarchy: Level 0 = top assembly; Level 1 = component or sub-assembly; Level 2 = sub-assembly component. Indented descriptions belong to the sub-assembly immediately above. Quantities are per one (1) next-higher assembly.

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
1	0	ACT-CR-5500	CEMENT RETAINER ASSY, 5-1/2 IN. DRILLABLE, 10K	1	EA	-	Set on wireline (ACT-ST-10) or tubing (ACT-SRT-55 stinger)
2	1	ACT-CR-5500-01	■ MANDREL, RETAINER, PORTED	1	EA	CAST IRON CL 40 (ASTM A48)	
3	1	ACT-CR-5500-02	■ VALVE ASSY, SLIDING SLEEVE (2-WAY)	1	EA	-	Opens w/ stinger; closes on pull-out
4	2	ACT-CR-5500-02A	■ SLEEVE, VALVE, INNER	1	EA	AISI 12L14	
5	2	ACT-CR-5500-02B	■ SEAT, VALVE, POPPET	1	EA	BRASS C36000	
6	2	ACT-CR-5500-02C	■ SPRING, POPPET RETURN	1	EA	302 SS	
7	2	ACT-ORG-214-H80	■ O-RING, -214, 80 DURO	3	EA	HNBR 80A	
8	1	ACT-CR-5500-03	■ ELEMENT, PACKING, 3-PIECE	1	EA	HNBR 80/90/80A	
9	1	ACT-CR-5500-04	■ SLIP, UPPER, SEGMENTED	6	EA	CAST IRON CL 40, HT INSERTS 55 HRC	
10	1	ACT-CR-5500-05	■ SLIP, LOWER, SEGMENTED	6	EA	CAST IRON CL 40, HT INSERTS 55 HRC	
11	1	ACT-CR-5500-06	■ CONE, UPPER	1	EA	CAST IRON CL 40	
12	1	ACT-CR-5500-07	■ CONE, LOWER	1	EA	CAST IRON CL 40	

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
13	1	ACT-CR-5500-08	■ NUT, TENSION, RELEASING STUD	1	EA	AISI 12L14	Shears at 38,000 lbf +/- 10%
14	1	ACT-SRT-55	■ STINGER, SEAL NIPPLE, TUBING SET	1	EA	AISI 4140	Optional; for squeeze ops
15	2	ACT-SRT-55-01	■ NIPPLE, SEAL, STINGER	1	EA	AISI 4140 HT 28-32 HRC	
16	2	ACT-CHV-200-M	■ SEAL STACK, CHEVRON, 2.00 BORE	2	ST	HNBR/PTFE MOLDED	

General Notes

- All elastomer components are single-use: replace at every redress from the applicable redress kit.
- Load-path metallic components require heat traceability to a mill certificate (EN 10204 Type 3.1) retained in the device history record.
- Shear devices (rings, screws, pins) are calibrated items - substitute parts are prohibited.
- Torque all threaded connections per ACT specification TS-100 (packers/plugs) or TS-200 (accessories).
- Sour service (NACE MR0175/ISO 15156) configurations use the materials noted; verify trim level on the sales order before assembly.
- Referenced documents: datasheet DS-CR-5500, applicable manual/procedure, and quality plan ACT-QP-08.

Approvals

Role	Name	Signature	Date
Design Engineering	A. Gutierrez	/signed electronically/	2024-08-14
Manufacturing Engineering	T. Okafor	/signed electronically/	2024-08-14
Quality Assurance	S. Nguyen	/signed electronically/	2024-08-14
Engineering Manager	J. Martinez, P.E.	/signed electronically/	2024-08-14