

ACT-CR-5500 Drillable Cement Retainer, 5-1/2 in.

Technical Datasheet DS-CR-5500 Rev B | Product family: ACT-CR-5500

1. Product Overview

The ACT-CR-5500 cement retainer provides positive isolation for squeeze cementing operations in 5-1/2 in. casing. A two-way poppet/sleeve valve allows circulation and squeeze through the retainer, then closes on stinger pull-out to hold squeeze pressure from below. Set on wireline with the ACT-ST-10 or on tubing with the ACT-SRT-55 stinger assembly.

2. Applications

- Squeeze cementing above or between perforations
- Plug-and-abandonment cement placement
- Casing leak repair squeezes

3. Features

- Two-way valve: pump-through open, closes on stinger removal
- Drillable cast iron Class 40 construction
- Same slip/element stack as field-proven ACT-BP-5500
- Wireline or tubing set
- Holds 10,000 psi from below after squeeze

4. Technical Specifications

Parameter	Specification
Casing Size	5-1/2 in., 14 - 23 lb/ft
Maximum OD	4.437 in.
Valve Bore	1.00 in.
Overall Length	31.2 in.
Pressure Rating	10,000 psi from below; 5,000 psi pump-through
Temperature Rating	300 degF
Setting	ACT-ST-10 (#10, kit AK-55) or ACT-SRT-55 tubing stinger
Stinger Seal Bore	2.00 in., chevron seal stack

All ratings are at ambient temperature unless otherwise noted. Performance envelope per API 11D1 V3 qualification testing where indicated. Consult ACT Engineering for combined load conditions.

5. Materials of Construction

Component	Material
Body components	Cast iron Class 40 (ASTM A48)
Valve trim	AISI 12L14 / brass C36000 / 302 SS spring
Element	HNBR 80/90/80
Stinger seals	HNBR/PTFE chevron, 2.00 in. bore

6. Ordering & Reference Documents

Order by part number and specify: casing size and weight, service trim (standard or NACE sour), elastomer option, end connections, and any customer inspection requirements. Related documents:

- BOM-CR-5500 Rev B
- RSP-CR-5500 Running & Squeeze Procedure
- TS-100

Datasheet DS-CR-5500 Rev B issued 2024-08-14. Prepared by R. Callahan; approved by J. Martinez, P.E.. Specifications subject to change; confirm with ACT Engineering for well-specific designs.