

Bill of Materials - ACT-PKR-5500 Permanent Packer, 5-1/2 in.

Engineering Bill of Materials | Document BOM-PKR-5500 Rev B

Product / Assembly	ACT-PKR-5500
Document No. / Rev	BOM-PKR-5500 Rev B
Effective Date	2024-11-05
Prepared By	A. Gutierrez
Checked By	T. Okafor
Approved By	J. Martinez, P.E.
ERP Reference	ITEM-PKR-5500

Revision History

Rev	Date	Description of Change	By
A	2023-09-01	Initial release	R. Callahan
B	2024-11-05	13Cr mandrel made standard; millout extension added as optional item	A. Gutierrez

Bill of Materials

Hierarchy: Level 0 = top assembly; Level 1 = component or sub-assembly; Level 2 = sub-assembly component. Indented descriptions belong to the sub-assembly immediately above. Quantities are per one (1) next-higher assembly.

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
1	0	ACT-PKR-5500	PACKER ASSY, 5-1/2 IN. HYDRAULIC SET PERMANENT, 10K	1	EA	-	Top-level assembly
2	1	ACT-PKR-5500-01	■ SUB, TOP, 2-7/8 EUE BOX UP	1	EA	AISI 4140 HT 28-32 HRC	13Cr optional (-01-CR)
3	1	ACT-PKR-5500-02	■ MANDREL, PACKER, 5-1/2	1	EA	API 5CT L80-13Cr	Sour service std; heat traceable
4	1	ACT-PKR-5500-03	■ ELEMENT ASSY, BONDED, 3-ELEMENT	1	EA	-	
5	2	ACT-PKR-5500-03A	■ RING, ANTI-EXTRUSION, FOLDBACK	2	EA	AISI 1018 W/ PTFE BACKUP	
6	2	ACT-PKR-5500-03B	■ ELEMENT, CENTER, 95 DURO	1	EA	HNBR 95A	
7	2	ACT-PKR-5500-03C	■ ELEMENT, END, 80 DURO	2	EA	HNBR 80A	
8	1	ACT-PKR-5500-04	■ SLIP, ONE-PIECE C-RING, UPPER	1	EA	CAST DUCTILE IRON 80-55-06	Wickers induction hardened 50 HRC min
9	1	ACT-PKR-5500-05	■ SLIP, ONE-PIECE C-RING, LOWER	1	EA	CAST DUCTILE IRON 80-55-06	
10	1	ACT-PKR-5500-06	■ CONE, UPPER	1	EA	AISI 4140 HT 28-32 HRC	
11	1	ACT-PKR-5500-07	■ CONE, LOWER	1	EA	AISI 4140 HT 28-32 HRC	

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
12	1	ACT-PKR-5500-08	■ PISTON, SETTING, ANNULAR	1	EA	AISI 4140 HT 28-32 HRC	
13	1	ACT-PKR-5500-09	■ SCREW, SHEAR, 10-24 UNC BRASS	10	EA	BRASS C36000	Set force 45,000 lbf nominal
14	1	ACT-PKR-5500-10	■ RING, LOCK, BODY	1	EA	AISI 4140 HT 32-36 HRC	
15	1	ACT-PKR-5500-11	■ GUIDE, MULE SHOE, BOTTOM	1	EA	AISI 4140	
16	1	ACT-PKR-5500-12	■ MILLOUT EXTENSION, 2-7/8	1	EA	AISI 4140	Optional; qty per sales order
17	1	ACT-PKR-5500-RK	■ REDRESS KIT, PKR-5500	1	KT	-	
18	2	ACT-ORG-235-V90	■ O-RING, -235, 90 DURO	4	EA	VITON 90A	
19	2	ACT-ORG-338-V90	■ O-RING, -338, 90 DURO	2	EA	VITON 90A	
20	2	ACT-BU-338-P	■ BACK-UP RING, -338, PEEK	4	EA	PEEK	
21	2	ACT-PKR-5500-09	■ SCREW, SHEAR, 10-24 UNC BRASS	10	EA	BRASS C36000	

General Notes

- All elastomer components are single-use: replace at every redress from the applicable redress kit.
- Load-path metallic components require heat traceability to a mill certificate (EN 10204 Type 3.1) retained in the device history record.
- Shear devices (rings, screws, pins) are calibrated items - substitute parts are prohibited.
- Torque all threaded connections per ACT specification TS-100 (packers/plugs) or TS-200 (accessories).
- Sour service (NACE MR0175/ISO 15156) configurations use the materials noted; verify trim level on the sales order before assembly.
- Referenced documents: datasheet DS-PKR-5500, applicable manual/procedure, and quality plan ACT-QP-08.

Approvals

Role	Name	Signature	Date
Design Engineering	A. Gutierrez	/signed electronically/	2024-11-05
Manufacturing Engineering	T. Okafor	/signed electronically/	2024-11-05
Quality Assurance	S. Nguyen	/signed electronically/	2024-11-05
Engineering Manager	J. Martinez, P.E.	/signed electronically/	2024-11-05