

Bill of Materials - ACT-SPM-2875 Side Pocket Mandrel w/ ACT-GLV-1000 Gas Lift Valve

Engineering Bill of Materials | Document BOM-SPM-2875 Rev B

Product / Assembly	ACT-SPM-2875
Document No. / Rev	BOM-SPM-2875 Rev B
Effective Date	2024-12-09
Prepared By	A. Gutierrez
Checked By	T. Okafor
Approved By	J. Martinez, P.E.
ERP Reference	ITEM-SPM-2875

Revision History

Rev	Date	Description of Change	By
A	2023-10-30	Initial release	R. Callahan
B	2024-12-09	Latch seat material to 17-4 PH H1150; WPS-ACT-21 weld spec adopted	A. Gutierrez

Bill of Materials

Hierarchy: Level 0 = top assembly; Level 1 = component or sub-assembly; Level 2 = sub-assembly component. Indented descriptions belong to the sub-assembly immediately above. Quantities are per one (1) next-higher assembly.

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
1	0	ACT-SPM-2875	MANDREL ASSY, SIDE POCKET, 2-7/8, 1 IN. POCKET	1	EA	-	Accepts ACT-GLV-1000 series valves
2	1	ACT-SPM-2875-01	■ BODY, MANDREL, OVAL, FORGED	1	EA	AISI 4130 75K (NACE)	Forging F-SPM-287
3	1	ACT-SPM-2875-02	■ POCKET, SIDE, 1.000 IN. BORE	1	EA	AISI 4130 75K (NACE)	Welded per WPS-ACT-21
4	2	ACT-SPM-2875-02A	■ SEAT, LATCH, POCKET (RK PROFILE)	1	EA	17-4 PH H1150	
5	2	ACT-SPM-2875-02B	■ GUIDE, DISCRIMINATOR, KICKOVER	1	EA	AISI 4130	Orients kickover tool
6	1	ACT-SPM-2875-03	■ SUB, TOP, 2-7/8 EUE BOX	1	EA	AISI 4130 75K	
7	1	ACT-SPM-2875-04	■ SUB, BOTTOM, 2-7/8 EUE PIN	1	EA	AISI 4130 75K	
8	1	ACT-GLV-1000	■ VALVE, GAS LIFT, 1 IN. IPO, MONEL BELLOWS	1	EA	MONEL K-500 / 316 SS	Ordered separately; see DS-GLV-1000
9	2	ACT-GLV-1000-01	■ BELLOWS ASSY, N2 CHARGED	1	EA	MONEL K-500	Dome charge per valve design sheet
10	2	ACT-GLV-1000-02	■ SEAT, PORT, CARBIDE, 3/16	1	EA	TUNGSTEN CARBIDE	Ports: 1/8 - 5/16 available

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
11	2	ACT-GLV-1000-03	■ CHECK, REVERSE FLOW, DART	1	EA	17-4 PH / VITON 90A	
12	2	ACT-GLV-1000-04	■ LATCH, RK, 1 IN.	1	EA	17-4 PH H1150	

General Notes

- All elastomer components are single-use: replace at every redress from the applicable redress kit.
- Load-path metallic components require heat traceability to a mill certificate (EN 10204 Type 3.1) retained in the device history record.
- Shear devices (rings, screws, pins) are calibrated items - substitute parts are prohibited.
- Torque all threaded connections per ACT specification TS-100 (packers/plugs) or TS-200 (accessories).
- Sour service (NACE MR0175/ISO 15156) configurations use the materials noted; verify trim level on the sales order before assembly.
- Referenced documents: datasheet DS-SPM-2875, applicable manual/procedure, and quality plan ACT-QP-08.

Approvals

Role	Name	Signature	Date
Design Engineering	A. Gutierrez	/signed electronically/	2024-12-09
Manufacturing Engineering	T. Okafor	/signed electronically/	2024-12-09
Quality Assurance	S. Nguyen	/signed electronically/	2024-12-09
Engineering Manager	J. Martinez, P.E.	/signed electronically/	2024-12-09