

Bill of Materials - ACT-TA-2875 Tubing Anchor Catcher, 2-7/8 in.

Engineering Bill of Materials | Document BOM-TA-2875 Rev A

Product / Assembly	ACT-TA-2875
Document No. / Rev	BOM-TA-2875 Rev A
Effective Date	2025-05-12
Prepared By	A. Gutierrez
Checked By	T. Okafor
Approved By	J. Martinez, P.E.
ERP Reference	ITEM-TA-2875

Revision History

Rev	Date	Description of Change	By
A	2025-05-12	Initial release	A. Gutierrez

Bill of Materials

Hierarchy: Level 0 = top assembly; Level 1 = component or sub-assembly; Level 2 = sub-assembly component. Indented descriptions belong to the sub-assembly immediately above. Quantities are per one (1) next-higher assembly.

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
1	0	ACT-TA-2875	TUBING ANCHOR CATCHER ASSY, 2-7/8, 5-1/2 CSG	1	EA	-	Mechanical set, RH release
2	1	ACT-TA-2875-01	■ MANDREL, ANCHOR, 2-7/8 EUE	1	EA	AISI 4140 HT 28-32 HRC	
3	1	ACT-TA-2875-02	■ SLIP, ANCHOR, WICKER	3	EA	AISI 8620 CARBURIZED 58-62 HRC	
4	1	ACT-TA-2875-03	■ CONE, EXPANDER, DUAL TAPER	1	EA	AISI 4140 HT 28-32 HRC	
5	1	ACT-TA-2875-04	■ SPRING, DRAG, BOW TYPE	3	EA	6150 SPRING STEEL	
6	1	ACT-TA-2875-05	■ BLOCK, DRAG, CAGE	3	EA	AISI 1026	
7	1	ACT-TA-2875-06	■ PIN, SHEAR, SAFETY RELEASE, 5/16	6	EA	BRASS C36000	Shear release 60,000 lbf total (10,000/pin)
8	1	ACT-TA-2875-07	■ CLUTCH, JAY, LOWER	1	EA	AISI 4140 HT 28-32 HRC	
9	1	ACT-TA-2875-08	■ COLLAR, STOP, SWIVEL	1	EA	AISI 4140	
10	1	ACT-TA-2875-RK	■ REDRESS KIT, TA-2875	1	KT	-	
11	2	ACT-TA-2875-06	■ PIN, SHEAR, SAFETY RELEASE	6	EA	BRASS C36000	
12	2	ACT-ORG-220-H80	■ O-RING, -220, 80 DURO	2	EA	HNBR 80A	

General Notes

- All elastomer components are single-use: replace at every redress from the applicable redress kit.
- Load-path metallic components require heat traceability to a mill certificate (EN 10204 Type 3.1) retained in the device history record.
- Shear devices (rings, screws, pins) are calibrated items - substitute parts are prohibited.
- Torque all threaded connections per ACT specification TS-100 (packers/plugs) or TS-200 (accessories).
- Sour service (NACE MR0175/ISO 15156) configurations use the materials noted; verify trim level on the sales order before assembly.
- Referenced documents: datasheet DS-TA-2875, applicable manual/procedure, and quality plan ACT-QP-08.

Approvals

Role	Name	Signature	Date
Design Engineering	A. Gutierrez	/signed electronically/	2025-05-12
Manufacturing Engineering	T. Okafor	/signed electronically/	2025-05-12
Quality Assurance	S. Nguyen	/signed electronically/	2025-05-12
Engineering Manager	J. Martinez, P.E.	/signed electronically/	2025-05-12