

ACT-TA-2875 Tubing Anchor Catcher, 2-7/8 in.

Technical Datasheet DS-TA-2875 Rev A | Product family: ACT-TA-2875

1. Product Overview

The ACT-TA-2875 tubing anchor catcher stabilizes rod-pumped tubing strings in 5-1/2 in. casing, preventing tubing movement and breathing that rob pump efficiency. Set with 1/4 turn right-hand rotation at depth; releases with right-hand rotation or, in an emergency, by straight pull shear release. As a catcher, it prevents dropped tubing strings from falling.

2. Applications

- Rod pump (sucker rod) completions
- Preventing tubing breathing and rod wear
- Tubing string catch protection

3. Features

- 1/4 turn RH set / RH release - jay-slot mechanism
- Emergency shear release: 6 brass pins, 60,000 lbf total
- Bow-spring drag blocks maintain position while running
- Bi-directional wicker slips

4. Technical Specifications

Parameter	Specification
Casing Size	5-1/2 in., 14 - 23 lb/ft
Tubing Connection	2-7/8 in. EUE 8RD box x pin
Maximum OD	4.531 in.
Minimum ID	2.441 in.
Slip Rating	90,000 lbf tension/compression
Emergency Shear Release	60,000 lbf (6 x 10,000 lbf brass pins)
Temperature Rating	300 degF
Working Pressure	5,000 psi differential

All ratings are at ambient temperature unless otherwise noted. Performance envelope per API 11D1 V3 qualification testing where indicated. Consult ACT Engineering for combined load conditions.

5. Materials of Construction

Component	Material
Mandrel / cone / clutch	AISI 4140 28-32 HRC
Slips	AISI 8620 carburized 58-62 HRC
Drag springs	6150 spring steel
Shear pins	Brass C36000, 5/16 in.

6. Ordering & Reference Documents

Order by part number and specify: casing size and weight, service trim (standard or NACE sour), elastomer option, end connections, and any customer inspection requirements. Related documents:

- BOM-TA-2875 Rev A
- MAN-TA-2875 Manual
- TS-200

Datasheet DS-TA-2875 Rev A issued 2025-05-12. Prepared by R. Callahan; approved by J. Martinez, P.E.. Specifications subject to change; confirm with ACT Engineering for well-specific designs.