

Hydrostatic Test Report HTR-2025-0512

ACT-SSD-2875 | Serial No. SSD-25-0218

Report No. / Date	HTR-2025-0512 / 2025-09-04
Part / Serial No.	ACT-SSD-2875 / SSD-25-0218
Work Order	WO-25-1799
Customer / Order	SO-30411 (Eagle Ford operator)
Test Procedure	HTP-10 Rev E + functional shift test FST-28
Test Medium	Fresh water
Instrumentation	Crystal nVision SN 77102 (cal due 2026-02-28)
Ambient Temperature	81 degF
Rated Working Pressure	10,000 psi WP
Test Pressure / Hold	10,000 psi for 30 min
Acceptance Criteria	Max 2% drop; shift force < 600 lbf; no leakage past seals in CLOSED position

Pressure Log

Elapsed Time / Event	Gauge Pressure (psi)
0 (start)	0
Closed sleeve - test pressure 09:12	10,008
10 min	10,000
20 min	9,995
30 min (end hold)	9,990
Cycle sleeve OPEN-CLOSE x3, retest 10:05	10,010
10 min	10,005
15 min (end)	10,000

Recorded pressure decay over hold: 18 psi (0.18%) initial; 10 psi (0.10%) after cycling. Chart recording retained as attachment A (chart no. HTR-2025-0512-CH1).

Result: PASS

Remarks

Combined hydrostatic and functional test. Sleeve cycled open/close three times at zero differential; shift forces recorded 340-380 lbf (spec < 600). Seal integrity retest after cycling passed. Unit shipped with cert package CP-25-0871.

Certification

We certify that the above equipment was tested as described and met the stated acceptance criteria. Testing performed at ACT Burleson test bay 2 in accordance with the referenced procedure and ACT-QP-11 (pressure testing quality plan).

Role	Name	Signature	Date
------	------	-----------	------

Test Technician	M. Brennan	/signed electronically/	2025-09-04
QC Witness	D. Whitfield	/signed electronically/	2025-09-04
QA Approval	S. Nguyen	/signed electronically/	2025-09-04