

Torque Specification TS-200 - Flow Controls, Setting Tools, Anchors & Accessories

Engineering Specification TS-200 Rev B | Effective 2026-01-12

1. Purpose and Conditions

Companion to TS-100. Covers sliding sleeves, landing nipples, flow couplings, side pocket mandrels, tubing anchors, setting tools and seal assemblies. Same compound and calibration rules as TS-100 apply.

2. Table 1 - Flow Control Bodies

Product	Joint	Min (ft-lb)	Optimum (ft-lb)	Max (ft-lb)
ACT-SSD-2875	Upper body to ported body	2,000	2,200	2,400
ACT-SSD-2875	Ported body to lower body	2,000	2,200	2,400
ACT-LN-2875	EUE field connections	1,650	1,850	2,050
ACT-FC-2875	EUE field connections	1,650	1,850	2,050
ACT-SPM-2875	Top/bottom sub to body	2,400	2,650	2,900

3. Table 2 - Setting Tools

Product	Joint	Min (ft-lb)	Optimum (ft-lb)	Max (ft-lb)
ACT-ST-10	Firing head to upper chamber	450	500	550
ACT-ST-10	Chamber to chamber	450	500	550
ACT-ST-10	Oil cylinder to lower chamber	380	420	460
ACT-ST-10	Crossover sleeve	300	330	360
ACT-ST-20	All housing joints	700	780	860
ACT-ST-10/20	1/4 NPT fill plugs	18	20	22

4. Table 3 - Anchors and Seal Assemblies

Product	Joint	Min (ft-lb)	Optimum (ft-lb)	Max (ft-lb)
ACT-TA-2875	Mandrel connections	1,650	1,850	2,050
ACT-TA-2875	Clutch to mandrel	1,300	1,450	1,600
ACT-SA-4000	Seal unit stack make-up	1,000	1,100	1,200
ACT-SA-4000	Ratch-latch to mandrel	1,800	2,000	2,200
ACT-LH-RT-45	Release nut (LH thread)	900	1,000	1,100

5. General Notes

- ACT-LH-RT-45 release nut is LEFT-HAND thread - reverse wrench direction.
- Seal assembly units: apply compound sparingly; excess compound on seal ODs causes swab-off.

- NPT plugs: 2 wraps PTFE tape plus compound, torque per Table 2.

Role	Name	Signature	Date
Prepared (Mfg Engineering)	T. Okafor	/signed electronically/	2026-01-12
Approved (Engineering Manager)	J. Martinez, P.E.	/signed electronically/	2026-01-12
Document Control	L. Hargrove	/signed electronically/	2026-01-12