

PRODUCT MANUAL

Running & Removal Manual - ACT-BP Series Drillable Bridge Plugs

Document MAN-BP-SER | Revision D | 2025-10-21

Product Family	ACT-BP series
Prepared By	A. Gutierrez
Approved By	J. Martinez, P.E.
Document Control	L. Hargrove
Distribution	Field operations, service centers, licensed distributors

Table of Contents

1. GENERAL
2. SAFETY
3. WIRELINE SETTING
4. DRILL-OUT / REMOVAL
5. CASING RANGE TABLE
6. RECORDS

1. GENERAL

Applies to ACT-BP-4500 (4-1/2 in.) and ACT-BP-5500 (5-1/2 in.) drillable cast iron bridge plugs, 10,000 psi / 300 degF. Plugs set on wireline with the ACT-ST-10 setting tool and the size-matched adapter kit (AK-45 or AK-55), or mechanically on tubing.

2. SAFETY

WARNING: Verify well control barriers before rig-up. The plug is not a tested barrier until pressure-verified from above.

- Cast iron parts chip - wear eye protection during handling.
- Do not hammer on the element area.
- Explosive setting tools: API RP 67 applies.

3. WIRELINE SETTING

Step	Action	Check
1	Verify plug size vs casing weight from the table in Section 5.	Casing tally
2	Make up adapter kit to ST-10; torque tension rod 90 ft-lb.	TS-200
3	Thread tension nut onto plug mandrel to shoulder; back off 1/4 turn.	-
4	RIH max 300 ft/min; slow to 100 ft/min in fluid.	Line speed
5	Correlate depth (CCL/GR), position plug, fire charge.	Depth log
6	Confirm shear-out: 32,000 lbf (BP-4500) or 38,000 lbf (BP-5500) tension spike then release.	Tension chart
7	POOH; inspect setting sleeve for complete stroke (witness groove exposed).	Stroke check
8	Pressure test plug from above per program before declaring barrier.	Test chart

4. DRILL-OUT / REMOVAL

Mill or drill with a flat-bottom junk mill or rock bit. Class 40 cast iron drills freely: expect 35 min (BP-4500) to 42 min (BP-5500) average. Use 60-100 RPM, 2,000-5,000 lbf WOB. Circulate cuttings clear before tagging remaining fish.

5. CASING RANGE TABLE

Plug	Casing	Weight (lb/ft)	Casing ID range (in.)	Max plug OD (in.)
ACT-BP-4500	4-1/2 in.	9.5 - 13.5	3.920 - 4.090	3.750
ACT-BP-4500-SL (slim)	4-1/2 in.	13.5 - 15.1	3.826 - 3.920	3.687
ACT-BP-5500	5-1/2 in.	14 - 23	4.670 - 5.012	4.437
ACT-BP-5500-HW	5-1/2 in.	23 - 26	4.548 - 4.670	4.375

NOTE: For casing weights outside this table contact ACT Engineering; do not run undersized plugs.

6. RECORDS

Retain the wireline setting chart, tension log, and pressure test chart in the well file. Slip insert hardness is certified per lot; see QIR-2025-0198 for the current inspection format.

Document Approval

Role	Name	Signature	Date
Prepared	A. Gutierrez	/signed electronically/	2025-10-21
Quality Review	S. Nguyen	/signed electronically/	2025-10-21
Approved	J. Martinez, P.E.	/signed electronically/	2025-10-21