

Bill of Materials - ACT-LH-7625 Hydraulic Liner Hanger System, 7-5/8 x 4-1/2 in.

Engineering Bill of Materials | Document BOM-LH-7625 Rev A

Product / Assembly	ACT-LH-7625
Document No. / Rev	BOM-LH-7625 Rev A
Effective Date	2024-05-27
Prepared By	A. Gutierrez
Checked By	T. Okafor
Approved By	J. Martinez, P.E.
ERP Reference	ITEM-LH-7625

Revision History

Rev	Date	Description of Change	By
A	2024-05-27	Initial release	R. Callahan

Bill of Materials

Hierarchy: Level 0 = top assembly; Level 1 = component or sub-assembly; Level 2 = sub-assembly component. Indented descriptions belong to the sub-assembly immediately above. Quantities are per one (1) next-higher assembly.

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
1	0	ACT-LH-7625	LINER HANGER ASSY, HYDRAULIC, 7-5/8 x 4-1/2	1	EA	-	Single-cone, 3-slip hydraulic hanger
2	1	ACT-LH-7625-01	■ BODY, HANGER, 7-5/8	1	EA	API 5CT L80-13Cr	
3	1	ACT-LH-7625-02	■ SLIP, HANGER, TAPERED	3	EA	AISI 8620 CARBURIZED 58-62 HRC	120 deg spacing
4	1	ACT-LH-7625-03	■ CONE, FLOATING, SINGLE	1	EA	AISI 4140 HT 28-32 HRC	
5	1	ACT-LH-7625-04	■ CYLINDER, SETTING, HYDRAULIC	1	EA	AISI 4140 HT 28-32 HRC	
6	1	ACT-LH-7625-05	■ PISTON, SETTING	1	EA	AISI 4140 HT 28-32 HRC	
7	1	ACT-LH-7625-06	■ SCREW, SHEAR, SETTING PORT, 10-24	6	EA	BRASS C36000	Set pressure 2,200 +/- 150 psi
8	1	ACT-LH-7625-07	■ RING, LOCK, RATCHET, HANGER	1	EA	AISI 4340 HT 36-40 HRC	
9	1	ACT-LH-7625-08	■ SUB, EXTENSION, POLISHED BORE RECEPTACLE (PBR)	1	EA	API 5CT L80-13Cr, HONED ID	Mates ACT-SA-4000 seal assy
10	2	ACT-LH-7625-08A	■ RECEPTACLE, POLISHED BORE, 4.000 ID	1	EA	L80-13Cr, 16 RMS HONE	

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
11	2	ACT-LH-7625-08B	■ MUFF, PROTECTION, THREAD	1	EA	HDPE	
12	1	ACT-LH-7625-09	■ SUB, LANDING COLLAR, 4-1/2 LTC	1	EA	AISI 4140	
13	1	ACT-LH-7625-10	■ JUNK BONNET / PACKOFF, RUNNING	1	EA	AISI 4140 / HNBR 80A	
14	1	ACT-LH-RT-45	■ TOOL, RUNNING, HYD RELEASE, 4-1/2	1	EA	AISI 4140 HT 28-32 HRC	Rental; RH release 10 turns
15	2	ACT-LH-RT-45-01	■ NUT, RELEASE, LH THREAD	1	EA	AISI 4140	
16	2	ACT-LH-RT-45-02	■ KEY, ANTI-ROTATION	4	EA	AISI 4140 HT 32-36 HRC	

General Notes

- All elastomer components are single-use: replace at every redress from the applicable redress kit.
- Load-path metallic components require heat traceability to a mill certificate (EN 10204 Type 3.1) retained in the device history record.
- Shear devices (rings, screws, pins) are calibrated items - substitute parts are prohibited.
- Torque all threaded connections per ACT specification TS-100 (packers/plugs) or TS-200 (accessories).
- Sour service (NACE MR0175/ISO 15156) configurations use the materials noted; verify trim level on the sales order before assembly.
- Referenced documents: datasheet DS-LH-7625, applicable manual/procedure, and quality plan ACT-QP-08.

Approvals

Role	Name	Signature	Date
Design Engineering	A. Gutierrez	/signed electronically/	2024-05-27
Manufacturing Engineering	T. Okafor	/signed electronically/	2024-05-27
Quality Assurance	S. Nguyen	/signed electronically/	2024-05-27
Engineering Manager	J. Martinez, P.E.	/signed electronically/	2024-05-27