

ACT-LH-7625 Hydraulic Liner Hanger System, 7-5/8 x 4-1/2 in.

Technical Datasheet DS-LH-7625 Rev A | Product family: ACT-LH-7625

1. Product Overview

The ACT-LH-7625 hydraulic liner hanger suspends 4-1/2 in. liners in 7-5/8 in. casing. A single floating cone and three carburized slips distribute hanging load into the casing wall. The system includes a polished bore receptacle (PBR) that accepts the ACT-SA-4000 anchor seal assembly for tieback or production seal integrity.

2. Applications

- Drilling and production liner suspension
- Liner-top isolation with PBR/seal assembly
- Cemented or open-hole liners

3. Features

- Hydraulic set at 2,200 psi - no liner rotation or reciprocation required
- 3 x tapered slips, 120 deg spacing, 250,000 lbf hanging capacity
- Integral PBR, 4.000 in. honed bore (16 RMS)
- Hydraulic-release running tool (10 turns RH backup release)
- 13Cr body for sour service

4. Technical Specifications

Parameter	Specification
Parent Casing	7-5/8 in., 26.4 - 39 lb/ft
Liner Size	4-1/2 in.
Maximum OD	6.500 in.
Minimum ID (through hanger)	3.920 in.
Hanging Capacity	250,000 lbf
Setting Pressure	2,200 +/- 150 psi (6 brass screws)
PBR Bore	4.000 in., honed 16 RMS, length 10 ft (std)
Pressure Rating	8,000 psi
Temperature Rating	325 degF
Seal Assembly	ACT-SA-4000 (see DS-SA-4000)

All ratings are at ambient temperature unless otherwise noted. Performance envelope per API 11D1 V3 qualification testing where indicated. Consult ACT Engineering for combined load conditions.

5. Materials of Construction

Component	Material
Body / PBR	API 5CT L80-13Cr
Slips	AISI 8620 carburized 58-62 HRC
Cone / cylinder / piston	AISI 4140 28-32 HRC

Component	Material
Shear screws	Brass C36000

6. Ordering & Reference Documents

Order by part number and specify: casing size and weight, service trim (standard or NACE sour), elastomer option, end connections, and any customer inspection requirements. Related documents:

- BOM-LH-7625 Rev A
- LRP-LH-7625 Running Procedure
- HTR-2024-0389
- DS-SA-4000

Datasheet DS-LH-7625 Rev A issued 2024-05-27. Prepared by R. Callahan; approved by J. Martinez, P.E.. Specifications subject to change; confirm with ACT Engineering for well-specific designs.