

# ACT-PKR-7000 HPHT Hydraulic Set Permanent Packer, 15K

Technical Datasheet DS-PKR-7000 Rev A | Product family: ACT-PKR-7000

## 1. Product Overview

The ACT-PKR-7000 is a 15,000 psi HPHT permanent packer for 7 in. casing built for deep, hot, sour wells. Inconel 718 mandrel and subs, Aflas HPHT element package, and carbide-insert slips allow setting in CRA casing. A dual-piston setting module reduces required surface pressure. Qualified to API 11D1 Grade V0.

## 2. Applications

- HPHT completions to 15,000 psi differential
- Deep sour gas wells (H<sub>2</sub>S/CO<sub>2</sub>)
- CRA casing programs (13Cr, 25Cr)
- Extended-life subsea and tieback completions

## 3. Features

- 15,000 psi / 400 degF rating, API 11D1 V0 qualified
- Inconel 718 (UNS N07718) mandrel per AMS 5662, NACE MR0175 compliant
- Dual-piston setting module - full set at 4,500 psi applied
- Aflas 95/90 element system with garter-spring anti-extrusion
- Carbide-insert slips for CRA casing, 8 segments per slip
- 3-1/2 in. premium thread connections standard

## 4. Technical Specifications

| Parameter                    | Specification                               |
|------------------------------|---------------------------------------------|
| Casing Size                  | 7 in., 29 - 35 lb/ft                        |
| Maximum Tool OD              | 5.875 in.                                   |
| Minimum Bore ID              | 2.875 in.                                   |
| Overall Length               | 72.40 in.                                   |
| Differential Pressure Rating | 15,000 psi                                  |
| Temperature Rating           | 400 degF                                    |
| Setting Pressure             | 4,500 +/- 200 psi                           |
| End Connections              | 3-1/2 in. premium box up x pin down         |
| Tensile Rating (body)        | 310,000 lbf                                 |
| Gas Envelope                 | API 11D1 Grade V0 (gas-tight)               |
| Service                      | Sour, HPHT; NACE MR0175/ISO 15156 compliant |

All ratings are at ambient temperature unless otherwise noted. Performance envelope per API 11D1 V3 qualification testing where indicated. Consult ACT Engineering for combined load conditions.

## 5. Materials of Construction

| Component       | Material                                       |
|-----------------|------------------------------------------------|
| Mandrel / Subs  | Inconel 718 (UNS N07718), AMS 5662, 40 HRC max |
| Cones / Pistons | API 5CT L80-13Cr                               |
| Slips           | 8620 carburized with tungsten carbide inserts  |
| Element         | Aflas 95A/90A (compounds ACT-A95/ACT-A90)      |
| Seals           | Aflas 90A with PEEK backups                    |

## 6. Ordering & Reference Documents

Order by part number and specify: casing size and weight, service trim (standard or NACE sour), elastomer option, end connections, and any customer inspection requirements. Related documents:

- BOM-PKR-7000 Rev A
- MAN-PKR-7000 Operations Manual
- HTR-2025-0456 (15K hydrotest)
- MTR heat HT-71834 (Inconel 718)

Datasheet DS-PKR-7000 Rev A issued 2025-06-22. Prepared by R. Callahan; approved by J. Martinez, P.E.. Specifications subject to change; confirm with ACT Engineering for well-specific designs.