

Bill of Materials - ACT-SSD-2875 Sliding Sleeve, 2-7/8 in.

Engineering Bill of Materials | Document BOM-SSD-2875 Rev B

Product / Assembly	ACT-SSD-2875
Document No. / Rev	BOM-SSD-2875 Rev B
Effective Date	2025-01-29
Prepared By	A. Gutierrez
Checked By	T. Okafor
Approved By	J. Martinez, P.E.
ERP Reference	ITEM-SSD-2875

Revision History

Rev	Date	Description of Change	By
A	2023-04-03	Initial release	A. Gutierrez
B	2025-01-29	Detent ring material to Be-Cu Alloy 25; port count 8 to 12	R. Callahan

Bill of Materials

Hierarchy: Level 0 = top assembly; Level 1 = component or sub-assembly; Level 2 = sub-assembly component. Indented descriptions belong to the sub-assembly immediately above. Quantities are per one (1) next-higher assembly.

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
1	0	ACT-SSD-2875	SLIDING SLEEVE ASSY, 2-7/8, 10K	1	EA	-	Shifts w/ ACT-SFT-20 shifting tool
2	1	ACT-SSD-2875-01	■ BODY, UPPER, 2-7/8 EUE BOX	1	EA	AISI 4140 HT 22 HRC MAX	NACE MR0175 compliant
3	1	ACT-SSD-2875-02	■ BODY, PORTED, CENTER	1	EA	AISI 4140 HT 22 HRC MAX	12 ports x 0.50 dia; 4.7 sq-in flow area
4	1	ACT-SSD-2875-03	■ SLEEVE, INNER, SHIFTING	1	EA	AISI 4140 QPQ NITRIDED	X-profile top
5	2	ACT-SSD-2875-03A	■ PROFILE, SHIFTING, X-TYPE	1	EA	INTEGRAL	Accepts B shifting tool
6	2	ACT-SSD-2875-03B	■ RING, DETENT, COLLET	1	EA	BE-CU ALLOY 25	Open/close detent 350 lbf
7	1	ACT-SSD-2875-04	■ SEAL STACK, UPPER, V-PACKING	1	ST	HNBR/PTFE/PEEK CHEVRON	5-element stack
8	1	ACT-SSD-2875-05	■ SEAL STACK, LOWER, V-PACKING	1	ST	HNBR/PTFE/PEEK CHEVRON	5-element stack
9	1	ACT-SSD-2875-06	■ BODY, LOWER, 2-7/8 EUE PIN	1	EA	AISI 4140 HT 22 HRC MAX	
10	1	ACT-SSD-2875-07	■ SCREW, SET, BODY LOCK, 1/4-20	4	EA	ALLOY STEEL GR 8	Torque 15 ft-lb + thread locker
11	1	ACT-SSD-2875-RK	■ REDRESS KIT, SSD-2875	1	KT	-	

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
12	2	ACT-CHV-238-M	■ SEAL STACK, CHEVRON, 2.38 BORE	2	ST	HNBR/PTFE/PEEK	
13	2	ACT-ORG-222-H80	■ O-RING, -222, 80 DURO	4	EA	HNBR 80A	

General Notes

- All elastomer components are single-use: replace at every redress from the applicable redress kit.
- Load-path metallic components require heat traceability to a mill certificate (EN 10204 Type 3.1) retained in the device history record.
- Shear devices (rings, screws, pins) are calibrated items - substitute parts are prohibited.
- Torque all threaded connections per ACT specification TS-100 (packers/plugs) or TS-200 (accessories).
- Sour service (NACE MR0175/ISO 15156) configurations use the materials noted; verify trim level on the sales order before assembly.
- Referenced documents: datasheet DS-SSD-2875, applicable manual/procedure, and quality plan ACT-QP-08.

Approvals

Role	Name	Signature	Date
Design Engineering	A. Gutierrez	/signed electronically/	2025-01-29
Manufacturing Engineering	T. Okafor	/signed electronically/	2025-01-29
Quality Assurance	S. Nguyen	/signed electronically/	2025-01-29
Engineering Manager	J. Martinez, P.E.	/signed electronically/	2025-01-29