

Bill of Materials - ACT-ST-10 Wireline Pressure Setting Tool, Size #10

Engineering Bill of Materials | Document BOM-ST-10 Rev B

Product / Assembly	ACT-ST-10
Document No. / Rev	BOM-ST-10 Rev B
Effective Date	2026-03-02
Prepared By	A. Gutierrez
Checked By	T. Okafor
Approved By	J. Martinez, P.E.
ERP Reference	ITEM-ST-10

Revision History

Rev	Date	Description of Change	By
A	2021-07-14	Initial release	J. Martinez, P.E.
B	2026-03-02	Firing head o-rings Viton to HNBR per ECO-2026-008	A. Gutierrez

Bill of Materials

Hierarchy: Level 0 = top assembly; Level 1 = component or sub-assembly; Level 2 = sub-assembly component. Indented descriptions belong to the sub-assembly immediately above. Quantities are per one (1) next-higher assembly.

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
1	0	ACT-ST-10	SETTING TOOL ASSY, WIRELINE PRESSURE, SIZE #10	1	EA	-	Rev B per ECO-2026-008
2	1	ACT-ST-10-01	■ HEAD, FIRING, TOP	1	EA	AISI 4140 HT 28-32 HRC	
3	2	ACT-ST-10-01A	■ INITIATOR, IGNITER ADAPTER	1	EA	AISI 4140	Accepts std wireline igniter
4	2	ACT-ORG-116-H90	■ O-RING, -116, 90 DURO	2	EA	HNBR 90A	Viton -> HNBR per ECO-2026-008 (low-temp)
5	1	ACT-ST-10-02	■ CHAMBER, POWER CHARGE, UPPER	1	EA	AISI 4140 HT 28-32 HRC	Accepts #10 power charge (not incl.)
6	1	ACT-ST-10-03	■ CHAMBER, GAS EXPANSION, LOWER	1	EA	AISI 4140 HT 28-32 HRC	
7	1	ACT-ST-10-04	■ PISTON, PRIMARY	1	EA	AISI 4140 HT 28-32 HRC	
8	1	ACT-ST-10-05	■ PISTON, SECONDARY (FLOATING)	1	EA	AISI 4140 HT 28-32 HRC	
9	1	ACT-ST-10-06	■ CYLINDER, OIL, HYDRAULIC DELAY	1	EA	AISI 4140	Fill w/ 10W hyd. oil, 410 mL
10	2	ACT-ST-10-06A	■ ORIFICE, BLEED, 0.028 DIA	1	EA	17-4 PH SS	Controls stroke rate

Item	Lvl	Part Number	Description	Qty	UOM	Material / Spec	Notes
11	2	ACT-ST-10-06B	■ PLUG, FILL, 1/4 NPT	2	EA	AISI 4140	
12	1	ACT-ST-10-07	■ ROD, PISTON, OUTPUT	1	EA	AISI 4340 HT 32-36 HRC	60,000 lbf max output
13	1	ACT-ST-10-08	■ SLEEVE, CROSSOVER, BOTTOM	1	EA	AISI 4140	Mates AK-45/AK-55/FP-AK-55 kits
14	1	ACT-ST-10-09	■ PIN, SHEAR, RELEASE, 1/4 DIA	3	EA	STEEL AISI 1018	
15	1	ACT-ST-10-RK	■ REDRESS KIT, ST-10	1	KT	-	
16	2	ACT-ORG-116-H90	■ O-RING, -116, 90 DURO	2	EA	HNBR 90A	
17	2	ACT-ORG-210-H90	■ O-RING, -210, 90 DURO	6	EA	HNBR 90A	
18	2	ACT-ORG-218-H90	■ O-RING, -218, 90 DURO	4	EA	HNBR 90A	
19	2	ACT-ST-10-09	■ PIN, SHEAR, RELEASE	3	EA	AISI 1018	

General Notes

- All elastomer components are single-use: replace at every redress from the applicable redress kit.
- Load-path metallic components require heat traceability to a mill certificate (EN 10204 Type 3.1) retained in the device history record.
- Shear devices (rings, screws, pins) are calibrated items - substitute parts are prohibited.
- Torque all threaded connections per ACT specification TS-100 (packers/plugs) or TS-200 (accessories).
- Sour service (NACE MR0175/ISO 15156) configurations use the materials noted; verify trim level on the sales order before assembly.
- Referenced documents: datasheet DS-ST-10, applicable manual/procedure, and quality plan ACT-QP-08.

Approvals

Role	Name	Signature	Date
Design Engineering	A. Gutierrez	/signed electronically/	2026-03-02
Manufacturing Engineering	T. Okafor	/signed electronically/	2026-03-02
Quality Assurance	S. Nguyen	/signed electronically/	2026-03-02
Engineering Manager	J. Martinez, P.E.	/signed electronically/	2026-03-02