

## ACT-ST Series Wireline Pressure Setting Tools (#10 / #20)

Technical Datasheet DS-ST-SERIES Rev B | Product family: ACT-ST-10 / ACT-ST-20

### 1. Product Overview

ACT-ST series wireline pressure setting tools convert the gas pressure of a slow-burning power charge into controlled linear stroke to set bridge plugs, frac plugs, cement retainers and permanent packers. An oil-filled hydraulic delay section meters the stroke to protect the element system of the tool being set. Compatible with industry-standard #10 and #20 power charges and igniters.

### 2. Applications

- Setting ACT-BP, ACT-FP, ACT-CR series plugs and retainers
- Setting wireline-adapted permanent packers

### 3. Features

- Field-proven dual-piston, oil-metered design
- Redress in the field with kit ACT-ST-10-RK / ST-20-RK
- HNBR o-rings standard for -20 degF to 300 degF service (per ECO-2026-008)
- Quick-change bottom crossover accepts all ACT adapter kits

### 4. Technical Specifications

| Parameter                | ACT-ST-10 (#10)    | ACT-ST-20 (#20)    |
|--------------------------|--------------------|--------------------|
| Tool OD                  | 1.6875 in.         | 2.750 in.          |
| Length (w/o adapter kit) | 68 in.             | 74 in.             |
| Maximum Output Force     | 60,000 lbf         | 120,000 lbf        |
| Stroke                   | 7.5 in.            | 9.0 in.            |
| Power Charge             | #10 (not supplied) | #20 (not supplied) |
| Oil Fill Volume (10W)    | 410 mL             | 780 mL             |
| Temperature Rating       | 300 degF           | 300 degF           |
| Max Hydrostatic          | 15,000 psi         | 15,000 psi         |
| Redress Kit              | ACT-ST-10-RK       | ACT-ST-20-RK       |

All ratings are at ambient temperature unless otherwise noted. Performance envelope per API 11D1 V3 qualification testing where indicated. Consult ACT Engineering for combined load conditions.

### 5. Materials of Construction

| Component         | Material                                |
|-------------------|-----------------------------------------|
| Pressure housings | AISI 4140, 28-32 HRC                    |
| Output rod        | AISI 4340, 32-36 HRC                    |
| Bleed orifice     | 17-4 PH SS                              |
| O-rings           | HNBR 90A (Viton optional for >300 degF) |

## 6. Ordering & Reference Documents

Order by part number and specify: casing size and weight, service trim (standard or NACE sour), elastomer option, end connections, and any customer inspection requirements. Related documents:

- BOM-ST-10 Rev B
- MAN-ST-10 Operation & Redress Manual
- ECO-2026-008
- TS-200

Datasheet DS-ST-SERIES Rev B issued 2026-02-19. Prepared by R. Callahan; approved by J. Martinez, P.E.. Specifications subject to change; confirm with ACT Engineering for well-specific designs.