

Hydrostatic Test Report HTR-2024-0389

ACT-LH-7625 | Serial No. LH76-24-0003

Report No. / Date	HTR-2024-0389 / 2024-11-21
Part / Serial No.	ACT-LH-7625 / LH76-24-0003
Work Order	WO-24-2110
Customer / Order	Qualification unit (engineering)
Test Procedure	HTP-8 Rev A
Test Medium	Fresh water
Instrumentation	Crystal XP2i SN 812277 (cal due 2025-03-31)
Ambient Temperature	59 degF
Rated Working Pressure	8,000 psi WP
Test Pressure / Hold	8,000 psi for 30 min
Acceptance Criteria	Max 2% drop in 30 min; no leakage at PBR seal joint

Pressure Log

Elapsed Time / Event	Gauge Pressure (psi)
0 (start)	0
Step 4,000 - 5 min	4,000
Test pressure reached 14:40	8,010
10 min	8,000
20 min	7,995
30 min (end hold)	7,990

Recorded pressure decay over hold: 20 psi (0.25%). Chart recording retained as attachment A (chart no. HTR-2024-0389-CH1).

Result: PASS

Remarks

Qualification body test including PBR extension joint. Setting cylinder isolated with test plugs (setting function tested separately on bench TB-2 at 2,250 psi actuation). This report is the referenced protocol for production units (see QIR-2026-0031).

Certification

We certify that the above equipment was tested as described and met the stated acceptance criteria. Testing performed at ACT Burleson test bay 2 in accordance with the referenced procedure and ACT-QP-11 (pressure testing quality plan).

Role	Name	Signature	Date
Test Technician	M. Brennan	/signed electronically/	2024-11-21

QC Witness	D. Whitfield	/signed electronically/	2024-11-21
QA Approval	S. Nguyen	/signed electronically/	2024-11-21