



Chapter 7: Normalization

Database System Concepts, 7th Ed.


©Silberschatz, Korth and Sudarshan

See www.db-book.com for conditions on re-use



Outline

- Features of Good Relational Model Design
- Functional Dependencies
- Decomposition Using Functional Dependencies
- Normal Forms
- Functional Dependency Theory
- Algorithms for Decomposition using Functional Dependencies
- Decomposition Using Multivalued Dependencies
- More Normal Form
- Atomic Domains and First Normal Form
- Database-Design Process
- Modeling Temporal Data



Database Design and Normal Forms

Database Design

- coming up with a ‘good’ schema is very important

How do we characterize the “goodness” of a schema ?

If two or more alternative schemas are available

how do we compare them ?

What are the problems with “bad” schema designs ?

Normal Forms:

Each normal form specifies certain conditions

If the conditions are satisfied by the schema

certain kind of problems are avoided

Details follow....

An Example

student relation with attributes: studName, rollNo, sex, studDept

department relation with attributes: deptName, officePhone, hod

Several students belong to a department.

studDept gives the name of the student's department.

Correct schema:

Student

studName	<u>rollNo</u>	sex	studDept
----------	---------------	-----	----------

Department

<u>deptName</u>	officePhone	HOD
-----------------	-------------	-----



Incorrect schema:

Student Dept

studName	rollNo	sex	deptName	officePhone	HOD
----------	--------	-----	----------	-------------	-----

What are the problems that arise ?



Problems with bad schema

Redundant storage of data:

Office Phone & HOD info - stored redundantly

- once with each student that belongs to the department
- wastage of disk space

A program that updates Office Phone of a department

- must change it at several places
 - more running time
 - error - prone

Transactions running on a database

- must take as short time as possible to increase transaction throughput



Update Anomalies

Another kind of problem with bad schema

Insertion anomaly:

No way of inserting info about a new department unless we also enter details of a (dummy) student in the department


Deletion anomaly:

If all students of a certain department leave and we delete their tuples, information about the department itself is lost

Update Anomaly:

Updating officePhone of a department

- value in several tuples needs to be changed
- if a tuple is missed - inconsistency in data



Normal Forms

First Normal Form (1NF) - included in the definition of a relation

Second Normal Form (2NF)

Third Normal Form (3NF)

Boyce-Codd Normal Form (BCNF)

} defined in terms of
functional dependencies

Fourth Normal Form (4NF) - defined using multivalued
dependencies

Fifth Normal Form (5NF) or Project Join Normal Form (PJNF)
defined using join dependencies



Features of Good Relational Model Designs

- Suppose we combine *instructor* and *department* into *in_dep*, which represents the natural join on the relations *instructor* and *department*

<i>ID</i>	<i>name</i>	<i>salary</i>	<i>dept_name</i>	<i>building</i>	<i>budget</i>
22222	Einstein	95000	Physics	Watson	70000
12121	Wu	90000	Finance	Painter	120000
32343	El Said	60000	History	Painter	50000
45565	Katz	75000	Comp. Sci.	Taylor	100000
98345	Kim	80000	Elec. Eng.	Taylor	85000
76766	Crick	72000	Biology	Watson	90000
10101	Srinivasan	65000	Comp. Sci.	Taylor	100000
58583	Califieri	62000	History	Painter	50000
83821	Brandt	92000	Comp. Sci.	Taylor	100000
15151	Mozart	40000	Music	Packard	80000
33456	Gold	87000	Physics	Watson	70000
76543	Singh	80000	Finance	Painter	120000

- Anomalies
 - Update
 - Insertion
 - Deletion

- There is repetition of information
- Need to use null values (if we add a new department with no instructors)



A Combined Schema Without Repetition

Not all combined schemas result in repetition of information

- Consider combining relations
 - *sec_class(sec_id, building, room_number)* and
 - *section(course_id, sec_id, semester, year)*into one relation
 - *section(course_id, sec_id, semester, year, building, room_number)*
- No repetition in this case



Decomposition

- The only way to avoid the repetition-of-information problem in the *in_dep* schema is to decompose it into two schemas – *instructor* and *department* schemas.
- Not all decompositions are good. Suppose we decompose

employee(*ID*, *name*, *street*, *city*, *salary*)

into

employee1 (*ID*, *name*)


employee2 (*name*, *street*, *city*, *salary*)

The problem arises when we have two employees with the same name

- The next slide shows how we lose information -- we cannot reconstruct the original *employee* relation -- and so, this is a **lossy decomposition**.



A Lossy Decomposition





Lossless Decomposition

- Let R be a relation schema and let R_1 and R_2 form a decomposition of R . That is $R = R_1 \cup R_2$
- We say that the decomposition is a **lossless decomposition** if there is no loss of information by replacing R with the two relation schemas $R_1 \cup R_2$
- Formally,

$$\Pi_{R_1}(r) \bowtie \Pi_{R_2}(r) = r$$

- And, conversely a decomposition is lossy if

$$r \subset \Pi_{R_1}(r) \bowtie \Pi_{R_2}(r)$$



Example of Lossless Decomposition

□ Decomposition of $R = (A, B, C)$

$$R_1 = (A, B)$$

$$R_2 = (B, C)$$

A	B	C
α	1	A
β	2	B

r

A	B
α	1
β	2

$\Pi_{A,B}(r)$

B	C
1	A
2	B

$\Pi_{B,C}(r)$

$\Pi_A(r) \bowtie \Pi_B(r)$

A	B	C
α	1	A
β	2	B



Normalization Theory

- Decide whether a particular relation R is in “good” form.
- In the case that a relation R is not in “good” form, decompose it into set of relations $\{R_1, R_2, \dots, R_n\}$ such that
 - Each relation is in good form
 - The decomposition is a lossless decomposition
- Our theory is based on:
 - Functional dependencies
 - Multivalued dependencies



Functional Dependencies

- There are usually a variety of constraints (rules) on the data in the real world.
- For example, some of the constraints that are expected to hold in a university database are:
 - Students and instructors are uniquely identified by their ID.
 - Each student and instructor has only one name.
 - Each instructor and student is (primarily) associated with only one department.
 - Each department has only one value for its budget, and only one associated building.



Functional Dependencies (Cont.)

- An instance of a relation that satisfies all such real-world constraints is called a **legal instance** of the relation;
- A legal instance of a database is one where all the relation instances are legal instances
- Constraints on the set of legal relations require that the value for a certain set of attributes determines uniquely the value for another set of attributes.
- $\alpha \rightarrow \beta$ (α **determines** β), where α and β indicates set of attributes
- A functional dependency is a generalization of the notion of a *key*.



Functional Dependencies Definition

- Let R be a relation schema

$$\alpha \subseteq R \text{ and } \beta \subseteq R$$

- The **functional dependency**

$$\alpha \rightarrow \beta$$

holds on R if and only if for any legal relations $r(R)$, whenever any two tuples t_1 and t_2 of r agree on the attributes α , they also agree on the attributes β . That is,

$$t_1[\alpha] = t_2[\alpha] \Rightarrow t_1[\beta] = t_2[\beta]$$

- Example: Consider $r(A, B)$ with the following instance of r .

1	4
1	5
3	7

- On this instance, $B \rightarrow A$ hold; $A \rightarrow B$ does **NOT** hold.



Closure of a Set of Functional Dependencies

- Given a set F of functional dependencies, there are certain other functional dependencies that are logically implied by F .
 - If $A \rightarrow B$ and $B \rightarrow C$, then we can infer that $A \rightarrow C$, etc.
- The set of **all** functional dependencies logically implied by F is the **closure** of F .
- We denote the *closure* of F by F^+ .



Keys and Functional Dependencies

- K is a superkey for relation schema R if and only if $K \rightarrow R$
- K is a candidate key for R if and only if
 - $K \rightarrow R$, and
 - for no $\alpha \subset K$, $\alpha \rightarrow R$
- Functional dependencies allow us to express constraints that cannot be expressed using superkeys. Consider the schema:

in_dep (ID, name, salary, dept_name, building, budget).

We expect these functional dependencies to hold:

dept_name \rightarrow *building*, *budget*

ID, *dept_name* \rightarrow *name*, *salary*, *building*, *budget* (superkey)

ID \rightarrow *name*, *salary*, *dept_name*, *building*, *budget* (candidate key)

but would not expect the following to hold:

dept_name \rightarrow *salary*



Use of Functional Dependencies

- We use functional dependencies to:
 - To test relations to see if they are legal under a given set of functional dependencies.
 - ▶ If a relation r is legal under a set F of functional dependencies, we say that r **satisfies** F .
 - To specify constraints on the set of legal relations
 - ▶ We say that F **holds on** R if all legal relations on R satisfy the set of functional dependencies F .
- Note: A specific instance of a relation schema may satisfy a functional dependency even if the functional dependency does not hold on all legal instances.
 - For example, a specific instance of *instructor* may, by chance, satisfy

$name \rightarrow ID.$



Trivial Functional Dependencies

- Some functional dependencies are **trivial**, if they satisfy all relations.
- Example:
 - $ID, name \rightarrow ID$
 - $name \rightarrow name$
- In general, $\alpha \rightarrow \beta$ is trivial if $\beta \subseteq \alpha$



Lossless Decomposition

- We can use functional dependencies to show when certain decompositions are lossless.
- For the case of $R = (R_1, R_2)$, we require that for all possible relations r on schema R

$$r = \Pi_{R_1}(r) \bowtie \Pi_{R_2}(r)$$

- A decomposition of R into R_1 and R_2 is lossless decomposition if at least one of the following dependencies is in F^+ :
 - $R_1 \cap R_2 \rightarrow R_1$
 - $R_1 \cap R_2 \rightarrow R_2$
- The above functional dependencies are a sufficient condition for lossless join decomposition;



Example

- $R = (A, B, C)$

$$F = \{A \rightarrow B, B \rightarrow C\}$$

- $R_1 = (A, B), \quad R_2 = (B, C)$

- Lossless decomposition:

$$R_1 \cap R_2 = \{B\} \text{ and } B \rightarrow BC$$

- $R_1 = (A, B), \quad R_2 = (A, C)$

- Lossless decomposition:

$$R_1 \cap R_2 = \{A\} \text{ and } A \rightarrow AB$$

- *Note:*

- $B \rightarrow BC$

is a shorthand notation for

- $B \rightarrow \{B, C\}$



Dependency Preservation

- ❑ Testing functional dependency constraints each time the database is updated can be costly
- ❑ It is useful to design the database in a way that constraints can be tested efficiently.
- ❑ If testing a functional dependency can be done by considering just one relation, then the cost of testing this constraint is low
- ❑ When decomposing a relation it is possible that it is no longer possible to do the testing without having to perform a Cartesian Product.
- ❑ A decomposition that makes it computationally hard to enforce functional dependency is said to be NOT **dependency preserving**.



Dependency Preservation Example

- Consider a schema: $dept_advisor(s_ID, i_ID, department_name)$
- With function dependencies:
$$i_ID \rightarrow dept_name$$
$$s_ID, dept_name \rightarrow i_ID$$
- In the above design we are forced to repeat the department name once for each time an instructor participates in a $dept_advisor$ relationship.
- To fix this, we need to decompose $dept_advisor$ into (s_ID, i_ID) & $(i_ID, dept_name)$
- Any decomposition will not include all the attributes in
$$s_ID, dept_name \rightarrow i_ID$$
- Thus, the decomposition NOT be dependency preserving




Figure 7.6 The $dept_advisor$ relationship set.
©Silberschatz, Korth and Sudarshan




Figure 7.6 The *dept_advisor* relationship set.



Normal Forms



Normal Forms

First Normal Form (1NF) - included in the definition of a relation

Second Normal Form (2NF)

Third Normal Form (3NF)

Boyce-Codd Normal Form (BCNF)

} defined in terms of
functional dependencies

Fourth Normal Form (4NF) - defined using multivalued
dependencies

Fifth Normal Form (5NF) or Project Join Normal Form (PJNF)
defined using join dependencies



- Features of Good Relational Design
- Atomic Domains and First Normal Form
- Functional Dependencies

ATOMIC DOMAINS AND FIRST NORMAL FORM



First Normal Form (1NF)

- Domain is **atomic** if its elements are considered to be indivisible units
 - Examples of non-atomic domains:
 - Set of names, composite attributes
 - Identification numbers like CS101 that can be broken up into parts
- A relational schema R is in **first normal form** if
 - the domains of all attributes of R are atomic
 - the value of each attribute contains only a single value from that domain
- Non-atomic values complicate storage and encourage redundant (repeated) storage of data
 - Example: Set of accounts stored with each customer, and set of owners stored with each account
 - We assume all relations are in first normal form



First Normal Form (Cont'd)

- The following is not in 1NF

Customer

Customer ID	First Name	Surname	Telephone Number
123	Pooja	Singh	555-861-2025, 192-122-1111
456	San	Zhang	(555) 403-1659 Ext. 53; 182-929-2929
789	John	Doe	555-808-9633

- A telephone number is composite
- Telephone number is multi-valued

Source: https://en.wikipedia.org/wiki/First_normal_form



First Normal Form (Cont'd)


- Consider:

Customer

Customer ID	First Name	Surname	Telephone Number1	Telephone Number2
123	Pooja	Singh	555-861-2025	192-122-1111
456	San	Zhang	(555) 403-1659 Ext. 53	182-929-2929
789	John	Doe	555-808-9633	

- Is in 1NF if telephone number is not considered composite
- However, conceptually, we have two attributes for the same concept
 - Arbitrary and meaningless ordering of attributes
 - How to search telephone numbers
 - Why only two numbers?

Source: https://en.wikipedia.org/wiki/First_normal_form





First Normal Form (Cont'd)


- Is the following in 1NF?

Customer

Customer ID	First Name	Surname	Telephone Number
123	Pooja	Singh	555-861-2025
123	Pooja	Singh	192-122-1111
456	San	Zhang	182-929-2929
456	San	Zhang	(555) 403-1659 Ext. 53
789	John	Doe	555-808-9633

- Duplicated information
- ID is no more the key. Key is (ID, Telephone Number)

Source: https://en.wikipedia.org/wiki/First_normal_form





First Normal Form (Cont'd)

- Better to have 2 relations:

Customer Name			Customer Telephone Number	
<u>Customer ID</u>	First Name	Surname	<u>Customer ID</u>	<u>Telephone Number</u>
123	Pooja	Singh	123	555-861-2025
456	San	Zhang	123	192-122-1111
789	John	Doe	456	(555) 403-1659 Ext. 53
			456	182-929-2929
			789	555-808-9633

- One-to-Many relationship between parent and child relations
- Incidentally, satisfies 2NF and 3NF

Source: https://en.wikipedia.org/wiki/First_normal_form





Normal Forms – 2NF

Full functional dependency:

An FD $X \rightarrow A$ for which there is no proper subset Y of X
such that $Y \rightarrow A$
(A is said to be fully functionally dependent on X)

2NF: A relation schema R is in 2NF if
every non-prime attribute is fully functionally dependent on any
key of R

prime attribute: A attribute that is part of some key

non-prime attribute: An attribute that is not part of any key



Example

1) Book (authorName, title, authorAffiliation, ISBN, publisher, pubYear)

Keys: (authorName, title), ISBN

Not in 2NF as authorName \rightarrow authorAffiliation

(authorAffiliation is not fully functionally dependent on the first key)

2) Student (rollNo, name, dept, sex, hostelName, roomNo, admitYear)

Keys: rollNo, (hostelName, roomNo)

Not in 2NF as hostelName \rightarrow sex

student (rollNo, name, dept, hostelName, roomNo, admitYear)

hostelDetail (hostelName, sex)

- There are both in 2NF



Transitive Dependencies

Transitive dependency:

An FD $X \rightarrow Y$ in a relation schema R for which there is a set of attributes $Z \subseteq R$ such that

$X \rightarrow Z$ and $Z \rightarrow Y$ and Z is not a subset of any key of R

Ex: student (rollNo, name, dept, hostelName, roomNo, headDept)

Keys: rollNo, (hostelName, roomNo)

rollNo \rightarrow dept; dept \rightarrow headDept hold

So, rollNo \rightarrow headDept a transitive dependency

Head of the dept of dept D is stored redundantly in every tuple where D appears.

Relation is in 2NF but redundancy still exists.



Normal Forms – 3NF

Relation schema R is in 3NF if it is in 2NF and no non-prime attribute of R is transitively dependent on any key of R

student (rollNo, name, dept, hostelname, roomNo, headDept)
is not in 3NF

Decompose: student (rollNo, name, dept, hostelName, roomNo)
deptInfo (dept, headDept)
both in 3NF

Redundancy in data storage - removed



Another definition of 3NF

Relation schema R is in 3NF if for any nontrivial FD $X \rightarrow A$ either (i) X is a superkey or (ii) A is prime.

Suppose some R violates the above definition

\Rightarrow There is an FD $X \rightarrow A$ for which both (i) and (ii) are false

$\Rightarrow X$ is not a superkey and A is non-prime attribute

Two cases arise:


1) X is contained in a key – A is not fully functionally dependent on this key

- violation of 2NF condition

2) X is not contained in a key

$K \rightarrow X, X \rightarrow A$ is a case of transitive dependency

(K – any key of R)



Motivating example for BCNF

gradeInfo (rollNo, studName, course, grade)

Suppose the following FDs hold:

- 1) rollNo, course \rightarrow grade
- 2) studName, course \rightarrow grade
- 3) rollNo \rightarrow studName
- 4) studName \rightarrow rollNo

Keys:

- (rollNo, course)
- (studName, course)

For 1,2 lhs is a key. For 3,4 rhs is prime

So gradeInfo is in 3NF

But studName is stored redundantly along with every course
being done by the student



Motivating example for BCNF

gradeInfo (rollNo, studName, course, grade)

Suppose the following FDs hold:

- 1) rollNo, course \rightarrow grade
- 2) studName, course \rightarrow grade
- 3) rollNo \rightarrow studName
- 4) studName \rightarrow rollNo

Keys:

- (rollNo, course)
- (studName, course)

For 1,2 lhs is a key. For 3,4 rhs is prime

So gradeInfo is in 3NF

But studName is stored redundantly along with every course
being done by the student



Boyce-Codd Normal Form

- A relation schema R is in BCNF with respect to a set F of functional dependencies if for all functional dependencies in F^+ of the form

$$\alpha \rightarrow \beta$$

where $\alpha \subseteq R$ and $\beta \subseteq R$, at least one of the following holds:

- $\alpha \rightarrow \beta$ is trivial (i.e., $\beta \subseteq \alpha$)
- α is a superkey for R



Boyce-Codd Normal Form (Cont.)

- Example schema that is **not** in BCNF:

in_dep (ID, *name*, *salary*, *dept_name*, *building*, *budget*)

because :

- *dept_name* → *building*, *budget* holds on *in_dep*
- but *dept_name* is not a superkey
- When decompose *in_dept* into *instructor* and *department*
 - *instructor* is in BCNF
 - *department* is in BCNF



Decomposing a Schema into BCNF

- Let R be a schema that is not in BCNF.
- Let $\alpha \rightarrow \beta$ be the FD that causes a violation of BCNF.
- We decompose R into:
 - $(\alpha \cup \beta)$
 - $(R - (\beta - \alpha))$
- In our example of *in_dep*,
 - $\alpha = dept_name$
 - $\beta = building, budget$and *in_dep* is replaced by
 - $(\alpha \cup \beta) = (dept_name, building, budget)$
 - $(R - (\beta - \alpha)) = (ID, name, dept_name, salary)$



Example

□ $R = (A, B, C)$

$$F = \{A \rightarrow B, B \rightarrow C\}$$

□ $R_1 = (A, B), \quad R_2 = (B, C)$

□ Lossless-join decomposition:

$$R_1 \cap R_2 = \{B\} \quad \text{and} \quad B \rightarrow BC$$

□ Dependency preserving

□ $R_1 = (A, B), \quad R_2 = (A, C)$

□ Lossless-join decomposition:

$$R_1 \cap R_2 = \{A\} \quad \text{and} \quad A \rightarrow AB$$

□ Not dependency preserving

(cannot check $B \rightarrow C$ without computing $R_1 \bowtie R_2$)



BCNF and Dependency Preservation

- It is not always possible to achieve both BCNF and dependency preservation

- Consider a schema:

dept_advisor(s_ID, i_ID, department_name)

- With function dependencies:

$i_ID \rightarrow dept_name$

$s_ID, dept_name \rightarrow i_ID$

- *dept_advisor* is not in BCNF

- *i_ID* is not a superkey.

- Any decomposition of *dept_advisor* (*s_ID, i_ID*) & (*i_ID, dept_name*) will not include all the attributes in $s_ID, dept_name \rightarrow i_ID$

- Thus, the decomposition is NOT be dependency preserving




Figure 7.6 The *dept_advisor* relationship set.

- Any decomposition of *dept_advisor* (*s_ID, i_ID*) & (*i_ID, dept_name*) will not include all the attributes in $s_ID, dept_name \rightarrow i_ID$
- Thus, the decomposition is NOT be dependency preserving



Third Normal Form

- A relation schema R is in **third normal form (3NF)** if for all:

$$\alpha \rightarrow \beta \text{ in } F^+$$

at least one of the following holds:

- $\alpha \rightarrow \beta$ is trivial (i.e., $\beta \in \alpha$)
- α is a superkey for R
- Each attribute A in $\beta - \alpha$ is contained in a candidate key for R .

(NOTE: each attribute may be in a different candidate key)

- If a relation is in BCNF it is in 3NF (since in BCNF one of the first two conditions above must hold).
- Third condition is a minimal relaxation of BCNF to ensure dependency preservation (will see why later).



3NF Example

- Consider a schema:

dept_advisor(s_ID, i_ID, dept_name)

- With function dependencies:

$i_ID \rightarrow dept_name$

$s_ID, dept_name \rightarrow i_ID$

- Two candidate keys = $\{s_ID, dept_name\}, \{s_ID, i_ID\}$

- We have seen before that *dept_advisor* is **not** in BCNF

- *R*, however, is in 3NF

- $s_ID, dept_name$ is a superkey

- $i_ID \rightarrow dept_name$ and i_ID is NOT a superkey, but:

- ▶ $\{dept_name\} - \{i_ID\} = \{dept_name\}$ and

- ▶ $dept_name$ is contained in a candidate key



Redundancy in 3NF

□ Consider the schema R below, which is in 3NF

- $R = (J, K, L)$
- $F = \{JK \rightarrow L, L \rightarrow K\}$
- And an instance of a table:

J	L	K
j_1	l_1	k_1
j_2	l_1	k_1
j_3	l_1	k_1
$null$	l_2	k_2

□ What is wrong with the table?

- Repetition of information
- Need to use null values (e.g., to represent the relationship l_2, k_2 where there is no corresponding value for J)



Comparison of BCNF and 3NF

- Advantages to 3NF over BCNF. It is always possible to obtain a 3NF design without sacrificing losslessness or dependency preservation.
- Disadvantages to 3NF.
 - We may have to use null values to represent some of the possible meaningful relationships among data items.
 - There is the problem of repetition of information.



Goals of Normalization

- Let R be a relation scheme with a set F of functional dependencies.
- Decide whether a relation scheme R is in “good” form.
- In the case that a relation scheme R is not in “good” form, need to decompose it into a set of relation scheme $\{R_1, R_2, \dots, R_n\}$ such that:
 - Each relation scheme is in good form
 - The decomposition is a lossless decomposition
 - Preferably, the decomposition should be dependency preserving.



How good is BCNF?

- There are database schemas in BCNF that do not seem to be sufficiently normalized
- Consider a relation

inst_info (*ID*, *child_name*, *phone*)

- where an instructor may have more than one phone and can have multiple children
- Instance of *inst_info*

<i>ID</i>	<i>child_name</i>	<i>phone</i>
99999	David	512-555-1234
99999	David	512-555-4321
99999	William	512-555-1234
99999	William	512-555-4321



How good is BCNF? (Cont.)

- There are no non-trivial functional dependencies and therefore the relation is in BCNF
- Insertion anomalies – i.e., if we add a phone 981-992-3443 to 99999, we need to add two tuples
(99999, David, 981-992-3443)
(99999, William, 981-992-3443)



Higher Normal Forms

- It is better to decompose *inst_info* into:

- *inst_child*:

<i>ID</i>	<i>child_name</i>
99999	David
99999	William

- *inst_phone*:

<i>ID</i>	<i>phone</i>
99999	512-555-1234
99999	512-555-4321

- This suggests the need for higher normal forms, such as Fourth Normal Form (4NF), which we shall see later



Functional-Dependency Theory



Functional-Dependency Theory Roadmap

- We now consider the formal theory that tells us which functional dependencies are implied logically by a given set of functional dependencies.
- We then develop algorithms to generate lossless decompositions into BCNF and 3NF
- We then develop algorithms to test if a decomposition is dependency-preserving



Closure of a Set of Functional Dependencies

- Given a set F of functional dependencies, there are certain other functional dependencies that are logically implied by F .
 - If $A \rightarrow B$ and $B \rightarrow C$, then we can infer that $A \rightarrow C$, etc.
- The set of **all** functional dependencies logically implied by F is the **closure** of F .
- We denote the *closure* of F by F^+ .



Closure of a Set of Functional Dependencies

- We can compute F^+ , the closure of F , by repeatedly applying **Armstrong's Axioms**:
 - **Reflexive rule**: if $\beta \subseteq \alpha$, then $\alpha \rightarrow \beta$
 - **Augmentation rule**: if $\alpha \rightarrow \beta$, then $\gamma \alpha \rightarrow \gamma \beta$
 - **Transitivity rule**: if $\alpha \rightarrow \beta$, and $\beta \rightarrow \gamma$, then $\alpha \rightarrow \gamma$
- These rules are
 - **Sound** -- generate only functional dependencies that actually hold (correct)
 - **Complete** -- generate all functional dependencies that hold.



Example of F^+

□ $R = (A, B, C, G, H, I)$

$F = \{ A \rightarrow B$

$A \rightarrow C$

$CG \rightarrow H$

$CG \rightarrow I$

$B \rightarrow H \}$

□ Some members of F^+

□ $A \rightarrow H$

▶ by transitivity from $A \rightarrow B$ and $B \rightarrow H$

□ $AG \rightarrow I$

▶ by augmenting $A \rightarrow C$ with G , to get $AG \rightarrow CG$
and then transitivity with $CG \rightarrow I$

□ $CG \rightarrow HI$

▶ by augmenting $CG \rightarrow I$ to infer $CG \rightarrow CGI$,
and augmenting of $CG \rightarrow H$ to infer $CGI \rightarrow HI$,
and then transitivity



Closure of Functional Dependencies (Cont.)

□ Additional rules:

□ **Union rule:** If $\alpha \rightarrow \beta$ holds and $\alpha \rightarrow \gamma$ holds, then $\alpha \rightarrow \beta \gamma$ holds.

□ **Decomposition rule:** If $\alpha \rightarrow \beta \gamma$ holds, then $\alpha \rightarrow \beta$ holds and $\alpha \rightarrow \gamma$ holds.

□ **Pseudotransitivity rule:** If $\alpha \rightarrow \beta$ holds and $\gamma \beta \rightarrow \delta$ holds, then $\alpha \gamma \rightarrow \delta$ holds.

□ The above rules can be inferred from Armstrong's axioms.



Procedure for Computing F^+

- To compute the closure of a set of functional dependencies F :

$$F^+ = F$$

repeat

for each functional dependency f in F^+

 apply reflexivity and augmentation rules on f

 add the resulting functional dependencies to F^+

for each pair of functional dependencies f_1 and f_2 in F^+

if f_1 and f_2 can be combined using transitivity

then add the resulting functional dependency to F^+

until F^+ does not change any further

- **NOTE:** We shall see an alternative procedure for this task later



Closure of Attribute Sets

- Given a set of attributes α , define the **closure** of α **under** F (denoted by α^+) as the set of attributes that are functionally determined by α under F
- Algorithm to compute α^+ , the closure of α under F

result := α ;

while (changes to *result*) **do**

for each $\beta \rightarrow \gamma$ **in** F **do**

begin

if $\beta \subseteq \textit{result}$ **then** *result* := *result* $\cup \gamma$

end



Example of Attribute Set Closure

- $R = (A, B, C, G, H, I)$
- $F = \{A \rightarrow B$
 $A \rightarrow C$
 $CG \rightarrow H$
 $CG \rightarrow I$
 $B \rightarrow H\}$
- $(AG)^+$
 1. $result = AG$
 2. $result = ABCG$ ($A \rightarrow C$ and $A \rightarrow B$)
 3. $result = ABCGH$ ($CG \rightarrow H$ and $CG \subseteq AGBC$)
 4. $result = ABCGHI$ ($CG \rightarrow I$ and $CG \subseteq AGBCH$)
- Is AG a candidate key?
 1. Is AG a super key?
 1. Does $AG \rightarrow R?$ == Is $R \supseteq (AG)^+$
 2. Is any subset of AG a superkey?
 1. Does $A \rightarrow R?$ == Is $R \supseteq (A)^+$
 2. Does $G \rightarrow R?$ == Is $R \supseteq (G)^+$
 3. In general: check for each subset of size $n-1$



Uses of Attribute Closure

There are several uses of the attribute closure algorithm:

- Testing for superkey:
 - To test if α is a superkey, we compute α^+ , and check if α^+ contains all attributes of R .
- Testing functional dependencies
 - To check if a functional dependency $\alpha \rightarrow \beta$ holds (or, in other words, is in F^+), just check if $\beta \subseteq \alpha^+$.
 - That is, we compute α^+ by using attribute closure, and then check if it contains β .
 - Is a simple and cheap test, and very useful
- Computing closure of F
 - For each $\gamma \subseteq R$, we find the closure γ^+ , and for each $S \subseteq \gamma^+$, we output a functional dependency $\gamma \rightarrow S$.



Canonical Cover

- Suppose that we have a set of functional dependencies F on a relation schema. Whenever a user performs an update on the relation, the database system must ensure that the update does not violate any functional dependencies; that is, all the functional dependencies in F are satisfied in the new database state.
- If an update violates any functional dependencies in the set F , the system must roll back the update.
- We can reduce the effort spent in checking for violations by testing a simplified set of functional dependencies that has the same closure as the given set.
- This simplified set is termed the **canonical cover**
- To define canonical cover we must first define **extraneous attributes**.
 - An attribute of a functional dependency in F is **extraneous** if we can remove it without changing F^+



Extraneous Attributes

- Removing an attribute from the left side of a functional dependency could make it a stronger constraint.
 - For example, if we have $AB \rightarrow C$ and remove B, we get the possibly stronger result $A \rightarrow C$. It may be stronger because $A \rightarrow C$ logically implies $AB \rightarrow C$, but $AB \rightarrow C$ does not, on its own, logically imply $A \rightarrow C$
- But, depending on what our set F of functional dependencies happens to be, we may be able to remove B from $AB \rightarrow C$ safely.
 - For example, suppose that
 - $F = \{AB \rightarrow C, A \rightarrow D, D \rightarrow C\}$
 - Then we can show that F logically implies $A \rightarrow C$, making extraneous in $AB \rightarrow C$.



Extraneous Attributes (Cont.)

- Removing an attribute from the right side of a functional dependency could make it a weaker constraint.
 - For example, if we have $AB \rightarrow CD$ and remove C , we get the possibly weaker result $AB \rightarrow D$. It may be weaker because using just $AB \rightarrow D$, we can no longer infer $AB \rightarrow C$.
- But, depending on what our set F of functional dependencies happens to be, we may be able to remove C from $AB \rightarrow CD$ safely.
 - For example, suppose that
$$F = \{ AB \rightarrow CD, A \rightarrow C \}.$$
 - Then we can show that even after replacing $AB \rightarrow CD$ by $AB \rightarrow D$, we can still infer $AB \rightarrow C$ (from $A \rightarrow C$) and thus $AB \rightarrow CD$.



Extraneous Attributes

- An attribute of a functional dependency in F is **extraneous** if we can remove it without changing F^+
- Consider a set F of functional dependencies and the functional dependency $\alpha \rightarrow \beta$ in F .
 - **Remove from the left side:** Attribute A is **extraneous** in α if
 - ▶ $A \in \alpha$ and
 - ▶ F logically implies $(F - \{\alpha \rightarrow \beta\}) \cup \{(\alpha - A) \rightarrow \beta\}$.
 - **Remove from the right side:** Attribute A is **extraneous** in β if
 - ▶ $A \in \beta$ and
 - ▶ The set of functional dependencies $(F - \{\alpha \rightarrow \beta\}) \cup \{\alpha \rightarrow (\beta - A)\}$ logically implies F .
- *Note:* implication in the opposite direction is trivial in each of the cases above, since a “stronger” functional dependency always implies a weaker one



Testing if an Attribute is Extraneous

- Let R be a relation schema and let F be a set of functional dependencies that hold on R . Consider an attribute in the functional dependency $\alpha \rightarrow \beta$.
- To test if attribute $A \in \beta$ is extraneous in β
 - Consider the set:
$$F' = (F - \{\alpha \rightarrow \beta\}) \cup \{\alpha \rightarrow (\beta - A)\},$$
 - check that α^+ contains A ; if it does, A is extraneous in β
- To test if attribute $A \in \alpha$ is extraneous in α
 - Let $\gamma = \alpha - \{A\}$. Check if $\gamma \rightarrow \beta$ can be inferred from F
 - ▶ Compute γ^+ using the dependencies in F
 - ▶ If γ^+ includes all attributes of β then, A is extraneous in α



Examples of Extraneous Attributes

- Let $F = \{AB \rightarrow CD, A \rightarrow E, E \rightarrow C\}$
- To check if C is extraneous in $AB \rightarrow CD$, we:
 - Compute the attribute closure of AB under $F = \{AB \rightarrow D, A \rightarrow E, E \rightarrow C\}$
 - The closure is $ABCDE$, which includes CD
 - This implies that C is extraneous



Canonical Cover

A **canonical cover** for F is a set of dependencies F_c such that

- F logically implies all dependencies in F_c , and
- F_c logically implies all dependencies in F , and
- No functional dependency in F_c contains an extraneous attribute, and
- Each left side of functional dependency in F_c is unique.
That is, there are no two dependencies in F_c
 - $\alpha_1 \rightarrow \beta_1$ and $\alpha_2 \rightarrow \beta_2$ such that $\alpha_1 = \alpha_2$



Canonical Cover

- To compute a canonical cover for F :

repeat

Use the union rule to replace any dependencies in F of the form

$$\alpha_1 \rightarrow \beta_1 \text{ and } \alpha_1 \rightarrow \beta_2 \text{ with } \alpha_1 \rightarrow \beta_1 \beta_2$$

Find a functional dependency $\alpha \rightarrow \beta$ in F_c with an extraneous attribute either in α or in β

/* Note: test for extraneous attributes done using F_c , not F^* /*

If an extraneous attribute is found, delete it from $\alpha \rightarrow \beta$

until (F_c does not change)

- Note: Union rule may become applicable after some extraneous attributes have been deleted, so it has to be re-applied



Example: Computing a Canonical Cover

- $R = (A, B, C)$
 $F = \{A \rightarrow BC$
 $B \rightarrow C$
 $A \rightarrow B$
 $AB \rightarrow C\}$
- Combine $A \rightarrow BC$ and $A \rightarrow B$ into $A \rightarrow BC$
 - Set is now $\{A \rightarrow BC, B \rightarrow C, AB \rightarrow C\}$
- A is extraneous in $AB \rightarrow C$
 - Check if the result of deleting A from $AB \rightarrow C$ is implied by the other dependencies
 - ▶ Yes: in fact, $B \rightarrow C$ is already present!
 - Set is now $\{A \rightarrow BC, B \rightarrow C\}$
- C is extraneous in $A \rightarrow BC$
 - Check if $A \rightarrow C$ is logically implied by $A \rightarrow B$ and the other dependencies
 - ▶ Yes: using transitivity on $A \rightarrow B$ and $B \rightarrow C$.
 - Can use attribute closure of A in more complex cases
- The canonical cover is: $A \rightarrow B$
 $B \rightarrow C$



Example: Computing a Canonical Cover (Cont..)

□ $R = (A, B, C)$

$F = \{A \rightarrow BC, B \rightarrow AC, \text{ and } C \rightarrow AB\}.$

$A \rightarrow BC$ (Both B and C are extraneous, but we cannot delete both)

□ If C deleted, then $F' = \{A \rightarrow B, B \rightarrow AC, \text{ and } C \rightarrow AB\}.$

Now A and B are found to be extraneous in $C \rightarrow AB$, this leads to two choices

$$F_c = \{A \rightarrow B, B \rightarrow C, C \rightarrow A\}$$

$$F_c = \{A \rightarrow B, B \rightarrow AC, C \rightarrow B\}.$$

□ If B deleted, then $\{A \rightarrow C, B \rightarrow AC, \text{ and } C \rightarrow AB\}.$

Now A and C are found to be extraneous in $B \rightarrow AC$, this leads to two choices

$$F_c = \{A \rightarrow C, C \rightarrow B, \text{ and } B \rightarrow A\}$$

$$F_c = \{A \rightarrow C, B \rightarrow C, \text{ and } C \rightarrow AB\}.$$



Dependency Preservation

- Let F_i be the set of dependencies in F^+ that include only attributes in R_i .
 - A decomposition is **dependency preserving**, if
$$(F_1 \cup F_2 \cup \dots \cup F_n)^+ = F^+$$
- Using the above definition, testing for dependency preservation take exponential time.
- Not that if a decomposition is NOT dependency preserving then checking updates for violation of functional dependencies may require computing joins, which is expensive.

```
compute F+ ;
for each schema Ri in D do
begin
  Fi := the restriction of F+ to Ri ;
end
F' := ∅
for each restriction Fi do
begin
  F' = F' ∪ Fi
end
compute F'+ ;
if (F'+ = F+ ) then return (true)
else return (false);
```



Testing for Dependency Preservation

- To check if a dependency $\alpha \rightarrow \beta$ is preserved in a decomposition of R into R_1, R_2, \dots, R_n , we apply the following test (with attribute closure done with respect to F)
 - $result = \alpha$
repeat
 for each R_i in the decomposition
 $t = (result \cap R_i)^+ \cap R_i$
 $result = result \cup t$
 until ($result$ does not change)
 - If $result$ contains all attributes in β , then the functional dependency $\alpha \rightarrow \beta$ is preserved.
- We apply the test on all dependencies in F to check if a decomposition is dependency preserving
- This procedure takes polynomial time, instead of the exponential time required to compute F^+ and $(F_1 \cup F_2 \cup \dots \cup F_n)^+$



Example

□ $R = (A, B, C)$

$F = \{A \rightarrow B$

$B \rightarrow C\}$

Key = $\{A\}$

□ R is not in BCNF

□ Decomposition $R_1 = (A, B)$, $R_2 = (B, C)$

□ R_1 and R_2 in BCNF

□ Lossless-join decomposition

□ Dependency preserving



Algorithm for Decomposition Using Functional Dependencies



Testing for BCNF

- To check if a non-trivial dependency $\alpha \rightarrow \beta$ causes a violation of BCNF
 1. compute α^+ (the attribute closure of α), and
 2. verify that it includes all attributes of R , that is, it is a superkey of R .
- **Simplified test:** To check if a relation schema R is in BCNF, it suffices to check only the dependencies in the given set F for violation of BCNF, rather than checking all dependencies in F^+ .
 - If none of the dependencies in F causes a violation of BCNF, then none of the dependencies in F^+ will cause a violation of BCNF either.
- However, **simplified test** using only F is incorrect when testing a relation in a decomposition of R
 - Consider $R = (A, B, C, D, E)$, with $F = \{ A \rightarrow B, BC \rightarrow D \}$
 - ▶ Decompose R into $R_1 = (A, B)$ and $R_2 = (A, C, D, E)$
 - ▶ Neither of the dependencies in F contain only attributes from (A, C, D, E) so we might be misled into thinking R_2 satisfies BCNF.
 - ▶ In fact, dependency $AC \rightarrow D$ in F^+ shows R_2 is not in BCNF.



Testing Decomposition for BCNF

To check if a relation R_i in a decomposition of R is in BCNF

- Either test R_i for BCNF with respect to the **restriction** of F^+ to R_i (that is, all FDs in F^+ that contain only attributes from R_i)
- Or use the original set of dependencies F that hold on R , but with the following test:
 - ▶ for every set of attributes $\alpha \subseteq R_i$, check that α^+ (the attribute closure of α) either includes no attribute of $R_i - \alpha$, or includes all attributes of R_i .
- If the condition is violated by some $\alpha \rightarrow \beta$ in F , the dependency $\alpha \rightarrow (\alpha^+ - \alpha) \cap R_i$ can be shown to hold on R_i , and R_i violates BCNF.
- We use above dependency to decompose R_i



BCNF Decomposition Algorithm

result := {*R*};

done := false;

while (**not** *done*) **do**

if (there is a schema R_i in *result* that is not in BCNF)

then begin

 let $\alpha \rightarrow \beta$ be a nontrivial functional dependency that holds on R_i such that α^+ does not contain R_i and $\alpha \cap \beta = \emptyset$;

result := (*result* – R_i) \cup ($R_i - \beta$) \cup (α, β);

end

else *done* := **true**;

Note: each R_i is in BCNF, and decomposition is lossless-join.



Example of BCNF Decomposition

- *class* (*course_id*, *title*, *dept_name*, *credits*, *sec_id*, *semester*, *year*, *building*, *room_number*, *capacity*, *time_slot_id*)
- Functional dependencies:
 - *course_id* → *title*, *dept_name*, *credits*
 - *building*, *room_number* → *capacity*
 - *course_id*, *sec_id*, *semester*, *year* → *building*, *room_number*, *time_slot_id*
- A candidate key {*course_id*, *sec_id*, *semester*, *year*}.
- BCNF Decomposition:
 - *course_id* → *title*, *dept_name*, *credits* holds
 - ▶ but *course_id* is not a superkey.
 - We replace *class* by:
 - ▶ *course*(*course_id*, *title*, *dept_name*, *credits*)
 - ▶ *class-1* (*course_id*, *sec_id*, *semester*, *year*, *building*, *room_number*, *capacity*, *time_slot_id*)



BCNF Decomposition (Cont.)

- *course* is in BCNF
- *building, room_number* → *capacity* holds on *class-1*
 - but {*building, room_number*} is not a superkey for *class-1*.
 - We replace *class-1* by:
 - ▶ *classroom* (*building, room_number, capacity*)
 - ▶ *section* (*course_id, sec_id, semester, year, building, room_number, time_slot_id*)
- *classroom* and *section* are in BCNF.



Third Normal Form

- There are some situations where
 - BCNF is not dependency preserving, and
 - efficient checking for FD violation on updates is important
- Solution: define a weaker normal form, called Third Normal Form (3NF)
 - Allows some redundancy (with resultant problems; we will see examples later)
 - But functional dependencies can be checked on individual relations without computing a join.
 - There is always a lossless-join, dependency-preserving decomposition into 3NF.



3NF Example -- Relation *dept_advisor*

- $dept_advisor(s_ID, i_ID, dept_name)$
 $F = \{s_ID, dept_name \rightarrow i_ID, i_ID \rightarrow dept_name\}$
- Two candidate keys: $(s_ID, dept_name)$ and (i_ID, s_ID)
- R is in 3NF
 - $s_ID, dept_name \rightarrow i_ID$
 - $i_ID \rightarrow dept_name$
 - ▶ $dept_name$ is contained in a candidate key



Testing for 3NF

- Need to check only FDs in F , need not check all FDs in F^+ .
- Use attribute closure to check for each dependency $\alpha \rightarrow \beta$, if α is a superkey.
- If α is not a superkey, we have to verify if each attribute in β is contained in a candidate key of R
 - This test is rather more expensive, since it involve finding candidate keys
 - Testing for 3NF has been shown to be NP-hard
 - Interestingly, decomposition into third normal form (described shortly) can be done in polynomial time



3NF Decomposition Algorithm

Let F_c be a canonical cover for F ;

$i := 0$;

for each functional dependency $\alpha \rightarrow \beta$ in F_c

$i := i + 1$;

$R_i := \alpha \beta$

if none of the schemas R_j , $1 \leq j \leq i$ contains a candidate key for R
then

$i := i + 1$;

$R_i :=$ any candidate key for R ;

/ Optionally, remove redundant relations */*

repeat

if any schema R_j is contained in another schema R_k

then */* delete R_j */*

$R_j = R_i$;

$i = i - 1$;

return (R_1, R_2, \dots, R_i)



3NF Example -- Relation

dept_advisor

- $dept_advisor(s_ID, i_ID, dept_name)$
 $F = \{s_ID, dept_name \rightarrow i_ID, i_ID \rightarrow dept_name\}$
- Two candidate keys: $(s_ID, dept_name)$ and (i_ID, s_ID)
- $F1 = \{s_ID, dept_name \rightarrow i_ID\}, F2 = \{i_ID \rightarrow dept_name\}$
- $F_C = F$
- $R1 = (s_ID, dept_name, i_ID)$
- $R2 = (i_ID \rightarrow dept_name)$
- $R2$ is subset of $R1$, also $R1$ contains the candidate key $\Rightarrow R1$ is in 3 NF



3NF Decomposition: An Example

- Relation schema:

cust_banker_branch = (customer_id, employee_id, branch_name, type)

- The functional dependencies for this relation schema are:

- *customer_id, employee_id → branch_name, type*

- *employee_id → branch_name*

- *customer_id, branch_name → employee_id*

- We first compute a canonical cover

- *branch_name* is extraneous in the r.h.s. of the 1st dependency

- No other attribute is extraneous, so we get $F_C =$

customer_id, employee_id → type

employee_id → branch_name

customer_id, branch_name → employee_id



3NF Decomposition Example (Cont.)

- The **for** loop generates following 3NF schema:

(customer_id, employee_id, type)

(employee_id, branch_name)

(customer_id, branch_name, employee_id)

- Observe that *(customer_id, employee_id, type)* contains a candidate key of the original schema, so no further relation schema needs be added
- At end of for loop, detect and delete schemas, such as *(employee_id, branch_name)*, which are subsets of other schemas
 - result will not depend on the order in which FDs are considered
- The resultant simplified 3NF schema is:
(customer_id, employee_id, type)
(customer_id, branch_name, employee_id)



Comparison of BCNF and 3NF

- It is always possible to decompose a relation into a set of relations that are in 3NF such that:
 - The decomposition is lossless
 - The dependencies are preserved
- It is always possible to decompose a relation into a set of relations that are in BCNF such that:
 - The decomposition is lossless
 - It may not be possible to preserve dependencies.



Design Goals

- Goal for a relational database design is:
 - BCNF.
 - Lossless join.
 - Dependency preservation.
- If we cannot achieve this, we accept one of
 - Lack of dependency preservation
 - Redundancy due to use of 3NF
- Interestingly, SQL does not provide a direct way of specifying functional dependencies other than superkeys.

Can specify FDs using assertions, but they are expensive to test, (and currently not supported by any of the widely used databases!)
- Even if we had a dependency preserving decomposition, using SQL we would not be able to efficiently test a functional dependency whose left hand side is not a key.



Multivalued Dependencies



Multivalued Dependencies (MVDs)

- Suppose we record names of children, and phone numbers for instructors:
 - *inst_child*(*ID*, *child_name*)
 - *inst_phone*(*ID*, *phone_number*)
- If we were to combine these schemas to get
 - *inst_info*(*ID*, *child_name*, *phone_number*)
 - Example data:
 - (99999, David, 512-555-1234)
 - (99999, David, 512-555-4321)
 - (99999, William, 512-555-1234)
 - (99999, William, 512-555-4321)
- This relation is in BCNF
 - Why?



Multivalued Dependencies

- Let R be a relation schema and let $\alpha \subseteq R$ and $\beta \subseteq R$. The **multivalued dependency**

$$\alpha \twoheadrightarrow \beta$$

holds on R if in any legal relation $r(R)$, for all pairs for tuples t_1 and t_2 in r such that $t_1[\alpha] = t_2[\alpha]$, there exist tuples t_3 and t_4 in r such that:

$$t_1[\alpha] = t_2[\alpha] = t_3[\alpha] = t_4[\alpha]$$

$$t_3[\beta] = t_1[\beta]$$

$$t_3[R - \beta] = t_2[R - \beta]$$

$$t_4[\beta] = t_2[\beta]$$

$$t_4[R - \beta] = t_1[R - \beta]$$



MVD -- Tabular representation

□ Tabular representation of $\alpha \twoheadrightarrow \beta$

	α	β	$R - \alpha - \beta$
t_1	$a_1 \dots a_i$	$a_{i+1} \dots a_j$	$a_{j+1} \dots a_n$
t_2	$a_1 \dots a_i$	$b_{i+1} \dots b_j$	$b_{j+1} \dots b_n$
t_3	$a_1 \dots a_i$	$a_{i+1} \dots a_j$	$b_{j+1} \dots b_n$
t_4	$a_1 \dots a_i$	$b_{i+1} \dots b_j$	$a_{j+1} \dots a_n$



MVD (Cont.)

- Let R be a relation schema with a set of attributes that are partitioned into 3 nonempty subsets.

Y, Z, W

- We say that $Y \twoheadrightarrow Z$ (Y **multidetermines** Z) if and only if for all possible relations $r(R)$

$\langle y_1, z_1, w_1 \rangle \in r$ and $\langle y_1, z_2, w_2 \rangle \in r$

then

$\langle y_1, z_1, w_2 \rangle \in r$ and $\langle y_1, z_2, w_1 \rangle \in r$

- Note that since the behavior of Z and W are identical it follows that

$Y \twoheadrightarrow Z$ if $Y \twoheadrightarrow W$



Example

- In our example:

$ID \rightarrow\rightarrow child_name$

$ID \rightarrow\rightarrow phone_number$

- The above formal definition is supposed to formalize the notion that given a particular value of Y (ID) it has associated with it a set of values of Z ($child_name$) and a set of values of W ($phone_number$), and these two sets are in some sense independent of each other.

- Note:

- If $Y \rightarrow Z$ then $Y \rightarrow\rightarrow Z$

- Indeed we have (in above notation) $Z_1 = Z_2$

The claim follows.



Use of Multivalued Dependencies

- We use multivalued dependencies in two ways:
 1. To test relations to **determine** whether they are legal under a given set of functional and multivalued dependencies
 2. To specify **constraints** on the set of legal relations. We shall concern ourselves *only* with relations that satisfy a given set of functional and multivalued dependencies.
- If a relation r fails to satisfy a given multivalued dependency, we can construct a relations r' that does satisfy the multivalued dependency by adding tuples to r .



Theory of MVDs

- From the definition of multivalued dependency, we can derive the following rule:

- If $\alpha \rightarrow \beta$, then $\alpha \twoheadrightarrow \beta$

That is, every functional dependency is also a multivalued dependency

- The **closure** D^+ of D is the set of all functional and multivalued dependencies logically implied by D .
 - We can compute D^+ from D , using the formal definitions of functional dependencies and multivalued dependencies.
 - We can manage with such reasoning for very simple multivalued dependencies, which seem to be most common in practice
 - For complex dependencies, it is better to reason about sets of dependencies using a system of inference rules (Appendix C).



Fourth Normal Form

- A relation schema R is in **4NF** with respect to a set D of functional and multivalued dependencies if for all multivalued dependencies in D^+ of the form $\alpha \twoheadrightarrow \beta$, where $\alpha \subseteq R$ and $\beta \subseteq R$, at least one of the following hold:
 - $\alpha \twoheadrightarrow \beta$ is trivial (i.e., $\beta \subseteq \alpha$ or $\alpha \cup \beta = R$)
 - α is a superkey for schema R
- If a relation is in 4NF it is in BCNF



Restriction of Multivalued Dependencies

- The restriction of D to R_i is the set D_i consisting of
 - All functional dependencies in D^+ that include only attributes of R_i
 - All multivalued dependencies of the form

$$\alpha \twoheadrightarrow \twoheadrightarrow (\beta \cap R_i)$$

where $\alpha \subseteq R_i$ and $\alpha \twoheadrightarrow \twoheadrightarrow \beta$ is in D^+



4NF Decomposition Algorithm

result := { R };

done := false;

compute D^+ ;

Let D_i denote the restriction of D^+ to R_i

while (**not** *done*)

if (there is a schema R_i in *result* that is not in 4NF) **then**

begin

 let $\alpha \twoheadrightarrow \beta$ be a nontrivial multivalued dependency that holds

 on R_i such that $\alpha \twoheadrightarrow R_i$ is not in D_i , and $\alpha \cap \beta = \emptyset$;

result := (*result* - R_i) \cup (R_i - β) \cup (α, β);

end

else *done* := true;

Note: each R_i is in 4NF, and decomposition is lossless-join \rightarrow



Example

□ $R = (A, B, C, G, H, I)$

$F = \{ A \twoheadrightarrow B$

$B \twoheadrightarrow HI$

$CG \twoheadrightarrow H \}$

□ R is not in 4NF since $A \twoheadrightarrow B$ and A is not a superkey for R

□ Decomposition

a) $R_1 = (A, B)$

(R_1 is in 4NF)

b) $R_2 = (A, C, G, H, I)$
and R_4)

(R_2 is not in 4NF, decompose into R_3

c) $R_3 = (C, G, H)$

(R_3 is in 4NF)

d) $R_4 = (A, C, G, I)$

(R_4 is not in 4NF, decompose into R_5 and R_6)

□ $A \twoheadrightarrow B$ and $B \twoheadrightarrow HI \Rightarrow A \twoheadrightarrow HI$, (MVD transitivity), and

□ and hence $A \twoheadrightarrow I$ (MVD restriction to R_4)

e) $R_5 = (A, I)$

(R_5 is in 4NF)

f) $R_6 = (A, C, G)$

(R_6 is in 4NF)



Additional issues



Further Normal Forms

- **Join dependencies** generalize multivalued dependencies
 - lead to **project-join normal form (PJNF)** (also called **fifth normal form**)
- A class of even more general constraints, leads to a normal form called **domain-key normal form**.
- Problem with these generalized constraints: are hard to reason with, and no set of sound and complete set of inference rules exists.
- Hence rarely used



Overall Database Design Process

We have assumed schema R is given

- R could have been generated when converting E-R diagram to a set of tables.
- R could have been a single relation containing *all* attributes that are of interest (called **universal relation**).
- Normalization breaks R into smaller relations.
- R could have been the result of some ad hoc design of relations, which we then test/convert to normal form.



ER Model and Normalization

- When an E-R diagram is carefully designed, identifying all entities correctly, the tables generated from the E-R diagram should not need further normalization.
- However, in a real (imperfect) design, there can be functional dependencies from non-key attributes of an entity to other attributes of the entity
 - Example: an *employee* entity with
 - ▶ attributes
department_name and *building*,
 - ▶ functional dependency
department_name → *building*
 - ▶ Good design would have made department an entity
- Functional dependencies from non-key attributes of a relationship set possible, but rare --- most relationships are binary



Denormalization for Performance

- May want to use non-normalized schema for performance
- For example, displaying *prereqs* along with *course_id*, and *title* requires join of *course* with *prereq*
- Alternative 1: Use denormalized relation containing attributes of *course* as well as *prereq* with all above attributes
 - faster lookup
 - extra space and extra execution time for updates
 - extra coding work for programmer and possibility of error in extra code
- Alternative 2: use a materialized view defined a *course* *prereq*
 - Benefits and drawbacks same as above, except no extra coding work for programmer and avoids possible errors



Other Design Issues

- Some aspects of database design are not caught by normalization
- Examples of bad database design, to be avoided:

Instead of *earnings* (*company_id*, *year*, *amount*), use

- *earnings_2004*, *earnings_2005*, *earnings_2006*, etc., all on the schema (*company_id*, *earnings*).
 - ▶ Above are in BCNF, but make querying across years difficult and needs new table each year
- *company_year* (*company_id*, *earnings_2004*, *earnings_2005*, *earnings_2006*)
 - ▶ Also in BCNF, but also makes querying across years difficult and requires new attribute each year.
 - ▶ Is an example of a **crosstab**, where values for one attribute become column names
 - ▶ Used in spreadsheets, and in data analysis tools



Modeling Temporal Data

- **Temporal data** have an association time interval during which the data are *valid*.
- A **snapshot** is the value of the data at a particular point in time
- Several proposals to extend ER model by adding valid time to
 - attributes, e.g., address of an instructor at different points in time
 - entities, e.g., time duration when a student entity exists
 - relationships, e.g., time during which an instructor was associated with a student as an advisor.
- But no accepted standard
- Adding a temporal component results in functional dependencies like
$$ID \rightarrow street, city$$
not holding, because the address varies over time
- A **temporal functional dependency** $X \rightarrow Y$ holds on schema R if the functional dependency $X \rightarrow Y$ holds on all snapshots for all legal instances $r(R)$.



Modeling Temporal Data (Cont.)

- In practice, database designers may add start and end time attributes to relations
 - E.g., *course(course_id, course_title)* is replaced by *course(course_id, course_title, start, end)*
 - Constraint: no two tuples can have overlapping valid times
 - ▶ Hard to enforce efficiently
- Foreign key references may be to current version of data, or to data at a point in time
 - E.g., student transcript should refer to course information at the time the course was taken



End of Chapter 7



Proof of Correctness of 3NF Decomposition Algorithm



Correctness of 3NF Decomposition Algorithm

- 3NF decomposition algorithm is dependency preserving (since there is a relation for every FD in F_c)
- Decomposition is lossless
 - A candidate key (C) is in one of the relations R_i in decomposition
 - Closure of candidate key under F_c must contain all attributes in R .
 - Follow the steps of attribute closure algorithm to show there is only one tuple in the join result for each tuple in R_i



Correctness of 3NF Decomposition Algorithm (Cont.)

- Claim: if a relation R_i is in the decomposition generated by the above algorithm, then R_i satisfies 3NF.
- Proof:
 - Let R_i be generated from the dependency $\alpha \rightarrow \beta$
 - Let $\gamma \rightarrow B$ be any non-trivial functional dependency on R_i . (We need only consider FDs whose right-hand side is a single attribute.)
 - Now, B can be in either β or α but not in both. Consider each case separately.



Correctness of 3NF Decomposition (Cont.)

- Case 1: If B in β :
 - If γ is a superkey, the 2nd condition of 3NF is satisfied
 - Otherwise α must contain some attribute not in γ
 - Since $\gamma \rightarrow B$ is in F^+ it must be derivable from F_c , by using attribute closure on γ .
 - Attribute closure not have used $\alpha \rightarrow \beta$. If it had been used, α must be contained in the attribute closure of γ , which is not possible, since we assumed γ is not a superkey.
 - Now, using $\alpha \rightarrow (\beta - \{B\})$ and $\gamma \rightarrow B$, we can derive $\alpha \rightarrow B$
(since $\gamma \subseteq \alpha$, and $B \notin \gamma$ since $\gamma \rightarrow B$ is non-trivial)
 - Then, B is extraneous in the right-hand side of $\alpha \rightarrow \beta$; which is not possible since $\alpha \rightarrow \beta$ is in F_c .
 - Thus, if B is in β then γ must be a superkey, and the second condition of 3NF must be satisfied.



Correctness of 3NF Decomposition (Cont.)

- Case 2: B is in α .
 - Since α is a candidate key, the third alternative in the definition of 3NF is trivially satisfied.
 - In fact, we cannot show that γ is a superkey.
 - This shows exactly why the third alternative is present in the definition of 3NF.

Q.E.D.



First Normal Form

- Domain is **atomic** if its elements are considered to be indivisible units
 - Examples of non-atomic domains:
 - ▶ Set of names, composite attributes
 - ▶ Identification numbers like CS101 that can be broken up into parts
- A relational schema R is in **first normal form** if the domains of all attributes of R are atomic
- Non-atomic values complicate storage and encourage redundant (repeated) storage of data
 - Example: Set of accounts stored with each customer, and set of owners stored with each account
 - We assume all relations are in first normal form (and revisit this in Chapter 22: Object Based Databases)



First Normal Form (Cont.)

- Atomicity is actually a property of how the elements of the domain are used.
 - Example: Strings would normally be considered indivisible
 - Suppose that students are given roll numbers which are strings of the form *CS0012* or *EE1127*
 - If the first two characters are extracted to find the department, the domain of roll numbers is not atomic.
 - Doing so is a bad idea: leads to encoding of information in application program rather than in the database.