

8 Puzzle using DFS and BFS

i) DFS :

```
cnt = 0;
def print_state(in_array):
    global cnt
    cnt += 1
    for row in in_array:
        print(' '.join(str(num) for num in row))
    print() # Print a blank line for better readability

def helper(goal, in_array, row, col, vis):
    # Mark the current position as visited
    vis[row][col] = 1
    drow = [-1, 0, 1, 0] # Directions for row movements: up, right, down, left
    dcol = [0, 1, 0, -1] # Directions for column movements
    dchange = ['U', 'R', 'D', 'L']

    # Print the current state print("Current
    state:") print_state(in_array)

    # Check if the current state is the goal state
    if in_array == goal:
        print_state(in_array)
        print(f"Number of states : {cnt}")
        return True

    # Explore all possible directions
    for i in range(4):
        nrow = row + drow[i]
        ncol = col + dcol[i]

        # Check if the new position is within bounds and not visited
        if 0 <= nrow < len(in_array) and 0 <= ncol < len(in_array[0]) and not
            vis[nrow][ncol]: # Make the move (swap the empty space with the adjacent tile)
            print(f"Took a {dchange[i]} move")
            in_array[row][col], in_array[nrow][ncol] = in_array[nrow][ncol], in_array[row][col]

            # Recursive call
            if helper(goal, in_array, nrow, ncol, vis):
                return True

            # Backtrack (undo the move)
            in_array[row][col], in_array[nrow][ncol] = in_array[nrow][ncol], in_array[row][col]
```

```

# Mark the position as unvisited before returning
vis[row][col] = 0
return False

# Example usage
initial_state = [[1, 2, 3], [0, 4, 6], [7, 5, 8]] # 0 represents the empty space
goal_state = [[1, 2, 3], [4, 5, 6], [7, 8, 0]]
visited = [[0] * 3 for _ in range(3)] # 3x3 visited matrix
empty_row, empty_col = 1, 0 # Initial position of the empty space

found_solution = helper(goal_state, initial_state, empty_row, empty_col, visited)
print("Solution found:", found_solution)

```

Output :

```

Took a L move
Current state:
1 2 3
4 6 8
0 7 5

```

```

Took a D move
Current state:
1 2 3
4 5 6
7 0 8

```

```

Took a R move
Current state:
1 2 3
4 5 6
7 8 0

```

```

1 2 3
4 5 6
7 8 0

```

```

Number of states : 42
Solution found: True

```

```

i)    BFS :
      from collections import deque

      GOAL_STATE = (1, 2, 3, 4, 5, 6, 7, 8,

0)

      def find_empty(state):
          return state.index(0)

      def get_neighbors(state):
          neighbors = []
          empty_index = find_empty(state)
          row, col = divmod(empty_index, 3)
          directions = [(-1, 0), (1, 0), (0, -1), (0, 1)]
          for dr, dc in directions:
              new_row, new_col = row + dr, col + dc
              if 0 <= new_row < 3 and 0 <= new_col < 3:
                  new_index = new_row * 3 + new_col
                  new_state = list(state)
                  new_state[empty_index], new_state[new_index] = new_state[new_index],
new_state[empty_index]
                  neighbors.append(tuple(new_state))
          return neighbors

      def bfs(initial_state):
          queue = deque([(initial_state, [])])
          visited = set()
          visited.add(initial_state)
          visited_count = 1 # Initialize visited count
          while queue:
              current_state, path = queue.popleft() if
              current_state == GOAL_STATE:
                  return path, visited_count # Return path and count
              for neighbor in get_neighbors(current_state):
                  if neighbor not in visited:
                      visited.add(neighbor) queue.append((neighbor,
                      path + [neighbor])) visited_count += 1 #
                      Increment visited count
          return None, visited_count # Return count if no solution found

      def input_start_state():
          print("Enter the starting state as 9 numbers (0 for the empty space):")
          input_state = input("Format: 1 2 3 4 5 6 7 8 0\n")
          numbers = list(map(int, input_state.split()))
          if len(numbers) != 9 or set(numbers) != set(range(9)):
              print("Invalid input. Please enter numbers from 0 to 8 with no duplicates.") return
              input_start_state()
          return tuple(numbers)

```

```

def print_matrix(state):
    for i in range(0, 9, 3):
        print(state[i:i+3])

if __name__ == "__main__":
    initial_state = input_start_state()
    print("Initial state:")
    print_matrix(initial_state)
    solution, visited_count = bfs(initial_state)
    print(f"Number of states visited: {visited_count}")
    if solution:
        print("\nSolution found with the following steps:")
        for step in solution:
            print_matrix(step)
            print()
    else:
        print("No solution found.")

```

Output :

Enter the starting state as 9 numbers (0 for the empty space):

Format: 1 2 3 4 5 6 7 8 0

1 2 3 0 4 6 7 5 8

Initial state:

(1, 2, 3)

(0, 4, 6)

(7, 5, 8)

Number of states visited: 30

Solution found with the following steps:

(1, 2, 3)

(4, 0, 6)

(7, 5, 8)

(1, 2, 3)

(4, 5, 6)

(7, 0, 8)

(1, 2, 3)

(4, 5, 6)

(7, 8, 0)