

```

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* searchRange(int* nums, int numsSize, int target, int* returnSize) {
    int f = -1, l = -1;
    for (int i = 0; i < numsSize; i++) {
        if (nums[i] == target) {
            if (f == -1) {
                f = i;
            }
            l = i;
        }
    }

    int* result = (int*)malloc(2 * sizeof(int));
    result[0] = f;
    result[1] = l;
    *returnSize = 2; //Update the return size
    return result;
}

```

}

Problem List

Run

Submit

Auto

20K151

Description

Editorial

Solutions

Submissions

34. Find First and Last Position of Element in Sorted Array

Solved

MediumTopicsCompanies

Given an array of integers `nums` sorted in non-decreasing order, find the starting and ending position of a given `target` value.

If `target` is not found in the array, return `[-1, -1]`.

You must write an algorithm with $O(\log n)$ runtime complexity.

Example 1:

Input: `nums = [5,7,7,8,8,10]`, `target = 8`
Output: `[3,4]`

Example 2:

Input: `nums = [5,7,7,8,8,10]`, `target = 6`
Output: `[-1,-1]`

Example 3:

Input: `nums = []`, `target = 0`
Output: `[-1,-1]`

Code

Auto

```
1 int* searchRange(int* nums, int n) {
2     int f = -1, l = -1;
3     for (int i = 0; i < numsSize; i++) {
4         if (nums[i] == target) {
5             if (f == -1) {
6                 f = i;
7             }
8             l = i;
9         }
10    }
11
12    int* result = (int*)malloc(2 * sizeof(int));
13    result[0] = f;
14    result[1] = l;
15    *returnSize = 2; // Update the return size
16    return result;
17 }
```

Saved to local

Testcase Test Result

Case 1 Case 2 Case 3 +

nums =

[5,7,7,8,8,10]

</> Source

Sohan_AR

Access all features with our Premium subscription!

My Lists

Notebook

Submissions

Progress

Points

Session

Try New Features

Orders

My Playgrounds

Revert to old version

Appearance

Sign Out

Ln 1, Col 1