

6 – Axis collaborative robot

The ASYSTR Robotics **ASYSTR 3C** is a **6-axis collaborative robot (cobot)** designed for industrial automation applications.

A collaborative robot is a robot that can safely work alongside humans without heavy safety fencing.

The robot is mainly used for:

- Pick and place operations
- Machine tending
- Assembly operations
- Packaging
- Welding support
- Material handling

SPECIFICATIONS:

Category	Parameter	Specification
General	Payload	3 kg
	Reach	600 mm
	Number of Axes	6
	Repeatability	±0.05 mm
	Max. Translational Speed	1000 mm/sec
Electrical	Power Supply	100–240 VAC, 50–60 Hz
	Power Consumption	< 500 W (typical cycle)
Protection	Wrist Protection	IP67
	Body Protection	IP60
Physical	Weight	17 kg
	Operating Temperature	0 – 50 °C
	Tool Flange	ISO 9409-1:2004
	Robot Footprint	115 × 115 mm
	Mounting Position	Floor, ceiling & wall
Connectivity	Communication	Wi-Fi (802.11 b/g/m), IoT ready
Joint Motion	Waist (J1) Range / Speed	±180° / 150°/sec
	Shoulder (J2) Range / Speed	±150° / 150°/sec
	Elbow (J3) Range / Speed	±150° / 180°/sec
	Wrist (J4) Range / Speed	±180° / 180°/sec
	Bend (J5) Range / Speed	±180° / 180°/sec
	Roll (J6) Range / Speed	±180° / 180°/sec
I/O Interface	Digital Input	2 Emergency + 2 Safety
	Digital Output	2 Safety
	Additional I/O	10 user-configurable digital I/O
	Tool I/O	8 configurable points
	Communication Protocol	MODBUS RTU (Half-Duplex 10 Mbps)
	Integrated Power	24V, 0.5A
	Mounting Type	DIN Rail

Price:14,57,142+18%gst

