Namespace Session_1

Classes

AsCanvas

A class that implements the abstract commands of ICanvas.

AsCommandFactory

A Class of BOOSE Commands

Clear

Class to implement the Clear() command from the AsCommandFactory.

Form1

Form1

Rect

Class to implement the Rect() command from the AsCommandFactory.

Reset

A class that implements the Reset() command from the AsCommandFactory.

Tri

A class that implements the Tri() command from the AsCommandFactory.

WriteText

A class that implements the WriteText() command from the AsCommandFactory.

Class AsCanvas

Namespace: Session_1

Assembly: Session 1.dll

A class that implements the abstract commands of ICanvas.

```
public class AsCanvas : ICanvas
```

Inheritance

object ← AsCanvas

Implements

ICanvas

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

AsCanvas()

Constructor that calls Set().

```
public AsCanvas()
```

Properties

PenColour

Gets or sets the color of the pen used for drawing.

```
public object PenColour { get; set; }
```

Property Value

object

Xpos

Gets or sets the X position on the canvas.

```
public int Xpos { get; set; }
```

Property Value

int

Ypos

Gets or sets the Y position on the canvas.

```
public int Ypos { get; set; }
```

Property Value

int

Methods

Circle(int, bool)

Draws a circle on the canvas/bitmap.

```
public void Circle(int radius, bool filled)
```

Parameters

`radius` int

The radius of the circle.

`filled` bool

Indicates whether the circle is filled or not.

Exceptions

CanvasException

Thrown if the radius is invalid.

Clear()

Clears the canvas/bitmap

```
public void Clear()
```

DrawTo(int, int)

Draws a line from the current position to a specified (x, y) position.

```
public void DrawTo(int x, int y)
```

Parameters

x int

The x-coordinate.

y int

The y-coordinate.

Exceptions

CanvasException

Thrown if the position is invalid.

MoveTo(int, int)

Moves the current position on the canvas to the specified (x, y) coordinates.

```
public void MoveTo(int x, int y)
```

Parameters

`x` int

The x-coordinate.

`y` int

The y-coordinate.

Exceptions

CanvasException

Thrown if the position is invalid.

Rect(int, int, bool)

Draws a rectangle on the canvas/bitmap.

```
public void Rect(int width, int height, bool filled)
```

Parameters

`width` int

The width of the rectangle.

`height` int

The height of the rectangle.

`filled` bool

Indicates whether the rectangle is filled or not.

Exceptions

CanvasException

Thrown if the dimensions are invalid.

Reset()

Resets the position on the canvas/bitmap

```
public void Reset()
```

Set(int, int)

Initializes the canvas with specified dimensions.

```
public void Set(int width, int height)
```

Parameters

`width` int

The width of the PictureBox.

`height` int

The height of the PictureBox.

SetColour(int, int, int)

Sets the color of the pen using RGB values.

```
public void SetColour(int red, int green, int blue)
```

Parameters

`red` int

The red component (0-255).

`green` int

The green component (0-255).

`blue` int

The blue component (0-255).

Exceptions

CanvasException

Thrown if RGB values are invalid.

Tri(int, int)

Draws a triangle on the canvas/bitmap.

```
public void Tri(int width, int height)
```

Parameters

`width` int

The width of the triangle.

`height` int

The height of the triangle.

Exceptions

CanvasException

Thrown if the values are not valid.

WriteText(string)

Writes text onto the canvas/bitmap.

```
public void WriteText(string text)
```

Parameters

`text` string

The text to write.

getBitmap()

Returns the bitmap containing the graphics.

```
public object getBitmap()
```

Returns

object

The Bitmap

Class AsCommandFactory

Namespace: Session_1

Assembly: Session 1.dll

A Class of BOOSE Commands

```
public class AsCommandFactory : CommandFactory, ICommandFactory
```

Inheritance

object ← CommandFactory ← AsCommandFactory

Implements

ICommandFactory

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Methods

MakeCommand(string)

This is a class off all the commands

```
public override ICommand MakeCommand(string commandType)
```

Parameters

`commandType` string

Returns

ICommand

Exceptions

FactoryException

Class Clear

Namespace: Session_1

Assembly: Session 1.dll

Class to implement the Clear() command from the AsCommandFactory.

```
public class Clear : CommandOneParameter, ICommand
```

Inheritance

object ← Command ← CanvasCommand ← CommandOneParameter ← Clear

Implements

ICommand

Inherited Members

CommandOneParameter.param1 , CommandOneParameter.param1unprocessed , CommandOneParameter.CheckParameters(string[]) , CanvasCommand.yPos , CanvasCommand.xPos , CanvasCommand.canvas , CanvasCommand.Canvas , Command.program , Command.parameterList , Command.parameters , Command.paramsint , Command.Set(StoredProgram, string) , Command.Compile() , Command.ProcessParameters(string) , Command.ToString() , Command.Program , Command.Name , Command.ParameterList , Command.Parameters , Command.Paramsint , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

Constructors

Clear()

Default constructor that is called from AsCommandFactory.

```
public Clear()
```

Clear(Canvas)

Constructor that initializes the Clear command with a specific canvas.

```
public Clear(Canvas c)
```

Parameters

`c` Canvas

The canvas on which the clear operation will be performed.

Methods

Execute()

Executes the Clear command by calling the Clear() method of the AsCanvas class.

```
public override void Execute()
```

Class Form1

Namespace: Session_1

Assembly: Session 1.dll

Form1

```
public class Form1 : Form, IDropTarget, ISynchronizeInvoke, IWin32Window,
IBindableComponent, IComponent, IDisposable, IContainerControl
```

Inheritance

object ← MarshalByRefObject ← Component ← Control ← ScrollableControl ← ContainerControl ← Form ← Form1

Implements

IDropTarget, ISynchronizeInvoke, IWin32Window, IBindableComponent, IComponent, IDisposable, IContainerControl

Inherited Members

Form.SetVisibleCore(bool) , Form.Activate() , Form.ActivateMdiChild(Form) , Form.AddOwnedForm(Form) , Form.AdjustFormScrollbars(bool) , Form.Close() , Form.CreateAccessibilityInstance() , Form.CreateControlsInstance() , Form.CreateHandle() , Form.DefWndProc(ref Message) , Form.ProcessMnemonic(char) , Form.CenterToParent() , Form.CenterToScreen() , Form.LayoutMdi(MdiLayout) , Form.OnActivated(EventArgs) , Form.OnBackgroundImageChanged(EventArgs) , Form.OnBackgroundImageLayoutChanged(EventArgs) , Form.OnClosing(CancelEventArgs) , Form.OnClosed(EventArgs) , Form.OnFormClosing(FormClosingEventArgs) , Form.OnFormClosed(FormClosedEventArgs) , Form.OnCreateControl() , Form.OnDeactivate(EventArgs) , Form.OnEnabledChanged(EventArgs) , Form.OnEnter(EventArgs) , Form.OnFontChanged(EventArgs) , Form.OnGotFocus(EventArgs) , Form.OnHandleCreated(EventArgs) , Form.OnHandleDestroyed(EventArgs) , Form.OnHelpButtonClicked(CancelEventArgs) , Form.OnLayout(LayoutEventArgs) , Form.OnLoad(EventArgs) , Form.OnMaximizedBoundsChanged(EventArgs) , Form.OnMaximumSizeChanged(EventArgs) , Form.OnMinimumSizeChanged(EventArgs) , Form.OnInputLanguageChanged(InputLanguageChangedEventArgs) , Form.OnInputLanguageChanging(InputLanguageChangingEventArgs) , Form.OnVisibleChanged(EventArgs) , Form.OnMdiChildActivate(EventArgs) , Form.OnMenuStart(EventArgs) , Form.OnMenuComplete(EventArgs) , Form.OnPaint(PaintEventArgs) , Form.OnResize(EventArgs) , Form.OnDpiChanged(DpiChangedEventArgs) , Form.OnGetDpiScaledSize(int, int, ref Size) ,

Form.OnRightToLeftLayoutChanged(EventArgs) , Form.OnShown(EventArgs) ,
Form.OnTextChanged(EventArgs) , Form.ProcessCmdKey(ref Message, Keys) ,
Form.ProcessDialogKey(Keys) , Form.ProcessDialogChar(char) ,
Form.ProcessKeyPreview(ref Message) , Form.ProcessTabKey(bool) ,
Form.RemoveOwnedForm(Form) , Form.Select(bool, bool) ,
Form.ScaleMinMaxSize(float, float, bool) ,
Form.GetScaledBounds(Rectangle, SizeF, BoundsSpecified) ,
Form.ScaleControl(SizeF, BoundsSpecified) , Form.SetBoundsCore(int, int, int, int, BoundsSpecified) ,
Form.SetClientSizeCore(int, int) , Form.SetDesktopBounds(int, int, int, int) ,
Form.SetDesktopLocation(int, int) , Form.Show(IWin32Window) , Form.ShowDialog() ,
Form.ShowDialog(IWin32Window) , Form.ToString() , Form.UpdateDefaultButton() ,
Form.OnResizeBegin(EventArgs) , Form.OnResizeEnd(EventArgs) ,
Form.OnStyleChanged(EventArgs) , Form.ValidateChildren() ,
Form.ValidateChildren(ValidationConstraints) , Form.WndProc(ref Message) , Form.AcceptButton ,
Form.ActiveForm , Form.ActiveMdiChild , Form.AllowTransparency , Form.AutoScroll ,
Form.AutoSize , Form.AutoSizeMode , Form.AutoValidate , Form.BackColor ,
Form.FormBorderStyle , Form.CancelButton , Form.ClientSize , Form.ControlBox ,
Form.CreateParams , Form.DefaultImeMode , Form.DefaultSize , Form.DesktopBounds ,
Form.DesktopLocation , Form.DialogResult , Form.HelpButton , Form.Icon , Form.IsMdiChild ,
Form.IsMdiContainer , Form.IsRestrictedWindow , Form.KeyPreview , Form.Location ,
Form.MaximizedBounds , Form.MaximumSize , Form.MainMenuStrip , Form.MinimumSize ,
Form.MaximizeBox , Form.MdiChildren , Form.MdiChildrenMinimizedAnchorBottom ,
Form.MdiParent , Form.MinimizeBox , Form.Modal , Form.Opacity , Form.OwnedForms ,
Form.Owner , Form.RestoreBounds , Form.RightToLeftLayout , Form.ShowInTaskbar ,
Form.ShowIcon , Form.ShowWithoutActivation , Form.Size , Form.SizeGripStyle ,
Form.StartPosition , Form.Text , Form.TopLevel , Form.TopMost , Form.TransparencyKey ,
Form.WindowState , Form.AutoSizeChanged , Form.AutoValidateChanged ,
Form.HelpButtonClicked , Form.MaximizedBoundsChanged , Form.MaximumSizeChanged ,
Form.MinimumSizeChanged , Form.Activated , Form.Deactivate , Form.FormClosing ,
Form.FormClosed , Form.Load , Form.MdiChildActivate , Form.MenuComplete ,
Form.MenuStart , Form.InputLanguageChanged , Form.InputLanguageChanging ,
Form.RightToLeftLayoutChanged , Form.Shown , Form.DpiChanged , Form.ResizeBegin ,
Form.ResizeEnd , ContainerControl.OnAutoValidateChanged(EventArgs) ,
ContainerControl.OnMove(EventArgs) , ContainerControl.OnParentChanged(EventArgs) ,
ContainerControl.PerformAutoScale() , ContainerControl.RescaleConstantsForDpi(int, int) ,
ContainerControl.Validate() , ContainerControl.Validate(bool) ,
ContainerControl.AutoScaleDimensions , ContainerControl.AutoScaleFactor ,
ContainerControl.AutoScaleMode , ContainerControl.BindingContext ,
ContainerControl.CanEnableIme , ContainerControl.ActiveControl ,
ContainerControl.CurrentAutoScaleDimensions , ContainerControl.ParentForm ,

ScrollableControl.ScrollStateAutoScrolling , ScrollableControl.ScrollStateHScrollVisible , ScrollableControl.ScrollStateVScrollVisible , ScrollableControl.ScrollStateUserHasScrolled , ScrollableControl.ScrollStateFullDrag , ScrollableControl.GetScrollState(int) , ScrollableControl.OnMouseWheel(MouseEventArgs) , ScrollableControl.OnRightToLeftChanged(EventArgs) , ScrollableControl.OnPaintBackground(PaintEventArgs) , ScrollableControl.OnPaddingChanged(EventArgs) , ScrollableControl.SetDisplayRectLocation(int, int) , ScrollableControl.ScrollControlIntoView(Control) , ScrollableControl.ScrollToControl(Control) , ScrollableControl.OnScroll(ScrollEventArgs) , ScrollableControl.SetAutoScrollMargin(int, int) , ScrollableControl.SetScrollState(int, bool) , ScrollableControl.AutoScrollMargin , ScrollableControl.AutoScrollPosition , ScrollableControl.AutoScrollMinSize , ScrollableControl.DisplayRectangle , ScrollableControl.HScroll , ScrollableControl.HorizontalScroll , ScrollableControl.VScroll , ScrollableControl.VerticalScroll , ScrollableControl.Scroll , Control.GetAccessibilityObjectById(int) , Control.SetAutoSizeMode(AutoSizeMode) , Control.GetAutoSizeMode() , Control.GetPreferredSize(Size) , Control.AccessibilityNotifyClients(AccessibleEvents, int) , Control.AccessibilityNotifyClients(AccessibleEvents, int, int) , Control.BeginInvoke(Delegate) , Control.BeginInvoke(Action) , Control.BeginInvoke(Delegate, params object[]) , Control.BringToFront() , Control.Contains(Control) , Control.CreateGraphics() , Control.CreateControl() , Control.DestroyHandle() , Control.DoDragDrop(object, DragDropEffects) , Control.DoDragDrop(object, DragDropEffects, Bitmap, Point, bool) , Control.DrawToBitmap(Bitmap, Rectangle) , Control.EndInvoke(IAsyncResult) , Control.FindForm() , Control.GetTopLevel() , Control.RaiseKeyEvent(object, KeyEventArgs) , Control.RaiseMouseEvent(object, MouseEventArgs) , Control.Focus() , Control.FromChildHandle(nint) , Control.FromHandle(nint) , Control.GetChildAtPoint(Point, GetChildAtPointSkip) , Control.GetChildAtPoint(Point) , Control.GetContainerControl() , Control.GetNextControl(Control, bool) , Control.GetStyle(ControlStyles) , Control.Hide() , Control.InitLayout() , Control.Invalidate(Region) , Control.Invalidate(Region, bool) , Control.Invalidate() , Control.Invalidate(bool) , Control.Invalidate(Rectangle) , Control.Invalidate(Rectangle, bool) , Control.Invoke(Action) , Control.Invoke(Delegate) , Control.Invoke(Delegate, params object[]) , Control.Invoke<T>(Func<T>) , Control.InvokePaint(Control, PaintEventArgs) , Control.InvokePaintBackground(Control, PaintEventArgs) , Control.IsKeyLocked(Keys) , Control.IsInputChar(char) , Control.IsInputKey(Keys) , Control.IsMnemonic(char, string) , Control.LogicalToDeviceUnits(int) , Control.LogicalToDeviceUnits(Size) , Control.ScaleBitmapLogicalToDevice(ref Bitmap) , Control.NotifyInvalidate(Rectangle) , Control.InvokeOnClick(Control, EventArgs) , Control.OnAutoSizeChanged(EventArgs) , Control.OnBackColorChanged(EventArgs) , Control.OnBindingContextChanged(EventArgs) , Control.OnCausesValidationChanged(EventArgs) , Control.OnContextMenuStripChanged(EventArgs) , Control.OnCursorChanged(EventArgs) , Control.OnDataContextChanged(EventArgs) ,

Control.OnDockChanged(EventArgs) , Control.OnForeColorChanged(EventArgs) ,
Control.OnNotifyMessage(Message) , Control.OnParentBackColorChanged(EventArgs) ,
Control.OnParentBackgroundImageChanged(EventArgs) ,
Control.OnParentBindingContextChanged(EventArgs) , Control.OnParentCursorChanged(EventArgs) ,
Control.OnParentDataContextChanged(EventArgs) , Control.OnParentEnabledChanged(EventArgs) ,
Control.OnParentFontChanged(EventArgs) , Control.OnParentForeColorChanged(EventArgs) ,
Control.OnParentRightToLeftChanged(EventArgs) , Control.OnParentVisibleChanged(EventArgs) ,
Control.OnPrint(PaintEventArgs) , Control.OnTabIndexChanged(EventArgs) ,
Control.OnTabStopChanged(EventArgs) , Control.OnClick(EventArgs) ,
Control.OnClientSizeChanged(EventArgs) , Control.OnControlAdded(ControlEventArgs) ,
Control.OnControlRemoved(ControlEventArgs) , Control.OnLocationChanged(EventArgs) ,
Control.OnDoubleClick(EventArgs) , Control.OnDragEnter(DragEventArgs) ,
Control.OnDragOver(DragEventArgs) , Control.OnDragLeave(EventArgs) ,
Control.OnDragDrop(DragEventArgs) , Control.OnGiveFeedback(GiveFeedbackEventArgs) ,
Control.InvokeGotFocus(Control, EventArgs) , Control.OnHelpRequested(HelpEventArgs) ,
Control.OnInvalidated(InvalidateEventArgs) , Control.OnKeyDown(KeyEventArgs) ,
Control.OnKeyPress(KeyPressEventArgs) , Control.OnKeyUp(KeyEventArgs) ,
Control.OnLeave(EventArgs) , Control.InvokeLostFocus(Control, EventArgs) ,
Control.OnLostFocus(EventArgs) , Control.OnMarginChanged(EventArgs) ,
Control.OnMouseDoubleClick(MouseEventArgs) , Control.OnMouseClick(MouseEventArgs) ,
Control.OnMouseCaptureChanged(EventArgs) , Control.OnMouseDown(MouseEventArgs) ,
Control.OnMouseEnter(EventArgs) , Control.OnMouseLeave(EventArgs) ,
Control.OnDpiChangedBeforeParent(EventArgs) , Control.OnDpiChangedAfterParent(EventArgs) ,
Control.OnMouseHover(EventArgs) , Control.OnMouseMove(MouseEventArgs) ,
Control.OnMouseUp(MouseEventArgs) ,
Control.OnQueryContinueDrag(QueryContinueDragEventArgs) ,
Control.OnRegionChanged(EventArgs) , Control.OnPreviewKeyDown(PreviewKeyDownEventArgs) ,
Control.OnSizeChanged(EventArgs) , Control.OnChangeUICues(UICuesEventArgs) ,
Control.OnSystemColorsChanged(EventArgs) , Control.OnValidating(CancelEventArgs) ,
Control.OnValidated(EventArgs) , Control.PerformLayout() , Control.PerformLayout(Control, string) ,
Control.PointToClient(Point) , Control.PointToScreen(Point) ,
Control.PreProcessMessage(ref Message) , Control.PreProcessControlMessage(ref Message) ,
Control.ProcessKeyEventArgs(ref Message) , Control.ProcessKeyMessage(ref Message) ,
Control.RaiseDragEvent(object, DragEventArgs) , Control.RaisePaintEvent(object, PaintEventArgs) ,
Control.RecreateHandle() , Control.RectangleToClient(Rectangle) ,
Control.RectangleToScreen(Rectangle) , Control.ReflectMessage(nint, ref Message) ,
Control.Refresh() , Control.ResetMouseEventArgs() , Control.ResetText() , Control.ResumeLayout() ,
Control.ResumeLayout(bool) , Control.Scale(SizeF) , Control.Select() ,
Control.SelectNextControl(Control, bool, bool, bool, bool) , Control.SendToBack() ,
Control.SetBounds(int, int, int, int) , Control.SetBounds(int, int, int, int, BoundsSpecified) ,

Control.SizeFromClientSize(Size) , Control.SetStyle(ControlStyles, bool) , Control.SetTopLevel(bool) , Control.RtlTranslateAlignment(HorizontalAlignment) , Control.RtlTranslateAlignment(LeftRightAlignment) , Control.RtlTranslateAlignment(ContentAlignment) , Control.RtlTranslateHorizontal(HorizontalAlignment) , Control.RtlTranslateLeftRight(LeftRightAlignment) , Control.RtlTranslateContent(ContentAlignment) , Control.Show() , Control.SuspendLayout() , Control.Update() , Control.UpdateBounds() , Control.UpdateBounds(int, int, int, int) , Control.UpdateBounds(int, int, int, int, int, int) , Control.UpdateZOrder() , Control.UpdateStyles() , Control.OnImeModeChanged(EventArgs) , Control.AccessibilityObject , Control.AccessibleDefaultActionDescription , Control.AccessibleDescription , Control.AccessibleName , Control.AccessibleRole , Control.AllowDrop , Control.Anchor , Control.AutoScrollOffset , Control.LayoutEngine , Control.DataContext , Control.BackgroundImage , Control.BackgroundImageLayout , Control.Bottom , Control.Bounds , Control.CanFocus , Control.CanRaiseEvents , Control.CanSelect , Control.Capture , Control.CausesValidation , Control.CheckForIllegalCrossThreadCalls , Control.ClientRectangle , Control.CompanyName , Control.ContainsFocus , Control.ContextMenuStrip , Control.Controls , Control.Created , Control.Cursor , Control.DataBindings , Control.DefaultBackColor , Control.DefaultCursor , Control.DefaultFont , Control.DefaultForeColor , Control.DefaultMargin , Control.DefaultMaximumSize , Control.DefaultMinimumSize , Control.DefaultPadding , Control.DeviceDpi , Control.IsDisposed , Control.Disposing , Control.Dock , Control.DoubleBuffered , Control.Enabled , Control.Focused , Control.Font , Control.FontHeight , Control.ForeColor , Control.Handle , Control.HasChildren , Control.Height , Control.IsHandleCreated , Control.InvokeRequired , Control.IsAccessible , Control.IsAncestorSiteInDesignMode , Control.IsMirrored , Control.Left , Control.Margin , Control.ModifierKeys , Control.MouseButtons , Control.MousePosition , Control.Name , Control.Parent , Control.ProductName , Control.ProductVersion , Control.RecreatingHandle , Control.Region , Control.RenderRightToLeft , Control.ResizeRedraw , Control.Right , Control.RightToLeft , Control.ScaleChildren , Control.Site , Control.TabIndex , Control.TabStop , Control.Tag , Control.Top , Control.TopLevelControl , Control.ShowKeyboardCues , Control.ShowFocusCues , Control.UseWaitCursor , Control.Visible , Control.Width , Control.PreferredSize , Control.Padding , Control.ImeMode , Control.ImeModeBase , Control.PropagatingImeMode , Control.BackColorChanged , Control.BackgroundImageChanged , Control.BackgroundImageLayoutChanged , Control.BindingContextChanged , Control.CausesValidationChanged , Control.ClientSizeChanged , Control.ContextMenuStripChanged , Control.CursorChanged , Control.DockChanged , Control.EnabledChanged , Control.FontChanged , Control.ForeColorChanged , Control.LocationChanged , Control.MarginChanged , Control.RegionChanged , Control.RightToLeftChanged , Control.SizeChanged , Control.TabIndexChanged , Control.TabStopChanged , Control.TextChanged , Control.VisibleChanged , Control.Click ,

Control.ControlAdded , Control.ControlRemoved , Control.DataContextChanged , Control.DragDrop , Control.DragEnter , Control.DragOver , Control.DragLeave , Control.GiveFeedback , Control.HandleCreated , Control.HandleDestroyed , Control.HelpRequested , Control.Invalidated , Control.PaddingChanged , Control.Paint , Control.QueryContinueDrag , Control.QueryAccessibilityHelp , Control.DoubleClick , Control.Enter , Control.GotFocus , Control.KeyDown , Control.KeyPress , Control.KeyUp , Control.Layout , Control.Leave , Control.LostFocus , Control.MouseClick , Control.MouseDoubleClick , Control.MouseCaptureChanged , Control.MouseDown , Control.MouseEnter , Control.MouseLeave , Control.DpiChangedBeforeParent , Control.DpiChangedAfterParent , Control.MouseHover , Control.MouseMove , Control.MouseUp , Control.MouseWheel , Control.Move , Control.PreviewKeyDown , Control.Resize , Control.ChangeUICues , Control.StyleChanged , Control.SystemColorsChanged , Control.Validating , Control.Validated , Control.ParentChanged , Control.ImeModeChanged , Component.Dispose() , Component.GetService(Type) , Component.Container , Component.DesignMode , Component.Events , Component.Disposed , MarshalByRefObject.GetLifetimeService() , MarshalByRefObject.InitializeLifetimeService() , MarshalByRefObject.MemberwiseClone(bool) , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

Constructors

Form1()

```
public Form1()
```

Methods

Dispose(bool)

Clean up any resources being used.

```
protected override void Dispose(bool disposing)
```

Parameters

`disposing` bool

true if managed resources should be disposed; otherwise, false.

Class Rect

Namespace: Session_1

Assembly: Session 1.dll

Class to implement the Rect() command from the AsCommandFactory.

```
public class Rect : CommandTwoParameters, ICommand
```

Inheritance

object ← Command ← CanvasCommand ← CommandOneParameter ← CommandTwoParameters ← Rect

Implements

ICommand

Inherited Members

CommandTwoParameters.param2 , CommandTwoParameters.param2unprocessed , CommandOneParameter.param1 , CommandOneParameter.param1unprocessed , CanvasCommand.yPos , CanvasCommand.xPos , CanvasCommand.canvas , CanvasCommand.Canvas , Command.program , Command.parameterList , Command.parameters , Command.paramsint , Command.Set(StoredProgram, string) , Command.Compile() , Command.ProcessParameters(string) , Command.ToString() , Command.Program , Command.Name , Command.ParameterList , Command.Parameters , Command.Paramsint , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

Constructors

Rect()

Default constructor.

```
public Rect()
```

Rect(Canvas, int, int)

Constructor that initializes the Rect command with a specific canvas and dimensions.

```
public Rect(Canvas c, int width, int height)
```

Parameters

`c` Canvas

The canvas on which the rectangle will be drawn.

`width` int

The width of the rectangle.

`height` int

The height of the rectangle.

Methods

CheckParameters(string[])

Checks the number of parameters provided for the Rect command.

```
public override void CheckParameters(string[] parameterList)
```

Parameters

`parameterList` string[]

The list of parameters to check.

Exceptions

CommandException

Thrown if the number of parameters is invalid.

Execute()

Executes the Rect command by drawing a rectangle on the canvas.

```
public override void Execute()
```

Exceptions

RestrictionException

Thrown if the rectangle size exceeds allowed limits.

Class Reset

Namespace: Session_1

Assembly: Session 1.dll

A class that implements the Reset() command from the AsCommandFactory.

```
public class Reset : CommandOneParameter, ICommand
```

Inheritance

object ← Command ← CanvasCommand ← CommandOneParameter ← Reset

Implements

ICommand

Inherited Members

CommandOneParameter.param1 , CommandOneParameter.param1unprocessed , CommandOneParameter.CheckParameters(string[]) , CanvasCommand.yPos , CanvasCommand.xPos , CanvasCommand.canvas , CanvasCommand.Canvas , Command.program , Command.parameterList , Command.parameters , Command.paramsint , Command.Set(StoredProgram, string) , Command.Compile() , Command.ProcessParameters(string) , Command.ToString() , Command.Program , Command.Name , Command.ParameterList , Command.Parameters , Command.Paramsint , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

Constructors

Reset()

Default constructor.

```
public Reset()
```

Reset(Canvas)

Constructor that initializes the Reset command with a specific canvas.

```
public Reset(Canvas c)
```

Parameters

`c` Canvas

The canvas to be reset.

Methods

Execute()

Executes the Reset command by calling the Reset method on the canvas.

```
public override void Execute()
```

Class Tri

Namespace: Session_1

Assembly: Session 1.dll

A class that implements the Tri() command from the AsCommandFactory.

```
public class Tri : CommandTwoParameters, ICommand
```

Inheritance

object ← Command ← CanvasCommand ← CommandOneParameter ← CommandTwoParameters ← Tri

Implements

ICommand

Inherited Members

CommandTwoParameters.param2 , CommandTwoParameters.param2unprocessed , CommandOneParameter.param1 , CommandOneParameter.param1unprocessed , CanvasCommand.yPos , CanvasCommand.xPos , CanvasCommand.canvas , CanvasCommand.Canvas , Command.program , Command.parameterList , Command.parameters , Command.paramsint , Command.Set(StoredProgram, string) , Command.Compile() , Command.ProcessParameters(string) , Command.ToString() , Command.Program , Command.Name , Command.ParameterList , Command.Parameters , Command.Paramsint , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

Constructors

Tri()

Default constructor.

```
public Tri()
```

Tri(Canvas, int, int)

Constructor that initializes the Tri command with a specific canvas and dimensions.

```
public Tri(Canvas c, int width, int height)
```

Parameters

`c` Canvas

The canvas on which the triangle will be drawn.

`width` int

The width of the triangle.

`height` int

The height of the triangle.

Methods

CheckParameters(string[])

Checks the number of parameters provided for the Tri command.

```
public override void CheckParameters(string[] parameterList)
```

Parameters

`parameterList` string[]

The list of parameters to check.

Exceptions

CommandException

Thrown if the number of parameters is invalid.

Execute()

Executes the Tri command by calling the Tri method on the canvas.

```
public override void Execute()
```

Exceptions

RestrictionException

Thrown if the dimensions exceed allowed limits.

Class WriteText

Namespace: Session_1

Assembly: Session 1.dll

A class that implements the WriteText() command from the AsCommandFactory.

```
public class WriteText : CommandOneParameter, ICommand
```

Inheritance

object ← Command ← CanvasCommand ← CommandOneParameter ← WriteText

Implements

ICommand

Inherited Members

CommandOneParameter.param1 , CommandOneParameter.param1unprocessed , CanvasCommand.yPos , CanvasCommand.xPos , CanvasCommand.canvas , CanvasCommand.Canvas , Command.program , Command.parameterList , Command.parameters , Command.paramsint , Command.Set(StoredProgram, string) , Command.Compile() , Command.ProcessParameters(string) , Command.ToString() , Command.Program , Command.Name , Command.ParameterList , Command.Parameters , Command.Paramsint , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

Constructors

WriteText()

Default constructor.

```
public WriteText()
```

WriteText(Canvas, string)

Constructor that initializes the WriteText command with a specific canvas and text.

```
public WriteText(Canvas c, string text)
```

Parameters

`c` Canvas

The canvas where text will be written.

`text` string

The text to be written.

Methods

CheckParameters(string[])

Checks the number of parameters provided for the WriteText command.

```
public override void CheckParameters(string[] parameterList)
```

Parameters

`parameterList` string[]

The list of parameters to check.

Exceptions

CommandException

Thrown if the number of parameters is invalid.

Execute()

Executes the WriteText command by calling the WriteText method on the canvas.

```
public override void Execute()
```

Exceptions

RestrictionException

Thrown if the text is empty.