

Lecture 2, Part 2

Scribed by Hao Chen, Wengong Jin and Wen Xu

In this class we talked about Extensive form game with perfect information and its Nash equilibrium, subgame perfect equilibrium and the one deviation property.

1 Extensive form game with perfect information

Definition 1 *An extensive form game is tuple (N, T, r, D, Z, P, u) .*

$N = \{1, 2, \dots, n\}$ is set of players.

T is a tree(game tree).

r is the root.

D is the set of non-terminal nodes(decision nodes).

Z is the set of terminal nodes.

P is called player function: $D \rightarrow N \forall x \in D P(x) = i$ means i acts at x .

u is the utility function. $u = (u_1, u_2, \dots, u_n)$ where $u_i : Z \rightarrow \mathbb{R}$.

Now we introduce some basic concepts of extensive form game.

Action

$\forall x \in D$ $A(x)$ is set of actions(i.e. set of children of node x).

Strategy

Strategy of i S_i maps each x with $P(x) = i$ to an action in $A(x)$.

History

$\forall x \in D \cup Z$ history leading to x $h(x)$ is the sequence of actions leading to x .

$h(x) = \perp$ denotes an empty string.

Example 1




Figure 1: example 1

$$N = \{1, 2\}$$

$$S_1 = \{L, M, R\}$$

$$S_2 = \{ll'l'', ll'r'', lr'l'', lr'r'', rl'l'', rl'r'', rr'l'', rr'r''\}$$

Given strategy profiles $s = (L, lr'l'')$, $h(s)$ is path selected by s .

$u(s)$ is utility at terminal nodes.

The game follows illustrates an important point: given some strategy profile s , the path selected by s , namely $h(s)$, may meet a “dead end” halfway.

Example 2




Figure 2: example 2

$$S_1 = \{AE, AF, BE, BF\}$$

While after player 1 chosen action B, he can never choose action E and F, BE and BF is still a eligible strategy of player 1.

2 Nash equilibrium

Definition 2 A strategy profile s^* is a Nash equilibrium if $\forall i \forall s_i \in S_i u_i(s_i^*, s_{-i}^*) \geq u_i(s_i, s_{-i}^*)$

Now we introduce the Normal Form representation $(N, S, (u)_{i \in N})$ of an extensive form game. We will illustrate it by the example above.

1/2	C	D
AE	1,2	0,1
AF	3,0	0,1
BE	2,2	2,2
BF	2,2	2,2

It's easy to notice that s^* is a Nash equilibrium of the extensive form game iff it is a Nash equilibrium of the Normal Form representation.

The unsatisfactory of Nash equilibrium in extensive form game

Sometimes the Nash equilibrium in extensive form game lacks plausibility.

Example 3




Figure 3: example 3

In this game, both (A, R) and (B, L) is Nash equilibrium. The reason that (B, L) is a Nash equilibrium is that $u_1(A, L) = 0 < u_1(B, L)$ and $u_2(B, R) = u_2(B, L)$. However, if player 1 chooses action A, then player 2(rational) would choose action R over L because he can obtain higher payoff by doing so. The equilibrium is sustained by the “threat” of

player 2 to chooses L if player 1 chooses A. In fact, if we change the utility \mathbf{u} (the end of AL) = $(-\infty, \infty)$, the equilibrium still holds. Therefore, the Nash equilibrium (B, L) is not so persuasive.

3 Subgame perfect equilibrium

Motivated by the unsatisfactory of Nash equilibrium, we introduce a better equilibrium: subgame perfect equilibrium. First, we define the notion of subgame.

Definition 3 *The subgame after history h is an extensive game*

$$G(h) = (N, T|_h, r, D|_h, Z|_h, P|_h, u|_h)$$

The notion of subgame can be illustrated by the notion of subtree.

Strategy of subgame

$S_i|_h : \forall x \in D|_h$ such that $P|_h(x) = i, S_i|_h(x) = s_i(x)$.

Definition 4 *A strategy profile s^* is a subgame perfect equilibrium(SPE) if $\forall i \forall$ non-terminal history h leading to x with $P(x) = i$, we have $u_i(s_i^*|_h, s_{-i}^*|_h) \geq u_i(s_i, s_{-i}^*|_h)$ for any $s_i \in S_i|_h$. Equivalently, s^* is a subgame perfect equilibrium if $\forall h : s_i^*|_h$ is a Nash equilibrium in subgame $G(h)$.*

Lemma 1 *(The one deviation property) \forall finite horizon extensive game Γ with perfect information, s^* is a SPE of $\Gamma \iff \forall i \forall h$ leading to x where $P(x) = i, \forall s_i \in S_i|_h$ satisfying s_i and $s_i^*|_h$ differ only at $x, u_i(s_i^*|_h, s_{-i}^*|_h) \geq u_i(s_i, s_{-i}^*|_h)$.*

Proof. The " \implies " part is trivial.

As for the " \impliedby " part, we can prove it by contradiction. Assume that s^* satisfies the one deviation property but it is not a SPE. Then $\exists i, h', i$ can deviate profitably in $G(h')$. $\exists s_i \in S_i|_{h'}$, so that $u_i(s_i', s_{-i}^*|_{h'}) > u_i(s_i^*, s_{-i}^*|_{h'})$.

Without loss of generality, s_i' is the strategy with the least nodes satisfying $s_i'(x) \neq s_i^*$ for at most l nodes where $l = \text{height of } G(h)$. It is profitable deviation, which means that it can result to better outcome. Then take the **longest** path \hat{h} so that $s_i'(\hat{x}) \neq s_i^*|_{h(\hat{x})}$. Then $s_i'|_{\hat{h}}$ is a deviation from $s_i^*|_{\hat{h}}$. Thus, we can claim that $s_i'|_{\hat{h}}$ is a profitable deviation in $G(\hat{h})$. Define \hat{s}_i , and it is profitable with less nodes. Then it contradicts the assumption. \square

References

- [1] M. J. Osborne and A. Rubinstein. *A course in game theory*. MIT Press, 1994.
- [2] N. Nisan, T. Roughgarden, E. Tardos, and V. Vazirani (eds). *Algorithmic game theory*. Cambridge University Press, 2007. (Available at http://www.cambridge.org/journals/nisan/downloads/Nisan_Non-printable.pdf.)