

Blockchain Security | Smart Contract Audits | KYC Development | Marketing



Unicrypt

V2 ENMT TaxToken

Audit

Security Assessment 22. June, 2023

For







| Disclaimer | 3 |
|--|----|
| Description | 5 |
| Project Engagement | 5 |
| Logo | 5 |
| Contract Link | 5 |
| Methodology | 7 |
| Used Code from other Frameworks/Smart Contracts (direct imports) | 8 |
| Tested Contract Files | 9 |
| Source Lines | 10 |
| Risk Level | 10 |
| Capabilities | 11 |
| Inheritance Graph | 12 |
| CallGraph | 13 |
| Scope of Work/Verify Claims | 14 |
| Modifiers and public functions | 26 |
| Source Units in Scope | 34 |
| Critical issues | 36 |
| High issues | 36 |
| Medium issues | 36 |
| Low issues | 36 |
| Informational issues | 37 |
| Audit Comments | 40 |
| SWC Attacks | 41 |

Disclaimer

<u>SolidProof.io</u> reports are not, nor should be considered, an "endorsement" or "disapproval" of any particular project or team. These reports are not, nor should be considered, an indication of the economics or value of any "product" or "asset" created by any team. SolidProof.io do not cover testing or auditing the integration with external contract or services (such as Unicrypt, Uniswap, PancakeSwap etc'...)

SolidProof.io Audits do not provide any warranty or guarantee regarding the absolute bug- free nature of the technology analyzed, nor do they provide any indication of the technology proprietors. SolidProof Audits should not be used in any way to make decisions around investment or involvement with any particular project. These reports in no way provide investment advice, nor should be leveraged as investment advice of any sort.

SolidProof.io Reports represent an extensive auditing process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology. Blockchain technology and cryptographic assets present a high level of ongoing risk. SolidProof's position is that each company and individual are responsible for their own due diligence and continuous security. SolidProof in no way claims any guarantee of security or functionality of the technology we agree to analyze.

| Version | Date | Description |
|---------|-------------------------|---|
| 1.0 | 15. October 2022 | Layout projectAutomated-Security Testing |
| | 1617. October 2022 | Code reviewManual-Security Testing |
| | 1819. October 2022 | Finishing audit |
| 1.1 | 14 15. November 2022 | · Reaudit |
| 1.2 | 09. December 2022 | Small updates reviewUpdating report |
| 1.3 | 13 15. March 2023 | · Reaudit |
| | 22. June 2023 | All issues have been acknowledged by the unicrypt team |

Network

Ethereum (ERC20)

Website

https://unicrypt.network/

Telegram

https://t.me/uncx_token

Twitter

https://twitter.com/UNCX_token

Medium

https://unicrypt.medium.com/

Description

TBA

Project Engagement

During the 12th of October 2022, **Unicrypt Team** engaged Solidproof.io to audit smart contracts that they created. The engagement was technical in nature and focused on identifying security flaws in the design and implementation of the contracts. They provided Solidproof.io with access to their code repository and whitepaper.

Logo



Contract Link

v1.3

· TBA

Vulnerability & Risk Level

Risk represents the probability that a certain source-threat will exploit vulnerability, and the impact of that event on the organization or system. Risk Level is computed based on CVSS version 3.0.

| Level | Value | Vulnerability | Risk (Required Action) |
|---------------|---------|---|---|
| Critical | 9 - 10 | A vulnerability that can disrupt the contract functioning in a number of scenarios, or creates a risk that the contract may be broken. | Immediate action to reduce risk level. |
| High | 7 – 8.9 | A vulnerability that affects the desired outcome when using a contract, or provides the opportunity to use a contract in an unintended way. | Implementation of corrective actions as soon aspossible. |
| Medium | 4 – 6.9 | A vulnerability that could affect the desired outcome of executing the contract in a specific scenario. | Implementation of corrective actions in a certain period. |
| Low | 2 – 3.9 | A vulnerability that does not have a significant impact on possible scenarios for the use of the contract and is probably subjective. | Implementation of certain corrective actions or accepting the risk. |
| Informational | 0 – 1.9 | A vulnerability that have informational character but is not effecting any of the code. | An observation that does not determine a level of risk |

Auditing Strategy and Techniques Applied

Throughout the review process, care was taken to evaluate the repository for security-related issues, code quality, and adherence to specification and best practices. To do so, reviewed line-by-line by our team of expert pentesters and smart contract developers, documenting any issues as there were discovered.

Methodology

The auditing process follows a routine series of steps:

- 1. Code review that includes the following:
 - i) Review of the specifications, sources, and instructions provided to SolidProof to make sure we understand the size, scope, and functionality of the smart contract.
 - ii) Manual review of code, which is the process of reading source code line-byline in an attempt to identify potential vulnerabilities.
 - iii) Comparison to specification, which is the process of checking whether the code does what the specifications, sources, and instructions provided to SolidProof describe.
- 2. Testing and automated analysis that includes the following:
 - i) Test coverage analysis, which is the process of determining whether the test cases are actually covering the code and how much code is exercised when we run those test cases.
 - ii) Symbolic execution, which is analysing a program to determine what inputs causes each part of a program to execute.
- 3. Best practices review, which is a review of the smart contracts to improve efficiency, effectiveness, clarify, maintainability, security, and control based on the established industry and academic practices, recommendations, and research.
- 4. Specific, itemized, actionable recommendations to help you take steps to secure your smart contracts.

Used Code from other Frameworks/Smart Contracts (direct imports)

Imported packages:

| Dependency / Import Path | Count |
|---|-------|
| @uniswap/lib/contracts/libraries/TransferHelper.sol | 4 |
| @uniswap/v2-core/contracts/interfaces/IUniswapV2Callee.sol | 1 |
| @uniswap/v2-core/contracts/interfaces/IUniswapV2Factory.sol | 6 |
| @uniswap/v2-core/contracts/interfaces/IUniswapV2Pair.sol | 6 |
| hardhat/console.sol | 5 |

Tested Contract Files

This audit covered the following files listed below with a SHA-1 Hash.


A file with a different Hash has been modified, intentionally or otherwise, after the security review. A different Hash could be (but not necessarily) an indication of a changed condition or potential vulnerability that was not within the scope of this review.

v1.3

| File Name | SHA-1 Hash |
|--|--|
| contracts/facets/AntiBot.sol | 98ad58a80bb0aaf2871f1e7001735de9f27949fe |
| contracts/BuyBackWallet.sol | 31173a0f571e96f03028569d7960e7c341e7f335 |
| contracts/facets/Tax.sol | a3b7554e0c64b58262bbad573775226bffe7dac5 |
| contracts/facets/Constructor.sol | c377f635835740d618b020c2e720058dfa4df6c7 |
| contracts/facets/Storage.sol | f3d2da9616f81464aaa0a007eb93c4394342fa3a |
| contracts/facets/Multicall.sol | c2ff3f5f4ea08aa9f47026b4fb83213f980bd905 |
| contracts/facets/Lossless.sol | b6180eccf843e7c1e7f838f35a5e9714817e5e25 |
| contracts/facets/Wallets.sol | aef7deec00a0d0c6562e1d2051c307a41f188486 |
| contracts/facets/Settings.sol | 7ff8c5eb9e27f736014b1d9c644cd0098f291d56 |
| contracts/FacetHelper.sol | a9c6306e0212bde84c83dc7ffd25bbf7dd7cdc08 |
| contracts/TaxToken.sol | 77e18f1e36bbf483414c2469e3dfe3b2a2a39738 |
| contracts/FeeHelper.sol | 9648534df6a81f7e93b3e5dce724b6cf8b5809f2 |
| contracts/MintGenerator.sol | de2e4e76438e80c4e248e046cc81ce78bad5ed8 |
| contracts/MintFactory.sol | 66f7f112a50c505500330e32c8fc76d2830b45f3 |
| contracts/TaxHelperUniswapV2.sol | 8c40c9cbd233b6c5d23cb65165d26b8940c68560 |
| contracts/LPWallet.sol | b835b362c0bfdcd40fbeb8187e9f346a5ad6e3b6 |
| contracts/interfaces/IERC20.sol | 4f02a422b8d0ebe0d3c2bc02461bbbc034286d5b |
| contracts/interfaces/ILosslessController.sol | d5a753d5bfc5598f8013c1c246ba37fe542508ae |
| contracts/interfaces/IFacetHelper.sol | a9a7f19c5d8439dd6daa4ce46d26b5a3cd87171b |
| contracts/interfaces/IUniswapV2Pair.sol | ccd8036e1ef9d2430f46a45fa801fc625dd80d8e |
| contracts/libraries/FullMath.sol | 31b683e9e7e70a069d84e392c81093ddbc345b5 |
| contracts/libraries/Context.sol | 4465015f0682ad5930d21821c9d58be709195bfc |
| contracts/libraries/EnumerableSet.sol | 9cdc08ba9455c2127e7c5d5651a036baab76f2c2 |
| contracts/interfaces/IUniswapV2Factory.sol | a5d78edcba4e2228f92a4a0df03190c12d869184 |
| contracts/libraries/Ownable.sol | 0510660ea05a9ff29d6c9b87a4166c7a4eeed2f8 |
| contracts/libraries/Pausable.sol | b9ec1611b977ebcc3120e85cc10768dd192a7c78 |
| contracts/libraries/ERC20.sol | 68259afa71414e00c0afbe20cde382b556db6699 |
| contracts/interfaces/IBuyBackWallet.sol | 5df276446174391d0b00c2a7d25698d6441be04d |
| contracts/interfaces/ITaxToken.sol | e25accb168f50f19cd0fd6579b47caceb5ca6c50 |
| contracts/interfaces/ILPWallet.sol | 7c35ba43f899da2cf0345b3311b9bae5b65fa019 |
| contracts/interfaces/IFeeHelper.sol | b565b226d1a2e5f80a78f5ac982e6a1d818398ac |
| contracts/interfaces/ISettings.sol | f76d561e54e059bd8c499fdaea6ac69307809aea |
| contracts/interfaces/IUniswapV2Router02.sol | 9b9f4c23ac1e66692519984e3d449605afa8a3bc |
| contracts/interfaces/IUniswapV2Router01.sol | fc9a0f0007cb1ba6c3f8f3e63f0fa6280d4459d4 |
| contracts/interfaces/IWallets.sol | 824e9e9be847aec317932f57e63da03b842c80e4 |
| contracts/interfaces/ITaxHelper.sol | f95d7952b05ae9588189c0195309df3f3eb80755 |
| contracts/interfaces/IMintFactory.sol | b2f2e3a08a9e5431748dbe79ff3e03ab87c369b6 |

Metrics

Source Lines v1.3



Capabilities

Components

| Version | Contracts | Libraries | Interfaces | Abstract |
|---------|-----------|-----------|------------|----------|
| 1.0 | 16 | 2 | 15 | 3 |

Exposed Functions

This section lists functions that are explicitly declared public or payable. Please note that getter methods for public stateVars are not included.

| Version | | Public | Payable |
|---------|--|--------|---------|
| 1.0 | | 330 | 9 |

| Version | External | Internal | Private | Pure | View |
|---------|----------|----------|---------|------|------|
| 1.0 | 191 | 252 | 18 | 13 | 181 |

State Variables


| Version | Total | Public |
|---------|-------|--------|
| 1.0 | 41 | 9 |

Capabilities

| Version | Solidity Versions observed | Experim ental Features | Can Receive Funds | Uses Assembl Y | Has Destroya ble Contract s |
|---------|----------------------------------|------------------------------|-------------------------|---------------------------|---|
| 1.0 | 0.8.17 >=0.5. 0 >=0.6. | | yes | yes (11 asm blocks) | |

| Version | Transfer s ETH | Low- Level Calls | Deleg ateCa II | Uses Hash Function s | EC Rec ove r | New/ Create/ Create2 |
|---------|-------------------|------------------------|----------------------|-------------------------------|-----------------------|---|
| 1.0 | yes | | yes | yes | | yes → NewC ontrac t:BuyB ackWal let → NewC ontrac t:LPWa llet → NewC ontrac t:TaxT oken |

Inheritance Graph v1.3



CallGraph

v1.3



Scope of Work/Verify Claims

The above token Team provided us with the files that needs to be tested (Github, Bscscan, Etherscan, files, etc.). The scope of the audit is the main contract (usual the same name as team appended with .sol).

We will verify the following claims:

- 1. Is contract an upgradeable
- 2. Correct implementation of Token standard
- 3. Deployer cannot mint any new tokens
- 4. Deployer cannot burn or lock user funds
- 5. Deployer cannot pause the contract
- 6. Deployer cannot set fees
- 7. Deployer cannot blacklist/antisnipe addresses
- 8. Overall checkup (Smart Contract Security)

Is contract an upgradeable

Name Is contract an upgradeable? Yes

Comments:

v1.0

 Since this contract is based on the diamond-3 pattern of Nick Mudge (For more information visit: https://eips.ethereum.org/EIPS/eip-2535, https://github.com/mudgen/diamond-3) parts of the project can be replaced by the owner. The team can also implement new functionalities after the deployment.

Correct implementation of Token standard

| | ERC20 | | | | | | | |
|--------------|---|--------------|----------|--------------|--|--|--|--|
| Function | Description | Exist | Tested | Verified | | | | |
| TotalSupply | Provides information about the total token supply | \checkmark | √ | \checkmark | | | | |
| BalanceOf | Provides account balance of the owner's account | \checkmark | √ | \checkmark | | | | |
| Transfer | Executes transfers of a specified number of tokens to a specified address | √ | √ | √ | | | | |
| TransferFrom | Executes transfers of a specified number of tokens from a specified address | √ | √ | √ | | | | |
| Approve | Allow a spender to withdraw a set number of tokens from a specified account | 1 | √ | √ | | | | |
| Allowance | Returns a set number of tokens from a spender to the owner | √ | 1 | ✓ | | | | |

| | ERC721 | | | |
|-------------------|--|--------------|----------|--------------|
| Function | Description | Exist | Tested | Verified |
| BalanceOf | Count all NFTs assigned to an owner | \checkmark | √ | √ |
| OwnerOf | Find the owner of an NFT | \checkmark | √ | \checkmark |
| SafeTransferFrom | Transfers the ownership of an NFT from one address to another address | √ | √ | √ |
| SafeTransferFrom | See above - Difference is that this function has an extra data parameter | √ | √ | √ |
| TransferFrom | Transfer ownership of an NFT | \checkmark | √ | \checkmark |
| Approve | Change or reaffirm the approved address for an NFT | √ | √ | √ |
| SetApprovalForAll | Enable or disable approval for a third party ("operator") to manage all of `msg.sender`'s assets | 1 | √ | √ |
| GetApproved | Get the approved address for a single NFT | √ | √ | √ |
| IsApprovedForAll | Query if an address is an authorized operator for another address | √ | √ | √ |
| SupportsInterface | Query if a contract implements an interface | √ | √ | √ |
| Name | Provides information about the name | √ | √ | √ |
| Symbol | Provides information about the symbol | √ | √ | √ |
| TokenURI | Provides information about the TokenUri | √ | 1 | √ |

Write functions of contract v1.0

AntiBot

setIncrement
setEndDate
setInitialMaxHold
updateAntiBot
antiBotCheck
addMaxBalanceWhitelistedAddress
removeMaxBalanceWhitelistedAddress
updateMaxBalanceWhitelistBatch
updateMaxBalanceAfterBuy
addSwapWhitelistedAddress
removeSwapWhitelistedAddress
updateSwapWhitelistEndDate
updateSwapWhitelistEndDate
updateSwapWhitelisting

Constructor

swapWhitelistingCheck

constructorHandler

Lossless

setLosslessAdmin
transferRecoveryAdminOwnership
acceptRecoveryAdminOwnership
proposeLosslessTurnOff
executeLosslessTurnOff
executeLosslessTurnOn

ERC20

transfer
approve
transferFrom
increaseAllowance
decreaseAllowance

Ownable

renounceOwnership transferOwnership

BuyBackWallet

sendEthToTaxHelper updateThreshold

FacetHelper

addFacet
addSelector
removeSelector
resetFacetStorage
updateSettingsFacet
updateLosslessFacet
updateTaxFacet
updateConstructorFacet
updateWalletsFacet
updateAntiBotFacet
updateMulticallFacet

Multicall

multicallAdminUpdate multicallAntiBotUpdate

Settings

addLPToken
removeLPToken
togglePause
addBlacklistedAddress
removeBlacklistedAddress
updateBlacklistBatch
updateCustomTaxes
updateTaxFees
updateTransactionTaxAddress
lockSettings
updateSettings
updatePairAddress
updateTaxHelperIndex

Tax

handleTaxes
_transfer
reflect
excludeAccount
includeAccount
mint
burn

Wallets

createBuyBackWallet createLPWallet updateBuyBackWalletThreshold updateLPWalletThreshold

FeeHelper

setGeneratorFee setFee setFeeAddress

LPWallet

sendEthToTaxHelper transferBalanceToTaxHelper updateThreshold

MintFactory

adminAllowTokenGenerator addTaxHelper updateTaxHelper registerToken updateFacetHelper updateFeeHelper updateLosslessController

MintGenerator

createToken 👸

TaxHelperUniswapV2

initiateBuyBackTax initiateLPTokenTax createLPToken

TaxToken

transferOutBlacklistedFunds
buyBackBurn
transfer
approve
transferFrom
increaseAllowance
decreaseAllowance

Deployer cannot mint any new tokens

| Name | Exist | Tested | Status |
|----------------------|----------|----------|--------|
| Deployer cannot mint | √ | √ | X |

Comments:

v1.0

· Owner can mint new tokens

Deployer cannot burn or lock user funds

| Name | Exist | Tested | Status |
|----------------------|--------------|----------|--------|
| Deployer cannot lock | \checkmark | √ | X |
| Deployer cannot burn | √ | √ | X |

Comments:

v1.0

- · Owner can lock user funds by
 - blacklisting addresses
 - Settings fees too high
- Tokens
 - · can be burned by the owner
 - · can be burned by msg.sender
 - Will be burned in the "initialBuyBackTax" function in the TaxHelperUniswapV2 contract L41

Deployer cannot pause the contract

| Name | Exist | Tested | Status |
|-----------------------|--------------|----------|--------|
| Deployer cannot pause | \checkmark | √ | X |

Comments:

v1.0

· Owner can pause contract

Deployer cannot set fees

| Name | Exist | Tested | Status |
|--|--------------|----------|--------|
| Deployer cannot set fees over 25% | \checkmark | √ | X |
| Deployer cannot set fees to nearly 100% or to 100% | √ | √ | X |

Comments:

v1.0

- FeeHelper
 - Fees can be set without any limitations

Deployer can blacklist/antisnipe addresses

| Name | Exist | Tested | Status |
|---|--------------|----------|--------|
| Deployer cannot blacklist/antisnipe addresses | \checkmark | √ | X |

Comments:

v1.0

· Only contracts can be blacklisted



Overall checkup (Smart Contract Security)



Legend


| Attribute | Symbol |
|--------------------------|--------------|
| Verified / Checked | \checkmark |
| Partly Verified | P |
| Unverified / Not checked | X |
| Not available | - |

Modifiers and public functions v1.0


Lossless

✓ \$ setLosslessAdmin ❷ onlyRecoveryAdminOwnership ❷ onlyRecoveryAdminOwnership ❷ acceptRecoveryAdminOwnership ✓ \$ proposeLosslessTurnOff ❷ onlyRecoveryAdmin ✓ \$ executeLosslessTurnOff ❷ onlyRecoveryAdmin ✓ \$ executeLosslessTurnOff ❷ onlyRecoveryAdmin ✓ \$ executeLosslessTurnOn ❷ onlyRecoveryAdmin


MintFactory



MintGenerator




TaxHelperUniswapV2




TaxToken

transferOutBlacklistedFunds
 buyBackBurn
 transfer
 approve
 transferFrom
 increaseAllowance
 decreaseAllowance

AntiBot Settings




FacetHelper






Multicall




Wallets




BuyBackWallet

sendEthToTaxHelperupdateThresholdonlyOwner

FeeHelper



LPWallet



Comments

- · Deployer can set following state variables without any limitations
 - AntiBot
 - maxBalanceAfterBuy
 - · antiBotSettings.initialMaxHold
 - antiBotSettings.increment
 - Multicall
 - fees.transactionTax.buy
 - fees.transactionTax.sell

- fees.buyBackTax
- fees.holderTax
- fees.lpTax
- antiBotSettings.increment
- antiBotSettings.initialMaxHold

Settings

- taxHelperIndex
 - Max to 2^8 1

BuyBackWallet

threshold

FacetHelper

- isFacet
- facetsList
- selectorToFacet
- selectorsList

FeeHelper

- SETTINGS.FEE
- SETTINGS.GENERATOR_FEE

LPWallet

threshold

• Deployer can enable/disable following state variables

AntiBot

- swapWhitelistingSettings.isActive
- antiBotSettings.isActive
- swapWhitelistlist
- maxBalanceWhitelistlist

Lossless

- isLosslessTurnOffProposed
- isLosslessOn

Multicall

- taxSettings.transactionTax
- taxSettings.holderTax
- taxSettings.buyBackTax
- taxSettings.lpTax
- taxSettings.canMint
- taxSettings.canPause
- taxSettings.canBlacklist
- taxSettings.maxBalanceAfterBuy
- isLocked.transactionTax
- isLocked.holderTax
- isLocked.buyBackTax
- isLocked.lpTax

- isLocked.canMint
- isLocked.canPause
- isLocked.canBlacklist
- isLocked.maxBalanceAfterBuy
- · antiBotSettings.isActive
- swapWhitelistingSettings.isActive

Settings

- taxSettings.transactionTax
- taxSettings.holderTax
- taxSettings.buyBackTax
- taxSettings.lpTax
- taxSettings.canMint
- taxSettings.canPause
- taxSettings.canBlacklist
- taxSettings.maxBalanceAfterBuy
- isLocked.transactionTax
- isLocked.holderTax
- isLocked.buyBackTax
- isLocked.lpTax
- isLocked.canMint
- isLocked.canPause
- isLocked.canBlacklist
- isLocked.maxBalanceAfterBuy
- blacklist
- isPaused
- IpTokens

Tax

- isExcluded
- excluded

Deployer can set following addresses/string

Lossless

- recoveryAdmin
- recoveryAdminCandidate
- recoveryAdminKeyHash
- admin

Settings

- pairAddress
- transactionTaxWallet

FacetHelper

- facets.Multicall
- facets.AntiBot
- facets.Wallets
- facets.Constructor

- facets.Settings
- facets.Lossless
- facets.Tax
- FeeHelper
 - · SETTINGS.FEE_ADDRESS
- MintFactory
 - LosslessController
 - FeeHelper
 - FacetHelper
 - taxHelpersData.Address
 - taxHelpers
 - tokenGenerators
- Existing Modifiers
 - TaxHelperUniswapV2
 - isToken
 - Antibot
 - antiBotIsActive
 - Lossless
 - onlyRecoveryAdmin
 - Settings
 - canBlacklist
 - Ownable
 - onlyOwner
 - Pausable
 - whenNotPaused
 - whenPaused
- The project is a diamond-3 structured. That means, that the owner can upgrade contracts on the fly.
- Tax
 - Owner can mint new tokens
- Wallets
 - Anybody is able to call "createBuyBackWallet" and "createLPWallet"
 - This function returns only the address of the new created wallets but it will not set a state variable in the storage
 - Owner can update buyback/lp wallets from the facet
- MintFactory
 - · Can add new taxHelper
- FacetHelper
 - Owner can reset facet storage and remove all selector and facet list

Please check if an OnlyOwner or similar restrictive modifier has been forgotten.



Source Units in Scope

v1.3

| Туре | File | Logic Contracts | Interfaces | Lines | nLines | nSLOC | Comment Lines | Complex. Score | Capabilities |
|--------------------|---|-----------------|------------|------------|------------|-----------|---------------|----------------|-------------------------|
| 2 | contracts/facets/AntiBot.sol | 1 | | 184 | 184 | 144 | 7 | 111 | |
| 2 | contracts/BuyBackWallet.sol | 1 | | 63 | 63 | 43 | 3 | 36 | <u>Š</u> . |
| <i>)</i> | contracts/facets/Tax.sol | 1 | | 353 | 353 | 281 | 23 | 175 | |
| 2 | contracts/facets/Constructor.sol | 1 | | 188 | 188 | 165 | 9 | 95 | |
| | contracts/facets/Storage.sol | | | 310 | 310 | 89 | 142 | | |
| 2 | contracts/facets/Multicall.sol | 1 | | 200 | 200 | 157 | 13 | 76 | |
| > | contracts/facets/Lossless.sol | 1 | | 76 | 76 | 56 | 4 | 42 | RIFF. |
| <i>y</i> | contracts/facets/Wallets.sol | 1 | | 48 | 48 | 32 | 3 | 48 | 6 |
| 9 | contracts/facets/Settings.sol | 1 | | 226 | 226 | 190 | 4 | 131 | |
| 9 | contracts/FacetHelper.sol | 1 | | 346 | 327 | 199 | 82 | 151 | |
|) | contracts/TaxToken.sol | 1 | | 499 | 499 | 382 | 31 | 360 | =99 |
| > | contracts/FeeHelper.sol | 1 | | 55 | 55 | 38 | 3 | 22 | |
| y | contracts/MintGenerator.sol | 1 | | 47 | 45 | 22 | 8 | 34 | . <u>\$</u> .4 <u>6</u> |
| 2 | contracts/MintFactory.sol | 1 | | 181 | 181 | 109 | 35 | 84 | |
| <i>y</i> | contracts/TaxHelperUniswapV2.sol | 1 | | 116 | 116 | 92 | 6 | 107 | . <u></u> |
|) | contracts/LPWallet.sol | 1 | | 74 | 74 | 51 | 3 | 45 | . <u>Š</u> .÷ |
| Q | contracts/interfaces/IERC20.sol | | 1 | 79 | 28 | 17 | 58 | 13 | 滋 |
| Q | contracts/interfaces/ILosslessController.sol | | 1 | 24 | 7 | 3 | 1 | 25 | |
| Q | contracts/interfaces/IFacetHelper.sol | | 1 | 70 | 17 | 7 | 17 | 39 | |
| Q | contracts/interfaces/IUniswapV2Pair.sol | | 1 | 52 | 7 | 5 | | 55 | |
| * | contracts/libraries/FullMath.sol | 1 | | 126 | 118 | 57 | 59 | 104 | ΞΣ |
| • | contracts/libraries/Context.sol | 1 | | 26 | 26 | 10 | 13 | 1 | |
| 8 | contracts/libraries/EnumerableSet.sol | 1 | | 357 | 357 | 118 | 196 | 49 | _ |
| Q | contracts/interfaces/IUniswapV2Factory.sol | | 1 | 17 | 6 | 4 | | 17 | |
| \$ | contracts/libraries/Ownable.sol | 1 | | 70 | 70 | 27 | 34 | 24 | |
| 8 | contracts/libraries/Pausable.sol | 1 | | 91 | 91 | 29 | 51 | 16 | |
| · | contracts/libraries/ERC20.sol | 1 | | 305 | 305 | 90 | 179 | 73 | |
| Q . | contracts/interfaces/IBuyBackWallet.sol | | 1 | 19 | 10 | 3 | 3 | 11 | |
| ۹ | contracts/interfaces/ITaxToken.sol | | 1 | 19 | 12 | 4 | 3 | 9 | |
| Q. | contracts/interfaces/ILPWallet.sol | | 1 | 21 | 10 | 3 | 3 | 13 | |
| ۹ . | contracts/interfaces/IFeeHelper.sol | | 1 | 22 | 9 | 3 | 3 | 15 | |
| ٠ <u>,</u> | contracts/interfaces/ISettings.sol | | 1 | 13 | 10 | 3 | 3 | 7 | |
| • | | | 1 | 44 | 6 | 4 | | 16 | × |
| ~ | contracts/interfaces/IUniswapV2Router02.sol | | | | | | | | |
| Q. | contracts/interfaces/IUniswapV2Router01.sol | | 1 | 95 | 4 | 3 | | 48 | <u>š</u> . |
| ۹, | contracts/interfaces/IWallets.sol | | 1 | 16 | 10 | 3 | 3 | 9 | |
| ۹, | contracts/interfaces/ITaxHelper.sol | | 1 | 23 | 10 | 3 | 3 | 9 | |
| ્ ∌ ક ્ર | contracts/interfaces/IMintFactory.sol Totals | 21 | 1 15 | 43 4498 | 16 4074 | 8 2454 | 1008 | 29 | <u></u> |

Legend

| Attribute | Description |
|---------------|---|
| Lines | total lines of the source unit |
| nLines | normalised lines of the source unit (e.g. normalises functions spanning multiple lines) |
| nSLOC | normalised source lines of code (only source-code lines; no comments, no blank lines) |
| Comment Lines | lines containing single or block comments |

| | a custom complexity score derived from code statements that |
|------------------|---|
| Complexity Score | are known to introduce code complexity (branches, loops, calls, |
| | external interfaces,) |



Audit Results

Critical issues

No critical issues

High issues

No high issues

Medium issues

No medium issues

Low issues

| | | Low | issues | acknowledged | |
|-----------|------------------------------------|---|--------|------------------------------------|----------------------|
| Issu e | File | Туре | Line | Description | Status |
| #1 | TaxH elper Unis wapV 2 | Missing Zero Address Validation (missing-zero- check) | 69, 70 | Check that the address is not zero | Ackno wledge d |
| #2 | TaxTo ken | Missing Zero Address Validation (missing-zero-check) | 59 | Check that the address is not zero | Ackno wledge d |
| #3 | Setti ngs | Missing Zero Address Validation (missing-zero-check) | 219 | Check that the address is not zero | Ackno wledge d |
| #4 | Unis wapV 2Rou ter02 | Missing Zero Address Validation (missing-zero- check) | 25, 27 | Check that the address is not zero | Ackno wledge d |

| #5 | Unis wapV 2Rou ter01 | Missing Zero Address Validation (missing-zero- check) | 21, 22 | Check that the address is not zero | Ackno wledge d |
|----|------------------------------------|---|---------|--|----------------------|
| #6 | TaxH elper Unis wapV 2 | State variable visibility is not set | 23-25 | It is best practice to set the visibility of state variables explicitly | Ackno wledge d |
| #7 | Multi call | Variable is not defined | 137-140 | Make sure to check whether s.lpWallet is set before calling updateThreshold of it. | Ackno wledge d |
| #8 | Multi call | Missing parameter in the MulticallAdminU pdateParams | 32 | The multicall struct does not have a property for the Ip wallet and buy back wallet. | Ackno wledge d |
| | | | | See Issue one line above | |

Informational issues

| Informational issues acknowledged | | | | | |
|-----------------------------------|---------------------|-----------------------------|------------------|--|----------------------|
| Issu e | File | Туре | Line | Description | Status |
| #1 | LPW allet | Error message is missing | 55 | Provide an error message for require statement | Ackno wledge d |
| #2 | Mint Facto ry | Error message is missing | 157, 167, 177 | Provide an error message for require statement | Ackno wledge d |
| #3 | Setti ngs | Error message is missing | 95, 129 | Provide an error message for require statement | Ackno wledge d |
| #4 | AntiB ot | Error message is missing | 65, 120 | Provide an error message for require statement | Ackno wledge d |
| #5 | Const ructo r | Error message is missing | 114 | Provide an error message for require statement | Ackno wledge d |
| #6 | Tax | Error message is missing | 56, 145 | Provide an error message for require statement | Ackno wledge d |

| #7 | FullM ath | Error message is missing | 34, 43, 122 | Provide an error message for require statement | Ackno wledge d |
|-----|--------------------------------|---|------------------------|---|----------------------|
| #8 | All | NatSpec documentation missing | - | If you started to comment your code, also comment all other functions, variables etc. | Ackno wledge d |
| #9 | Lossl | Set recoveryAdminC andidate to address zero after accepting | 50 | Don't forget to set the "recoveryAdminCandidate" to address zero after accepting the ownership | Ackno wledge d |
| #10 | AntiB ot | Visibility first | 32 | The visibility modifier "internal" should come before other modifiers. We recommend you to put internal before the view key here. | Ackno wledge d |
| #11 | IUnis wapV 2Fact ory | SPDX License is missing | See descripti on | Add a SPDX License at the top of source file | Ackno wledge d |
| #12 | IUnis wapV 2Pair | SPDX License is missing | See descripti on | Add a SPDX License at the top of source file | Ackno wledge d |
| #13 | IUnis wapV 2Rou ter01 | SPDX License is missing | See descripti on | Add a SPDX License at the top of source file | Ackno wledge d |
| #14 | IUnis wapV 2Rou ter02 | SPDX License is missing | See descripti on | Add a SPDX License at the top of source file | Ackno wledge d |

Acknowledged by Unicrypt team

Low Issues

#1-#2: These checks are not needed, as the addresses are all defined by the Unicrypt team previously.

#3: UpdatePairAddress could potentially use a check, but we check on the front end already. Also, the Pair address is set to zero address on arbitrum using camelot, and then updated immediately after. No check is needed in this case.

#4-#5: Uniswap router is not our code, this was only used for local testing.

#6: Doesn't change anything, addressed..

#7-#8: These variables are all defined and used upon token creation.

Informational Issues

#1-#6: While true that we can add more error messages for each require statement, I am not for redeploying for these errors. These require statements are for specific things, like if they try blacklisting the fee address for example. Addressed.

#7: This is a library we are using, pretty sure it's being called by uniswap routers for local testing. So no changes will be made.

#8: While we could, we will not proceed with this one. Addressed.

#9: While this makes sense, this is lossless code, and we should not modify it as it is intentionally written this way by their devs. Have tested myself, and everything works with the recovery admin function. Have tested multiple changes.

#10: Something to note moving forward, addressed.

#11-#14: We have the code flattened when verifying so they are all covered by the licensing.

Audit Comments

We recommend you use the special form of comments (NatSpec Format, Follow the link for more information https://docs.soliditylang.org/en/latest/natspec-format.html) for your contracts to provide rich documentation for functions, return variables, and more. This helps investors to make clear what those variables, functions, etc. do.

15. November 2022:

- · We recommend you to follow the terms of the diamond-3 pattern
 - · This project is a modified diamond-3 pattern
- · Read the whole report and modifiers section for more information

09. December 2022:

· Read the whole report and modifiers section for more information

13. March 2023:

- · Changes of the new version of the project
 - The Architecture of the project was changed. Contracts are not inheriting from Storage anymore. The storage contract was implemented like an Interface where the owner can pass the "storage" address to interact with it.
 - External/Public functions were prevented to call be require statements
 - More Events were added to the project
 - Files
 - TaxFacet
 - Functions removed
 - mint
 - MulticallFacet
 - Added LPWallet
 - Diamond-3 standards were implemented into the project from Nick Mudge
- · Read whole report and modifiers section for more information

22. June 2023:

· All issues have been acknowledged by the unicrypt team.

SWC Attacks

| ID | Title | Relationships | Status |
|--------------------------------------|--|--|--------|
| <u>SW</u> <u>C-1</u> <u>36</u> | Unencrypted Private Data On-Chain | CWE-767: Access to Critical Private Variable via Public Method | PASSED |
| <u>SW</u> <u>C-1</u> <u>35</u> | Code With No Effects | CWE-1164: Irrelevant Code | PASSED |
| <u>SW</u> <u>C-1</u> <u>34</u> | Message call with hardcoded gas amount | CWE-655: Improper Initialization | PASSED |
| <u>SW</u> <u>C-1</u> <u>33</u> | Hash Collisions With Multiple Variable Length Arguments | CWE-294: Authentication Bypass by Capture-replay | PASSED |
| <u>SW</u> <u>C-1</u> <u>32</u> | Unexpected Ether balance | CWE-667: Improper Locking | PASSED |
| <u>SW</u> <u>C-1</u> <u>31</u> | Presence of unused variables | CWE-1164: Irrelevant Code | PASSED |
| <u>SW</u> <u>C-1</u> <u>30</u> | Right-To-Left- Override control character (U+202E) | CWE-451: User Interface (UI) Misrepresentation of Critical Information | PASSED |
| <u>SW</u> <u>C-1</u> <u>29</u> | Typographical Error | CWE-480: Use of Incorrect Operator | PASSED |
| <u>SW</u> <u>C-1</u> <u>28</u> | DoS With Block Gas Limit | CWE-400: Uncontrolled Resource Consumption | PASSED |

| <u>SW</u> <u>C-1</u> <u>27</u> | Arbitrary Jump with Function Type Variable | CWE-695: Use of Low-Level Functionality | PASSED |
|--------------------------------------|--|---|--------|
| SW C-1 25 | Incorrect Inheritance Order | CWE-696: Incorrect Behavior Order | PASSED |
| <u>SW</u> <u>C-1</u> <u>24</u> | Write to Arbitrary Storage Location | CWE-123: Write-what-where Condition | PASSED |
| <u>SW</u> <u>C-1</u> <u>23</u> | Requirement Violation | CWE-573: Improper Following of Specification by Caller | PASSED |
| <u>SW</u> <u>C-1</u> <u>22</u> | Lack of Proper Signature Verification | CWE-345: Insufficient Verification of Data Authenticity | PASSED |
| SW C-1 21 | Missing Protection against Signature Replay Attacks | CWE-347: Improper Verification of Cryptographic Signature | PASSED |
| SW C-1 20 | Weak Sources of Randomness from Chain Attributes | CWE-330: Use of Insufficiently Random Values | PASSED |
| <u>SW</u> <u>C-11</u> <u>9</u> | Shadowing State Variables | CWE-710: Improper Adherence to Coding Standards | PASSED |
| <u>SW</u> <u>C-11</u> <u>8</u> | Incorrect Constructor Name | CWE-665: Improper Initialization | PASSED |
| <u>SW</u> <u>C-11</u> <u>7</u> | Signature Malleability | CWE-347: Improper Verification of Cryptographic Signature | PASSED |

| <u>SW</u> <u>C-11</u> <u>6</u> | Timestamp Dependence | CWE-829: Inclusion of Functionality from Untrusted Control Sphere | PASSED |
|--------------------------------------|---|--|--------|
| <u>SW</u> <u>C-11</u> <u>5</u> | Authorization through tx.origin | CWE-477: Use of Obsolete Function | PASSED |
| <u>SW</u> <u>C-11</u> <u>4</u> | Transaction Order Dependence | CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') | PASSED |
| <u>SW</u> <u>C-11</u> <u>3</u> | DoS with Failed Call | CWE-703: Improper Check or Handling of Exceptional Conditions | PASSED |
| <u>SW</u> <u>C-11</u> <u>2</u> | Delegatecall to Untrusted Callee | CWE-829: Inclusion of Functionality from Untrusted Control Sphere | PASSED |
| <u>SW</u> <u>C-11</u> <u>1</u> | Use of Deprecated Solidity Functions | CWE-477: Use of Obsolete Function | PASSED |
| <u>SW</u> <u>C-11</u> <u>O</u> | Assert Violation | CWE-670: Always-Incorrect Control Flow Implementation | PASSED |
| SW C-1 09 | Uninitialized Storage Pointer | CWE-824: Access of Uninitialized Pointer | PASSED |
| <u>SW</u> <u>C-1</u> <u>08</u> | State Variable Default Visibility | CWE-710: Improper Adherence to Coding Standards | PASSED |
| SW C-1 07 | Reentrancy | CWE-841: Improper Enforcement of Behavioral Workflow | PASSED |
| <u>SW</u> <u>C-1</u> <u>06</u> | Unprotected SELFDESTRUC T Instruction | CWE-284: Improper Access Control | PASSED |

| SW C-1 05 | Unprotected Ether Withdrawal | CWE-284: Improper Access Control | PASSED |
|--------------------------------------|--------------------------------------|--|--------|
| <u>SW</u> <u>C-1</u> <u>04</u> | Unchecked Call Return Value | CWE-252: Unchecked Return Value | PASSED |
| <u>SW</u> <u>C-1</u> <u>03</u> | Floating Pragma | CWE-664: Improper Control of a Resource Through its Lifetime | PASSED |
| <u>SW</u> <u>C-1</u> <u>02</u> | Outdated Compiler Version | CWE-937: Using Components with Known Vulnerabilities | PASSED |
| <u>SW</u> <u>C-1</u> <u>01</u> | Integer Overflow and Underflow | CWE-682: Incorrect Calculation | PASSED |
| <u>SW</u> <u>C-1</u> <u>00</u> | Function Default Visibility | CWE-710: Improper Adherence to Coding Standards | PASSED |
| | | | |







Blockchain Security | Smart Contract Audits | KYC Development | Marketing

