



SUBSTRATE INFORMATION SHEET

Details

TEKpvc is a superior quality, extremely versatile PVC foam sheet. The combination of lightweight and extremely good dimensional stability makes it the perfect display board for all structural applications. Its fine cell structure, smooth and robust surface plus its high durability make it the preferred choice for signage and exhibition applications for both interior and short-term exterior applications.

Available in 2mm, 3mm and 5mm

Features

- High quality
- Hi-white, smooth surface finish with high surface hardness
- Universal sheet for all display applications
- Light weight, strong and durable
- Suitable for indoor and short term outdoor applications
- Eyelet up to 3mm

Applications

Signage and Display Panels POS Displays Hanging signs **Exhibition Stands** Shop Fitting Wall Cladding

Partitioning Interior Design

Technical Data

Thickness	2mm	3mm	5mm
Apparent density	400-550kg/m3	400-550kg/m3	400-550kg/m3
Surface hardness	35 Shore D	35 Shore D	35 Shore D
Max service temperature	55° Celsius	55° Celsius	55° Celsius
Coefficient of linear expansion	0.05mm/(m-K)	0.05mm/(m-K)	0.05mm/(m-K)
Water absorption	<1%	<1%	<1%
Eyelet	•	•	

Finishing Options

Router Cut









Important Note

All values presented in this data sheet provide the general characteristics of the product and are a guide only. Stock can change vary over time due to availability of supply. It is the responsibility of the customer and/or end user to determine that the product is fit for the specific application it is to be used for. If specifics requirements are to be adhered to, it is the responsibility of the customer and/or end user to request an up to date Technical Data Sheet.

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufaturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.

