

Magnet



SUBSTRATE INFORMATION SHEET

Details

0.8mm magnet with a gloss white PVC printable face film supplied with your choice of overlaminate, Gloss, Matt or Whiteboard.

Features

- 0.8mm thickness for automotive applications

Applications

Temporary Automotive Signage

Magnetic Surfaces

POS Displays

Promotional Graphics

Wall Graphics

Technical Data

| Item | Description | Remarks |
|---|-------------|------------|
| Thickness | 0.8 | |
| Specific Gravity (g/cm ³) | 3.6 | |
| Elongation (%) MD CD | 112.5 ↑ | CNS 1441 |
| | 25 ↑ | |
| Tensile Strength MD (kg/mm ²) CD | 0.96 ↑ | |
| | 0.5 ↑ | |
| Hardness (Shore A) | 45 | |
| Vicinity Soft Temp | 140° C | ASTM D1525 |
| Temperature Range | -5°C - 80°C | ASTM D1790 |

Finishing Options

Laminate



Router Cut



Important Note

All values presented in this data sheet provide the general characteristics of the product and are a guide only. Stock can change vary over time due to availability of supply. It is the responsibility of the customer and/or end user to determine that the product is fit for the specific application it is to be used for. If specifics requirements are to be adhered to, it is the responsibility of the customer and/or end user to request an up to date Technical Data Sheet.

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.