

Floor Display



SUBSTRATE INFORMATION SHEET

Details

Indoor floor display is a removable vinyl with an anti-slip, deep-grain, textured, matt, floor graphic over-laminate. This is a short term removable product. Removability is dependent on time of application. If left installed for an extended timeframe, a heat source is recommended to aid removal.

Features

- Can be router cut to shape.

Applications

Please consider where your customer intends to install this product. It is only suitable for adhesion to surfaces that are;

- Indoor
- Flat
- Clean
- Smooth
- Hard
- Polished/painted

Examples of these include;

- Floorboards
- Lino
- Polished/Painted Concrete

They may adhere to some of these surfaces, but we recommend testing before ordering;

- Industrial carpet
- Gloss/Non
- Teflon coated tiles (not over the grout)
- Perspex
- Glass that remains a consistent temperature

IF IN DOUBT PLEASE TEST A STOCK SAMPLE

Technical Data

Item	Standard
Film	3.2 mils(80microns) opaque film with gloss finish
Thickness	4.1 mils (105 microns) with adhesive ($\pm 10\%$)
Laminate thickness	0.20mm 0.01 with adhesive ($\pm 10\%$)
Adhesive	Acrylic based pressure sensitive (Solvent based)
Adhesive colour	Grey
Liner	Double side PE coated paper
Application surfaces	Flat surfaces
Application temp.	>10°C (18 to 25°C optimum)

P3 non-slip rating in accordance with AS 4586:2013 Slip resistance classification of new pedestrian surface materials, Appendix A - Wet Pendulum Test (report available on request)

Finishing Options

Router Cut



Important Note

All values presented in this data sheet provide the general characteristics of the product and are a guide only. Stock can change vary over time due to availability of supply. It is the responsibility of the customer and/or end user to determine that the product is fit for the specific application it is to be used for. If specifics requirements are to be adhered to, it is the responsibility of the customer and/or end user to request an up to date Technical Data Sheet.

All statements, technical information and recommendation are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties of merchantability and fitness for the purpose: Sellers and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.