





Switch1

Physical

Config

CLI

Attributes

IOS Command Line Interface

Hardware Board Revision Number : 0x01

Switch	Ports	Model	SW Version	SW Image
*	1 26	WS-C2960-24TT-L	15.0(2)SE4	C2960-LANBASEK9-M

Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE (fcl)
Technical Support: <http://www.cisco.com/techsupport>
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnguyen

Press RETURN to get started!

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

Switch>en

Switch#conf t

Enter configuration commands, one per line. End with CNTL/Z.

Switch(config)#hostname 2ws

2ws(config)#int vlan 1

2ws(config-if)#no sh

2ws(config-if)#

%LINK-5-CHANGED: Interface Vlan1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

2ws(config-if)#ip address 192.168.0.4 255.255.255.0

2ws(config-if)#exit

2ws(config)#

Copy

Paste

☐ Top

2960-24T

Switch1



