





Server0

Physical **Config** Services Desktop Programming Attributes

GLOBAL

Settings

Algorithm Settings

INTERFACE

FastEthernet0

Port Status ☒ On

Bandwidth ☐ 100 Mbps ☐ 10 Mbps ☒ Auto

Duplex ☐ Half Duplex ☐ Full Duplex ☒ Auto

MAC Address 0009.7C49.6C0D

IP Configuration

☐ DHCP

☒ Static

IPv4 Address 30.30.30.1

Subnet Mask 255.0.0.0

IPv6 Configuration

☐ Automatic

☒ Static

IPv6 Address

Link Local Address FE80::209:7CFF:FE49:6C0D

Router0

PhysicalConfigCLIAttributes

IOS Command Line Interface

```
Router(config-if)#access-list 1 permit any
Router(config)#
Router(config)#ip nat inside source list 1 interface fa0/1 overload
Router(config)#int fa0/0
Router(config-if)#
Router(config-if)#ip nat inside
Router(config-if)# int fa0/1
Router(config-if)#ip nat outside
Router(config-if)#end
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#Show ip nat translations
Router#
Router#
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface FastEthernet0/1
Router(config-if)#no shutdown
Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up

Router(config-if)#exit
Router(config)#interface FastEthernet0/0
Router(config-if)#no shutdown
Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up

Router(config-if)#Show ip nat translations
^
% Invalid input detected at '^' marker.

Router(config-if)#
```

CopyPaste

☐ Top

Активация Windows
Чтобы активировать Windows, перейдите на

