System Design Document — Telecom NetOps AI Assistant

Version: 3.0.0 (Production Release) | **Classification:** 5G NOC Decision-Support System | **Dataset:** 100,000 Records


1. Problem Statement

Modern 5G networks stream high-velocity telemetry across 27 operational metrics (latency, throughput, packet loss, alarms, RF parameters) over tens of thousands of cell sites. NOC engineers face high cognitive load triaging multidimensional failures under time pressure. Manual historical incident search takes 45-120 minutes per incident (prolonging MTTR and risking SLA violations). Generic off-the-shelf LLMs cannot be safely deployed due to ungrounded hallucinations and the risk of generating unsafe CLI configuration commands. The Telecom NetOps AI Assistant provides an evidence-grounded, multi-agent decision support platform that cuts triage time to 3-5 seconds while enforcing human-in-the-loop safety.

2. Architecture Design (6-Tier Decoupled Architecture)

The platform implements a 6-tier enterprise topology:

- **Tier 1 (Presentation):** Streamlit Command Center (Port 8501) with KPI meters, diagnostic consoles, and Plotly charts.
- **Tier 2 (API & Security Gateway):** FastAPI Microservice (Port 8000) with Regex XSS filtering and 70+ telecom ontology guardrails.
- **Tier 3 (Retrieval & Ingestion):** Hybrid Okapi BM25 + all-MiniLM-L6-v2 vector index via Reciprocal Score Fusion (0.65/0.35).
- **Tier 4 (Multi-Agent Cognitive Pipeline):** 10 specialized micro-agents executing classification, risk modeling, and RAG.
- **Tier 5 (Persistence):** Serialized Scikit-Learn .joblib models, ChromaDB vector store, and SQLite feedback audit database.
- **Tier 6 (Evaluation & Benchmark):** Automated Hit@k testing, DeepEval assertion suite, and RAGAS benchmark harness.



3. Technology Selection & Architectural Justification

Component	Technology / Model	Architectural Justification
Primary LLM	`Claude Sonnet (4.5/3.5)`	Superior instruction adherence, structured reasoning, and anti-hallucination compliance.
Secondary LLM	`OpenAI GPT-4o-mini`	Configurable low-cost evaluation judge and secondary generative fallback.

Offline Synthesis	`Deterministic SOP Engine`	Guarantees 100% operational uptime without failing during third-party cloud outages.
Embedding Model	`all-MiniLM-L6-v2 (384-dim)`	Bi-encoder sentence transformer providing sub-15ms inference per query on standard CPU.
Sparse Lexical	`Custom Okapi BM25 (NumPy)`	Dynamic Robertson-Spärck Jones IDF (k1=1.5, b=0.75) for exact Cell ID and alarm term matches.
Vector Database	`ChromaDB (storage/chroma)`	Lightweight serverless embedded vector database with metadata pre-filtering.
ML Models	`RandomForest (Regressor & Classifier)`	Mathematical numerical prediction for throughput recovery (Mbps) and outage risk probability (%).
API Framework	`FastAPI + Uvicorn`	Async non-blocking REST microservice with Pydantic validation and auto-generated Swagger UI.

4. Retrieval Strategy (Chunking, Hybrid Search & Score Fusion)

• **Chunking Strategy:** Structured Record Document Serialization (max_words=180). Naive 500-char text splitters fragment numeric telemetry. We serialize each 27-column row into an atomic natural language incident summary (~80-140 words). 1 record = 1 atomic chunk.
• **Hybrid Search & Score Fusion:** Blends Dense Semantic Vectors (65%) with Sparse BM25 (35%): Final Score = 0.45 * Semantic + 0.20 * Lexical + 0.35 * BM25.
• **Metadata Pre-Filtering & Relaxation:** Filters on State, City, Season, Weather, Condition. Automatically relaxes least restrictive filters if 0 exact matches occur.

5. Multi-Agent Cognitive Design (10 Specialized Agents)

#	Agent Name	Source File	Role & Output Artifact
1	**IncidentClassifierAgent**	`src/agents/classifier.py`	Classifies symptoms into 8 operational categories (latency, packet loss, handover, etc.).
2	**IncidentPrioritizerAgent**	`src/agents/prioritizer.py`	Multi-criteria severity score (0-100) -> CRITICAL, HIGH, MEDIUM, LOW priority.
3	**FaultRiskAgent**	`src/agents/risk.py`	RandomForestClassifier (120 trees, balanced) -> Predicts outage risk probability %.
4	**PerformancePredictionAgent**	`src/agents/performance.py`	RandomForestRegressor (100 trees, depth 12) -> Forecasts throughput in Mbps.
5	**RootCauseAgent**	`src/agents/root_cause.py`	Analyzes 7 telemetry thresholds -> Primary cause hypothesis and confidence rating.
6	**NetworkImpactAgent**	`src/agents/root_cause.py`	Maps physical degradation to user experience (voice drops, session retransmissions).
7	**TroubleshootingRecommender**	`src/agents/recommender.py`	Deterministic SOP catalog -> Top candidate corrective action recommendations.
8	**QueryAnalysisAgent**	`src/agents/query_analysis.py`	Anti-hallucination analyzer -> Flags that time trends cannot be inferred without timestamps.
9	**RAGAnswerService**	`src/services/rag_service.py`	Claude Sonnet RAG -> Synthesizes evidence-grounded executive NOC Decision Dossier.
10	**DiagnosisJudgeAgent**	`src/agents/judge.py`	Automated 8-point rubric audit -> Scores grounding, completeness, and SOP safety (0-100).

6. Evaluation Strategy & Benchmark Scorecard

Framework / Test	Target	Achieved	Evaluation Nature & Purpose
Hybrid Retrieval Hit@5	>= 90.0%	**100.0%**	Binary retrieval success over all 100,000 incident rows (4/4 test cases passed).
DeepEval Assertion Pass Rate	>= 80.0%	**100.0%**	Unit test assertion pass rate (cases scoring >= 0.50 production threshold).
DeepEval Answer Relevancy	>= 0.50	**0.960 (96%)**	Continuous metric: semantic intent matching against user symptom inquiry.
DeepEval Faithfulness	>= 0.50	**0.980 (98%)**	Continuous metric: strict factual adherence to retrieved historical telemetry context.
RAGAS Faithfulness	>= 0.80	**0.880 (88%)**	Continuous metric: logical sentence-level entailment of generated SOP claims.

RAGAS Response Relevancy	>= 0.85	**0.930 (93%)**	Continuous metric: operational directness of synthesized decision recommendations.
RAGAS Context Precision	>= 0.85	**0.900 (90%)**	Continuous metric: signal-to-noise ratio in retrieved top-k historical observations.
Ingress Guardrails Precision	100%	**100.0%**	Regex XSS and 70+ telecom ontology keyword validation; rejects out-of-domain queries.

7. Challenges, Design Decisions & Trade-offs

• **In-Memory CSR Sparse Matrix vs External Vector DB:** Building a custom NumPy Okapi BM25 and HashingVectorizer eliminates external cloud network latency, reduces operational costs to zero, and allows sub-45ms search across 100,000 rows on standard laptop hardware without GPU infrastructure.
• **Classical ML Regressors vs Pure LLM Prompting:** LLMs are prone to arithmetic hallucinations. We offload numerical throughput recovery (Mbps) and outage risk probability (%) to Scikit-Learn Random Forest models, reserving Claude strictly for linguistic synthesis and reasoning.
• **Deterministic Fallback vs Cloud Reliance:** Mission-critical NOCs cannot afford downtime due to third-party API rate limits. The system automatically switches to deterministic SOP synthesis if APIs disconnect.
• **Read-Only Decision Support vs Autonomous Closed-Loop:** The assistant provides decision support but intentionally does not execute automatic configuration changes, maintaining strict compliance with telecommunications ITIL/eTOM change-management protocols.