Question 6 doesn't show the whole answer so I have it here:
ctor 1
ctor 2
middle
dtor 2
dtor 1

The text boxes for the short answers have a letter limit, so my answers will be here:

9. What happens if a class owns a heap array but has no destructor? What happens if it has a destructor but no copy constructor?:

If there is a heap array, but no destructor, then there will be a memory leak. If there is a destructor, but no copy constructor, then there will be a double free error.

10. What does the assignment operator need to do differently from the copy constructor? Why is the self-assignment check necessary?:

The copy operator simply has the new variable equal the old data slowly. When the assignment operator is used, it checks to see if the variables are the same, deletes the old data, and assigns the old data to the new variable. The assignment operator must use existing memory instead of using new, unutilized, memory. If the self assignment check wasn't done, then it could delete the data it is trying to reassign before it actually reassigns it.

11. Explain why a Queue needs two pointers (head_ and tail_) while a Stack only needs one (top_).

A queue has items taken from the top & added to the bottom, while a stack has items taken from & added on to the top. Thus, the queue must be able to go both directions on the node list, while the stack only needs to reach the "next" or "top" node in order to take things off or put them back on.

12. A Queue contains {10, 20, 30} (10 at head). dequeue() is called, then enqueue(99). What does front() return? Draw or describe the queue state.

Front() returns "20". At first the queue looks like 10, 20, 30. Then, 10 is removed from the top, and 99 is added to the bottom. The queue should look like 20, 30, 99 with 99 pointing to 30, 30 pointing to 20, and 20 having a null pointer.