

A detailed close-up photograph of a computer motherboard. The image shows various components including blue plastic connectors, yellow plastic connectors, and a large blue heat sink. The motherboard itself is black with visible circuitry and components like capacitors. The lighting is bright, highlighting the textures and colors of the hardware.


# Lecture Operating System

## **13. The Abstraction: Address Space**



# 13. Address Space

- 1. The Abstraction**
- 2. Physical Memory**
- 3. Address Space**
- 4. Virtual Address**



# Memory Virtualization

## ■ What is memory virtualization?


- OS virtualizes its physical memory.
- OS provides an illusion memory space per each process.
- It seems to be seen like each process uses the whole memory.

## ■ Benefit of Memory Virtualization:

- Ease of use in programming
- Memory efficiency in terms of times and space
- The guarantee of isolation for processes as well as OS
- Protection from errant accesses of other processes


# OS in The Early System

- Load only one process in memory.
  - Poor utilization and efficiency




# Multiprogramming and Time Sharing

- **Load multiple processes** in memory.
  - Execute one for a short while.
  - Switch processes between them in memory.
  - Increase utilization and efficiency.
- Cause an important **protection issue**.
  - Errant memory accesses from other processes



# Address Space per Process

- OS creates an **abstraction** of physical memory.
  - The address space contains all about a running process.
  - That is consist of program code, heap, stack and etc.
- Address space has static and dynamic components
  - *Static*: Code and some global variables
  - *Dynamic*: Stack and Heap



# Address Space per Process

### ■ Code


- Where instructions live

### ■ Heap

- Dynamically allocate memory.
  - `malloc` in C language
  - `new` in object-oriented language

### ■ Stack

- Store return addresses or values.
- Contain local variables arguments to routines.



# Motivation for Dynamic Memory

- Do **not know** amount of memory needed **at compile time**
- Must be **pessimistic** when allocate **memory statically**
  - Allocate enough for worst possible case; Storage is used inefficiently
- **Recursive** procedures:
  - Do not know how many times procedure will be nested
- **Complex data** structures: lists and trees
  - `struct my_t *p = (struct my_t *)malloc(sizeof(struct my_t));`
- → Two types of dynamic allocation:
  - **Stack** and **Heap**



# Stack Organization

- Definition: Memory is freed in opposite order from allocation
- Simple and efficient implementation:
  - Pointer separates allocated and freed space
    - Allocate: Increment pointer
    - Free: Decrement pointer
- No fragmentation
- OS uses stack for procedure call frames (local variables and parameters)

```
alloc(A);  
alloc(B);  
alloc(C);  
free(C);  
alloc(D);  
free(D);  
free(B);  
free(A);
```

```
main() {  
    int A = 0;  
    foo(A);  
    printf("A: %d\n", A);  
}  
  
void foo(int Z) {  
    int A = 2;  
    Z = 5;  
    printf("A : % d Z : % d\n", A, Z);  
}
```

# Heap Organization

- Definition: Allocate from any random location:
  - `malloc()`, `new()`
- Heap memory consists of allocated areas and free areas (holes)
  - Order of allocation and free is unpredictable



# Heap Organization (Cont.)

- Advantage
  - Works for all data structures
- Disadvantages
  - Allocation can be slow
  - End up with small chunks of free space - fragmentation
  - Where to allocate 12 bytes? 16 bytes? 24 bytes?
- What is OS's role in managing heap?
  - OS gives big chunk of free memory to process; library manages individual allocations

# Quiz: Match that Address Location

```
int x;  
  
main() {  
    int y;  
    int *z = malloc(sizeof(int));  
}
```

| Address | Location            |
|---------|---------------------|
| x       | Static data -> Code |
| main    | Code                |
| y       | Stack               |
| z       | Stack               |
| *z      | Heap                |

# Virtual Address

- Every address in a running program is virtual.
- OS translates the virtual address to physical address

addresses.c

```
#include <stdio.h>
#include <stdlib.h>

int main(int argc, char *argv[]){

    printf("location of code : %p\n", (void *) main);
    printf("location of heap : %p\n", (void *) malloc(1));
    int x = 3;
    printf("location of stack : %p\n", (void *) &x);


    return x;
}
```



# Virtual Address


- The output in 64-bit Linux machine

```
prompt> ./addresses
location of code : 0x40057d
location of heap : 0xcf2010
location of stack : 0x7fff9ca45fcc
```




# Virtual Address (Cont.)

- Code + Data
  - Usually starts at 0x400000
    - Rust uses `-fPIE` (position independent executable) linker flag: executable is mapped to random address
- Heap & Stack: continuous block
- Memory Mapping Segment
  - Several blocks
  - Not continuous!
- ASLR: Random offsets to increase security



# User Space and Kernel Space



- In theory 64 bit
  - 16 ExaBytes
- Today: 48 bit
  - Canonical form
  - 256 TB
- Separated between
  - User Space
  - Kernel Space

A detailed close-up photograph of a computer motherboard. The image shows various components including blue heat sinks, yellow RAM modules, and blue SATA connectors. The motherboard is black with visible circuitry and components like capacitors. The lighting is bright, highlighting the textures and colors of the hardware.

# Thanks

## Questions?