


Locality Optimization for traversal-based Queries on Graph Databases

Fabian Klopfer

Databases and Information Systems Group
Department of Computer and Information Science
University of Konstanz, 30.04.2021

Graphs




Data Structures I

Two essential record structures:


1. Node records
2. Relationship records

Inspired by Neo4J [1], [2].


Data Structures II




Data Structures III



Data Structures – Example




1 Introduction




Example Query

Show me all people that Bob knows:



⇒ Scanning and filtering read sequential.

⇒ Expand does not necessarily.



Motivation

- Expand's access pattern depends on the query, record and incidence list order.
- When these factors are not considered, access is random.

Potentially leads to

- ⇒ hard-to-predict access patterns.
- ⇒ cache & prefetch misses, thrashing and pollution.
- ⇒ inadequate page eviction behavior.

Traversals rely primarily on `expand`!

Locality I

- “memory references tend to be localized in time and space” [3].
- Tendency to access nearby memory locations based on previous accesses [4].
- Enables usage of memory hierarchy.

⇒ The more localized the access the less IO ops are necessary [5].

Locality II

Temporal locality based on blocks

$$P(X_{t+\Delta} = B | X_t = B)$$

Spatial locality in the same sense

$$P(X_{t+\Delta} = B \pm \varepsilon | X_t = B)$$

with $\varepsilon = \lceil \frac{p}{b} \rceil$ [5].

Problem Definition


Given a graph G , logical block size b , page size p .

Desired is

1. A partition of G into blocks of size b ,
2. permutations π_v, π_e of the blocks,

such that locality is as high as possible for traversal-based queries.

Example: Block Formation and Order




node.db	0, 5, 7	1, 4, 9	2, 6, 8	3		
edge.db	a, f	b, g	c, h	d, i	e, j	k

node.db	7, 8, 9	0, 1, 3	2, 4, 5	6		
edge.db	f, h	g, k	i, j	a, b	c, d	e

Record Layout Methods: Overview

- Existing methods
 - G-Store [6]
 - ICBL [7]
- Our approach
 - Community detection — Louvain method [8].
 - Incidence list reordering

G-Store I




G-Store II


1. Coarsening: Heavy-Edge Matching [9]
2. Turn-around
3. Uncoarsening
 - 3.1 Project
 - 3.2 Reorder
 - 3.3 Refine

$$\min \sum_{(u,v) \in E} |\phi(u) - \phi(v)|$$

G-Store III




ICBL I



ICBL II

- I Feature extraction: Do t random walks [10] of length l .
- C Coarse clustering: Adapted K-Means [11].
- B Block Formation: Agglomerative hierarchical clustering [12].
- L Layout Blocks: Sort blocks and subgraphs

Louvain Method I




Louvain Method II

1. Initialize all nodes in singleton community.
2. Merge community into a neighboring community where modularity gain is maximal, until modularity gain is below threshold.
3. Construct new graph from aggregated communities and go to 1.




$$\frac{1}{2m} \sum_{u,v \in V} \left(w_{(u,v)} - \frac{w_u w_v}{2m} \right) \cdot \delta(c_u, c_v)$$

Incidence List Rearrangement



Setup I

- Queries: BFS, DFS, Dijkstra, A*, ALT.



Setup II



- Datasets: [131, 1'134'890] nodes, [764, 2'987'624] edges, average degree [2.6, 25.5]
- Domains include biological neural net, e-mails, co-authors, frequent item sets, video channel subscriptions [13].

Setup III



- Simulate IOs using in-memory access layer, queries and record IDs.
- $\text{Block no.} = \text{record ID} \cdot \text{sizeof}(\text{record struct}) / \text{block size}$
- Consecutive accesses to same block require no IO op.
- All other accesses count as one IO op.

1. Import dataset.
2. Run query and log IDs of accessed nodes and relationships.
3. Calculate sequence of block no. from sequence of IDs.
4. Calculate sequence of page no. from sequence of block no.



Results I




Results II



Results III



Results IV



Summary

- Static rearrangement methods increase locality.
⇒ decrease number of block accesses
- The order of blocks is important for spatial locality
- Sorting the incidence lists leads to more sequential access sequences.
- Results differ between queries

Future Work

- Leiden [14] instead of Louvain
- RCM-based [15] rearrangement
- Dynamic Rearrangement
 - Query-based
 - History-based

7 References

- [1] M. A. Rodriguez and P. Neubauer, "Constructions from Dots and Lines", *ArXiv*, vol. abs/1006.2361, 2010.
- [2] I. Robinson, J. Webber, and E. Eifrem, *Graph databases: new opportunities for connected data*. "O'Reilly Media, Inc.", 2015.
- [3] B. Jacob, D. Wang, and S. Ng, *Memory systems: cache, DRAM, disk*. Morgan Kaufmann, 2010.
- [4] P. J. Denning, "The locality principle", in *Communication Networks And Computer Systems: A Tribute to Professor Erol Gelenbe*, World Scientific, 2006, pp. 43–67.
- [5] S. Gupta, P. Xiang, Y. Yang, and H. Zhou, "Locality principle revisited: A probability-based quantitative approach", *Journal of Parallel and Distributed Computing*, vol. 73, no. 7, pp. 1011–1027, 2013.
- [6] R. Steinhaus, D. Olteanu, and T. Furche, "G-Store: a storage manager for graph data", Ph.D. dissertation, University of Oxford, 2010.
- [7] A. Yaşar, B. Gedik, and H. Ferhatosmanoğlu, "Distributed block formation and layout for disk-based management of large-scale graphs", *Distributed and Parallel Databases*, vol. 35, no. 1, pp. 23–53, 2017.
- [8] V. D. Blondel, J.-L. Guillaume, R. Lambiotte, and E. Lefebvre, "Fast unfolding of communities in large networks", *Journal of statistical mechanics: theory and experiment*, vol. 2008, no. 10, P10008, 2008.
- [9] G. Karypis and V. Kumar, "A Fast and High Quality Multilevel Scheme for Partitioning Irregular Graphs", *SIAM Journal on Scientific Computing*, vol. 20, no. 1, pp. 359–392, 1998. DOI: 10.1137/S1064827595287997. eprint: <https://doi.org/10.1137/S1064827595287997>. [Online]. Available: <https://doi.org/10.1137/S1064827595287997>.
- [10] F. Fouss, A. Pirotte, J.-M. Renders, and M. Saerens, "Random-walk computation of similarities between nodes of a graph with application to collaborative recommendation", *IEEE Transactions on knowledge and data engineering*, vol. 19, no. 3, pp. 355–369, 2007.
- [11] S. Lloyd, "Least squares quantization in PCM", *IEEE transactions on information theory*, vol. 28, no. 2, pp. 129–137, 1982.
- [12] P. H. A. Sneath, "The Application of Computers to Taxonomy", *Microbiology*, vol. 17, no. 1, pp. 201–226, 1957, ISSN: 1350-0872. DOI: <https://doi.org/10.1099/00221287-17-1-201>. [Online]. Available: <https://www.microbiologyresearch.org/content/journal/micro/10.1099/00221287-17-1-201>.
- [13] J. Leskovec and A. Krevl, *SNAP Datasets: Stanford Large Network Dataset Collection*, <http://snap.stanford.edu/data>, Jun. 2014.
- [14] V. A. Traag, L. Waltman, and N. J. Van Eck, "From Louvain to Leiden: guaranteeing well-connected communities", *Scientific reports*, vol. 9, no. 1, pp. 1–12, 2019.
- [15] E. Cuthill and J. McKee, "Reducing the bandwidth of sparse symmetric matrices", in *ACM '69*, 1969.
- [16] J. Gross and J. Yellen, "Graph Theory and Its Applications", 1998.
- [17] P. E. Hart, N. J. Nilsson, and B. Raphael, "A formal basis for the heuristic determination of minimum cost paths", *IEEE transactions on Systems Science and Cybernetics*, vol. 4, no. 2, pp. 100–107, 1968.
- [18] A. V. Goldberg and C. Harrelson, "Computing the shortest path: A search meets graph theory.", in *SODA*, Citeseer, vol. 5, 2005, pp. 156–165.
- [19] M. Dewey, *Decimal Classification and Relative Index for Libraries: Clippings, Notes, Etc.* Library bureau, 1894.
- [20] R. Ramakrishnan and J. Gehrke, *Database Management Systems*. McGraw-Hill, 2000.
- [21] J. Hölisch and M. Grossniklaus, "An Algebra and Equivalences to Transform Graph Patterns in Neo4j", in *Proceedings of the Workshops of the EDBT/ICDT 2016 Joint Conference (EDBT/ICDT 2016)*, T. Palpanas and K. Stefanidis, Eds., ser. CEUR Workshop Proceedings, 2016. [Online]. Available: <http://ceur-ws.org/Vol-1558/paper24.pdf>.
- [22] M. R. Garey, D. S. Johnson, and L. Stockmeyer, "Some simplified NP-complete problems", in *Proceedings of the sixth annual ACM symposium on Theory of computing*, 1974, pp. 47–63.
- [23] P. Jaccard, "The distribution of the flora in the alpine zone. 1", *New phytologist*, vol. 11, no. 2, pp. 37–50, 1912.