

Minimization of Weighted Automata

Fabian Klopfer

Modelling of Complex Self-Organizing Systems Group, 12.06.2020

Introduction

In the last presentation . . .

- two models for stochastic dynamical systems were considered:
Weighted Automata (WA) and Differential Equations (DE)
- an example for modelling a CRN's dynamics in both models was given:
 - DE Solving Chemical Master Equation
 - WA Monte Carlo CTMC

Goals specified

1. Implement minimization algorithm for weighted automata [1]. ✓
2. Implement model reduction algorithm for ODEs [2].
3. Develop reproducible benchmarks
4. Write report including

What has been done so far

- Software Requirement Specification & Software Design Document
- Random Basis Minimal WA Construction Algorithm by Kiefer/Schützenberger [1]
- Execution of example by Matlab script and hand
- Implementation of minimization & equivalence algorithm, interfaces, TUI, CLI, tests

The Weighted Automaton Minimization Algorithm I

Weighted Automaton $A = (n, \Sigma, \alpha, \mu, \eta)$, where

- n the number of states
- Σ the input alphabet
- α the initial vector with a non-zero value for all starting states
- μ the set of transition matrices, one per input character
- η the final vector with non-zero values for all ending states

Author claims $\mathcal{O}(\log^2 n)$ runtime, but this is not correct as we will see later In the following slide we use the notion of a forward reduction, but the backwards reduction is analogous besides minor variations

The Weighted Automaton Minimization Algorithm II

- Find a basis F of the prefix space using random vectors r_i
 - Add the vectors of all prefix words up to length n together and multiply this vector by n different factors yielding $\{v_1, \dots, v_n\}$
 - Factors are derived by random vectors and structure of prefixes
 - Base is then the maximally linear independent subset of $\{\alpha, v_1, \dots, v_n\}$
- Use basis to do Schützenberger Construction [3]: $\vec{A} = (\vec{n}, \Sigma, \vec{\alpha}, \vec{\mu}, \vec{\eta})$ With
 - $\vec{\mu} = \vec{F} \mu \vec{F}^{-1}$
 - $\vec{\alpha} = e_1$
 - $\vec{\eta} = \vec{F} \eta$
 - $\vec{n} = \text{rank}(\vec{\mu})$

The Weighted Automaton Minimization Algorithm: Pseudo Code

b

The Weighted Automaton Minimization Algorithm: Example

C




Implementation Details

d

Up Next

e

Bibliography

-  S. Kiefer, A. S. Murawski, J. Ouaknine, B. Wachter, and J. Worrell, “On the complexity of equivalence and minimisation for q-weighted automata”, *Logical Methods in Computer Science*, vol. 9, 2013.
-  L. Cardelli, M. Tribastone, M. Tschaikowski, and A. Vandin, “Maximal aggregation of polynomial dynamical systems”, *Proceedings of the National Academy of Sciences of the United States of America*, vol. 114 38, pp. 10 029–10 034, 2017.
-  M. P. Schützenberger, “On the definition of a family of automata”, *Information and control*, vol. 4, no. 2-3, pp. 245–270, 1961.