

PLASMA CUT 200

IGBT INVERTER AIR PLASMA CUTTING MACHINE



POWERFUL PERFORMANCE

Clean, fast and precise cutting with 100% arc striking success.



IGBT INVERTER TECHNOLOGY

Advanced IGBT inverter technology ensures stable arc, high efficiency and energy saving.



BUILT TO LAST

Robust design with high duty cycle for long hours of continuous operation in tough conditions.



WIDE APPLICATION

Ideal for CNC & automated cutting in fabrication, manufacturing and maintenance applications.



HIGH FREQUENCY
ARC START



SMOOTH & STABLE
ARC PERFORMANCE



HIGH DUTY CYCLE
FOR HEAVY USE



PRECISE CUTTING
CLEAN EDGE



ENERGY EFFICIENT
& RELIABLE



CNC COMPATIBLE
SIGNAL OUTPUT

IDEAL FOR

-  Fabrication Shops
-  Metal Workshops
-  Automotive Industry
-  CNC & Automation
-  Construction Industry
-  Ship Building & Heavy Fabrication

PLASMA CUT 200

SMART CUTTING. STRONG PERFORMANCE.

PRODUCT OVERVIEW

Plasma Cut 200 is a high performance IGBT inverter based air plasma cutting machine designed for precision cutting with speed and reliability. It produces a stable arc with clean cut quality even under heavy industrial conditions. Compact, durable and service friendly, it is the ideal solution for modern fabrication and automation needs.

KEY FEATURES

- ✓ Designed for plasma arc cutting of medium air.
- ✓ Suitable for cutting a wide range of metals including stainless steel, carbon steel, cast iron, copper, aluminium, manganese & titanium.
- ✓ Built-in high frequency, soft-switching IGBT technology for stable and efficient performance.
- ✓ Excellent power source control system with fast response speed.
- ✓ Wide grid voltage adaptability with stable plasma arc combustion.
- ✓ 100% arc striking success rate.
- ✓ High duty cycle for long time operation at maximum cutting.
- ✓ Compact, durable and service friendly design. Ideal for fabrication, manufacturing, maintenance and on-site cutting jobs.

TECHNICAL PARAMETERS

PARAMETER	PLASMA CUT 200
Voltage (V)	3P 380V ± 15%
Frequency (Hz)	50/60
Rated Input Capacity (Kva)	47
Rated Input Current (A)	63
Power Factor	0.89
Rated Output Current (A)	200
Rated Output Voltage (V)	150
Rated Duty Cycle (%)	100
Output Floating Voltage (V)	340
Output Current Range (A)	30 – 200
Plasma Gas Usage	Compressed Air

PARAMETER	PLASMA CUT 200
Working Gas Pressure Scope (Mpa)	0.45 – 0.55
Efficiency (%)	90
Insulation Class	F
Shell Protection Degree	IP21S
Torch Cooling	Water / Air Cooling
Arc Striking Mode	High Frequency Arc Striking
Weight (Kg)	75
Dimensions (Mm)	825 x 350 x 735

CUTTING CAPACITY

CUTTING CAPACITY	MILD STEEL (MS)	STAINLESS STEEL (SS)	ALUMINIUM (AL)
CLEAN CUT	38 – 42 mm	25 – 32 mm	33 – 38 mm
MAXIMUM PERFORATION	25 – 30 mm	15 – 20 mm	20 – 23 mm

APPLICATIONS



WHY BUY FROM ANU ARC GROUP OF BUSINESSES?

					
AUTHORISED DEALER & SERVICE SUPPORT	QUALITY ASSURED PRODUCTS	EXPERT TECHNICAL GUIDANCE	SPARES SERVICE AVAILABILITY	SKILLFUL SERVICE & SUPPORT	BEST VALUE FOR MONEY
Genuine products with manufacturer backed support.	100% genuine products with warranty support.	Right solutions for your cutting requirements.	Ready availability of spares to minimise downtime.	Quick response, fast support & prompt service.	Reliable performance at the right price point.

ANU ARC SALES AND SERVICES

- PRINCIPAL OFFICE**
Nigadi, Pune, Maharashtra
- BRANCH OFFICE**
Sukhaliya, Indore, Madhya Pradesh
- +91 9425317265
+91 9425066259
office@anuarc.in
www.anuarc.in

FOLLOW US & REVIEW US



Reviews ★★★★★