

```

-- Set operators:-
-- set operators are used to combine the results of two or more select
-- queries

-- In MySQL the main set operators are
-- 1) UNION
-- 2) UNION all
-- 3) Intersect(MySQL --> version 8.0.31+)
-- 3) Except(MySQL --> version 8.0.31+)

-- 1)Union :-
-- union combines results of two queries and removes duplicates.
-- syntax :-
/* select coulumn_list from table1
union
select column_list from table2;
*/
-- rules:-
-- same numbers of columns in all the tables
-- same order of columns
-- compatible data types.

-- 2) Union all
-- combines results but keeps duplicates
/* select coulumn_list from table1
union all
select column_list from table2;
*/
-- rules:-
-- same numbers of columns in all the tables
-- same order of columns
-- compatible data types.

-- difference between union and union all is that union all keeps all the
-- duplicate values, plus union all is faster than union.

-- 3) Intersect:-
-- returns only commonn rows between two queries
select * from cricket_team
intersect
select * from footaball_team;

-- 4) Except:-
-- Returns rows from first query not present in second query
select * from footaball_team
except
select * from cricket_team;

```

```
create database if not exists set_operators_demo;
use set_operators_demo;
create table students(student_id int primary key auto_increment,
name varchar(225) not null,
city varchar(225)) auto_increment = 101;

create table cricket_team(student_id int, name varchar(225), city varchar(225));

create table footaball_team(student_id int, name varchar(225), city varchar(225));

select * from students;
select * from cricket_team;
select * from footaball_team;

select student_id, name,city from cricket_team as sports_students
union
select * from footaball_team;

select * from cricket_team
union all
select * from footaball_team;

create table demo1 (d1 int, d2 varchar(225));
create table demo2 (d2 varchar(225), d1 int);

insert into demo1 values(1,"a"),(2,"b"),(3,"c");
insert into demo2 values("d",1),("a",4),("c",3);

select * from demo1;
select * from demo2;

select d1,d2 from demo1
union
select d1,d2 from demo2;
```