

```

#include<iostream.h>
#include<conio.h>
#define max 3
class Queue
{
    int a[max],front,rare,x;
public:
    Queue()
    {front=-1;
     rare=-1;
    }
    void insert();
    void deletee();
    void display();
};
void Queue::insert()
{
    if(rare==max-1)
    {
        cout<<"\n queue overflow";
    }
    else
    {cout<<"enter element";
     cin>>x;
     if(rare==max-1)
     {
         front=0;
         rare=0;
     }
     else
     {
         rare++;
         a[rare]=x;
     }
    }
}
void Queue::deletee()
{
    if(front==max-1)
    {
        cout<<"queue overflow";
    }
    else
    {
        x=a[front];
        if(front==rare)
        { front=-1;
          rare=-1;
        }
        else
        {front++;
        }
        cout<<"delete items="<<x;
    }
}
void Queue::display()
{
    if(front==max-1)
    {

```

```

        cout<<"queue has no element";
    }
else
{
    for(int i=front;i<rare;i++)
    {
        cout<<a[i]<<endl;
    }
}
}
void main()
{ clrscr();
  Queue b;
  int choice;
  char c;
  do{ cout<<"\n 1.insert 2.delete 3.display";
      cin>> choice;
      switch(choice)
      {
          case 1:
              b.insert();
              break;
          case 2:
              b.deletee();
              break;
          case 3:
              b.display();
              break;
      }
      cout<<"do you want to enter again?";
      c=getch();
  } while(c=='y' || c=='Y');
      getch();
}

```

DOSBox 0.74, Cpu speed: max 100% cycles, Frameskip 0, Progr...

```

1.insert 2.delete 3.display
enter element12
do you want to enter again?
1.insert 2.delete 3.display
enter element14
do you want to enter again?
1.insert 2.delete 3.display
enter element15
do you want to enter again?
1.insert 2.delete 3.display
delete items=-14do you want to enter again?
1.insert 2.delete 3.display
14
do you want to enter again?

```