



# 데이터 가드 구현

소유자	쏘니
태그	
다중 선택	



## 데이터 가드 구현

- Primary DB : 나의 영문 이니셜 DB(SHM DB)
- Standby DB : sbdb2

## primary db 구성 - 영문 이니셜 DB

1. 오라클 접속을 위한 환경 변수가 들어있는 .bash\_profile을 수정한다.

```
# ORACLE_SID 가 PROD로 되어있기 때문에 shm 으로 변경하기

[shm:~]$ vi .bash_profile
-----
:s/PROD/shm/g
-----
[shm:~]$ source .bash_profile
```

- 변경 전



```

# .bash_profile

# Get the aliases and functions
if [ -f ~/.bashrc ]; then
    . ~/.bashrc
fi

# User specific environment and startup programs

PATH=$PATH:$HOME/bin

export PATH
export JAVA_HOME=/usr/java/jdk1.6.0_18
export PATH=$JAVA_HOME/bin:$PATH
export PS1=['echo $ORACLE_SID':\w]$ '

export ORACLE_BASE=/u01/app/oracle
export ORACLE_SID=shm
export ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1
export PATH=$ORACLE_HOME/bin:$PATH
export GRID_HOME=/u01/app/oracle/product/11.2.0/grid
unset LANG
export LANG=ko_KR.UTF-8

echo /u01/app/oracle/product/11.2.0/dbhome_1 > x

alias alert='cd /u01/app/oracle/diag/rdbms/orcl/orcl/trace'
alias net='cd $ORACLE_HOME/network/admin'
alias ss='sqlplus / as sysdba'
alias scott='sqlplus scott/tiger'
alias dbs='cd $ORACLE_HOME/dbs'
alias oradata='cd /u01/app/oracle/oradata/shm/'
alias rnc='rman target sys/oracle nocatalog'

NLS_LANG=american_america.we8iso8859p15
NLS_DATE_FORMAT='RRRR/MM/DD:HH24:MI:SS'
export NLS_LANG
export NLS_DATE_FORMAT

```

2. DB를 생성할 디렉토리를 생성한다.

```

[shm:~]$ mkdir -p /u01/app/oracle/oradata/shm
[shm:~]$
[shm:~]$ ls -ld /u01/app/oracle/oradata/shm
drwxr-xr-x 2 oracle oinstall 4096  3월 14 16:50 /u01/app/oracle/oradata/shm
[shm:~]$
[shm:~]$ cd /u01/app/oracle/oradata/shm
[shm:shm]$
[shm:shm]$ mkdir disk1 disk2 disk3 disk4 disk5
[shm:shm]$
[shm:shm]$ ls
disk1  disk2  disk3  disk4  disk5

```

```
[shm:~]$ mkdir -p /u01/app/oracle/oradata/shm
[shm:~]$
[shm:~]$ ls -ld /u01/app/oracle/oradata/shm
drwxr-xr-x 2 oracle oinstall 4096 3월 14 16:50 /u01/app/oracle/oradata/shm
[shm:~]$
[shm:~]$ cd /u01/app/oracle/oradata/shm
[shm:shm]$
[shm:shm]$ mkdir disk1 disk2 disk3 disk4 disk5
[shm:shm]$
[shm:shm]$ ls
disk1 disk2 disk3 disk4 disk5
```

### 3. parameter file 을 만든다.

a. parameter file을 생성해야 nomount 단계로 올라갈 수 있다.

```
#1. parameter file이 있는 위치로 이동하여,
-- spfilesbm.ora와 initshm.ora가 없는지 확인(있으면 rm으로 지워버리기)
[shm:shm]$ cd $ORACLE_HOME/dbs
[shm:dbs]$
[shm:dbs]$ pwd
/u01/app/oracle/product/11.2.0/dbhome_1/dbs
[shm:dbs]$
[shm:dbs]$ ls
arch1_7_1163599733.dbf hc_DBUA0.dat hc_shm.dat initSBDB.ora orapwSBDB
arch1_8_1163599733.dbf hc_PROD.dat hc_shm2.dat lkPROD parameter.sql
arch1_9_1163599733.dbf hc_SBDB.dat init.ora lkSBDB peshm_DBUA0_0
demobld.sql hc_orcl.dat initPROD.ora orapwPROD peshm_DUMMY_0
```

#2. 없으면 parameter file (pfile) 생성해주기

```
[shm:dbs]$
vi $ORACLE_HOME/dbs/initshm.ora

-----아래 내용 넣기-----
db_name = shm
compatible=11.2.0.1.0

sga_target = 256M

undo_management = AUTO
undo_tablespace = UNDOTBS

processes = 100

remote_login_passwordfile = EXCLUSIVE

control_files = (/u01/app/oracle/oradata/shm/disk1/ctrl1.ctl ,
                /u01/app/oracle/oradata/shm/disk2/ctrl2.ctl ,
                /u01/app/oracle/oradata/shm/disk3/ctrl3.ctl)

                /u01/app/oracle/flash_recovery_area/ctl4.ctl )
-> 이걸 만들어 두면 나중에 불편하기 때문에 지워버림
```

#3. cat으로 initshm.ora 내용 출력하여 내용이 잘 들어갔는지 확인

```
[shm:dbs]$ cat $ORACLE_HOME/dbs/initshm.ora
```

```
db_name = shm
```

```
compatible=11.2.0.1.0
```

```
sga_target = 256M
```

```
undo_management = AUTO
```

```
undo_tablespace = UNDOTBS
```

```
processes = 100
```

```
remote_login_passwordfile = EXCLUSIVE
```

```
control_files = (/u01/app/oracle/oradata/shm/disk1/ctrl1.ctl ,  
                /u01/app/oracle/oradata/shm/disk2/ctrl2.ctl ,  
                /u01/app/oracle/oradata/shm/disk3/ctrl3.ctl)
```

```
[shm:~]$ mkdir -p /u01/app/oracle/oradata/shm  
[shm:~]$  
[shm:~]$ ls -ld /u01/app/oracle/oradata/shm  
drwxr-xr-x 2 oracle oinstall 4096 3월 14 16:50 /u01/app/oracle/oradata/shm  
[shm:~]$  
[shm:~]$ cd /u01/app/oracle/oradata/shm  
[shm:shm]$  
[shm:shm]$ mkdir disk1 disk2 disk3 disk4 disk5  
[shm:shm]$  
[shm:shm]$ ls  
disk1 disk2 disk3 disk4 disk5  
[shm:shm]$  
[shm:shm]$ cd $ORACLE_HOME/dbs  
[shm:dbs]$  
[shm:dbs]$ pwd  
/u01/app/oracle/product/11.2.0/dbhome_1/dbs  
[shm:dbs]$  
[shm:dbs]$ ls  
arch1_7_1163599733.dbf hc_DBUA0.dat hc_shm.dat initSBDB.ora orapwSBDB peshm_PROD_0 peshm_shm_0  
arch1_8_1163599733.dbf hc_PROD.dat hc_shm2.dat lkPROD parameter.sql peshm_SBDB_0  
arch1_9_1163599733.dbf hc_SBDB.dat init.ora lkSBDB peshm_DBUA0_0 peshm_orcl_0  
demobl1.sql hc_orcl.dat initPROD.ora orapwPROD peshm_DUMMY_0 peshm_shm2_0  
[shm:dbs]$  
[shm:dbs]$ vi $ORACLE_HOME/dbs/initshm.ora  
[shm:dbs]$  
[shm:dbs]$ cat $ORACLE_HOME/dbs/initshm.ora  
db_name = shm  
compatible=11.2.0.1.0  
  
sga_target = 256M  
  
undo_management = AUTO  
undo_tablespace = UNDOTBS  
  
processes = 100  
  
remote_login_passwordfile = EXCLUSIVE  
  
control_files = (/u01/app/oracle/oradata/shm/disk1/ctrl1.ctl ,  
                /u01/app/oracle/oradata/shm/disk2/ctrl2.ctl ,  
                /u01/app/oracle/oradata/shm/disk3/ctrl3.ctl)  
[shm:dbs]$
```

```

db_name = shm
compatible=11.2.0.1.0

sga_target = 256M

undo_management = AUTO
undo_tablespace = UNDOTBS

processes = 100

remote_login_passwordfile = EXCLUSIVE

control_files = (/u01/app/oracle/oradata/PROD/disk1/ctrl1.ctl ,
                /u01/app/oracle/oradata/PROD/disk2/ctrl2.ctl ,
                /u01/app/oracle/oradata/PROD/disk3/ctrl3.ctl)

```

#### 4. instance 를 nomount 로 올린다.

#1. 아래와 같이 sys에 접속하기  
[shm:~]\$ sqlplus / as sysdba

SQL\*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 16:57:37 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to an idle instance.

#2. startup nomount로 올립니다.(pfile을 사용해서 instance 구성)  
shm SYS > startup nomount pfile=\$ORACLE\_HOME/dbs/initshm.ora  
ORACLE instance started.

Total System Global Area	267825152 bytes
Fixed Size	1335924 bytes
Variable Size	92278156 bytes
Database Buffers	167772160 bytes
Redo Buffers	6438912 bytes

#3. DB STARTUP 단계 확인하기  
shm SYS > select instance\_name, status  
2 from v\$instance;

INSTANCE_NAME	STATUS
-----	-----
shm	STARTED

```

[shm:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 16:57:37 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to an idle instance.

shm SYS >
shm SYS > startup nomount pfile=$ORACLE_HOME/dbs/initshm.ora
ORACLE instance started.

Total System Global Area 267825152 bytes
Fixed Size 1335924 bytes
Variable Size 92278156 bytes
Database Buffers 167772160 bytes
Redo Buffers 6438912 bytes
shm SYS >
shm SYS > select instance_name, status
2 from v$instance;

INSTANCE_NAME STATUS
-----
shm STARTED

```

##### 5. create database 스크립트를 수행한다.

- database 를 생성한다는것은 어떠한 파일들을 생성하면 db 가 생성되는 것인가 ?
  1. data file
  2. controlfile
  3. redo log file
  4. parameter file
  5. archive log file
  6. password file
- database 를 수동으로 생성하는 스크립트를 수행하면 위의 파일중 3가지가 생성된다.
  1. data file
  2. controlfile
  3. redo logfile
- DB 수동으로 생성하기
  - SI DBA가 DB를 생성할 때 정석과 같은 스크립트

```

create database shm
user sys identified by oracle
user system identified by oracle
datafile '/u01/app/oracle/oradata/shm/disk1/system01.dbf'
size 100M autoextend on maxsize unlimited extent management local
sysaux
datafile '/u01/app/oracle/oradata/shm/disk2/sysaux01.dbf'

```

```

size 50M autoextend on maxsize unlimited
default temporary tablespace temp
tempfile '/u01/app/oracle/oradata/shm/disk3/temp01.dbf'
size 50M autoextend on maxsize unlimited
undo tablespace undotbs
datafile '/u01/app/oracle/oradata/shm/disk4/undotbs01.dbf'
size 50M autoextend on maxsize unlimited
logfile
group 1 ('/u01/app/oracle/oradata/shm/disk4/redoG1M1.rdo',
        '/u01/app/oracle/oradata/shm/disk5/redoG1M2.rdo') size 100M,
group 2 ('/u01/app/oracle/oradata/shm/disk4/redoG2M1.rdo',
        '/u01/app/oracle/oradata/shm/disk5/redoG2M2.rdo') size 100M,
group 3 ('/u01/app/oracle/oradata/shm/disk4/redoG3M1.rdo',
        '/u01/app/oracle/oradata/shm/disk5/redoG3M2.rdo') size 100M,
group 4 ('/u01/app/oracle/oradata/shm/disk4/redoG4M1.rdo',
        '/u01/app/oracle/oradata/shm/disk5/redoG4M2.rdo') size 100M,
group 5 ('/u01/app/oracle/oradata/shm/disk4/redoG5M1.rdo',
        '/u01/app/oracle/oradata/shm/disk5/redoG5M2.rdo') size 100M;

```

=====

**\*\* autoextend on maxsize unlimited \*\***

최초의 사이즈는 50M 이지만, 디스크 공간이 허용할 때 까지 무한하게 늘어날 수 있게 해주는 것.  
자동으로 늘어나게 됨!

따라서 테이블 스페이스 공간 부족 에러가 발생하지 않을 것(앞으로 계속! 디스크가 허용한다면!!)

**\*\* log file member를 2개 씩 구성을 해두는데, 디스크를 다른 곳에 각각 생성  
(디스크가 깨져도 문제가 생기지 않도록) \*\***

- DB를 생성하면, data file, control file, redo log file이 함께 생성되었기 때문에 DB가 OPEN으로 올라오게 됨.  
(startup 되기 위해 필요한 모든 파일이 존재하기 때문)

```

shm SYS >
select instance_name, status
  from v$instance;

INSTANCE_NAME    STATUS
-----
PROD             OPEN

```



```

shm SYS > create database shm
  2 user sys identified by oracle
  3 user system identified by oracle
  4 datafile '/u01/app/oracle/oradata/shm/disk1/system01.dbf'
  5 size 100M autoextend on maxsize unlimited extent management local
  6 sysaux
datafile '/u01/app/oracle/oradata/shm/disk2/sysaux01.dbf'
size 50M autoextend on maxsize unlimited
default temporary tablespace temp
tempfile '/u01/app/oracle/oradata/shm/disk3/temp01.dbf'
size 50M autoextend on maxsize unlimited
undo tablespace undotbs
datafile '/u01/app/oracle/oradata/shm/disk4/undotbs01.dbf'
size 50M autoextend on maxsize unlimited
logfile
group 1 ('/u01/app/oracle/oradata/shm/disk4/redoG1M1.rdo',
'/u01/app/oracle/oradata/shm/disk5/redoG1M2.rdo') size 100M,
group 2 ('/u01/app/oracle/oradata/shm/disk4/redoG2M1.rdo',
'/u01/app/oracle/oradata/shm/disk5/redoG2M2.rdo') size 100M,
group 3 ('/u01/app/oracle/oradata/shm/disk4/redoG3M1.rdo',
'/u01/app/oracle/oradata/shm/disk5/redoG3M2.rdo') size 100M,
group 4 ('/u01/app/oracle/oradata/shm/disk4/redoG4M1.rdo',
'/u01/app/oracle/oradata/shm/disk5/redoG4M2.rdo') size 100M,
group 5 ('/u01/app/oracle/oradata/shm/disk4/redoG5M1.rdo',
'/u01/app/oracle/oradata/shm/disk5/redoG5M2.rdo') size 100M;
6 17 18 19 20 21 22 23 24 25

Database created.

shm SYS >
shm SYS > select instance_name, status
  from v$instance; 2

INSTANCE_NAME    STATUS
-----
shm              OPEN

```

⇒ DBCA로 만든다면 Password를 입력하는 창이 나올 것이지만, 수동으로 생성하기 때문에 직접 이곳에 입력해줘야 함

## 6. data dictionary 를 생성하는 스크립트를 수행한다.

- a. data dictionary와 oracle에 필요한 필수 패키지 같은 것이 설치됨.

```

shm SYS >
@$ORACLE_HOME/rdbms/admin/catalog.sql

@$ORACLE_HOME/rdbms/admin/catproc.sql

connect system/oracle

shm SYSTEM >
@$ORACLE_HOME/sqlplus/admin/pupbld.sql

```

- 첫번째 스크립트 종료 캡처 사진

```
Grant succeeded.

PL/SQL procedure successfully completed.

TIMESTAMP
-----
COMP_TIMESTAMP CATALOG    2024-03-14 17:03:44
_connect_identifier _user > |
```

- 두번째 스크립트 종료 캡처 사진

```
shm SYS > SET SERVEROUTPUT ON
shm SYS >
shm SYS > Rem Indicate CATPROC load complete and check validity
shm SYS > BEGIN
2     dbms_registry.update_schema_list('CATPROC',
3     dbms_registry.schema_list_t('SYSTEM', 'OUTLN', 'DBSNMP', 'DIP',
4     'ORACLE_OCM', 'APPQOSSYS'));
5     dbms_registry.loaded('CATPROC');
6     dbms_registry_sys.validate_catproc;
7     dbms_registry_sys.validate_catalog;
8 END;
9 /

PL/SQL procedure successfully completed.

shm SYS >
shm SYS > SELECT dbms_registry_sys.time_stamp('CATPROC') AS timestamp FROM DUAL;

TIMESTAMP
-----
COMP_TIMESTAMP CATPROC    2024-03-14 17:08:29

1 row selected.

shm SYS >
shm SYS > SET SERVEROUTPUT OFF
```

- 세번째 스크립트 종료 캡처 사진

```
Synonym created.

shm SYSTEM > DROP PUBLIC SYNONYM PRODUCT_USER_PROFILE;
DROP PUBLIC SYNONYM PRODUCT_USER_PROFILE
*
ERROR at line 1:
ORA-01432: public synonym to be dropped does not exist

shm SYSTEM > CREATE PUBLIC SYNONYM PRODUCT_USER_PROFILE FOR SYSTEM.PRODUCT_PRIVS;

Synonym created.

shm SYSTEM >
shm SYSTEM > -- End of pupbld.sql
shm SYSTEM > |
```

## 7. shm DB 에 운영 DATA 생성

- scott 계정 생성하고 demobld 스크립트를 수행한다.

```
shm SYSTEM > connect / as sysdba
Connected.
shm SYS >
shm SYS > create user scott
identified by tiger; 2
```

```

User created.

shm SYS > grant dba to scott;

Grant succeeded.

shm SYS > connect scott/tiger
Connected.
shm SCOTT >
shm SCOTT > @demobld -- emp 테이블과 dept 테이블 구성

alter session set nls_Date_format='RR/MM/DD';

Session altered.

... 이하생략

```

```

shm SYSTEM > connect / as sysdba
Connected.
shm SYS >
shm SYS > create user scott
identified by tiger; 2

User created.

shm SYS > grant dba to scott;

Grant succeeded.

shm SYS > connect scott/tiger
Connected.
shm SCOTT >
shm SCOTT > @demobld
shm SCOTT > alter session set nls_Date_format='RR/MM/DD';

Session altered.

shm SCOTT > drop table emp;

```

- b. sqlplus 에서 vi 편집기를 실행할수 있도록 설정한다.

```

[shm:~]$ cd $ORACLE_HOME/sqlplus/admin
[shm:admin]$
[shm:admin]$ vi glogin.sql
[shm:admin]$
[shm:admin]$ pwd
/u01/app/oracle/product/11.2.0/dbhome_1/sqlplus/admin

-----아래의 내용 넣거나 있는지 확인-----
define _editor='vi'
set sqlprompt "_connect_identifier _user > "
-----

```

```
[shm:~]$ cd $ORACLE_HOME/sqlplus/admin
[shm:admin]$
[shm:admin]$ vi glogin.sql
[shm:admin]$
[shm:admin]$ pwd
/u01/app/oracle/product/11.2.0/dbhome_1/sqlplus/admin
```

```
--
-- Copyright (c) 1988, 2005, Oracle. All Rights Reserved.
--
-- NAME
--   glogin.sql
--
-- DESCRIPTION
--   SQL*Plus global login "site profile" file
--
--   Add any SQL*Plus commands here that are to be executed when a
--   user starts SQL*Plus, or uses the SQL*Plus CONNECT command.
--
-- USAGE
--   This script is automatically run
--
define _editor='vi'
set sqlprompt "_connect_identifier _user > "
```

## Standby DB 구성 - SBDB2 DB 구성

Primary DB에서 Standby DB로 archive log file을 보내야하기 때문에 archive log 상태로 설정해주는 것

### ■ Standby DB 구성 방법

1. standby DB 생성시 필요한 환경을 Primary DB 에 설정해준다.
2. Primary DB 의 파라미터 파일을 수정한다.
3. Standby DB 를 위한 Directory 를 생성
4. 모든 datafile ,temp file 을 standby DB 로 전달
5. Primary DB 에서 standby DB 를 위한 controlfile 을 생성한후 전달한다.

1. standby DB 생성시 필요한 환경을 Primary DB 에 설정해준다.

- DataGuard 를 구성하기 위해서 Primaryh DB 쪽에 필요한 환경설정 3가지

- 1) Password file 인증방법이어야한다.

```
shm SYS > show parameter remote_login_passwordfile
```

NAME	TYPE	VALUE
remote_login_passwordfile	string	EXCLUSIVE

```
shm SYS > show parameter remote_login_passwordfile
```

NAME	TYPE	VALUE
remote_login_passwordfile	string	EXCLUSIVE

2) Archive log mode 여야한다.

```
SQL> archive log list
SQL> shutdown immediate
SQL> startup mount
SQL> alter database archivelog;
SQL> alter database open;
SQL> archive log list
```

-----

```
shm SYS > archive log list
Database log mode                No Archive Mode
Automatic archival              Disabled
Archive destination             /u01/app/oracle/product/11.2.0/dbhome_1/
db/arch
Oldest online log sequence      3
Current log sequence            7
```

```
shm SYS > shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
```

```
shm SYS > startup mount
ORACLE instance started.
```

```
Total System Global Area  267825152 bytes
Fixed Size                  1335924 bytes
Variable Size               92278156 bytes
Database Buffers            167772160 bytes
Redo Buffers                 6438912 bytes
Database mounted.
```

```
shm SYS > alter database archivelog;
```

```
Database altered.
```

```
shm SYS > alter database open;
```

```
Database altered.
```

```
shm SYS >
```

```

shm SYS > archive log list
Database log mode           Archive Mode
Automatic archival         Enabled
Archive destination         /u01/app/oracle/product/11.2.0/dbhome_1/
                             dbs/arch
Oldest online log sequence  3
Next log sequence to archive 7
Current log sequence        7

```

```

shm SYS > archive log list
Database log mode           No Archive Mode
Automatic archival         Disabled
Archive destination         /u01/app/oracle/product/11.2.0/dbhome_1/dbs/arch
Oldest online log sequence  3
Current log sequence        7
shm SYS >
shm SYS > shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
shm SYS >
shm SYS > startup mount
ORACLE instance started.

Total System Global Area  267825152 bytes
Fixed Size                 1335924 bytes
Variable Size             92278156 bytes
Database Buffers          167772160 bytes
Redo Buffers               6438912 bytes
Database mounted.
shm SYS >
shm SYS > alter database archivelog;

Database altered.

shm SYS >
shm SYS > alter database open;

Database altered.

shm SYS >
shm SYS > archive log list
Database log mode           Archive Mode
Automatic archival         Enabled
Archive destination         /u01/app/oracle/product/11.2.0/dbhome_1/dbs/arch
Oldest online log sequence  3
Next log sequence to archive 7
Current log sequence        7
shm SYS >

```

3) Force logging 이 활성화 되어 있어야한다.( 무조건 log 정보가 생기게 하겠다)

⇒ 그래야 모든 log 정보가 넘어갈 수 있음.

PRIMARY DB에서 수행한 모든 DML문장들이 LOG에 기록이 되고 이 정보를 ARCHIVE LOG 에 기록되어 STANDBY DB에 넘기게 됨

db 전체에 대해서 강제로 log 정보가 생성되도록 설정해줘야한다.

```
SQL> alter database force logging;
```

```
SQL>
```

```
alter database add supplemental log data
(primary key, unique index) columns;

* primary db 에서 수행한 dml 문장들이 저장된다.
```

```
SQL> alter system archive log current;
```

```
SQL> alter system switch logfile;
```

```
SQL> select name from v$archived_log;
```

```
SQL> select FORCE_LOGGING from v$database;
```

----- 수행해보기 -----

```
shm SYS > alter database force logging;
```

Database altered.

```
shm SYS > alter database add supplemental log data
(primary key, unique index) columns; 2
```

Database altered.

```
shm SYS >
```

```
shm SYS > alter system archive log current;
```

System altered.

```
shm SYS > alter system switch logfile;
```

System altered.

```
shm SYS > select name from v$archived_log;
```

NAME

-----  
-----

/u01/app/oracle/product/11.2.0/dbhome\_1/dbs/arch1\_7\_1163610068.dbf

/u01/app/oracle/product/11.2.0/dbhome\_1/dbs/arch1\_8\_1163610068.dbf

```
shm SYS > select FORCE_LOGGING from v$database;
```

FOR

---

YES

```

shm SYS > alter database force logging;

Database altered.

shm SYS > alter database add supplemental log data
(primary key, unique index) columns; 2

Database altered.

shm SYS >
shm SYS > alter system archive log current;

System altered.

shm SYS > alter system switch logfile;

System altered.

shm SYS > select name from v$archived_log;

NAME
-----
/u01/app/oracle/product/11.2.0/dbhome_1/dbs/arch1_7_1163610068.dbf
/u01/app/oracle/product/11.2.0/dbhome_1/dbs/arch1_8_1163610068.dbf

shm SYS > select FORCE_LOGGING from v$database;

FOR
---
YES

```

⇒ YES 가 떠야 정상

## 2. Primary DB 의 파라미터 파일을 수정한다.

```

$ cd $ORACLE_HOME/dbs
$ vi initshm.ora
===== 내용 추가하기 =====
# 맨 아래쪽에 아래의 내용들을 추가한다.
# 아래 내용들을 왼쪽에 공백 없이 딱 붙여서 추가하기
# 지금부터는 data guard 를 구성하기 위한 파라미터들을 설정

db_unique_name=shm

# standby db 쪽의 db 이름도 shm 일것이므로
# primary db 쪽에 db_unique_name 을 shm 라고 셋팅해야한다.

~~~~~

standby_file_management=auto

# primary db 쪽에서 테이블 스페이스를 생성하면
# standby db 쪽에서도 똑같은 테이블 스페이스가 자동으로
# 만들어지게 하는 파라미터
# e.g 판교에서 테이블 스페이스 생성하면 원주에서도 동일한 테이블 스페이스가 생성되어야함
~~~~~

db_file_name_convert='/home/oracle/SBDB2', '/u01/app/oracle/oradata/shm'

# Primary db쪽에는 data file 이 아래의 위치에 있고
/u01/app/oracle/oradata/shm <---- 이 위치에 있고

```



```

# Standby db 쪽에는 data file 이 아래의 위치에 있다는 것을 오라클에게 알려줌
/home/oracle/SBDB2 <----- 이 위치에 있다는것을 알려줌

항상 primary db가 뒤에 있고 앞에 첫 인자에 standby DB가 있음
~~~~~

log_file_name_convert='/home/oracle/SBDB2','/u01/app/oracle/oradata/shm'

# Primary db쪽에는 redo log file 이
/u01/app/oracle/oradata/shm <---- 이 위치에 있고

# Standby db 쪽에는 redo log file 이
/home/oracle/SBDB2 <----- 이 위치에 있다는것을 알려줌 */

redo log file의 위치도 오라클에 알려주는 것
~~~~~

log_archive_dest_1='location=/home/oracle/shm/arch valid_for=(all_logfiles,all_roles)'

# primary DB 쪽에서 생성될 archive log file의 위치를 지정해주는 것
-- primary DB 쪽의 archive log file이 어디에 생성되어 있는지 알려주는 코드 (위치 지정)

~~~~~저장하고 나가기~~~~~

[shm:~]$ mkdir shm
mkdir: shm 디렉토리를 만들 수 없습니다: 파일이 존재합니다
[shm:~]$
[shm:~]$ ls -ld shm
drwxr-xr-x 2 oracle oinstall 4096 1월 18 12:13 shm
[shm:~]$
[shm:~]$ mkdir arch

$ pwd
/home/oracle/shm/arch
-- 이제 이 위치에 archive log file이 생성될 것

만약에 이미 있으면 arch 디렉토리만 생성해주면 됨

그리고 다시 $ORACLE_HOME/dbs 밑에 있는 initshm.ora를 엽니다.
~~~~~

# primary db 쪽에 아카이브 로그 파일의 위치를 하나 더 생성함
# 한줄로 넣어주기
log_archive_dest_2='service=SBDB2 LGWR SYNC AFFIRM valid_for=(online_logfiles,primary_role)'

-- service를 쓰고 SBDB2라는 tns 별칭을 사용하여
-- tns 별칭에 해당하는 DB 쪽에 archive log file이 넘어가는 것
primary db쪽에 log file 위치 하나 더 생성함

```

이제 standby DB 쪽에 archive log file이 실시간으로 넘어가게 됨

~~~~~  
만약에 STANDBY DB였던 것이 PRIMARY DB가 되는 상황이 되면

아래의 주석달린 두 코드가 필요함

그래서 주석을 달아서 혹시 몰라서 넣어둬.

언제 두 DB 들이 switch 될지 모르기 때문

# standby db 쪽에 생성할 아카이브 로그파일의 위치

-----아래의 두 코드 -----

#fal\_server=SBDB2

#fal\_client=shm

-----

# 나중에 primary db 가 standby db 가 될수있기 때문에 미리 적어놓은 파라미터

~~~~~다했으면 저장하고 나오기! ~~~~~

파라미터 파일 구성 끝!

db\_name = shm

compatible=11.2.0.1.0

sga\_target = 256M

undo\_management = AUTO

undo\_tablespace = UNDOTBS

processes = 100

remote\_login\_passwordfile = EXCLUSIVE

control\_files = (/u01/app/oracle/oradata/shm/disk1/ctrl1.ctl ,  
                  /u01/app/oracle/oradata/shm/disk2/ctrl2.ctl ,  
                  /u01/app/oracle/oradata/shm/disk3/ctrl3.ctl)

db\_unique\_name=shm

standby\_file\_management=auto

db\_file\_name\_convert='/home/oracle/SBDB2','/u01/app/oracle/oradata/shm'

log\_file\_name\_convert='/home/oracle/SBDB2','/u01/app/oracle/oradata/shm'

log\_archive\_dest\_1='location=/home/oracle/shm/arch valid\_for=(all\_logfiles,all\_roles)'

log\_archive\_dest\_2='service=SBDB2 LGWR SYNC AFFIRM valid\_for=(online\_logfiles,primary\_role)'

#fal\_server=SBDB2

#fal\_client=shm

```

[shm:~]$ cd $ORACLE_HOME/dbs
[shm:dbs]$ ls
arch1_7_1163599733.dbf  demobld.sql  hc_shm.dat  initshm.ora  orapwSBDB  peshm_SBDB_0
arch1_7_1163610068.dbf  hc_DBUA0.dat  hc_shm2.dat  lkPROD      parameter.sql  peshm_orcl_0
arch1_8_1163599733.dbf  hc_PROD.dat  init.ora     lkSBDB      peshm_DBUA0_0  peshm_shm2_0
arch1_8_1163610068.dbf  hc_SBDB.dat  initPROD.ora  lkSHM       peshm_DUMMY_0  peshm_shm_0
arch1_9_1163599733.dbf  hc_orcl.dat  initSBDB.ora  orapwPROD   peshm_PROD_0
[shm:dbs]$
[shm:dbs]$ vi initshm.ora
[shm:dbs]$
[shm:dbs]$ cd
[shm:~]$
[shm:~]$ mkdir shm
mkdir: `shm' 디렉토리를 만들 수 없습니다: 파일이 존재합니다
[shm:~]$
[shm:~]$ ls -ld shm
drwxr-xr-x 2 oracle oinstall 4096  1월 18 12:13 shm
[shm:~]$
[shm:~]$ mkdir arch
[shm:~]$
[shm:~]$ pwd
/home/oracle
[shm:~]$
[shm:~]$ cd $ORACLE_HOME/dbs
[shm:dbs]$
[shm:dbs]$ vi initshm.ora
[shm:dbs]$

```

```

db_name = shm
compatible=11.2.0.1.0

sga_target = 256M

undo_management = AUTO
undo_tablespace = UNDOTBS

processes = 100

remote_login_passwordfile = EXCLUSIVE

control_files = (/u01/app/oracle/oradata/shm/disk1/ctrl1.ctl ,
                /u01/app/oracle/oradata/shm/disk2/ctrl2.ctl ,
                /u01/app/oracle/oradata/shm/disk3/ctrl3.ctl)

db_unique_name=shm
standby_file_management=auto
db_file_name_convert='/home/oracle/SBDB2','/u01/app/oracle/oradata/shm'
log_file_name_convert='/home/oracle/SBDB2','/u01/app/oracle/oradata/shm'
log_archive_dest_1='location=/home/oracle/shm/arch valid_for=(all_logfiles,all_roles)'
log_archive_dest_2='service=SBDB2 LGWR SYNC AFFIRM valid_for=(online_logfiles,primary_role)'

#fal_server=SBDB2
#fal_client=shm

```

### 3. Standby DB 를 위한 Directory 를 생성

- a. primary DB의 datafile과 control file을 standby DB에 받기만 하면 됨(단, 원격 SCP로!)

```

[shm:~]$ mkdir -p /home/oracle/SBDB2
[shm:~]$
[shm:~]$ ls -ld /home/oracle/SBDB2
drwxr-xr-x 2 oracle oinstall 4096  3월 14 17:55 /home/oracle/SBDB2

```

⇒ standby DB 쪽에 데이터 파일과 control file을 받을 디렉토리 생성

```

[shm:~]$ mkdir -p /home/oracle/SBDB2
[shm:~]$
[shm:~]$ ls -ld /home/oracle/SBDB2
drwxr-xr-x 2 oracle oinstall 4096  3월 14 17:55 /home/oracle/SBDB2

```

#### 4. 모든 datafile ,temp file 을 standby DB 로 전달

##### a. 반드시 db를 정상 종료한 다음 수행해야함

```
shm SYS > shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
```

# 디렉토리를 통째로 넘길 것이기 때문에 -rp 옵션을 사용한다.

```
[shm:~]$ cp -rp /u01/app/oracle/oradata/shm/* /home/oracle/SBDB2
[shm:~]$
[shm:~]$ cd /home/oracle/SBDB2
[shm:SBDB2]$
[shm:SBDB2]$ ls
disk1 disk2 disk3 disk4 disk5
```

```
shm SYS > shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
shm SYS >
shm SYS > exit
Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
[shm:~]$
[shm:~]$ cp -rp /u01/app/oracle/oradata/shm/* /home/oracle/SBDB2
[shm:~]$
[shm:~]$ cd /home/oracle/SBDB2
[shm:SBDB2]$
[shm:SBDB2]$ ls
disk1 disk2 disk3 disk4 disk5
```

#### 5. Primary db 쪽에 아카이브 로그 파일과 flashback database log 가 저장될 위치를 생성하시오 ~

##### a. flashback database 를 가능하게 해주는

```
[shm:~]$ mkdir -p /home/oracle/shm/arch <--- 아카이브 로그파일 위치
[shm:~]$ mkdir -p /home/oracle/shm/flash <--- flashback database log 위치
```

```
[shm:~]$ cd shm
[shm:shm]$
[shm:shm]$ ls
arch      emp1.csv  emp2.csv  emp4.csv  emp6.csv  emp8.csv  emp_backup.csv  m
ovies.csv ratings.csv users.csv
emp.csv   emp10.csv emp3.csv  emp5.csv  emp7.csv  emp9.csv  flash           m
ovies2.csv report.csv
[shm:shm]$
[shm:shm]$ ls -ld arch
drwxr-xr-x 2 oracle oinstall 4096 3월 14 17:58 arch
[shm:shm]$
```

```
[shm:shm]$ ls -ld flash
drwxr-xr-x 2 oracle oinstall 4096  3월 14 17:58 flash
```

```
[shm:~]$ mkdir -p /home/oracle/shm/arch
[shm:~]$ mkdir -p /home/oracle/shm/flash
```

```
[shm:~]$ cd shm
[shm:shm]$
[shm:shm]$ ls
arch      emp1.csv  emp2.csv  emp4.csv  emp6.csv  emp8.csv  emp_backup.csv  movies.csv  ratings.csv  users.csv
emp.csv   emp10.csv emp3.csv  emp5.csv  emp7.csv  emp9.csv  flash           movies2.csv report.csv
[shm:shm]$
[shm:shm]$ ls -ld arch
drwxr-xr-x 2 oracle oinstall 4096  3월 14 17:58 arch
[shm:shm]$
[shm:shm]$ ls -ld flash
drwxr-xr-x 2 oracle oinstall 4096  3월 14 17:58 flash
```

6. standby db 쪽에 아카이브 로그 파일과 flasback database log 가  
저장될 위치를 생성하시오 ~

```
$ mkdir -p /home/oracle/SBDB2/arch
$ mkdir -p /home/oracle/SBDB2/flash

----- 수행 -----
[shm:~]$ mkdir -p /home/oracle/SBDB2/arch
[shm:~]$ mkdir -p /home/oracle/SBDB2/flash
[shm:~]$
[shm:~]$ cd SBDB2
[shm:SBDB2]$
[shm:SBDB2]$ ls
arch  disk1  disk2  disk3  disk4  disk5  flash
```

```
[shm:~]$
[shm:~]$ mkdir -p /home/oracle/SBDB2/arch
[shm:~]$ mkdir -p /home/oracle/SBDB2/flash
[shm:~]$
[shm:~]$ cd SBDB2
[shm:SBDB2]$
[shm:SBDB2]$ ls
arch  disk1  disk2  disk3  disk4  disk5  flash
```

- Primary db -----> standby db 넘겨줘야할 파일
  1. 모든 datafile 들
  2. tempfile
  3. redo log file
  4. standby 용 controlfile ----->

7. shm DB 를 mount 로 올리고 standby 용 controlfile 을 생성한다. - PRIMARY DB에서 생성

```
shm SYS > startup mount
ORACLE instance started.
```

```
Total System Global Area 267825152 bytes
```

```
Fixed Size          1335924 bytes
Variable Size       92278156 bytes
Database Buffers    167772160 bytes
Redo Buffers        6438912 bytes
Database mounted.
```

```
shm SYS > alter database create standby controlfile
as '$HOME/physical.ctl' reuse;
```

Database altered.

-- reuse를 사용하여 동일한 control file명이 존재하면 덮어쓰라는 의미이다.  
-- \$HOME = HOME 밑의 ORACLE = /home/oracle

```
shm SYS > startup mount
ORACLE instance started.

Total System Global Area 267825152 bytes
Fixed Size          1335924 bytes
Variable Size       92278156 bytes
Database Buffers    167772160 bytes
Redo Buffers        6438912 bytes
Database mounted.
shm SYS >
shm SYS > alter database create standby controlfile
as '$HOME/physical.ctl' reuse; 2

Database altered.
```

8. Primary DB 쪽에서 생성한 standby 용 controlfile 을 Standby 쪽으로 넘겨준다.

```
$ cp $HOME/physical.ctl /home/oracle/SBDB2/disk1/ctrl1.ctl
$ cp $HOME/physical.ctl /home/oracle/SBDB2/disk2/ctrl2.ctl
$ cp $HOME/physical.ctl /home/oracle/SBDB2/disk3/ctrl3.ctl
```

```
----- 수행 및 확인 -----
[shm:~]$ cp $HOME/physical.ctl /home/oracle/SBDB2/disk1/ctrl1.ctl
[shm:~]$ cp $HOME/physical.ctl /home/oracle/SBDB2/disk2/ctrl2.ctl
[shm:~]$ cp $HOME/physical.ctl /home/oracle/SBDB2/disk3/ctrl3.ctl

[shm:~]$ cd SBDB2
[shm:SBDB2]$

[shm:SBDB2]$ cd disk1
[shm:disk1]$
[shm:disk1]$ ls
ctrl1.ctl  system01.dbf
[shm:disk1]$
[shm:disk1]$ cd ..
```

```
[shm:SBDB2]$
[shm:SBDB2]$ cd disk2
[shm:disk2]$
[shm:disk2]$ ls
ctrl2.ctl  sysaux01.dbf
[shm:disk2]$
[shm:disk2]$ cd ..
[shm:SBDB2]$
[shm:SBDB2]$ cd disk3
[shm:disk3]$
[shm:disk3]$ ls
ctrl3.ctl  temp01.dbf
```

```
[shm:~]$ cp $HOME/physical.ctl /home/oracle/SBDB2/disk1/ctrl1.ctl
[shm:~]$ cp $HOME/physical.ctl /home/oracle/SBDB2/disk2/ctrl2.ctl
[shm:~]$ cp $HOME/physical.ctl /home/oracle/SBDB2/disk3/ctrl3.ctl
[shm:~]$
```

반드시 controlfile은 primary DB에서 standby db용 controlfile을 생성해줘야한다.

이제 standby db에는 datafile과 control file이 존재함

9. 리스너가 인식하고 있는 서비스가 무엇인지 확인한다.

- a. 동적 서비스 등록을 정적 서비스 등록으로 변경합니다.
- b. 동적 서비스 등록은 11g의 경우 PMON이 그 이후는 LREG가 직접 리스너에게 서비스를 등록해주는데, 느림....
- c. 그래서 정적 서비스 등록으로 해주어 빠르게 등록되도록 한다.
- d. 만약 동적 서비스 등록이면 데이터 가드가 잘 안될수도 있을 걸..?

```
[shm:~]$ lsnrctl status

LSNRCTL for Linux: Version 11.2.0.1.0 - Production on 14-MAR-2024 18:10:31

Copyright (c) 1991, 2009, Oracle. All rights reserved.

Connecting to (DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=192.168.19.51)(PORT=1521)))
STATUS of the LISTENER
-----
Alias                     LISTENER
Version                   TNSLSNR for Linux: Version 11.2.0.1.0 - Production
Start Date                14-MAR-2024 15:28:41
Uptime                    0 days 2 hr. 41 min. 49 sec
Trace Level               off
Security                  ON: Local OS Authentication
SNMP                      OFF
Listener Parameter File   /u01/app/oracle/product/11.2.0/dbhome_1/network/admin/listener.ora
Listener Log File         /u01/app/oracle/diag/tnslsnr/edydr1p0/listener/alert/log.xml
Listening Endpoints Summary...
```

```

      (DESCRIPTION=(ADDRESS=(PROTOCOL=tcp)(HOST=192.168.19.51)(PORT=1521)))
      (DESCRIPTION=(ADDRESS=(PROTOCOL=ipc)(KEY=EXTPROC1521)))
Services Summary...
Service "+ASM" has 1 instance(s).
  Instance "+ASM", status READY, has 1 handler(s) for this service...
Service "PROD" has 2 instance(s).
  Instance "PROD", status UNKNOWN, has 1 handler(s) for this service...
  Instance "PROD", status READY, has 1 handler(s) for this service...
Service "SBDB" has 2 instance(s).
  Instance "SBDB", status UNKNOWN, has 1 handler(s) for this service...
  Instance "SBDB", status READY, has 1 handler(s) for this service...
Service "shm" has 1 instance(s).
  Instance "shm", status READY, has 1 handler(s) for this service...
The command completed successfully

```

```

[shm:~]$ cd $ORACLE_HOME/network/admin
[shm:admin]$
[shm:admin]$ ls -l listener.ora
-rw-r--r-- 1 oracle oinstall 436  3월 14 15:28 listener.ora
[shm:admin]$
[shm:admin]$ mv listener.ora listener.bak
[shm:admin]$
[shm:admin]$ ls listener.*
listener.bak

```

```

# 이름 변경해두고(backup 본 만들어두고 새롭게 listener.ora를 구성할 것)
[shm:admin]$ vi listener.ora
[shm:admin]$

```

```

-----아래의 내용 입력 -----
LISTENER =
  (DESCRIPTION_LIST =
    (DESCRIPTION =
      (ADDRESS = (PROTOCOL = TCP)(HOST = 192.168.19.51)(PORT = 1521))
      (ADDRESS = (PROTOCOL = IPC)(KEY = EXTPROC1521))
    )
  )

SID_LIST_LISTENER=
  (SID_LIST =
    (SID_DESC =
      (ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1)
      (SID_NAME=shm)
    )
    (SID_DESC =
      (ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1)
      (SID_NAME=SBDB2)
    )
  )

```



```

-----
[shm:admin]$ ls
listener.bak  listener.ora  samples  shrept.lst  sqlnet.ora  tnsnames.ora

$ lsnrctl stop
$ lsnrctl start

[shm:admin]$ lsnrctl start

LSNRCTL for Linux: Version 11.2.0.1.0 - Production on 14-MAR-2024 18:18:37

Copyright (c) 1991, 2009, Oracle. All rights reserved.

Starting /u01/app/oracle/product/11.2.0/dbhome_1/bin/tnslsnr: please wait...

TNSLSNR for Linux: Version 11.2.0.1.0 - Production
System parameter file is /u01/app/oracle/product/11.2.0/dbhome_1/network/admi
n/listener.ora
Log messages written to /u01/app/oracle/diag/tnslsnr/edydr1p0/listener/alert/
log.xml
Listening on: (DESCRIPTION=(ADDRESS=(PROTOCOL=tcp)(HOST=192.168.19.51)(PORT=1
521)))
Listening on: (DESCRIPTION=(ADDRESS=(PROTOCOL=ipc)(KEY=EXTPROC1521)))

Connecting to (DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=192.168.19.51)(PORT=1
521)))
STATUS of the LISTENER
-----
Alias                LISTENER
Version              TNSLSNR for Linux: Version 11.2.0.1.0 - Production
Start Date           14-MAR-2024 18:18:37
Uptime                0 days 0 hr. 0 min. 0 sec
Trace Level           off
Security              ON: Local OS Authentication
SNMP                 OFF
Listener Parameter File /u01/app/oracle/product/11.2.0/dbhome_1/network/adm
in/listener.ora
Listener Log File     /u01/app/oracle/diag/tnslsnr/edydr1p0/listener/aler
t/log.xml
Listening Endpoints Summary...
  (DESCRIPTION=(ADDRESS=(PROTOCOL=tcp)(HOST=192.168.19.51)(PORT=1521)))
  (DESCRIPTION=(ADDRESS=(PROTOCOL=ipc)(KEY=EXTPROC1521)))
Services Summary...
Service "SBDB2" has 1 instance(s).
  Instance "SBDB2", status UNKNOWN, has 1 handler(s) for this service...
Service "shm" has 1 instance(s).
  Instance "shm", status UNKNOWN, has 1 handler(s) for this service...
The command completed successfully

```

```

[shm:~]$ cd $ORACLE_HOME/network/admin
[shm:admin]$
[shm:admin]$ ls -l listener.ora
-rw-r--r-- 1 oracle oinstall 436  3월 14 15:28 listener.ora
[shm:admin]$
[shm:admin]$ mv listener.ora listener.bak
[shm:admin]$
[shm:admin]$ ls listener.*
listener.bak
[shm:admin]$ vi listener.ora
[shm:admin]$
[shm:admin]$
[shm:admin]$ ls
listener.bak  listener.ora  samples  shrept.lst  sqlnet.ora  tnsnames.ora
[shm:admin]$

```

⇒ lsnrctl start 하자마자 바로 service가 등록되는 것을 확인할 수 있다.

리스너가 서비스 2개를 잘 인식하는지 확인 완료

```

LISTENER =
  (DESCRIPTION_LIST =
    (DESCRIPTION =
      (ADDRESS = (PROTOCOL = TCP)(HOST = 192.168.19.51)(PORT = 1521))
      (ADDRESS = (PROTOCOL = IPC)(KEY = EXTPROC1521))
    )
  )

SID_LIST_LISTENER=
  (SID_LIST =
    (SID_DESC =
      (ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1)
      (SID_NAME=shm)
    )
    (SID_DESC =
      (ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1)
      (SID_NAME=SBDB2)
    )
  )

```

```

[shm:admin]$ lsnrctl start

LSNRCTL for Linux: Version 11.2.0.1.0 - Production on 14-MAR-2024 18:18:37

Copyright (c) 1991, 2009, Oracle. All rights reserved.

Starting /u01/app/oracle/product/11.2.0/dbhome_1/bin/tnslnsr: please wait...

TNSLSNR for Linux: Version 11.2.0.1.0 - Production
System parameter file is /u01/app/oracle/product/11.2.0/dbhome_1/network/admin/listener.ora
Log messages written to /u01/app/oracle/diag/tnslnsr/edydr1p0/listener/alert/log.xml
Listening on: (DESCRIPTION=(ADDRESS=(PROTOCOL=tcp)(HOST=192.168.19.51)(PORT=1521)))
Listening on: (DESCRIPTION=(ADDRESS=(PROTOCOL=ipc)(KEY=EXTPROC1521)))

Connecting to (DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=192.168.19.51)(PORT=1521)))
STATUS of the LISTENER
-----
Alias                     LISTENER
Version                   TNSLSNR for Linux: Version 11.2.0.1.0 - Production
Start Date                14-MAR-2024 18:18:37
Uptime                    0 days 0 hr. 0 min. 0 sec
Trace Level               off
Security                  ON: Local OS Authentication
SNMP                      OFF
Listener Parameter File   /u01/app/oracle/product/11.2.0/dbhome_1/network/admin/listener.ora
Listener Log File         /u01/app/oracle/diag/tnslnsr/edydr1p0/listener/alert/log.xml
Listening Endpoints Summary...
  (DESCRIPTION=(ADDRESS=(PROTOCOL=tcp)(HOST=192.168.19.51)(PORT=1521)))
  (DESCRIPTION=(ADDRESS=(PROTOCOL=ipc)(KEY=EXTPROC1521)))
Services Summary...
Service "SBDB2" has 1 instance(s).
  Instance "SBDB2", status UNKNOWN, has 1 handler(s) for this service...
Service "shm" has 1 instance(s).
  Instance "shm", status UNKNOWN, has 1 handler(s) for this service...
The command completed successfully

```

10. tnsnames.ora 파일의 아래의 내용을 추가한다.

```

[shm:~]$ cd $ORACLE_HOME/network/admin
[shm:admin]$ vi tnsnames.ora

----- 중복된 것이 없는지 확인하고 넣기 -----
shm =
  (DESCRIPTION =
    (ADDRESS = (PROTOCOL = TCP)(HOST = 192.168.19.51)(PORT = 1521))
    (CONNECT_DATA =
      (SERVER = DEDICATED)
      (SERVICE_NAME = shm)
    )
  )

SBDB2 =
  (DESCRIPTION =
    (ADDRESS = (PROTOCOL = TCP)(HOST = 192.168.19.51)(PORT = 1521))
    (CONNECT_DATA =
      (SERVER = DEDICATED)
      (SERVICE_NAME = SBDB2)
    )
  )

```

```
)  
)
```

```
shm =  
(DESCRIPTION =  
  (ADDRESS = (PROTOCOL = TCP)(HOST = 192.168.19.51)(PORT = 1521))  
  (CONNECT_DATA =  
    (SERVER = DEDICATED)  
    (SERVICE_NAME = shm)  
  )  
)  
  
SBDB2 =  
(DESCRIPTION =  
  (ADDRESS = (PROTOCOL = TCP)(HOST = 192.168.19.51)(PORT = 1521))  
  (CONNECT_DATA =  
    (SERVER = DEDICATED)  
    (SERVICE_NAME = SBDB2)  
  )  
)  
-- 끼워 넣기 --
```

#### 11. shm 와 SBDB2 를 위한 패스워드 파일 생성

- 원격에서 유저를 통해서 sys에 접속하려면 반드시 password file이 있어야함.
- sys유저가 listener 를 통해서 원격에서 접속하려면 반드시 password file이 있어야함.
- 지역이 서로 멀기 때문에 원격으로 접속해야하는 것.
- 서로 sys유저로 접속하기 위해서 password file 생성
- sys유저의 password를 변경하기 위해서 password file을 생성하기도 하지만 위와 같은 이유로 생성하기도 함

```
[shm:admin]$ cd $ORACLE_HOME/dbs  
[shm:dbs]$  
[shm:dbs]$ pwd  
/u01/app/oracle/product/11.2.0/dbhome_1/dbs  
[shm:dbs]$  
[shm:dbs]$ orapwd file=orapwSBDB2 password=oracle ignorecase=Y  
[shm:dbs]$ orapwd file=orapwshm password=oracle ignorecase=Y  
[shm:dbs]$ ls orapw*  
orapwPROD orapwSBDB orapwSBDB2 orapwshm
```

- 설명 : 패스워드파일을 생성하는 이유는 원격에서 리스너 통해서 sys 유저로 접속하려고 생성
- orapwd : 패스워드 파일을 생성하는 유틸리티
- ignorecase=Y 는 패스워드 oracle 을 대문자로 쓰든 소문자로 쓰든 상관없이 접속하게 하겠다.

```
[shm:admin]$ cd $ORACLE_HOME/dbs  
[shm:dbs]$  
[shm:dbs]$ pwd  
/u01/app/oracle/product/11.2.0/dbhome_1/dbs  
[shm:dbs]$  
[shm:dbs]$ orapwd file=orapwSBDB2 password=oracle ignorecase=Y  
[shm:dbs]$ orapwd file=orapwshm password=oracle ignorecase=Y  
[shm:dbs]$ ls orapw*  
orapwPROD orapwSBDB orapwSBDB2 orapwshm
```

12. 위에서 구성한 network 설정이 정상인지 확인하시오 ~

- a. 리스너를 통해서 sys유저로 접속해보는 것 (대소문자 상관 없이 접속해보기)
- b. 4개를 접속해보고 아무 문제가 없으면 지금까지 잘 설정 한 것

```
$ sqlplus sys/oracle@prod as sysdba
$ sqlplus sys/ORACLE@prod as sysdba
$ sqlplus sys/oracle@sbdb as sysdba
$ sqlplus sys/ORACLE@sbdb as sysdba
```

-----해보기 -----

```
[shm:~]$ sqlplus sys/oracle@prod as sysdba
```

```
SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:24:33 2024
```

```
Copyright (c) 1982, 2009, Oracle. All rights reserved.
```

```
Connected to:
```

```
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
```

```
prod SYS > exit
```

```
Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - P
With the Partitioning, OLAP, Data Mining and Real Application Testing options
```

```
[shm:~]$
```

```
[shm:~]$ sqlplus sys/ORACLE@prod as sysdba
```

```
SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:24:41 2024
```

```
Copyright (c) 1982, 2009, Oracle. All rights reserved.
```

```
Connected to:
```

```
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
```

```
prod SYS > exit
```

```
Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - P
With the Partitioning, OLAP, Data Mining and Real Application Testing options
```

```
[shm:~]$
```

```
[shm:~]$ sqlplus sys/oracle@sbdb as sysdba
```

```
SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:24:51 2024
```

```
Copyright (c) 1982, 2009, Oracle. All rights reserved.
```

```
Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

sbdb SYS > exit
Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - P
With the Partitioning, OLAP, Data Mining and Real Application Testing options
[shm:~]$
[shm:~]$ sqlplus sys/ORACLE@sbdb as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:24:58 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.
```

```
Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

sbdb SYS > exit
Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - P
With the Partitioning, OLAP, Data Mining and Real Application Testing options
```

```

[shm:~]$ sqlplus sys/oracle@prod as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:24:33 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

prod SYS > exit
Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
[shm:~]$
[shm:~]$ sqlplus sys/ORACLE@prod as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:24:41 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

prod SYS > exit
Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
[shm:~]$
[shm:~]$ sqlplus sys/oracle@sbdb as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:24:51 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

sbdb SYS > exit
Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
[shm:~]$
[shm:~]$ sqlplus sys/ORACLE@sbdb as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:24:58 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production

```

13. `.bash_profile` 을 열어서 shm 와 SBDB2 로 접근하기 위한 alias 를 생성한다.

```

[shm:~]$ vi .bash_profile

-----아래의 내용 추가 -----
alias shm='export ORACLE_SID=shm'
alias sbdb2='export ORACLE_SID=SBDB2'
-----

[shm:~]$ source .bash_profile
[shm:~]$
[shm:~]$ shm
[shm:~]$
[shm:~]$ sbdb2
[SBDB2:~]$
[SBDB2:~]$ shm
[shm:~]$

```

```

[shm:~]$ sbdb2

$ prod
$ sqlplus / as sysdba

SQL> select instance_name, status from v$instance;
-- 이미 mount여도 내렸다 올리기
SQL> shutdown immediate
SQL> startup mount

----- 실행해보기 -----

[SBDB2:~]$ shm
[shm:~]$
[shm:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:28:04 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

shm SYS >
shm SYS > select instance_name, status from v$instance;

INSTANCE_NAME    STATUS
-----
shm              MOUNTED

shm SYS > shutdown immediate
ORA-01109: database not open

Database dismounted.
ORACLE instance shut down.
shm SYS > startup mount
ORACLE instance started.

Total System Global Area 267825152 bytes
Fixed Size                1335924 bytes
Variable Size             92278156 bytes
Database Buffers          167772160 bytes
Redo Buffers              6438912 bytes
Database mounted.
shm SYS > select instance_name, status from v$instance;

INSTANCE_NAME    STATUS

```



shm

MOUNTED

```
[shm:~]$ vi .bash_profile
[shm:~]$
[shm:~]$ source .bash_profile
[shm:~]$
[shm:~]$ shm
[shm:~]$
[shm:~]$ sbdb2
[SBDB2:~]$
[SBDB2:~]$ shm
[shm:~]$
[shm:~]$ sbdb2
```

```
# .bash_profile

# Get the aliases and functions
if [ -f ~/.bashrc ]; then
    . ~/.bashrc
fi

# User specific environment and startup programs

PATH=$PATH:$HOME/bin

export PATH
export JAVA_HOME=/usr/java/jdk1.6.0_18
export PATH=$JAVA_HOME/bin:$PATH
export PS1=['echo $ORACLE_SID':\W]$

export ORACLE_BASE=/u01/app/oracle
export ORACLE_SID=shm
export ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1
export PATH=$ORACLE_HOME/bin:$PATH
export GRID_HOME=/u01/app/oracle/product/11.2.0/grid
unset LANG
export LANG=ko_KR.UTF-8

echo /u01/app/oracle/product/11.2.0/dbhome_1 > x

alias alert='cd /u01/app/oracle/diag/rdbms/orcl/orcl/trace'
alias net='cd $ORACLE_HOME/network/admin'
alias ss='sqlplus / as sysdba'
alias scott='sqlplus scott/tiger'
alias dbs='cd $ORACLE_HOME/dbs'
alias oradata='cd /u01/app/oracle/oradata/shm/'
alias proc1man_target_sys/oracle_proc1log'
alias shm='export ORACLE_SID=shm'
alias sbdb2='export ORACLE_SID=SBDB2'

NLS_LANG=american_america.we8iso8859p15
NLS_DATE_FORMAT='RRRR/MM/DD:HH24:MI:SS'
export NLS_LANG
export NLS_DATE_FORMAT
```

```

[SBDB2:~]$ shm
[shm:~]$
[shm:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:28:04 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

shm SYS >
shm SYS > select instance_name, status from v$instance;

INSTANCE_NAME      STATUS
-----
shm                MOUNTED

shm SYS > shutdown immediate
ORA-01109: database not open

Database dismounted.
ORACLE instance shut down.
shm SYS > startup mount
ORACLE instance started.

Total System Global Area 267825152 bytes
Fixed Size                  1335924 bytes
Variable Size              92278156 bytes
Database Buffers          167772160 bytes
Redo Buffers                6438912 bytes
Database mounted.
shm SYS > select instance_name, status from v$instance;

INSTANCE_NAME      STATUS
-----
shm                MOUNTED

```

#### 14. SBDB 용 파라미터 파일 구성 - 새로이 생성하는 것

```

[PROD:~]$ cd $ORACLE_HOME/dbs
[PROD:dbs]$
[PROD:dbs]$ vi initSBDB2.ora

----- 아래의 내용 추가-----

compatible=11.2.0.1.0
control_files = (/home/oracle/SBDB2/disk1/ctrl1.ctl ,
                 /home/oracle/SBDB2/disk2/ctrl2.ctl ,
                 /home/oracle/SBDB2/disk3/ctrl3.ctl )
db_block_size=8192
db_name=shm
service_names=SBDB2
global_names=true
job_queue_processes=10
open_cursors=500
processes=100
remote_login_passwordfile='EXCLUSIVE'
sga_max_size=120M

```

```

sga_target=120M
undo_management='AUTO'
undo_tablespace='UNDOTBS'
db_recovery_file_dest_size=4G
db_recovery_file_dest=/home/oracle/SBDB2/flash
db_unique_name=SBDB2
standby_file_management=auto
db_file_name_convert='/u01/app/oracle/oradata/shm','/home/oracle/SBDB2'
log_file_name_convert='/u01/app/oracle/oradata/shm','/home/oracle/SBDB2'
log_archive_dest_1='location=/home/oracle/SBDB2/arch valid_for=(all_logfiles,
all_roles)'
log_archive_dest_2='service=shm LGWR SYNC AFFIRM valid_for=(online_logfiles,
primary_role)'
#standby_archive_dest=/home/oracle/SBDB2/arch
#recovery_parallelism=4
fal_server=shm
fal_client=SBDB2

```

```

compatible=11.2.0.1.0
control_files = (/home/oracle/SBDB2/disk1/ctrl1.ctl ,
/home/oracle/SBDB2/disk2/ctrl2.ctl ,
/home/oracle/SBDB2/disk3/ctrl3.ctl )
db_block_size=8192
db_name=shm
service_names=SBDB2
global_names=true
job_queue_processes=10
open_cursors=500
processes=100
remote_login_passwordfile='EXCLUSIVE'
sga_max_size=120M
sga_target=120M
undo_management='AUTO'
undo_tablespace='UNDOTBS'
db_recovery_file_dest_size=4G
db_recovery_file_dest=/home/oracle/SBDB2/flash
db_unique_name=SBDB2
standby_file_management=auto
db_file_name_convert='/u01/app/oracle/oradata/shm','/home/oracle/SBDB2'
log_file_name_convert='/u01/app/oracle/oradata/shm','/home/oracle/SBDB2'
log_archive_dest_1='location=/home/oracle/SBDB2/arch valid_for=(all_logfiles, all_roles)'
log_archive_dest_2='service=shm LGWR SYNC AFFIRM valid_for=(online_logfiles, primary_role)'
#standby_archive_dest=/home/oracle/SBDB2/arch
#recovery_parallelism=4
fal_server=shm
fal_client=SBDB2

```

※ standby DB 쪽에서 반드시 활성화 되어져야하는 파라미터

1. fal\_server=shm (Primary DB) → 아카이브 로그파일을 보내줘야하는 DB
2. fal\_client=SBDB2(Standby DB) → 아카이브 로그파일을 받아야하는 DB

```

shm -----> SBDB2
              archive log file

```

15. standby 용 redo log file 을 shm 와 SBDB2 에서 각각 생성

a. shm DB

```

alter database add standby logfile
'/u01/app/oracle/oradata/shm/disk1/standby01.log' size 10m;

```

```
alter database add standby logfile
'/u01/app/oracle/oradata/shm/disk1/standby02.log' size 10m;
```

```
shm SYS > alter database add standby logfile
'/u01/app/oracle/oradata/shm/disk1/standby01.log' size 10m;

Database altered.

shm SYS > alter database add standby logfile
'/u01/app/oracle/oradata/shm/disk1/standby02.log' size 10m;

Database altered.
```

b. SBDB2 DB

```
[PROD:~]$ sbdb
[SBDB:~]$
[SBDB:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 16:06:43 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to an idle instance.

SBDB SYS > startup
ORACLE instance started.

Total System Global Area 125538304 bytes
Fixed Size 1334968 bytes
Variable Size 75497800 bytes
Database Buffers 41943040 bytes
Redo Buffers 6762496 bytes
Database mounted.
Database opened.
SBDB SYS >
SBDB SYS >

alter database add standby logfile
'/home/oracle/SBDB2/disk1/standby01.log' size 10m;

alter database add standby logfile
'/home/oracle/SBDB2/disk1/standby02.log' size 10m;
```

```

[shm:~]$ sbdb2
[SBDB2:~]$
[SBDB2:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:34:38 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to an idle instance.

SBDB2 SYS > startup
ORACLE instance started.

Total System Global Area 125538304 bytes
Fixed Size 1334968 bytes
Variable Size 75497800 bytes
Database Buffers 41943040 bytes
Redo Buffers 6762496 bytes
Database mounted.
Database opened.
SBDB2 SYS >
SBDB2 SYS > alter database add standby logfile
'/home/oracle/SBDB2/disk1/standby01.log' size 10m; 2

Database altered.

SBDB2 SYS > alter database add standby logfile
'/home/oracle/SBDB2/disk1/standby02.log' size 10m; 2

Database altered.

```

16. shm 와 SBDB2 의 PMON 이 잘 떠있는지 확인한다.

a. 원주에 있는 db는 이제 항상 복구만 하고 있는 db가 되는 것

```

[SBDB2:~]$ ps -ef | grep pmon
oracle 5297 1 0 10:22 ? 00:00:05 asm_pmon_+ASM
oracle 23728 1 0 15:59 ? 00:00:01 ora_pmon_PROD
oracle 23898 1 0 16:11 ? 00:00:01 ora_pmon_SBDB
oracle 25180 1 0 18:28 ? 00:00:00 ora_pmon_shm
oracle 25271 1 0 18:34 ? 00:00:00 ora_pmon_SBDB2
oracle 25331 29987 0 18:35 pts/4 00:00:00 grep pmon

```

```

[SBDB2:~]$ ps -ef | grep pmon
oracle 5297 1 0 10:22 ? 00:00:05 asm_pmon_+ASM
oracle 23728 1 0 15:59 ? 00:00:01 ora_pmon_PROD
oracle 23898 1 0 16:11 ? 00:00:01 ora_pmon_SBDB
oracle 25180 1 0 18:28 ? 00:00:00 ora_pmon_shm
oracle 25271 1 0 18:34 ? 00:00:00 ora_pmon_SBDB2
oracle 25331 29987 0 18:35 pts/4 00:00:00 grep pmon

```

----- 여기서 부터가 중요 (sbdb2 를 복구모드로 변환하는 작업)

17. standby 디비인 SBDB2 를 복구모드로 변환한다.

- SBDB2 에서 수행한다.

SQL> shutdown immediate

```

SQL> startup mount

SQL> alter database flashback on;

-- MRP(Media Recovery Process) 가 떠있는지 확인하기위해 아래의 작업수행

SQL> select process, status from v$managed_standby;

<---- MRP 가 지금은 아직 안뜬다.

-- 복구모드로 변환하는 명령어를 수행한다.

SQL> recover managed standby database disconnect;

-- 다시 MRP 가 떠있는지 확인한다.
SQL> select process, status from v$managed_standby;

<---- MRP 가 지금 뜬다.

~~~~~ 실습해보기 ~~~~~

SBDB2 SYS > shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
SBDB2 SYS >
SBDB2 SYS > startup mount
ORACLE instance started.

Total System Global Area 125538304 bytes
Fixed Size 1334968 bytes
Variable Size 75497800 bytes
Database Buffers 41943040 bytes
Redo Buffers 6762496 bytes
Database mounted.
SBDB2 SYS >
SBDB2 SYS > select process, status from v$managed_standby;

PROCESS STATUS
-----
ARCH CONNECTED
ARCH CONNECTED
ARCH CONNECTED
ARCH CONNECTED

SBDB2 SYS >
SBDB2 SYS > recover managed standby database disconnect;
Media recovery complete.
SBDB2 SYS >
SBDB2 SYS > select process, status from v$managed_standby;

```

| PROCESS | STATUS       |
|---------|--------------|
| ARCH    | CONNECTED    |
| ARCH    | CONNECTED    |
| ARCH    | CONNECTED    |
| ARCH    | CONNECTED    |
| MRP0    | WAIT_FOR_LOG |

```
[SBDB2:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:36:32 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

SBDB2 SYS >
SBDB2 SYS > shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
SBDB2 SYS >
SBDB2 SYS > startup mount
ORACLE instance started.

Total System Global Area 125538304 bytes
Fixed Size 1334968 bytes
Variable Size 75497800 bytes
Database Buffers 41943040 bytes
Redo Buffers 6762496 bytes
Database mounted.
SBDB2 SYS >
SBDB2 SYS > select process, status from v$managed_standby;

PROCESS STATUS
-----
ARCH CONNECTED
ARCH CONNECTED
ARCH CONNECTED
ARCH CONNECTED

SBDB2 SYS >
SBDB2 SYS > recover managed standby database disconnect;
Media recovery complete.
SBDB2 SYS >
SBDB2 SYS > select process, status from v$managed_standby;

PROCESS STATUS
-----
ARCH CONNECTED
ARCH CONNECTED
ARCH CONNECTED
ARCH CONNECTED
MRP0 WAIT_FOR_LOG
```

18. shm 와 SBDB2 쪽에서 각각 아래의 명령어를 수행해서 datafile 의 갯수가 똑같은지 확인 (각각 3개씩 존재하는지 확인해야함!!)

a. SBDB2 DB

```
SBDB2 SYS > select name from v$datafile;
```

```
NAME
```

```
-----  
/home/oracle/SBDB2/disk1/system01.dbf  
/home/oracle/SBDB2/disk2/sysaux01.dbf  
/home/oracle/SBDB2/disk4/undotbs01.dbf
```

```
SBDB2 SYS > select name from v$datafile;
```

```
NAME
```

```
-----  
/home/oracle/SBDB2/disk1/system01.dbf  
/home/oracle/SBDB2/disk2/sysaux01.dbf  
/home/oracle/SBDB2/disk4/undotbs01.dbf
```

b. shm DB

```
[SBDB2:~]$ shm
```

```
[shm:~]$
```

```
[shm:~]$ sqlplus / as sysdba
```

```
SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:39:15 2024
```

```
Copyright (c) 1982, 2009, Oracle. All rights reserved.
```

```
Connected to:
```

```
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
```

```
With the Partitioning, OLAP, Data Mining and Real Application Testing option
```

```
shm SYS >
```

```
shm SYS > select name from v$datafile;
```

```
NAME
```

```
-----  
/u01/app/oracle/oradata/shm/disk1/system01.dbf  
/u01/app/oracle/oradata/shm/disk2/sysaux01.dbf  
/u01/app/oracle/oradata/shm/disk4/undotbs01.dbf
```



```

[SBDB2:~]$
[SBDB2:~]$ shm
[shm:~]$
[shm:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:39:15 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

shm SYS >
shm SYS > select name from v$datafile;

NAME
-----
/u01/app/oracle/oradata/shm/disk1/system01.dbf
/u01/app/oracle/oradata/shm/disk2/sysaux01.dbf
/u01/app/oracle/oradata/shm/disk4/undotbs01.dbf

```

19. shm 쪽 db 를 올리고 테이블스페이스를 생성해서 standby db 로 넘어가서 반영되는지 확인한다.

a. 주의 : SBDB2는 mount 상태여야함

```

- shm

SQL> alter database open;

SQL>
create tablespace ts9000
  datafile '/u01/app/oracle/oradata/shm/disk2/ts900.dbf' size 10m;

~~~~~ 실습 ~~~~~

shm SYS > alter database open;

Database altered.

shm SYS >
shm SYS > create tablespace ts9000
  datafile '/u01/app/oracle/oradata/shm/disk2/ts900.dbf' size 10m; 2

Tablespace created.

```

```

shm SYS > alter database open;

Database altered.

shm SYS >
shm SYS > create tablespace ts9000
  datafile '/u01/app/oracle/oradata/shm/disk2/ts900.dbf' size 10m;

Tablespace created.

```

20. 아래의 작업을 양쪽에서 각각 수행한다.

- shm

```
select name from v$datafile;
```

- SBDB2

```
select name from v$datafile;
```

# 계속 안뜨면 MRP가 뜨는지 확인해보기

```
SQL> select process, status from v$managed_standby;
```

| PROCESS | STATUS   |
|---------|--|
| ARCH    | CLOSING  |
| ARCH    | CONNECTED                                      |
| ARCH    | CONNECTED                                      |
| ARCH    | CONNECTED                                      |
| MRP0    | WAIT_FOR_LOG ---> 아카이브된 리두정보를 standby db 적용    |
| RFS     | IDLE (Remote File Server) ---> Primary db 로 부터 |
| RFS     | IDLE 리두정보를 수신하고 리두를                            |
| RFS     | IDLE standby db 의 리두로그와                        |
|         | 아카이브 리두로그에 직접기록                                |
|         | 하는 프로세서  |

- primary db

```
SQL>
select process, status from v$managed_standby;
```

| PROCESS | STATUS    |
|---------|-----------|
| ARCH    | CLOSING   |
| ARCH    | CONNECTED |
| ARCH    | CLOSING   |
| ARCH    | CLOSING   |
| LGWR    | WRITING   |

그래도 안만들어지면 shm DB에서 alter system switch log file을 해주어  
log switch를 일으킨 후 checkpoint를 일으킨 다음에 다시 SBSB2 쪽으로 가서  
select name from v\$datafile; 을 하면  
archive log file이 넘어간 것을 확인할 수 있다.  
⇒ 즉, 안되었을 경우 archive log file을 만든 것

- shm db로 이동 후 수행

```

[SBDB2:~]$ shm
[shm:~]$
[shm:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:43:04 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

shm SYS >
shm SYS > alter system switch logfile;

System altered.

shm SYS > alter system checkpoint;

System altered.

shm SYS >
shm SYS > exit
Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 -
Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
[shm:~]$
[shm:~]$ sbdb2
[SBDB2:~]$
[SBDB2:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:43:33 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

SBDB2 SYS >
SBDB2 SYS > select name from v$datafile;

NAME
-----
---
/home/oracle/SBDB2/disk1/system01.dbf
/home/oracle/SBDB2/disk2/sysaux01.dbf
/home/oracle/SBDB2/disk4/undotbs01.dbf
/home/oracle/SBDB2/disk2/ts900.dbf

```

~~~~~ 실습 ~~~~~

```
shm SYS > create tablespace ts9000
        datafile '/u01/app/oracle/oradata/shm/disk2/ts900.dbf' size 10m;  2
```

Tablespace created.

```
shm SYS > select name from v$datafile;
```

NAME

```
-----
---
/u01/app/oracle/oradata/shm/disk1/system01.dbf
/u01/app/oracle/oradata/shm/disk2/sysaux01.dbf
/u01/app/oracle/oradata/shm/disk4/undotbs01.dbf
/u01/app/oracle/oradata/shm/disk2/ts900.dbf
```

```
shm SYS > exit
```

Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 -  
Production

With the Partitioning, OLAP, Data Mining and Real Application Testing options

```
[shm:~]$
```

```
[shm:~]$ sbdb2
```

```
[SBDB2:~]$
```

```
[SBDB2:~]$ sqlplus / as sysdba
```

SQL\*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:41:29 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:

Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production

With the Partitioning, OLAP, Data Mining and Real Application Testing options

```
SBDB2 SYS >
```

```
SBDB2 SYS > select name from v$datafile;
```

NAME

```
-----
---
/home/oracle/SBDB2/disk1/system01.dbf
/home/oracle/SBDB2/disk2/sysaux01.dbf
/home/oracle/SBDB2/disk4/undotbs01.dbf
```

```
SBDB2 SYS >
```

```
SBDB2 SYS > select process, status from v$managed_standby;
```

| PROCESS | STATUS |
|---------|--------|
|---------|--------|

```

-----
ARCH      CONNECTED
ARCH      CONNECTED
ARCH      CONNECTED
ARCH      CLOSING
MRP0      WAIT_FOR_LOG
RFS       IDLE
RFS       IDLE

```

7 rows selected.

SBDB2 SYS > select process, status from v\$managed\_standby;

```

PROCESS    STATUS
-----
ARCH      CONNECTED
ARCH      CONNECTED
ARCH      CONNECTED
ARCH      CLOSING
MRP0      WAIT_FOR_LOG
RFS       IDLE
RFS       IDLE

```

7 rows selected.

SBDB2 SYS > exit

Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 -  
Production

With the Partitioning, OLAP, Data Mining and Real Application Testing options

[SBDB2:~]\$

[SBDB2:~]\$ shm

[shm:~]\$

[shm:~]\$ sqlplus / as sysdba

SQL\*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:43:04 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:

Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production

With the Partitioning, OLAP, Data Mining and Real Application Testing options

shm SYS >

shm SYS > alter system switch logfile;

System altered.

shm SYS > alter system checkpoint;

System altered.

```

shm SYS >
shm SYS > exit
Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 -
Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
[shm:~]$
[shm:~]$ sbdb2
[SBDB2:~]$
[SBDB2:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:43:33 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

SBDB2 SYS >
SBDB2 SYS > select name from v$datafile;

NAME
-----
---
/home/oracle/SBDB2/disk1/system01.dbf
/home/oracle/SBDB2/disk2/sysaux01.dbf
/home/oracle/SBDB2/disk4/undotbs01.dbf
/home/oracle/SBDB2/disk2/ts900.dbf

```

```

shm SYS > create tablespace ts9000
    datafile '/u01/app/oracle/oradata/shm/disk2/ts900.dbf' size 10m; 2

Tablespace created.

shm SYS > select name from v$datafile;

NAME
-----
/u01/app/oracle/oradata/shm/disk1/system01.dbf
/u01/app/oracle/oradata/shm/disk2/sysaux01.dbf
/u01/app/oracle/oradata/shm/disk4/undotbs01.dbf
/u01/app/oracle/oradata/shm/disk2/ts900.dbf

shm SYS > exit
Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
[shm:~]$
[shm:~]$ sbdb2
[SBDB2:~]$
[SBDB2:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:41:29 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

SBDB2 SYS >
SBDB2 SYS > select name from v$datafile;

NAME
-----
/home/oracle/SBDB2/disk1/system01.dbf
/home/oracle/SBDB2/disk2/sysaux01.dbf
/home/oracle/SBDB2/disk4/undotbs01.dbf

```

```

SBDB2 SYS > select process, status from v$managed_standby;

PROCESS      STATUS
-----
ARCH         CONNECTED
ARCH         CONNECTED
ARCH         CONNECTED
ARCH         CLOSING
MRP0         WAIT_FOR_LOG
RFS          IDLE
RFS          IDLE

7 rows selected.

SBDB2 SYS > select process, status from v$managed_standby;

PROCESS      STATUS
-----
ARCH         CONNECTED
ARCH         CONNECTED
ARCH         CONNECTED
ARCH         CLOSING
MRP0         WAIT_FOR_LOG
RFS          IDLE
RFS          IDLE

7 rows selected.

```

```

[SBDB2:~]$ shm
[shm:~]$
[shm:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:43:04 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

shm SYS >
shm SYS > alter system switch logfile;

System altered.

shm SYS > alter system checkpoint;

System altered.

shm SYS >
shm SYS > exit
Disconnected from Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options
[shm:~]$
[shm:~]$ sbdb2
[SBDB2:~]$
[SBDB2:~]$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Thu Mar 14 18:43:33 2024

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

SBDB2 SYS >
SBDB2 SYS > select name from v$datafile;

NAME
-----
/home/oracle/SBDB2/disk1/system01.dbf
/home/oracle/SBDB2/disk2/sysaux01.dbf
/home/oracle/SBDB2/disk4/undotbs01.dbf
/home/oracle/SBDB2/disk2/ts900.dbf

```

**LNS (Logwrite network Server)** ~> 리두를 standby db 의 RFS 에게 보낸다

Primary db -----> Standby db

|      |      |
|------|------|
| ARCH | ARCH |
| LGWR | RFS  |
| LNS  | MRP  |