

An Advanced Smart Biotechnological Algal Plate Air Purification System For Use In Conjunction With Real-Time Air Quality Monitoring

1st Bharathy S
dept. Computer Science
Sri Sairam Engineering College
Chennai, India
bharathy.cse@sairam.edu.in

2nd Srivatsaav Murali
dept. Computer Science
Sri Sairam Engineering College
Chennai, India
sec21cs126@sairamtap.edu.in

3rd Jaswant Singh
dept. Computer Science
Sri Sairam Engineering College
Chennai, India
sec122cs11@sairamtap.edu.in

Abstract—Air pollution has become a health and environmental hazard as its effects are worsened by the increase in pollution levels. Conventional air purification methods, although effective, are not environmentally friendly and can be expensive. We propose an Advanced Smart Biotechnological Algal Plate Air Purification System that combines the real-time monitoring of air quality with biological purification processes. An ATmega328 microcontroller, which synchronizes different parts of the system to function well together, powers the entire system. The gas sensor senses air contaminants and draws polluted air with a fan to the algal bioreactor chamber, onto which microalgae consume carbon dioxide and contaminants and output clean air. The biological system is controlled by a microcontroller where a DC fan is used to switch the flow of air in the system allowing the pollutants to be optimized to expose more and expose it to algae purification. It also handles the control of GPIO-based sensors and actuators to allow air quality metrics tracking and adaptive management. It contains an adjustable alarm and relay for turning on the fan in response to dangerous levels of pollution as well as an LCD for easy reading of system status. The GPIO interface provides the ease of connecting other sensors and actuators making scalability possible for various applications. This simple and low-cost environmental friendly approach combines microcontroller-assisted technology with biological cleaning to give environmentally friendly air to urban, industrial and household consumers as the cost-effective alternative to existing conventional air purifiers.

Keywords— Algae Air Purification, ATmega328, Microcontroller, Gas Sensors, Air Purifier Chamber, Algae Bioreactor, Sustainable air filter, LCD, Real-time pollutant detection, Eco-Friendly air purification.

I. INTRODUCTION

Air pollution is one of the biggest global problems, playing a major role in climate change, environmental destruction, and health care problems. Modern societies have rapidly industrialized and urbanized in a very short period of time, which has caused pollutant levels such as particulate matter, carbon dioxide, nitrogen oxides and other toxic gases to proliferate. These are also one of the harmful elements which degrade air quality, human health, and the ecosystem. While conventional air purification systems are efficient in

reducing pollutants, the purification processes are highly dependent on non-renewable resources, making their operational practices unsustainable. This project overcomes these challenges through the design of a sustainable Algae Based Air Purifier.

During photosynthesis, algae sequester carbon dioxide and produce oxygen at astonishing levels. And this property also makes them the perfect biological answer to pollution problems facing the air. Microcontroller technologies like the ATmega328 have made it possible to merge biology with real-time monitoring and control systems. These technologies work in unison to purify large volumes of air with minimal energy and environmental impact. The system suggested makes use of a gas sensor that senses and measures the presence of pollutants in the air and directs the contaminated air to an air purifier chamber containing algae bioreactor. This allows pollutants to be absorbed in the bioreactor and purified air to be released into the environment. The system also includes extra fittings (an air filter to improve the purity of the air in the box) and normal DC fans to provide optimal air displacement for stable output. LCD Display lets you read important air quality parameters in real time. An inbuilt alarm system and relay is also present which notifies users in case of system abnormal conditions or system failures, which further adds to the safety and operational efficiency of the product. It follows a modular design based on GPIO connections, which allows for future expansions and enhancements.

The new system not only cleans the air but it provides a sustainable substitute for the existing air purification solutions. The biological solution combined with the high tech automation driven by an industry/model easily scaled for urban, industrial, and residential applications. AMBIENT proposes a sustainable and impactful solution to air pollution by tapping into the natural benefits of algae and coupling them with modern technological frameworks. This paper describes the architecture, components, how the system works and the performance analysis of the system in the following sections. First, we present a literature survey that identifies the current technologies that are found to be in use

and then experimental results to demonstrate the efficiency of the proposed system on a real setup. In conclusion, algae-based air purifying is a new sustainable solution to air quality challenges that incorporates lessons from technology and the environment.

II. RELATED WORKS

Potential of Green Algae for Bio-Hydrogen Generation and Storage a Review Torres and De-la-Torre [1] We used machine learning methods for predicting algae growth patterns, energy yields under diverse environmental scenarios. Based on these predictions, the algae-based energy systems were optimized in real-time, demonstrating their reliability and efficiency in a sustainable manner. Yewale et al. On the other hand, [2] created the "Biosmotrap," a biological air filter that reduce air pollutants. The team also assessed the purifiers effectiveness by employing machine learning models to forecast pollutant concentration levels and determine its operational optimization in different indoor and ambient conditions. Wang et al. At the background, [3] developed machine learning models including different air quality parameters of interest in the binary classification of the air purifying capacity of microalgae strains. Abstract Comparing microalgae-based systems with conventional purification methods is essential but dealing with numerous variables and their interferences, leads to reduced efficiency and adaptability in comparison systems.

George [4] researched urban air purification with "Liquid Trees" using photobioreactors. Our data-driven modeling of CO₂ absorption and pollutant removal rates through the machine-learning algorithms allows better photobioreactor deployment strategies in extremely polluted urban areas. Gaston et al. A recent study from Weichenthal et al. [5] assessed air conditioner filters and facial masks for the removal of aerosolized algal toxins. The study was able to predict filtration efficiency at varying operating conditions via the integration of ML models, which can assist in developing filter design methods and filter usage protocols. Microbial filters for air treatment, were the focus of Thakur and Samuel [6]. Using machine learning predictive modeling, we optimized the filter performance and lifespan. The air purification models offered sustainable solutions to one of the major environmental and economic critical challenges. Shahi Khalaf Ansar et al. Particularly, [7] studied the potentials of the algae for removing organic and inorganic substances in air, soil, and water. Authors: Qian Mu contamination WellJing Zhang†null {contaminatioWellJing Zhang, null aSee {HuanJing,Zhang{HuanJing, Zhang †}2 Abstract Prediction of removal efficiency of contaminants in a contaminationWellJing Zhang in similar conditions will promote the development of species-specific environmentally-friendly electrokinetic technologies Szramowiat-Sala et al. An air purifier for outdoor particulate matter that is developed in an environmentally friendly manner with energy self-sufficient property [8]. To ensure that the air purifier is adaptable and efficient in various

environments, machine learning models were used to predict its performance.

Mata et al. Indoor air cleaning technologies: A review and machine learning integration for predictive performance analysis [9] In the second study, ML-based scrubbing technology frameworks were suggested that depend on the dynamic air quality data to limit the configurations of cleaning approaches. Kumar et al. Of note, [10] applied microalgal biochar to indoor air pollution by removing common indoor pollutants, such as particulate matter and total volatile organic compounds (TVOCs). Using machine learning models to enhance pollutant removal velocity are demonstrated and the feasibility of biochar as a green building element for indoor air quality is showcased.

Osama et al. Household photobioreactors to grow algae for household use was studied [11]. In this study applying machine learning methods to suggest optimal growth conditions of diverse growth conditions like light intensity, temperature, and nutrients in domestic set up. Applying predictive models to achieve the best algal biomass production and nutrient removal efficiency, this work indicates the potential of small algae setups for sustainable living. Subrahmanya et al. A microalgae-membrane photobioreactor system for sustainable onboard oxygen production systems in aircraft has been previously proposed by [12]. Oxygen production rates at different operational conditions as represented by flight altitude and cabin pressure were simulated and predicted by machine learning algorithms. This predictive modeling improved the performance of the system while allowing for the design of self-replenishing air support systems for use in aerospace applications. Kim et al. Cavitation electrolysis improved the performance of decomposition of algal blooms [13]. With machine learning, the study promised to predict how effectively different species of algae would decompose, depending on various cavitation parameters including pressure, temperature and the lay of electrodes. Based on the results, system optimization could be guided, allowing algae biomass to recover more resources and generate more energy efficiently.

Rahman et al. Dynamic bioprinting of algal cells: in situ ionic crosslinking of algal cells for complex and bio-ink free formulation for biomedical and industrial applications [14]. In the area of bioprinting, the crosslinking parameters were mapped with mechanistic understanding through machine learning models to predict the mechanical properties and structural stability of bioprinted constructs. This algorithmic predictive method simplified the bioprinting process and provided a high degree of precision and reproducibility in the bio-printed constructs. Tawfik et al. Neyerlin et al. [15] investigated algal cell valorization for biomass and biofuels production from wastewaters. The performance of nutrient uptake and biomass production in different wastewater conditions were analyzed by machine learning models. These models aided in the optimal algal

growth cycle tailoring to enhance bioenergy production along with environmental issues regarding wastewater handling.

III. METHODOLOGY

A. System Overview:

An affordable and environmentally friendly algae-based air purifier that combines biological air purification with microcontroller-driven automations for effective and sustainable air quality management is proposed. The system uses ATmega328 as the main controller, as shown in **Fig 1**, from which we will connect sensors, actuators, display units, etc. Gas sensor, air purifier chamber, algae bioreactor and other components such as LCD, DC fan, relay and alarm system.




Figure 1. Shows Proposed Architecture Methodology

B. Air Quality Detection :

The very first part is Gas Sensor, which senses or alerts the presence of harmful pollutants in the ambient air. It can be used to monitor pollutant levels like carbon dioxide (CO₂), particulate matter (PM), and volatile organic compounds (VOCs). Data collected from the Sensor Outputs is analyzed by the microcontroller in order to measure the level of pollution and to activate the corresponding air purification mechanism if the pollutant levels are above a certain threshold.

C. Air Purification Process:

The polluted air that is detected is allowed to enter an air purifier chamber, where it is made to pass through an air filter for large particles. The air then goes into the algae bioreactor, which is one of the main innovations of the system. Using the natural photosynthetic process of algae, the bioreactor absorbs carbon dioxide and other harmful gases and emits clean, oxygen-rich air. Its air purification is biologically-enhanced while enhancing an eco-friendly dwelling.

D. Live Monitoring and Assessment :

An LCD display interfaced to the microcontroller enables monitoring of air quality in real-time. The dashboard kinds out key parameters like pollutant ranges and machine situation. Finally, a relay and alarm system will sound an alarm if the system is operating abnormally or if the air quality is at a hazardous level. This provides safe and reliable operation.

E. Air Circulation and Output:

The purified air is then blown out of the system by a DC fan, always guarantees the delivery of purified air to the environment. Using a microcontroller the speed of the fan is controlled, adjusting the flow rate based on the pollution level detected, thus making this device an energy-efficient and effective air purification solution.

F. Power Supply and Integration:

Power supply: A transformer supplies power for proper and stable system working. With GPIO connections, this modular design makes it seamless to integrate additional sensors or components, making the system scalable and adaptable to future upgrades.

The technology uses a combination of sensing, biological purification and automation for an efficient and environmentally friendly solution for air purification. The design includes algae bioreactors, emphasizing the sustainability of the system, and a precision microcontroller-driven design that is also adaptable.

G. ATMEGA-328 Microcontroller :

ATmega328 Microcontroller The Advanced Smart Biotechnological Algal Plate Air Purification System centers around the ATmega328 microcontroller, which uses General Purpose Input/Output (GPIO) pins to connect, control, and coordinate multiple sensors and modules. Gas sensors are connected to the input GPIO pins of the microcontroller and constantly monitor air pollution levels in a particular unit and transmit the data in real time. The microcontroller processes this information, and then decides whether to turn components on or off, or how much to throttle them. The algal bioreactor has been controlled to manage GPIO outputs, maintaining exiting warm air by varying fan speed and also maintaining the optimum pollutant exposure for algae-based purification. That's why I also connected a relay module to GPIO output pins of the microcontroller, so that it pulls high or low to switch high power components like the DC fan and air purifier chamber on and off when needed.

Moreover, an I²C LCD display is interfaced, and it presents the air quality readings and other system status in real time for the user to check. When the concentration of harmful pollutants exceeds the level of safety, an alarm (buzzer) connected to one of the GPIO output pins changes its state to notify users. The GPIO architecture allow to add seamlessly more sensors and actuators in the future, and having the system adaptable to various environments. With GPIO based control, biological purification is synchronized to electronic automation, making it not just a high-tech but also a low-tech biological-electronic intervention into the environment, applicable as an urban, industrial and domestic air purifier with appropriate design for cost and novelty with environmental sustainability.

IV. RESULT AND DISCUSSION

1. System Performance :

In this study, an algae-based air purifier was subjected to controlled conditions simulating the air pollution as found indoors to assess its performance. The findings revealed that pollutant concentration was markedly lower, especially for carbon dioxide (CO₂) and particulate matter (PM_{2.5}). On average, the system was 85% effective at purifying air and improvements could be seen within 10 minutes of running. The CO₂ absorption efficiency of the algae bioreactor is found to be very high, which indicates that it represents a sustainable approach for air purification.



Figure 2.Shows Proposed Hardware Implementation

2. Real-Time Monitoring Accuracy :

The gas sensor and LCD display work seamless to give accurate and instantaneous readings of pollutants and hence there is accurate feedback to the user. The LCD showed pollutant levels in the surrounding HF mix, system health, and alerts during operations, allowing for monitoring of system performance. The alarm system proved effective at notifying users about the presence of dangerously high levels of a specific pollutant or instances of malfunctioning during peak

hours, which aided great operational safety and user awareness.




Figure 3.Shows Proposed Graph Chart

3. Power Efficiency :

The Design was effectively low power ,as shown in **Fig 3**, due to low power consumption of system DC fan and ATmega328 microcontroller. The optimization of control fan speed concerning pollution level achieved savings in energy consumption, pointing to system sustainability.

4. Discussion on Sustainability :

Algal is an environment-friendly medium to purify air; While regular air filters need to be constantly replaced and cause waste, the algae bioreactor works in a natural and regenerative manner according to green principles. Additionally, the modular nature of the system enables scalability, from residential to industrial and larger urban applications.

5.Comparison with Esisting Systems :

The algae-based system provides two main advantages over conventional air purifiers it removes pollutants and enriches indoor air with oxygen. Traditional systems are predominantly mechanical or chemical based, whereas this system combines biological purification and yet is automated which makes it cost-effective and environmentally friendly too.

6. Challenges and Limitations

While the system exhibited high purification efficiency, some limitations were noted. One of the limiting factors for an algae bioreactor is its culture performance in the presence of light, therefore their activity might be inhibited in low-light environments. Bioreactor maintenance Bioreactor maintenance will also be required to promote the optimal

growth of algae. Later models of the system would include artificial lighting and possibly even automated facilities to handle these limitations.

Parameter	Measured value	Accuracy Achieved	Efficiency
Co2 Reduction Efficiency	90%	High	Effective absorption via algae bioreactor
Particulate Matter (PM2.5)	80%	High	Efficient Filtering Through air Purifier
Sensor Detection Accuracy	±2% Deviation	Very High	Reliable Pollutant level
Air Circulation Efficiency	90%	High	Optimized Fan Speed Control

Table 1.Shows Proposed Model Comparison

7. Future Prospects :

This indicates that the bio-solution coupled with microcontroller based automation can lead to potential sustainable air quality management practices. In the future, improvements could be made for scalability, integration of more advanced sensors for the detection of a wider range of pollutants, and more robustness of the algae bioreactor under different environmental conditions.

V. FUTURE WORKS

The algae air-cleaner has great potential but still, it can be improved for sustainable air cleaning process. Follow-up implementations of this system can enhance the performance of algae bioreactor under various environmental conditions including low light and temperature dynamics . Artificial lighting systems such as LED grow lights can be integrated into various aspects of algae to promote growth and maintain constant purification efficiency. Furthermore, new materials for the air filter and gas sensor may enhance the detection and removal of pollutants. The ability to remotely monitor and control the system via mobile or web application, using IoT capabilities, would further improve the usability and scalability of the system. Further enhancement is focused on the system scalability for industrial plants or urban ambient air quality. Research is focused on automating operation of the algae bioreactor to less and less need for hands on aspects. Further development to include more sensors to measure other harmful pollutants including nitrogen oxides (NOx) and sulphur oxides (SOx) enable the system to be more widely applicable. A future step in the research could be potentially integrating solar panels to power the system entirely. Such improvements would make the system more efficient, adaptable, and less impactful on the environment, albeit making it more viable for widespread adoption in the household and industrial fields.

VI. CONCLUSION

This study demonstrates the successful merging of biological aspects and technological innovations to develop an algae-based air purifier system providing a sustainable means for air purification. The solution, which combines the natural ability of algae to absorb CO₂ with an automated monitoring system, not only reduces the amount of air pollutants, but also supplements the environment with oxygen. A close to 100% operational efficiency in PM2. 5) and other volatile organic compounds (VOCs), which position it as a suitable alternative from an air purification perspective to traditional air purifiers. In addition, the design of this feature also showcases how eco-friendly it operates, it is a great solution to the climate issues today. The results from the system are promising, but its limitations, including reliance on light for algae growth and continuous maintenance of the bioreactor, leave potential for improvement. This research enhances the body of work recent in the sustainable air quality management sector, proposing a scalable yet simple and affordable solution across residential and industrial settings. As it advances, especially with features like IoT and using renewable energy sources, the algae-based air purifier can potentially address air pollution and environment sustainability actively. This innovation not only alleviates immediate air quality issues, but also lays foundation for environmentally sustainable technological innovations.

REFERENCE

- [1].Torres, F. G., & De-la-Torre, G. E. (2022). Green algae as a sustainable source for energy generation and storage technologies. *Sustainable Energy Technologies and Assessments*, 53, 102658.
- [2].Yewale, P., Wagle, N., Lenka, S., Bannigol, P., Junnarkar, M., Prakash, D., ... & Nawani, N. (2022). Studies on Biosmotrap: A multipurpose biological air purifier to minimize indoor and outdoor air pollution. *Journal of Cleaner Production*, 357, 132001.
- [3].Wang, Q., Li, L., Hong, Y., Zhai, Q., & He, Y. (2023). Novel insights into indoor air purification capability of microalgae: characterization using multiple air quality parameters and comparison with common methods. *Environmental Science and Pollution Research*, 30(17), 49829-49839.
- [4].George, A. S. (2023). Liquifying Urban Lungs: Assessing the Air Purification Potential of Photobioreactor" Liquid Trees" in Highly Polluted Cities. *Partners Universal Innovative Research Publication*, 1(2), 1-14.
- [5].Gaston, C. J., Royer, H. M., Raymond III, J., Maizel, D., Lanpher, K. B., Solo-Gabriele, H., ... & Pependorf, K. J. (2021). Filtration efficiency of air conditioner filters and face masks to limit exposure to aerosolized algal toxins. *Aerosol and air quality research*, 21(8), 210016.

- [6].Thakur, N., & Samuel, J. (2023). Microbial filters for air treatment: A sustainable approach. In *Relationship Between Microbes and the Environment for Sustainable Ecosystem Services* (pp. 135-147). Elsevier.
- [7].Shahi Khalaf Ansar, B., Kavusi, E., Dehghanian, Z., Pandey, J., Asgari Lajayer, B., Price, G. W., & Astatkie, T. (2023). Removal of organic and inorganic contaminants from the air, soil, and water by algae. *Environmental Science and Pollution Research*, 30(55), 116538-116566.
- [8].Szramowiat-Sala, K., Goryl, W., Figaj, R., Filipowicz, M., Sornek, K., & Zyśk, J. (2024). Environmentally friendly and energy-self-sufficiency-based air purifier: an approach for mitigating outdoor particulate matter. *Clean Technologies and Environmental Policy*, 1-10.
- [9].Mata, T. M., Martins, A. A., Calheiros, C. S., Villanueva, F., Alonso-Cuevilla, N. P., Gabriel, M. F., & Silva, G. V. (2022). Indoor air quality: a review of cleaning technologies. *Environments*, 9(9), 118.
- [10].Kumar, R., Dalvi, V., Pant, K. K., & Malik, A. (2024). Microalgal biochar assisted simultaneous removal of particulate matter, formaldehyde, and total volatile organic compounds (TVOC's) from indoor air. *Chemosphere*, 355, 141866.
- [11].Osama, A., Hosney, H., & Moussa, M. S. (2021). Potential of household photobioreactor for algae cultivation. *Journal of Water and Climate Change*, 12(6), 2147-2180.
- [12].Subrahmanya, S., Kumar, N., Ranjan, J., & Kotnadh, S. (2024). *Sustainable Microalgae-Membrane Photobioreactor System for Onboard Oxygen Production in an Aircraft* (No. 2024-26-0402). SAE Technical Paper.
- [13].Kim, S., Ko, H. S., & Shin, D. H. (2022). Enhanced performance of algal decomposition of electrolysis under cavitation. *Journal of Electroanalytical Chemistry*, 920, 116596.
- [14].Rahman, T. T., Wood, N., Rahman, A. M., Pei, Z., & Qin, H. (2024). Applying In Situ Ionic Crosslinking in Bioprinting Using Algae Cells. *Journal of Manufacturing Science and Engineering*, 146(3).
- [15].Tawfik, A., Niaz, H., Qadeer, K., Qyyum, M. A., Liu, J. J., & Lee, M. (2022). Valorization of algal cells for biomass and bioenergy production from wastewater: sustainable strategies, challenges, and techno-economic limitations. *Renewable and Sustainable Energy Reviews*, 157, 112024.